

Use Case: Get User without active Token

The screenshot shows a REST client interface with a sidebar on the left containing a list of endpoints under 'bookmyconsultation'. The main panel displays a GET request to 'http://localhost:8080/users/TestUser@TestUser.com ...'. The 'Headers' tab is active, showing an 'Authorization' header with the value 'Bearer ((BMCAuthToken))'. The 'Body' tab is also active, showing a JSON response with the following content:

```
1 {
2   "timestamp": "2023-03-10T14:34:57.924+00:00",
3   "status": 401,
4   "error": "Unauthorized",
5   "path": "/users/TestUser@TestUser.com"
6 }
```

The status bar at the bottom indicates 'Status: 401 Unauthorized', 'Time: 951 ms', and 'Size: 796 B'. A 'Save Response' button is visible.

Use Case: Login

The screenshot shows a REST client interface with a sidebar on the left containing a list of endpoints under 'bookmyconsultation'. The main panel displays a POST request to 'http://localhost:8080/auth/login ...'. The 'Authorization' tab is active, showing 'Basic Auth' selected. The 'Body' tab is also active, showing a JSON response with the following content:

```
1 {
2   "id": "TestUser@TestUser.com",
3   "firstName": "TestUser",
4   "lastName": "TestUser",
5   "emailAddress": "TestUser@TestUser.com",
6   "mobilePhoneNumber": "8978742332",
7   "lastLoginTime": null,
8 }
```

The status bar at the bottom indicates 'Status: 200 OK', 'Time: 375 ms', and 'Size: 1.1 KB'. A 'Save Response' button is visible.

Use Case: Get User with active Token

The screenshot shows a REST client interface with a sidebar on the left containing a list of endpoints under 'bookmyconsultation'. The main panel displays a GET request to 'http://localhost:8080/users/TestUser@TestUser.com ...'. The 'Headers' tab is active, showing an 'Authorization' header with the value 'Bearer ((BMCAuthToken))'. The 'Body' tab is also active, showing a JSON response with the following content:

```
1 {
2   "firstName": "TestUser",
3   "lastName": "TestUser",
4   "dob": null,
5   "mobile": "8978742332",
6   "emailId": "TestUser@TestUser.com",
7   "password": "842761B7A83397C4",
8   "createdDate": "2023-03-10",
9   "salt": "n10hFSqNw2Lw1XfT6XeKYRK9spIFRwf8x1HUnzxbPg="
10 }
```

The status bar at the bottom indicates 'Status: 200 OK', 'Time: 70 ms', and 'Size: 891 B'. A 'Save Response' button is visible.

Use Case : Register User

The screenshot shows the Postman interface for a POST request to `http://localhost:8080/users/register`. The request body is a JSON object with the following fields:

```
{  "firstName": "fname",  "lastName": "lname",  "dob": "1993-08-06",  "mobile": "1234567890",  "password": "test",  "emailId": "test@gmail.com"}
```

The response status is 200 OK, with a time of 36 ms and a size of 842 B. The response body is a JSON object:

```
{  "firstName": "fname",  "lastName": "lname",  "dob": "1993-08-06",  "mobile": "1234567890",  "emailId": "test@gmail.com",  "password": "645f23386d717e59",  "createdDate": "2023-03-10",  "salt": "ph27e4xk4gMUKCL9IZN0q/rsJ1Ahz8dGX2+N7i5vLBM="}
```

Use Case : Login with registered user

The screenshot shows the Postman interface for a POST request to `http://localhost:8080/auth/login`. The request is configured with Basic Auth, with the username `test@gmail.com` and password `test`. The response status is 200 OK, with a time of 375 ms and a size of 1.1 KB. The response body is a JSON object:

```
{  "id": "TestUser@TestUser.com",  "firstName": "TestUser",  "lastName": "TestUser",  "emailAddress": "TestUser@TestUser.com",  "mobilePhoneNumber": "8978742332",  "lastLoginTime": null}
```

Use Case: Logout the active user

bookmyconsultation / Logout

POST http://localhost:8080/auth/logout...

Headers (8)

KEY	VALUE	DESCRIPTION
Authorization	Bearer ((BMCAuthToken))	
Key	Value	Description

Body Cookies Headers (11) Test Results

Status: 200 OK Time: 61 ms Size: 582 B

1

Use Case: Get All Doctor with speciality "DENTIST"

bookmyconsultation / get all doctor

GET http://localhost:8080/doctors?speciality=DENTIST

Query Params

KEY	VALUE	DESCRIPTION
speciality	DENTIST	

Body Cookies Headers (12) Test Results

Status: 200 OK Time: 86 ms Size: 11.26 KB

```
1 {
2   "id": "UUID-37",
3   "firstName": "Hermione",
4   "lastName": "Kelley",
5   "speciality": "DENTIST",
6   "dob": "2021-05-16",
7   "address": {
8     "id": "UUID-37",
9     "addressLine1": "Ap #256-8501 Id, Rd.",
10    "addressLine2": "49.0933, 122.50113",
11    "city": "Chicago",
12    "state": "Illinois",
13  }
```

Use Case: Get All Doctors

The screenshot shows the Postman interface for the 'bookmyconsultation / get all speciality' endpoint. The method is GET, and the URL is http://localhost:8080/doctors. The Headers tab is selected, showing an Authorization header with the value Bearer ((BMCAuthToken)). The Body tab is also selected, showing a JSON response in Pretty format. The response status is 200 OK, with a time of 314 ms and a size of 9.27 KB. The JSON response is as follows:

```
{  "id": "UUID-2",  "firstName": "Blossom",  "lastName": "Valentine",  "speciality": "PULMONOLOGIST",  "dob": "2021-09-16",  "address": {    "id": "UUID-2",    "addressLine1": "103-4867 Nullam Ave",    "addressLine2": "-45.85534, 146.33318",    "city": "Patalillo",    "state": "San José",    "country": "Costa Rica"  }}
```

Use Case: Get All Speciality

The screenshot shows the Postman interface for the 'bookmyconsultation / get all speciality' endpoint. The method is GET, and the URL is http://localhost:8080/doctors/speciality. The Headers tab is selected, showing an Authorization header with the value Bearer ((BMCAuthToken)). The Body tab is also selected, showing a JSON response in Pretty format. The response status is 200 OK, with a time of 13 ms and a size of 700 B. The JSON response is as follows:

```
[  "CARDIOLOGIST",  "GENERAL_PHYSICIAN",  "DENTIST",  "PULMONOLOGIST",  "ENT",  "GASTRO"]
```

Use Case: Get a Doctor

bookmyconsultation / get a doctor

GET http://localhost:8080/doctors/UUID-2

Params Authorization Headers (9) Body Pre-request Script Tests Settings Cookies

Query Params

KEY	VALUE	DESCRIPTION
-----	-------	-------------

Body Cookies Headers (12) Test Results Status: 200 OK Time: 20 ms Size: 1.05 KB Save Response

Pretty Raw Preview Visualize JSON

```
7 {
8   "address": {
9     "id": "UUID-2",
10    "addressLine1": "103-4867 Nullam Ave",
11    "addressLine2": "-46.85534, 146.33318",
12    "city": "Patalillo",
13    "state": "San José",
14    "postcode": "L2S 2T0"
15  },
16  "mobile": "16030720 0091",
17  "emailId": "malesuada@lacusMaurisnon.com",
18  "pan": "KAR90S3R5KQ",
19  "highestQualification": "MDS",
20  "college": "Enim Consequat Purus LLC",
21  "totalYearsOfExp": 20,
22  "rating": 5.0
23 }
```

Use Case : Get an Appointment by ID

bookmyconsultation / get an appointment

GET http://localhost:8080/appointments/5d579008-7a30-489b-a3ee-48d461176cff

Params Authorization Headers (9) Body Pre-request Script Tests Settings Cookies

KEY	VALUE	DESCRIPTION
☒ Authorization	Bearer ({BMCAuthToken})	
Key	Value	Description

Body Cookies Headers (12) Test Results Status: 200 OK Time: 71 ms Size: 916 B Save Response

Pretty Raw Preview Visualize JSON

```
1 {
2   "appointmentId": "5d579008-7a30-489b-a3ee-48d461176cff",
3   "doctorId": "UUID-36",
4   "doctorName": "Hilary Porter",
5   "userId": "TestUser@TestUser.com",
6   "userName": "TestUser TestUser",
7   "timeSlot": "12AM-01PM",
8   "appointmentDate": "2023-3-10",
9   "symptoms": "Cold and Blocked Nose",
10  "priorMedicalHistory": "No History"
11 }
```

Use Case: Add a Doctor

The screenshot shows the Postman interface for a REST client. The left sidebar lists the API collection 'bookmyconsultation' with various endpoints. The main panel displays a POST request to 'http://localhost:8080/doctors'. The request body is a JSON object with the following fields: 'firstName': 'Test', 'lastName': 'Doctor', and 'dob': '1983-08-06'. The response is a 200 OK status with a JSON body containing a doctor's details, including an 'id', 'firstName', 'lastName', 'speciality', 'dob', and an 'address' object with 'id', 'addressLine1', 'addressLine2', 'city', and 'state'.

```
POST http://localhost:8080/doctors

{
  "firstName": "Test",
  "lastName": "Doctor",
  "dob": "1983-08-06"
}
```

```
{
  "id": "853c2dfb-9d25-434f-a1bd-b4ce5310699d",
  "firstName": "Test",
  "lastName": "Doctor",
  "speciality": "GENERAL_PHYSICIAN",
  "dob": "1983-08-06",
  "address": {
    "id": "853c2dfb-9d25-434f-a1bd-b4ce5310699d",
    "addressLine1": "add1",
    "addressLine2": "add1",
    "city": "BHN",
    "state": "TN",
    "zipcode": null
  }
}
```

Use Case: Book an Appointment by Id : df9d9862-e9a1-4432-8eb5-df442fd96ce3

The screenshot shows the Postman interface for a REST client. The left sidebar lists the API collection 'bookmyconsultation' with various endpoints. The main panel displays a POST request to 'http://localhost:8080/appointments'. The request body is a JSON object with the following fields: 'doctorName': 'Jordan', 'userId': 'test@gmail.com', 'userName': 'fname', and 'userEmailId': 'test@gmail.com'. The response is a 200 OK status with a JSON body containing the appointment ID: 'df9d9862-e9a1-4432-8eb5-df442fd96ce3'.

```
POST http://localhost:8080/appointments

{
  "doctorName": "Jordan",
  "userId": "test@gmail.com",
  "userName": "fname",
  "userEmailId": "test@gmail.com"
}
```

```
{
  "id": "df9d9862-e9a1-4432-8eb5-df442fd96ce3"
}
```

Use Case : Add Ratings

backendTest

bookmyconsultation

GET get User

GET get User appointments

POST register

POST Login

POST Logout

GET get all doctor

GET get all speciality

GET get doctors timeslots

GET get a doctor

GET get an appointment

POST add doctor

POST book an appointment

POST post a rating

bookmyconsultation / post a rating

Save

POST

http://localhost:8080/ratings

Send

Params

Authorization

Headers (9)

Body

Pre-request Script

Tests

Settings

none

form-data

x-www-form-urlencoded

raw

binary

GraphQL

JSON

1

2

3

4

5

6

1

2

3

4

5

6

Body

Cookies

Headers (11)

Test Results

Status: 200 OK

Time: 156 ms

Size: 582 B

Save Response

Pretty

Raw

Preview

Visualize

Text

1