

Match the Git command to the GUI action

A live matching activity for the Git for Science workshop

How this works

In this workshop we drive Git through a graphical interface: buttons in the RStudio Git pane and on GitHub. Every click runs a Git command underneath. Clicking the push button *is* `git push`. Using the interface is not “cheating”; it runs the same commands a terminal user types, and it is the bridge to the agentic-coding follow-up where an agent drives Git by naming those same commands.

The activity (10 minutes, in pairs): draw a line from each Git command on the left to its matching GUI action on the right, then we compare as a group. One item on the left is a GitHub feature, not a Git command; matching it is part of the point.

Learner sheet

The dots mark where to start and end each line.

1. <code>git clone <url></code> •	• A. Click the down-arrow (pull) button in the RStudio Git pane
2. <code>git add <file> / stage</code> •	• B. Write a commit message, then click Commit
3. <code>git commit -m "..."</code> •	• C. On GitHub, click Add file > Create new file or Upload files , then Commit changes
4. <code>git push</code> •	• D. Copy the HTTPS URL, then File > New Project > Version Control > Git in RStudio
5. <code>git pull</code> •	• E. Click the up-arrow (push) button in the RStudio Git pane
6. <code>git status</code> •	• F. Tick the checkbox next to a file in the RStudio Git pane
7. <code>git log</code> •	• G. On GitHub, open the Pull requests tab and click New pull request
8. <code>git branch <name> / checkout</code> •	• H. Read the file list and status flags shown in the RStudio Git pane
9. <code>git revert <commit></code> •	• I. Click the branch dropdown in the Git pane and choose New Branch
10. <code>git add + git commit</code> (on GitHub) •	• J. Right-click a commit in History and choose Revert , or use the Git pane menu
11. open a pull request (GitHub feature, not a Git command) •	• K. Click History (the clock icon) in the RStudio Git pane

Facilitator answer key

Do not print this page for learners.

Command	Answer	GUI action
1. <code>git clone <url></code>	D	File > New Project > Version Control > Git
2. <code>git add / stage</code>	F	Tick the checkbox next to a file in the Git pane
3. <code>git commit -m "..."</code>	B	Write a message, click Commit
4. <code>git push</code>	E	Up-arrow (push) button in the Git pane
5. <code>git pull</code>	A	Down-arrow (pull) button in the Git pane
6. <code>git status</code>	H	Read the file list and status flags in the Git pane
7. <code>git log</code>	K	History (clock icon) in the Git pane
8. <code>git branch / checkout</code>	I	Branch dropdown > New Branch
9. <code>git revert <commit></code>	J	Right-click a commit in History > Revert
10. <code>git add + commit</code> on GitHub	C	Add file / Upload files, then Commit changes
11. open a pull request (<i>GitHub feature</i>)	G	Pull requests tab > New pull request

Talking points while reviewing

- Every button press ran a real command. Nothing was hidden or “easier”; it was the same operation.
- `git add` and `git commit` are two steps. In the RStudio pane you see this clearly: tick the box (add), then Commit. On GitHub the web editor bundles both into one “Commit changes” click.
- `git revert` makes a new commit that undoes an earlier one; it does not erase history. In the GUI this is a right-click on a commit in History. Good moment to contrast it with deleting or force-pushing.
- A pull request is not a Git command in the same sense; it is a GitHub feature built on top of branches you pushed. That is why it is called out separately on the sheet. Good moment to name where Git ends and GitHub begins.
- Tie-in to the agentic follow-up: an agent driving Git speaks these same command names. Knowing the mapping is what lets you read and check what the agent does.