US 20240061660A1

(19) United States
(12) Patent Application Publication
GRIGORE
(10) Pub. No.: US 2024/0061660 A1
(43) Pub. Date: Feb. 22, 2024

(54) **USER INTERFACE (UI) DESCRIPTORS, UI OBJECT LIBRARIES, UI OBJECT REPOSITORIES, AND UI OBJECT BROWSERS FOR ROBOTIC PROCESS AUTOMATION**

(71) Applicant: **UiPath, Inc.**, New York, NY (US)

(72) Inventor: **Mircea GRIGORE**, Bucharest (RO)

(73) Assignee: **UiPath, Inc.**, New York, NY (US)

(21) Appl. No.: **18/498,247**

(22) Filed: **Oct. 31, 2023**

**Related U.S. Application Data**

(63) Continuation of application No. 16/941,758, filed on Jul. 29, 2020, now Pat. No. 11,809,846, which is a continuation of application No. 16/922,289, filed on Jul. 7, 2020, now Pat. No. 11,748,069.

**Publication Classification**

(51) **Int. Cl.**

| | |
|---|---|
| ***G06F 8/38*** | (2006.01) |
| ***G06F 8/34*** | (2006.01) |
| ***G06F 9/451*** | (2006.01) |
| ***G06V 30/148*** | (2006.01) |

(52) **U.S. Cl.**
CPC ..... ***G06F 8/38*** (2013.01); ***G06F 8/34*** (2013.01); ***G06F 9/451*** (2018.02); ***G06V 30/153*** (2022.01); *G06V 30/10* (2022.01)

(57) **ABSTRACT**

User interface (UI) object descriptors, UI object libraries, UI object repositories, and UI object browsers for robotic process automation (RPA) are disclosed. A UI object browser may be used for managing, reusing, and increasing the reliability of UI descriptors in a project. UI descriptors may be added to UI object libraries and be published or republished as UI object libraries for global reuse in a UI object repository. The UI object browser, UI object libraries, and UI object repository may facilitate reusability of UI element identification frameworks and derivatives thereof.



FIG. 1


100
110
Designer
DEPLOY
120
Conductor
EXECUTE
MONITOR
130
Robot(s)
UNATTENDED ROBOT
134
AUTOMATE
</mainframe>
</web>
</VM>
</enterprise app>
</desktop app>
132
ATTENDED ROBOT


200
Client Side
Server Side
Presentation Layer
Service Layer
Persistence Layer
210
212
214
216
220
230
232
234
236
238
240
250
Executor
Designer
Agent(s)
Browser
Web Application (HTML/JS)
Notification and Monitoring API
Config. Logging Monitoring Queues
OData REST API Endpoints
API Implementation / Business Logic
Indexer Server
Database Server

FIG. 2

FIG. 3


300
Designer
310
User-Defined Activities
320
UI Automation Activities
330
Drivers
340
Enterprise
348
VM
346
Browser
344
OS
342
340

FIG. 4


400
410
Robots
420
Conductor
430
DB Server
440
Indexer
Server

FIG. 5


500
Processor(s)
510
Communication
Device
520
Bus
505
550
Other Functional
Modules
545
UI Object Operations
Module
540
Operating
System
Memory
515
Display
525
Keyboard
530
Cursor Control
Device
535

FIG. 6A



FIG. 6B




672




670

FIG. 6C


630
Outline
Main
Sequence
Attach Window 'calc1.exe...
Do
Click Button 2
Click Plus Button
Click Button 3
Click Button Equals
Get Full Text 'Result'
Click Button Clear
Write Line

FIG. 6D


620
622
621
623
624
625
626
623A
624A
625A
626A
UI Descriptors
Calculator
Win10
Standard Screen
Window Target
Button 2
Partial Selector Target
Button 3
Partial Selector Target
Cancel
Partial Selector Target
Equals
Partial Selector Target
Plus
Partial Selector Target
Result
Partial Selector Target
Win7
Standard Screen
Window Target
Button 2
Partial Selector Target
Button 3
Partial Selector Target
Cancel
Partial Selector Target
Equals
Partial Selector Target
Plus
Partial Selector Target
Result
Partial Selector Target
Samples
Project
Activities
Snippets

FIG. 6E


612
Sequence
Attach Window 'calc1.exe' 'Calculator'
View Edit Help
Do
Click Button 2
614
Click Plus Button
Click Button 3

# FIG. 6F


612
Click Button 3
Click Button Equals
Get Full Text 'Result'
Click Button Clear
Write Line
Text
"Result is: " + result

FIG. 6G


616
615
614
618
Click Button 2
Indicate on screen
Edit Selector
Open in UiExplorer
Add to UI Objects
Change Informative Screenshot
Remove Informative Screenshot
Show Informative Screenshot (double click)

FIG. 6H



# FIG. 6I


640
Properties
Activity is referencing a UI Descriptor. Please edit from UI Object Browser.
UIPath.Core.Activities.Click
Common
ContinueOnError
Specifies to continue
DelayAfter
Delay time (in milliseconds
DelayBefore
Delay time (in milliseconds
Display Name
Click Button 2
Input
ClickType
ClickType.CLICK_SINGLE
MouseButton
MouseButton.BTN_LEFT
Target
Target
Misc
Private
Options
AlterIfDisabled
If selected, the simulate
CursorPosition
CursorPosition
KeyModifiers
KeyModifiers.None
SendWindowMessages
If selected, the click is
SimulateClick
If selected, it simulate
652
Properties
UI Objects Browser (Experimen...
Orchestrator Resources

FIG. 6J



FIG. 6K


650
UI Objects Browser (Experimental)
Descriptors
UI Activities
Search UI Objects (Ctrl+Alt+O)
654A
Project UI Descriptors
UI Libraries
656A

# FIG. 6L


628
Win7
Add to Project
Publish
Create Screen
Edit Version
Delete
627
Button 3
Partial Selector Target
Cancel
Partial Selector Target
Equals
650
654A
Project UI Descriptors
Calculator
Standard Screen
Window Target
Button 2
Partial Selector Target
Button 3
Partial Selector Target
Cancel
Partial Selector Target
Equals
Partial Selector Target
Plus
Partial Selector Target
Result
Partial Selector Target
658A
UI Libraries
656A

FIG. 6M


650
UI Objects Browser (Experimental)
Descriptors
UI Activities
Search UI Activities
AutomateCalculator
654B
Main.xaml
Attach Window 'calc1.exe' 'Calculator'
Click Button 2
Button 2
Click Plus Button
Click Button 3
Click Button Equals
Get Full Text 'Result'
Click Button Clear
Selector Target
656B

# FIG. 6N


612
Sequence
Attach Window 'calc1.exe Calculator'
Calcul...
View Edit Help
Do
Click Button 2
Drop here...
Click Plus Button
Drop here...
Click Button 3
Drop here...
Click Button Equals
Drop here...

FIG. 6O



FIG. 6P


650
UI Objects Browser (Experimental)
Descriptors
UI Activities
Search UI Objects (Ctrl+Alt+O)
Project UI Descriptors
658
Calculator
Standard Screen
Window Target
Button 2
Partial Selector Target
Button 3
Partial Selector Target
Cancel
Partial Selector Target
Equals
Partial Selector Target
Plus
Partial Selector Target
Result
Partial Selector Target
UI Libraries

# FIG. 6Q


650
Sequence
Attach Window 'calc1.exe' Calculator
Calculator
Standard
Do
Click Button 2
1
2
Click Plus Button
3
+
Click Button 3
2
3
Click Button Equals
=

FIG. 6R


660
Package properties
Publish options
Certificate signing
Package properties
Package Name
Calculator.Descriptors
Version
Current Version
New Version
1.0.2
1.0.3
Is Prerelease
Release Notes
Cancel
Back
Next
Publish

FIG. 6S

662


Manage Packages
Settings
Project Dependencies
All Packages
Local
Official
Connect
Microsoft Visual Studio Offline
Orchestrator Tenant
Orchestrator Host
Alpha
UI Libraries
Search
Include Prerelease
Calculator.Descriptors by mirce
Object Browser Library
v1.1.0
Install
Calculator.Descriptors
Version:
1.1.0
Runtime Rules
Lowest Applicable Version
Description:
Object Browser Library
Version: 1.1.0
Owner(s): mirce
Author(s): mirce
Date Published: 4/16/2020 2:42:15 PM
Tags: UiPath.Object.Library
Dependencies:
UiPath.Excel.Activities [2.8.0-beta.881245, 2.8.0-beta.881245]
UiPath.Mail.Activities [1.8.0-beta.876342, 1.8.0-beta.876342]
UiPath.System.Activities [20.4.0-beta.873372, 20.4.0-beta.873372]
UiPath.UIAutomation.Activities [20.4.0-beta.880778, 20.4.0-beta.880778]
UiPath.UIAutomationNext.Activities [20.4.0-beta.880778, 20.4.0-beta.880778]
Save
Cancel

650

# FIG. 6T


UI Objects Project (Experimental)
Descriptors
UI Activities
Search UI Objects (Ctrl+Alt+O)
Project UI Descriptors
UI Libraries
Calculator.Descriptors 10.3.4
Calculator Win10
Standard Screen
Window Target
Button 2
Partial Selector Target
Button 3
Partial Selector Target
Cancel
Partial Selector Target
Equals
Partial Selector Target
Plus
Partial Selector Target
Result
Partial Selector Target

FIG. 7A



FIG. 7B


710
Sequence
Click - Selector Based Identification
720
Indicate on screen
721
CV Screen Scope - CV based Identification
730
Indicate on screen
731
MicrosoftOCR
732
Drop Activity here
Use Application/Browser - Unified Target based Identification
740
Indicate Application
741
Do
742
Drop Activity Here

FIG. 7C



FIG. 7D


710
722
720
724
Sequence
Click - Selector Based Identification
8
9
CV Screen Scope - CV based Identification
Indicate on screen
MicrosoftOCR
Drop Activity here
Use Application/Browser - Unified Target based Identification
Indicate Application
Do
Drop Activity Here

FIG. 7E


725
Indicate on screen
Edit Selector
Open in UiExplorer
Add to UI Objects
Change Informative Screenshot
Remove Informative Screenshot
Show Informative Screenshot (double click)

FIG. 7F


726
Selector Editor
Indicate Element
Highlight
Edit Attributes
app
applicationframehost.exe
appid
Microsoft.WindowsCalculator_8wekyb3d8bbwe!App
title
Calculator
cls
LandmarkTarget
automationid
NumberPad
cls
NamedContainerAutomationPeer
name
Number pad
automationid
numButton
cls
Button
Edit Selector
<wnd app='applicationframehost.exe' appid='Microsoft.WindowsCalculator_8wekyb3d8bbwe!App' title='Calculator' />
<uia cls='LandmarkTarget' />
<uia automationid='NumberPad' cls='NamedContainerAutomationPeer' name='Number pad' />
<uia automationid='numButton' cls='Button' name='Nine' />
Open in UI Explorer
OK
Cancel

FIG. 7G


Create New, Add to Existing or Update UI Descriptor
Create new UI Element with the UI Descriptor, add it to an existing UI Element or update an existing UI Descriptor.
UI Objects Browser
UI Descriptors details
Search UI Objects
Project UI Descriptors
NewApplication
NewScreen
Selecting a screen allows creating a new UI Element for this UI Descriptor within the screen. Please provide a name for the new UI Element.
UI Element Name
Button B
Descriptor Type
Selector Target
Screenshot
Finish
Cancel

728

FIG. 7H

706


UI Objects Browser (Experimental)
Descriptors
UI Activities
Search UI Objects (Ctrl+Alt+O)
Project UI Descriptors
NewApplication 1.0.0
NewScreen
Button 9
Selector Target
UI Libraries

FIG. 7I


710
Sequence
Click - Selector Based Identification
8
9
733
Detecting screen elements and labels ...
730
Drop Activity here
Use Application/Browser - Unified Target based Identification
Indicate Application
Do
Drop Activity Here

FIG. 7J


700
702
Main
Artist
10 results
Click Search
Click Event
Click Image Search
Cv Click Automation > Element > Move
Click Automation > UI Automation Run
Click Automation > UI Automation > Image > Move
Click Image Automation > UI Automation > OCR > Move
Click OCR Text Automation > UI Automation > OCR
Click Mouse on Screen Automation > UI Automation > Text > Move
Click Another Action Automation > UI Automation > Client Event > Trigger
Click Text Automation > Client Event > Trigger
Click Image Automation > Client Event > Image Trigger
Click Image Automation > Image Trigger
Cv Click Automation > Computer Vision
Double Click Automation > Element > Move
Double Click Image Automation > UI Automation > Image > Move
Automation Name
Microsoft OCR
Drop Activity Here

FIG. 7K


730
734
CV Screen Scope - CV based Identification
732
MicrosoftOCR
CV Click
Indicate on scope ()
736
735

FIG. 7L


750
Calculator
Standard
Indicate
Target
Show elements
Refresh Scope
Refresh after delay
Relative To
Cancel
Ok
754
752
0
M+
M-
MS
%
CE
C
7
8
9
4
5
6
1
2
3
+/-
0

# FIG. 7M


750
Calculator
Standard
Duplicate matches,
try adding an anchor.
Type:
Button
Show elements
Refresh Scope
Refresh after delay
Relative To
Cancel
Ok
0
M+
M-
MS
754
752

FIG. 7N


750
Calculator
Standard
757
758
756
Duplicate matches,
try adding another anchor.
Type: Text
Text: Standard
Show elements
Refresh Scope
Refresh after delay
Relative To
Cancel
OK
754
752
0
7
8
9
4
5
6
1
2
3
+
0

FIG. 7O


710
Sequence
Click - Selector Based Identification
8
9
CV Screen Scope - CV based Identification
730
734
0
732
MicrosoftOCR
CV Click - Button
737
735

FIG. 7P

760


Properties
UiPath.CV.Activities.CvClickWithDescriptor
Common
ContinueOnError
Specifies to a
DelayAfter
Delay time (in mi
DelayBefore
Delay time (in mi
DisplayName
CV Click - Button
Input
ClickType
ClickType.CU
Descriptor
"Target: Button ("
MouseButton
MouseButtor
TimeoutMS
Specifies the ono
Misc
Private
Options
KeyModifiers
KeyModifiers
Reusable Region
InputRegion
Use the result of
OutputRegion
Outputs a region

FIG. 7Q


740
Use Application: Calculator
743
744
Application path
"Microsoft.WindowsCalculator_8wekyb3d8bbwe!App"
Application arguments
Text must be quoted
745
Do
Drop Activity Here
742

FIG. 7R


click
8 months
Click Recent
Click Recent
Click Trigger Recent
Click Recent
Click Available > UI Automation Mouse
Click Available > UI Automation > Mouse
Click Available > UI Automation Mouse
Click Available > UI Automation > Image > Mouse
Click Image Available > UI Automation > Mouse
Click OCR Text Available > UI Automation > OCR > Mouse
Click Picture on Screen Available > UI Automation > SAP
Click Toolbar Button Available > UI Automation > SAP
Click Text Available > UI Automation > Text > Mouse
Click Trigger Available > User Events > Element Trigger
Click Image Trigger Available > User Events > Image Trigger
Click Available > Computer Vision
Double Click Available > UI Automation > Element > Mouse
Double Click Available > UI Automation > Image > Mouse

708

FIG. 7S


740
Use Application: Calculator
743
744
Application path
"Microsoft.WindowsCalculator_8wekyb3d8bbwe!App"
Application arguments
Text must be quoted
745
Do
742
Click
747
Indicate target on screen
746
Click type
Mouse button
Single
Left

FIG. 7T


750
770
772
Standard
Hover over the element you want to indicate and click to select it.
If the element is not being detected/highlighted, try changing the detection framework (E2) or using region selection (E3).
Pause configuration for 15 seconds
Image selection mode
UI framework: Default
Cancel
Continue

FIG. 7U


750
770
772
774
Standard
No anchor automatically found.
Does this element have an anchor (e.g. label)?
If so, indicate it to help in identifying the
target element. Learn more
Pause configuration for 15 seconds
Image selection mode
Validate
Cancel

FIG. 7V


750
770
774
776
Standard
Target & anchors OK.
Hit enter to confirm.
Pause configuration for 5 seconds
Image selection mode
Validate
Cancel

FIG. 7W


750
770
778
Standard
Validation successful.
Hit enter to confirm.
Route configuration for
seconds
Image selection mode
Validate
Cancel

FIG. 7X


740
Use Application: Calculator
Application path
"Microsoft.WindowsCalculator_8wekyb3d8bbwe!App"
Application arguments
Text must be quoted
Do
Click '9'
7
8
9
×
748
Click type
Mouse button
st on screen to indicate the UI element to click.

FIG. 7Y


740
Use Application: Calculator
Application path
"Microsoft.WindowsCalculator_8wekyb3d8bbwe!App"
Application arguments
Text must be quoted
Do
Click '9'
Click type
Mouse button
Single
Left
780
Click Image
Indicate image on screen
782

FIG. 7Z


750
Calculator
Standard
0
M+
M-
MS
%
CE
C
7
8
9
4
5
6
1
2
3
0
784
Click Image 'ApplicationFrameHost.ex...'
9
786
780

# FIG. 7a

760


Properties
UiPath.Core.Activities.ClickImage
Common
ContinueOnError
Specifies to continue
DelayAfter
Delay time (in milliseco
DelayBefore
Delay time (in milliseco
Display Name
Click Image 'ApplicationFram
Input
ClickType
ClickType.CLICK_SIN
Image
ImageTarget
Accuracy
0.8
Image
Enter a VB expression
Profile
ImageFindProfile.Ba
MouseButton
MouseButton.BTN_L
Target
Target
ClippingRegion
Element
Enter a VB expression
Selector
"<wnd app='application
Timeout (milliseconds)
Enter a VB expression
WaitForReady
Before performing th
Misc
Private
Options
CursorPosition
CursorPosition
KeyModifiers
KeyModifiers.None
SendWindowMessages
If this check box is se

FIG. 7b


788


Selector Editor
Indicate Element
Highlight
Edit Attributes
app applicationframehost.exe
appid Microsoft.WindowsCalculator_8wekyb3d8bbwe!App
title Calculator
Edit Selector
<wnd app='applicationframehost.exe' appid='Microsoft.WindowsCalculator_8wekyb3d8bbwe!Ap
Open in UI Explorer
OK
Cancel

FIG. 7c


750
780
Click Image 'ApplicationFrameHost.ex...'
9
Click OCR Text
790
Indicate on screen
792
Text must be quoted
Tesseract OCR
794
796

FIG. 7d


750
790
798
Click OCR Text 'button Nine'
8
9
Text must be quoted
Tesseract OCR


800
FIG. 8
START
810
Generate Selector-Based Activity
820
Receive Indicate on Screen Command
830
Detect Application
840
Detect UI Elements
850
Receive Indication of UI Element for Activity
860
Generate Selector and Configure Activity
END

FIG. 9


900
START
910
Generate CV Descriptor-Based Activity
920
Receive Indicate on Screen Command and User Screen Selection
930
Detect Application
940
Detect UI Elements using CV
950
Receive Command to Designate UI Elements and Display Interface
960
Receive User Target Selection
970
Unique?
NO
YES
980
Generate CV Descriptor and Configure Activity
990
Require and Receive Anchor Designations until Unique
END

FIG. 10


1000
START
1010
Unified Target-Based Activity
1020
Receive Indicate Application Command and User Screen Selection
1030
Detect Application
1040
Detect UI Elements
950
Receive Command to Designate UI Elements and Display Interface
960
Receive User Target Selection
970
Unique?
NO
YES
990
Require and Receive Anchor Designations until Unique
980
Generate CV Descriptor and Configure Activity
END


1100
FIG. 11
START
1110
Generate Image Matching Activity
1120
Receive Indicate on Screen Command
1130
Detect Application
1140
Receive Region of UI Element Image for Activity
1150
Generate Selector and Configure Activity
END

FIG. 12


1200
START
1210
Generate Selector and OCR-Based Activity
1220
Receive Indicate on Screen Command
1230
Detect Application
1240
Detect UI Elements
1250
Receive Indication of UI Element for Activity
1260
Generate Selector and Configure Activity
1270
Receive OCR Engine Selection and Configure Activity
END


1300
FIG. 13
START
1310
Generate UI Element Identification and Interaction Activities
1320
Configure Generated UI Element Identification and Interaction Activities into Logical Relationship
1330
Generate RPA Robot Implementing Workflow
1340
Execute RPA Robot to Detect and Interact with UI Element
END


1400
FIG. 14
START
1410
Load One or More Existing UI Object Libraries
1420
Create and/or Add UI Descriptors for RPA Workflow Activities
1430
Generate UI Object Library Including UI Descriptors
1440
Publish or Re-Publish UI Object Library
END

# USER INTERFACE (UI) DESCRIPTORS, UI OBJECT LIBRARIES, UI OBJECT REPOSITORIES, AND UI OBJECT BROWSERS FOR ROBOTIC PROCESS AUTOMATION

## CROSS-REFERENCE TO RELATED APPLICATIONS

**[0001]** This application is a continuation of U.S. Nonprovisional patent application Ser. No. 16/941,758 filed Jul. 29, 2020, which is a continuation of U.S. Nonprovisional patent application Ser. No. 16/922,289 filed Jul. 7, 2020, which issued on Sep. 5, 2023, as U.S. Pat. No. 11,748,069. The subject matter of these earlier filed applications is hereby incorporated by reference in its entirety.

## FIELD

**[0002]** The present invention generally relates to robotic process automation (RPA), and more specifically, to user interface (UI) object descriptors, UI object libraries, UI object repositories, and/or UI object browsers for RPA.

## BACKGROUND

**[0003]** For RPA automation in a user interface (UI), developers typically build descriptors (e.g., selectors) for each UI action. Default descriptors are typically generated. However, building a reliable descriptor may consume developer time for troubleshooting and trial-and-error development, which may not be efficient. There is also a lack of reusability of descriptors when the same descriptor is needed. Furthermore, when systems and applications are changed or upgraded, the process upgrade path may not be straightforward. Accordingly, an improved approach may be beneficial.

## SUMMARY

**[0004]** Certain embodiments of the present invention may provide solutions to the problems and needs in the art that have not yet been fully identified, appreciated, or solved by current RPA technologies. For example, some embodiments of the present invention pertain to UI descriptors, UI object libraries, UI object repositories, and/or UI object browsers for RPA.

**[0005]** In an embodiment, a computer program for creating a user interface (UI) object library for RPA is embodied on a non-transitory computer-readable medium. The program is configured to cause at least one processor to detect an application associated with a screen of a UI and detect UI elements on the screen. The program is also configured to cause the at least one processor to receive a selection of a target UI element and generate a UI descriptor for the selected UI element and add the generated UI descriptor for the selected UI element to a respective RPA workflow activity. The program is further configured to cause the at least one processor to create and publish a UI object library including the UI descriptor in a UI object repository.

**[0006]** In another embodiment, a computer program is embodied on a non-transitory computer-readable medium. The program is configured to cause at least one processor to receive a selection of a target UI element on a screen of an application and generate a UI descriptor for the selected UI element. The program is also configured to cause the at least one processor to add the generated UI descriptor for the selected UI element to a respective RPA workflow activity. The RPA workflow activity is or includes a CV-based identification activity or a unified target identification activity.

**[0007]** In yet another embodiment, an RPA developer application is embodied on a non-transitory computer-readable medium. The RPA developer application is configured to cause at least one processor to detect an application associated with a screen of a UI and detect UI elements on the screen. The RPA application is also configured to cause the at least one processor to receive a selection of a target UI element and generate a UI descriptor for the selected UI element. The RPA developer application is further configured to cause the at least one processor to add the generated UI descriptor for the selected UI element to a respective RPA workflow activity. The RPA workflow activity is or includes a selector-based identification activity, a CV-based identification activity, a unified target identification activity, an image matching identification activity, or a selector and OCR-based identification activity. The RPA application includes a UI object browser that displays UI descriptors in one or more UI object libraries of a UI object repository, the one or more UI object libraries organized by application and version.

## BRIEF DESCRIPTION OF THE DRAWINGS

**[0008]** In order that the advantages of certain embodiments of the invention will be readily understood, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments that are illustrated in the appended drawings. While it should be understood that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings, in which:

**[0009]** FIG. **1** is an architectural diagram illustrating a robotic process automation (RPA) system, according to an embodiment of the present invention.

**[0010]** FIG. **2** is an architectural diagram illustrating a deployed RPA system, according to an embodiment of the present invention.

**[0011]** FIG. **3** is an architectural diagram illustrating the relationship between a designer, activities, and drivers, according to an embodiment of the present invention.

**[0012]** FIG. **4** is an architectural diagram illustrating an RPA system, according to an embodiment of the present invention.

**[0013]** FIG. **5** is an architectural diagram illustrating a computing system configured to provide UI descriptors, object libraries, UI object repositories, and/or object browsers for RPA, according to an embodiment of the present invention.

**[0014]** FIG. **6**A is a screenshot illustrating an RPA designer application, according to an embodiment of the present invention.

**[0015]** FIG. **6**B is a screenshot illustrating the Windows® 7 calculator standard view screen and the view selector tab.

**[0016]** FIG. **6**C is an enlarged screenshot view illustrating the sequence in an outline pane of the RPA development application as shown in FIG. **6**A, according to an embodiment of the present invention.

**[0017]** FIG. **6**D is an enlarged screenshot view illustrating a snippets pane of the RPA development application as shown in FIG. **6**A, according to an embodiment of the present invention.

**[0018]** FIGS. **6**E and **6**F are screenshots showing activities of an RPA workflow with screenshots of respective UI elements for each activity, according to an embodiment of the present invention.

**[0019]** FIG. **6**G is a screenshot illustrating a menu of options for a workflow activity, according to an embodiment of the present invention.

**[0020]** FIG. **6**H is a screenshot illustrating the RPA designer application with properties for a click activity shown in a properties pane, according to an embodiment of the present invention.

**[0021]** FIG. **6**I is an enlarged screenshot illustrating the properties pane of the RPA development application as shown in FIG. **6**H, according to an embodiment of the present invention.

**[0022]** FIG. **6**J is a screenshot illustrating the RPA designer application with a UI object browser pane, according to an embodiment of the present invention.

**[0023]** FIG. **6**K is an enlarged screenshot illustrating a UI descriptors view of the UI object browser pane of the RPA development application as shown in FIG. **6**J, according to an embodiment of the present invention.

**[0024]** FIG. **6**L is an enlarged screenshot illustrating a UI descriptors view of the UI object browser pane of the RPA development application as shown in FIG. **6**J, according to an embodiment of the present invention.

**[0025]** FIG. **6**M is a screenshot illustrating a UI activities view of a UI object browser pane, according to an embodiment of the present invention.

**[0026]** FIG. **6**N is a screenshot illustrating drag-and-drop functionality to drop selectors into a desired activity of the RPA workflow, according to an embodiment of the present invention.

**[0027]** FIG. **6**O is a screenshot illustrating the Windows® 10 calculator.

**[0028]** FIG. **6**P is a screenshot illustrating the UI activities view of the UI object browser pane with Windows® 10 calculator selectors, according to an embodiment of the present invention.

**[0029]** FIG. **6**Q is a screenshot illustrating some of the activities of the RPA workflow with updated screenshots of respective UI elements for each activity for the Windows® 10 calculator, according to an embodiment of the present invention.

**[0030]** FIG. **6**R is a screenshot illustrating a publish UI object library window, according to an embodiment of the present invention.

**[0031]** FIG. **6**S is a screenshot illustrating a manage packages window, according to an embodiment of the present invention.

**[0032]** FIG. **6**T is a screenshot illustrating the UI activities view of the UI object browser pane with Windows® 10 calculator selectors added to the UI object libraries, according to an embodiment of the present invention.

**[0033]** FIG. **7**A is a screenshot illustrating an RPA designer application, according to an embodiment of the present invention.

**[0034]** FIG. **7**B is a screenshot illustrating an RPA workflow that will be configured to use three different UI element detection techniques, according to an embodiment of the present invention.

**[0035]** FIG. **7**C is a screenshot illustrating the Windows® 10 calculator as modified by UiPath Studio™ after a developer selects "indicate on screen", according to an embodiment of the present invention.

**[0036]** FIG. **7**D is a screenshot illustrating the RPA workflow of FIG. **7**B with a screenshot of the selected UI element from the Windows® 10 calculator, according to an embodiment of the present invention.

**[0037]** FIG. **7**E is a screenshot illustrating an activity options menu, according to an embodiment of the present invention.

**[0038]** FIG. **7**F is a screenshot illustrating a selector editor, according to an embodiment of the present invention.

**[0039]** FIG. **7**G is a screenshot illustrating add to UI objects library functionality, according to an embodiment of the present invention.

**[0040]** FIG. **7**H is a screenshot illustrating a UI descriptors pane, according to an embodiment of the present invention.

**[0041]** FIG. **7**I is a screenshot illustrating the RPA workflow with a detecting screen elements and labels message, according to an embodiment of the present invention.

**[0042]** FIG. **7**J is a screenshot illustrating a search interface, according to an embodiment of the present invention.

**[0043]** FIG. **7**K is a screenshot illustrating a CV-based identification activity, according to an embodiment of the present invention.

**[0044]** FIG. **7**L is a screenshot illustrating the Windows® 10 calculator as modified by UiPath Studio™ after a developer selects "indicate on scope" with a CV click interface, according to an embodiment of the present invention.

**[0045]** FIG. **7**M is a screenshot illustrating the Windows® 10 calculator as modified by UiPath Studio™ and the CV click interface after a developer makes a target selection, according to an embodiment of the present invention.

**[0046]** FIG. **7**N is a screenshot illustrating the Windows® 10 calculator as modified by UiPath Studio™ and the CV click interface after a developer makes the target selection and anchor selections, according to an embodiment of the present invention.

**[0047]** FIG. **7**O is a screenshot illustrating the CV-based identification activity in the workflow after the CV-based identification activity is configured with the target and anchors, according to an embodiment of the present invention.

**[0048]** FIG. **7**P is a screenshot illustrating a properties tab with the CV click with descriptor properties, according to an embodiment of the present invention.

**[0049]** FIG. **7**Q is a screenshot illustrating a unified target-based identification activity, according to an embodiment of the present invention.

**[0050]** FIG. **7**R is a screenshot illustrating the search interface with a unified target click activity highlighted, according to an embodiment of the present invention.

**[0051]** FIG. **7**S is a screenshot illustrating the unified target-based identification activity with a nested click activity, according to an embodiment of the present invention.

**[0052]** FIG. **7**T is a screenshot illustrating the Windows® 10 calculator as modified by UiPath Studio™ and a unified target selection options window, according to an embodiment of the present invention.

**[0053]** FIG. **7**U is a screenshot illustrating the Windows® 10 calculator as modified by UiPath Studio™ with a selected target and the unified target selection options window, according to an embodiment of the present invention.

**[0054]** FIG. **7**V is a screenshot illustrating the Windows® 10 calculator as modified by UiPath Studio™ with the selected target and a selected anchor, as well as the unified target selection options window, according to an embodiment of the present invention.

**[0055]** FIG. **7**W is a screenshot illustrating the Windows® 10 calculator as modified by UiPath Studio™ with the selected target and the selected anchor being validated via the unified target selection options window, according to an embodiment of the present invention.

**[0056]** FIG. **7**X is a screenshot illustrating the unified target-based identification activity with a screenshot of the target and anchor in the nested click activity, according to an embodiment of the present invention.

**[0057]** FIG. **7**Y is a screenshot illustrating a click image activity added to the workflow, according to an embodiment of the present invention.

**[0058]** FIG. **7**Z illustrates screenshots of the Windows® 10 calculator as modified by UiPath Studio™ with a box drawn around the image to be clicked and a screenshot of the image from the selection box in the click image activity, according to an embodiment of the present invention.

**[0059]** FIG. **7***a* is a screenshot illustrating the properties tab with click image activity properties, according to an embodiment of the present invention.

**[0060]** FIG. **7***b* is a screenshot illustrating the selector editor for a selector for the image to be clicked, according to an embodiment of the present invention.

**[0061]** FIG. **7***c* is a screenshot illustrating a click OCR text activity in the workflow, according to an embodiment of the present invention.

**[0062]** FIG. **7***d* is a screenshot illustrating the click OCR text activity with a screenshot of the button to be clicked, according to an embodiment of the present invention.

**[0063]** FIG. **8** is a flowchart illustrating a process for generating a selector-based activity, according to an embodiment of the present invention.

**[0064]** FIG. **9** is a flowchart illustrating a process for generating a CV descriptor-based activity, according to an embodiment of the present invention.

**[0065]** FIG. **10** is a flowchart illustrating a process for generating a unified target-based activity, according to an embodiment of the present invention.

**[0066]** FIG. **11** is a flowchart illustrating a process for generating an image matching activity, according to an embodiment of the present invention.

**[0067]** FIG. **12** is a flowchart illustrating a process for generating a selector and OCR-based activity, according to an embodiment of the present invention.

**[0068]** FIG. **13** is a flowchart illustrating a process for generating an RPA workflow that uses multiple identification techniques, according to an embodiment of the present invention.

**[0069]** FIG. **14** is a flowchart illustrating a process for creating a UI object library and configuring a project to work with a new version of an application, according to an embodiment of the present invention.

**[0070]** Unless otherwise indicated, similar reference characters denote corresponding features consistently throughout the attached drawings.

## DETAILED DESCRIPTION OF THE EMBODIMENTS

**[0071]** Some embodiments pertain to UI descriptors, UI object libraries, UI object repositories, and/or UI object browsers for RPA. UI elements on the screen (e.g., text fields, buttons, labels, menus, checkboxes, etc.) can be grouped by applications, application versions, application screens, and collections of UI elements, and each screen has multiple UI elements. As used herein, a "screen" is an image of an application UI or a portion of the application UI at a certain point in time. An "application" or a version of a given application may be a union of screens in this context. Each UI element may be described by one or more UI descriptors in some embodiments. The UI elements, UI descriptors, applications, and application screens are UI objects. In some embodiments, UI elements and screens may be further differentiated into specific types of UI elements (e.g., buttons, checkboxes, text fields, etc.) and screens (e.g., top windows, modal windows, popup windows, etc.).

**[0072]** A UI object browser may access libraries of UI objects that may be grouped by applications, application versions, application screens, collections of UI elements, a combination thereof, etc. The UI object libraries may be stored in a UI object repository in some embodiments. As used herein, the UI object repository is a collection of UI object libraries. In some embodiments, the UI object repository may be a NuGet™ feed, a web service, etc.

**[0073]** The object browser may be used in some embodiments for navigating, managing, and editing UI object libraries in the UI object repository. The UI object repository of UI object libraries in some embodiments may facilitate the managing, reusing, and increasing the reliability of UI descriptors in a project. UI descriptors may be added to UI libraries and be published or republished for global reuse in a UI object repository in some embodiments. The UI object browser, by providing access to the UI object repository and its UI object libraries, may facilitate reusability of UI element identification frameworks and derivatives thereof.

**[0074]** To make UI objects reusable, they may be extracted into UI object libraries that can be referenced by RPA processes. When selectors or other UI descriptors are modified due to a new version of an application, for example, the library may be recreated (or republished) to include the modified UI descriptors. RPA processes using the UI object library may then call the modified UI descriptor versions. References to the new application programming interface (API) associated with the new library may be modified for an RPA process manually by a developer, modified via a software tool (e.g., a tool that goes through an RPA process and updates UI descriptor references when selectors or other components thereof change), or automatically in some embodiments.

**[0075]** In some embodiments, packages of UI objects may be attached as a dependency (e.g., NuGet™ packages). However, in certain embodiments, the UI objects may be obtained via one or more API calls to a web service. This enables the UI objects to be stored remotely and retrieved and used during the automation.

**[0076]** Initial building of UI descriptors previously required developers with technical knowledge of what happens behind the UI descriptors. However, many RPA processes are no longer built by software developers. These individuals can create RPA workflows with UiPath StudioX™, for example, which does not require in-depth pro-

gramming knowledge. Some embodiments allow individuals creating RPA workflows to reuse descriptors, which provides time savings since a software developer is not required to build a new UI descriptor from scratch if a suitable UI descriptor is available to the individual creating the RPA workflow.

**[0077]** UI elements added to UI object libraries may represent selectors for use in RPA workflows. To automate specific actions in the UI, the RPA robot may interact with various windows, buttons, drop-down lists, and/or other graphical elements. Conventionally, this is done using the expected screen positions of UI elements. However, this is not dependable.

**[0078]** Some embodiments use selectors that overcome the problems associated with fixed coordinate identification by storing the attributes of a UI element and its parents in an XML fragment. While selectors may be automatically generated in some embodiments where the UI is static, some software programs, such as some web applications, have changing layouts and attribute nodes with volatile values. These changes may not be readily predictable, and this previously required manual generation of some selectors. However, the object browser of some embodiments may overcome this issue.

**[0079]** Selectors are a type of UI descriptor that may be used to detect UI elements in some embodiments. A selector has the following structure in some embodiments:

**[0080]** <node_1/><node_2/> . . . <node_N/>

**[0081]** The last node represents the GUI element of interest, and all previous nodes represent the parents of that element. <node_1> is usually referred to as a root node, and represents the top window of the application.

**[0082]** Each node may have one or more attributes that assist with correct identification of a specific level of the selected application. Each node has the following format in some embodiments:

**[0083]** <ui_system attr_name_1='attr_value_1' . . . attr_name_N='attr_value_N'/>

**[0084]** Every attribute may have an assigned value, and attributes with constant values may be selected. This is because changes to the value of an attribute each time the application is started may lead to the selector not being able to correctly identify the associated element.

**[0085]** UI object library descriptors may be added directly to an RPA workflow activity, saving developer time that may otherwise be required to create a custom selector for the activity. The object browser may provide a database storing created selectors in object libraries to enable the reusability of UI descriptors. An object library is defined herein as a collection of UI descriptors corresponding to one or more screens from a certain version of an application. A UI descriptor is a set of instructions for finding a UI element. UI descriptors in some embodiments are an encapsulated data/struct format that includes UI element selector(s), anchor selector(s), computer vision (CV) descriptor(s), unified target descriptor(s), a screen image capture (context), an element image capture, other metadata (e.g., the application and application version), a combination thereof, etc. The encapsulated data/struct format may be extensible with future updates to the platform and is not limited to the above definition. Any suitable UI descriptor for identifying a UI element on a screen may be used without deviating from the scope of the invention. A unified target descriptor chains together multiple types of UI descriptors. A unified target descriptor may function like a finite state machine (FSM), where in a first context, a first UI descriptor mechanism is applied, in a second context, a second UI descriptor is applied, etc.

**[0086]** In some embodiments, an RPA designer application may ask the user what type(s) of applications the user plans to automate. For instance, the user may specify Excel®, Workday®, SAP®, etc. The application may be programmed with logic regarding how to automate these applications since the RPA application already contains screen descriptors in UI object libraries for those applications. Out of the box selectors for various versions of these applications may be available, and the user may be able to designate version(s) to automate.

**[0087]** As used herein, the terms "user" and "developer" are used interchangeably. The user/developer may or may not have programming and/or technical knowledge. For instance, in some embodiments, the user/developer may create RPA workflows by configuring activities in the RPA workflow without manual coding. In certain embodiments, this may be done by clicking and dragging and dropping various features, for example.

**[0088]** Conventionally, making a selector reliable requires testing, understanding of intrinsic selector details, etc. This renders creating/refining selectors difficult or impossible for individuals without technical knowledge. By providing a library of working selectors for common UI elements and tasks, some embodiments allow development of automations that work in production by non-technical individuals. A user may indicate a screen of a version of an application to automate, and the RPA development application may fetch that screen. The user may then interact with the screen to define what he or she would like to do.

**[0089]** In some embodiments, as new UI descriptors are created and/or existing UI descriptors are modified, a global database of UI object libraries may be built that is sharable, collaborative, and potentially open source. In certain embodiments, taxonomies and ontologies may be used. Applications, versions, screens, UI elements, descriptors, etc. may be defined as a taxonomy, which is a hierarchical structure of subcategories.

**[0090]** However, many real-world concepts do not readily lend themselves to taxonomical organization. Rather, they may be closer to the concept of a mathematical ontology. In an ontology, the relationships between categories are not necessarily hierarchical. For instance, the case where a button on the screen takes the user to another screen when clicked cannot be readily capture by a taxonomy of that screen since the next screen is not in the hierarchy. When building graphs representing such a case, an object browser for an application may be modeled as an ontology that allows for the creation of interactions between UI elements on the same screen or different screens and provides more information on how UI elements relate to one another.

**[0091]** Consider the example where clicking an OK button leads to an employee screen. An ontological structure may cause the designer application to suggest that the user filter employees on the next screen. The ontological information of the relation between these screens via the OK button allows the designer application to do this. By defining a graphical structure that is not necessarily a tree, but rather, relates to what the application is actually doing, more complex and rich relationships can be captured.

**[0092]** Some embodiments pertain to or include a recorder that allows fetching screens and UI elements from an application faster. For instance, if a given screen has 250 different UI elements, it may take some time to fetch them one by one. A screen pointer may be used to fetch all UI elements that can then be edited. This may be helpful for creating the first version of the tree or ontology.

**[0093]** In some embodiments, the object browser may be exposed as a web service. If a user updates a selector or other UI descriptor, at runtime, an RPA robot may call the latest version of the service if appropriately configured. This allows the RPA robot to always use the current version of the UI descriptor.

**[0094]** UI descriptors may be extracted from activities in an RPA workflow and added to a structured schema that groups the UI descriptors by UI applications, screens, and UI elements. UI descriptors may be part of one project for wide reuse, part of global repositories for testing purposes, or part of UI object libraries for global cross-project sharing in some embodiments. An object library in some embodiments is an encapsulation of UI descriptors grouped by applications, application versions, and screens. UI descriptors can be defined and added to the object library, which can be installed in other projects as dependencies after publishing in some embodiments. This makes the object library of UI descriptors available for reuse. A UI application in some embodiments is a targeted application that has multiple versions where each version has multiple screens.

**[0095]** The UI object repository and UI descriptor reuse may be beneficial for a variety of reasons. For instance, if the location, appearance, and/or functionality of a UI element in an application changes, the UI descriptor may be changed, and the change may then be propagated to activities using the UI descriptor. Thus, reusability may be provided at the level of identifying graphical elements in a UI.

**[0096]** This may be especially beneficial for accommodating new versions of applications. For a new version, a software developer may only need to update UI descriptors and/or develop a few new selectors from scratch, substantially reducing development time. For a webpage, for instance, HyperText Markup Language (HTML) may be inspected to obtain paths to UI elements for the corresponding selectors. Selectors for corresponding UI elements may be different in different web browsers and/or different versions of the same web browser. This concept may and also apply to visual desktop, server, smart phone, and tablet applications. UI object libraries may contain the actual selectors for the application, which is just one type of UI descriptor, per the above. A UI object library may have multiple UI descriptors of different types for one or more applications. UI descriptors may also refer to different technologies with which the application is built. For instance, different UI descriptors may be created and used for standalone desktop, web, and mobile applications. For one technology, you may want to use selectors, for another, you may want to use CV descriptors, etc.

**[0097]** The UI descriptors may work with a unified target that encompasses all UI detection mechanisms through which image detection and definition are performed in some embodiments. The unified target may merge multiple techniques of identifying and automating UI elements into a single cohesive approach. The unified target may prioritize selector-based and driver-based UI detection mechanisms and fallback on CV to find an image if the first two mechanisms are not successful. A selector editor and UI explorer may be configured to support the unified target in some embodiments.

**[0098]** In some embodiments, the designer application includes a section or a panel as an "object browser" that loads object libraries from one or more sources. This object browser may allow a user to visualize the entire UI object set and use any of the UI descriptors via drag and drop and wizards or contextual actions. This may allow the user to choose an action to be performed in an RPA workflow activity, such as click, get text, type into, etc.

**[0099]** An example of an object library structure is provided below.

**[0100]** SAP
- **[0101]** version **1**
  - **[0102]** screen **1**
    - **[0103]** object **1**
    - **[0104]** object **2**
  - **[0105]** screen **2**
- **[0106]** version **2** . . .

**[0107]** Salesforce . . .

**[0108]** It should be noted that the hierarchy above is provided by way of example only. Any desired number of levels in the hierarchy and elements associated with each level may be used without deviating from the scope of the invention. In certain embodiments, the user can define the application map as he or she desires. Moreover, some nodes in the tree may only serve a management role and not a functional one in some embodiments. For instance, UI elements may be grouped together into a container that does not have UI descriptors. The container may exist for the purpose of grouping only in some embodiments.

**[0109]** A scope can be defined in the designer application by a user in some embodiments through a selection from a set of screens that are available in the object library. When the scope is tied 1-to-1 to a certain screen, the user can add UI actions (e.g., clicks, get text, etc.) and then use intelligent sensing of potential candidate options to map those actions to UI Objects. The set of objects may be limited to the list that is defined for the screen inside the UI object repository (e.g., a database of UI object libraries) in some embodiments.

**[0110]** For example, once the structure of the application screens, UI elements, etc. is determined, a list of identified applications may be provided. In certain embodiments, the user may then select an application for automation, drag the selected application to a canvas, write "SAP", press ".", and all SAP® screens may be listed. After selecting a screen, additional candidate elements, functions, etc. may appear. This allows the user to select the predicted UI elements, functions, applications, and screens.

**[0111]** In some embodiments, when an OLDB is configured in UiPath Studio™, for example, "indicate on screen" may look into the OLDB and pick up the UI descriptor, if available. If the UI descriptor is not available, the UI descriptor may be defined by the user by indicating the missing UI elements. The UI descriptor may then be generated and published in a UI object library.

**[0112]** Usage of the UI descriptors and UI object repository in some embodiments creates relationships and data that can be further expanded on. The UI steps from the automation process can be mapped to a single screen in some embodiments. For example, a screen that contains a form where the user adds and retrieves some data and then hits

submit can be documented with a single screenshot that contains the screen capture and each UI step performed on that screen, such as: (1) copied amount; (2) copied number; (3) added name; and (4) clicked "OK."

**[0113]** In case of upgrading processes affected by systems and applications upgrades, "find references" services may be implemented. The find references services may provide the ability to scan a set of projects from a repository and detect processes that are using UI descriptors that belong to a certain application version. The application version may be determined based on a corresponding screen of a UI descriptor in some embodiments. Further, a service may be implemented for detecting differences between UI descriptors that have matching elements from two different versions of an application. The detected processes and the differences of the UI descriptors provide information about processes that may break when an application or a system is upgraded. These processes may be automatically updated to use the UI descriptors from the new application version.

**[0114]** The OLDB UI object repository may be enhanced using OLDB analytics in some embodiments. A mechanism to extract a UI descriptor may be implemented. The extracted UI descriptor data may be sent via the OLDB analytics before or after creation/definition time. Further, the extracted UI descriptor data may give a set of new data that can be used to improve the strength of the UI descriptor for each UI element from any screen of any version of any application using artificial intelligence (AI) and machine learning (ML) techniques in some embodiments.

**[0115]** Certain embodiments may be employed for robotic process automation (RPA). FIG. **1** is an architectural diagram illustrating an RPA system **100**, according to an embodiment of the present invention. RPA system **100** includes a designer **110** that allows a developer to design and implement workflows. Designer **110** may provide a solution for application integration, as well as automating third-party applications, administrative Information Technology (IT) tasks, and business IT processes. Designer **110** may facilitate development of an automation project, which is a graphical representation of a business process. Simply put, designer **110** facilitates the development and deployment of workflows and robots.

**[0116]** The automation project enables automation of rule-based processes by giving the developer control of the execution order and the relationship between a custom set of steps developed in a workflow, defined herein as "activities." One commercial example of an embodiment of designer **110** is UiPath Studio™. Each activity may include an action, such as clicking a button, reading a file, writing to a log panel, etc. In some embodiments, workflows may be nested or embedded.

**[0117]** Some types of workflows may include, but are not limited to, sequences, flowcharts, FSMs, and/or global exception handlers. Sequences may be particularly suitable for linear processes, enabling flow from one activity to another without cluttering a workflow. Flowcharts may be particularly suitable to more complex business logic, enabling integration of decisions and connection of activities in a more diverse manner through multiple branching logic operators. FSMs may be particularly suitable for large workflows. FSMs may use a finite number of states in their execution, which are triggered by a condition (i.e., transition) or an activity. Global exception handlers may be particularly suitable for determining workflow behavior when encountering an execution error and for debugging processes.

**[0118]** Once a workflow is developed in designer **110**, execution of business processes is orchestrated by conductor **120**, which orchestrates one or more robots **130** that execute the workflows developed in designer **110**. One commercial example of an embodiment of conductor **120** is UiPath Orchestrator™. Conductor **120** facilitates management of the creation, monitoring, and deployment of resources in an environment. Conductor **120** may act as an integration point, or one of the aggregation points, with third-party solutions and applications.

**[0119]** Conductor **120** may manage a fleet of robots **130**, connecting and executing robots **130** from a centralized point. Types of robots **130** that may be managed include, but are not limited to, attended robots **132**, unattended robots **134**, development robots (similar to unattended robots **134**, but used for development and testing purposes), and non-production robots (similar to attended robots **132**, but used for development and testing purposes). Attended robots **132** may be triggered by user events or be scheduled to automatically happen, and operate alongside a human on the same computing system. Attended robots **132** may be used with conductor **120** for a centralized process deployment and logging medium. Attended robots **132** may help the human user accomplish various tasks, and may be triggered by user events. In some embodiments, processes cannot be started from conductor **120** on this type of robot and/or they cannot run under a locked screen. In certain embodiments, attended robots **132** can only be started from a robot tray or from a command prompt. Attended robots **132** should run under human supervision in some embodiments.

**[0120]** Unattended robots **134** run unattended in virtual environments or on physical machines, and can automate many processes. Unattended robots **134** may be responsible for remote execution, monitoring, scheduling, and providing support for work queues. Debugging for all robot types may be run from designer **110** in some embodiments. Both attended and unattended robots may automate various systems and applications including, but not limited to, mainframes, web applications, VMs, enterprise applications (e.g., those produced by SAP®, SalesForce®, Oracle®, etc.), and computing system applications (e.g., desktop and laptop applications, mobile device applications, wearable computer applications, etc.).

**[0121]** Conductor **120** may have various capabilities including, but not limited to, provisioning, deployment, versioning, configuration, queueing, monitoring, logging, and/or providing interconnectivity. Provisioning may include creating and maintenance of connections between robots **130** and conductor **120** (e.g., a web application). Deployment may include assuring the correct delivery of package versions to assigned robots **130** for execution. Versioning may include management of unique instances of some process or configuration in some embodiments. Configuration may include maintenance and delivery of robot environments and process configurations. Queueing may include providing management of queues and queue items. Monitoring may include keeping track of robot identification data and maintaining user permissions. Logging may include storing and indexing logs to a database (e.g., an SQL database) and/or another storage mechanism (e.g., ElasticSearch®, which provides the ability to store and quickly

query large datasets). Conductor **120** may provide interconnectivity by acting as the centralized point of communication for third-party solutions and/or applications.

**[0122]** Robots **130** are execution agents that run workflows built in designer **110**. One commercial example of some embodiments of robot(s) **130** is UiPath Robots™. In some embodiments, robots **130** install the Microsoft Windows® Service Control Manager (SCM)-managed service by default. As a result, such robots **130** can open interactive Windows® sessions under the local system account, and have the rights of a Windows® service.

**[0123]** In some embodiments, robots **130** can be installed in a user mode. For such robots **130**, this means they have the same rights as the user under which a given robot **130** has been installed. This feature may also be available for High Density (HD) robots, which ensure full utilization of each machine at its maximum potential. In some embodiments, any type of robot **130** may be configured in an HD environment.

**[0124]** Robots **130** in some embodiments are split into several components, each being dedicated to a particular automation task. The robot components in some embodiments include, but are not limited to, SCM-managed robot services, user mode robot services, executors, agents, and command line. SCM-managed robot services manage and monitor Windows® sessions and act as a proxy between conductor **120** and the execution hosts (i.e., the computing systems on which robots **130** are executed). These services are trusted with and manage the credentials for robots **130**. A console application is launched by the SCM under the local system.

**[0125]** User mode robot services in some embodiments manage and monitor Windows® sessions and act as a proxy between conductor **120** and the execution hosts. User mode robot services may be trusted with and manage the credentials for robots **130**. A Windows® application may automatically be launched if the SCM-managed robot service is not installed.

**[0126]** Executors may run given jobs under a Windows® session (i.e., they may execute workflows. Executors may be aware of per-monitor dots per inch (DPI) settings. Agents may be Windows® Presentation Foundation (WPF) applications that display the available jobs in the system tray window. Agents may be a client of the service. Agents may request to start or stop jobs and change settings. The command line is a client of the service. The command line is a console application that can request to start jobs and waits for their output.

**[0127]** Having components of robots **130** split as explained above helps developers, support users, and computing systems more easily run, identify, and track what each component is executing. Special behaviors may be configured per component this way, such as setting up different firewall rules for the executor and the service. The executor may always be aware of DPI settings per monitor in some embodiments. As a result, workflows may be executed at any DPI, regardless of the configuration of the computing system on which they were created. Projects from designer **110** may also be independent of browser zoom level in some embodiments. For applications that are DPI-unaware or intentionally marked as unaware, DPI may be disabled in some embodiments.

**[0128]** FIG. **2** is an architectural diagram illustrating a deployed RPA system **200**, according to an embodiment of the present invention. In some embodiments, RPA system **200** may be, or may be a part of, RPA system **100** of FIG. **1**. It should be noted that the client side, the server side, or both, may include any desired number of computing systems without deviating from the scope of the invention. On the client side, a robot application **210** includes executors **212**, an agent **214**, and a designer **216**. However, in some embodiments, designer **216** may not be running on computing system **210**. Executors **212** are running processes. Several business projects may run simultaneously, as shown in FIG. **2**. Agent **214** (e.g., a Windows® service) is the single point of contact for all executors **212** in this embodiment. All messages in this embodiment are logged into conductor **230**, which processes them further via database server **240**, indexer server **250**, or both. As discussed above with respect to FIG. **1**, executors **212** may be robot components.

**[0129]** In some embodiments, a robot represents an association between a machine name and a username. The robot may manage multiple executors at the same time. On computing systems that support multiple interactive sessions running simultaneously (e.g., Windows® Server 2012), multiple robots may be running at the same time, each in a separate Windows® session using a unique username. This is referred to as HD robots above.

**[0130]** Agent **214** is also responsible for sending the status of the robot (e.g., periodically sending a "heartbeat" message indicating that the robot is still functioning) and downloading the required version of the package to be executed. The communication between agent **214** and conductor **230** is always initiated by agent **214** in some embodiments. In the notification scenario, agent **214** may open a WebSocket channel that is later used by conductor **230** to send commands to the robot (e.g., start, stop, etc.).

**[0131]** On the server side, a presentation layer (web application **232**, Open Data Protocol (OData) Representative State Transfer (REST) Application Programming Interface (API) endpoints **234**, and notification and monitoring **236**), a service layer (API implementation/business logic **238**), and a persistence layer (database server **240** and indexer server **250**) are included. Conductor **230** includes web application **232**, OData REST API endpoints **234**, notification and monitoring **236**, and API implementation/business logic **238**. In some embodiments, most actions that a user performs in the interface of conductor **230** (e.g., via browser **220**) are performed by calling various APIs. Such actions may include, but are not limited to, starting jobs on robots, adding/removing data in queues, scheduling jobs to run unattended, etc. without deviating from the scope of the invention. Web application **232** is the visual layer of the server platform. In this embodiment, web application **232** uses Hypertext Markup Language (HTML) and JavaScript (JS). However, any desired markup languages, script languages, or any other formats may be used without deviating from the scope of the invention. The user interacts with web pages from web application **232** via browser **220** in this embodiment in order to perform various actions to control conductor **230**. For instance, the user may create robot groups, assign packages to the robots, analyze logs per robot and/or per process, start and stop robots, etc.

**[0132]** In addition to web application **232**, conductor **230** also includes service layer that exposes OData REST API endpoints **234**. However, other endpoints may be included without deviating from the scope of the invention. The REST API is consumed by both web application **232** and

agent **214**. Agent **214** is the supervisor of one or more robots on the client computer in this embodiment.

**[0133]** The REST API in this embodiment covers configuration, logging, monitoring, and queueing functionality. The configuration endpoints may be used to define and configure application users, permissions, robots, assets, releases, and environments in some embodiments. Logging REST endpoints may be used to log different information, such as errors, explicit messages sent by the robots, and other environment-specific information, for instance. Deployment REST endpoints may be used by the robots to query the package version that should be executed if the start job command is used in conductor **230**. Queueing REST endpoints may be responsible for queues and queue item management, such as adding data to a queue, obtaining a transaction from the queue, setting the status of a transaction, etc.

**[0134]** Monitoring REST endpoints may monitor web application **232** and agent **214**. Notification and monitoring API **236** may be REST endpoints that are used for registering agent **214**, delivering configuration settings to agent **214**, and for sending/receiving notifications from the server and agent **214**. Notification and monitoring API **236** may also use WebSocket communication in some embodiments.

**[0135]** The persistence layer includes a pair of servers in this embodiment—database server **240** (e.g., a SQL server) and indexer server **250**. Database server **240** in this embodiment stores the configurations of the robots, robot groups, associated processes, users, roles, schedules, etc. This information is managed through web application **232** in some embodiments. Database server **240** may manages queues and queue items. In some embodiments, database server **240** may store messages logged by the robots (in addition to or in lieu of indexer server **250**).

**[0136]** Indexer server **250**, which is optional in some embodiments, stores and indexes the information logged by the robots. In certain embodiments, indexer server **250** may be disabled through configuration settings. In some embodiments, indexer server **250** uses ElasticSearch®, which is an open source project full-text search engine. Messages logged by robots (e.g., using activities like log message or write line) may be sent through the logging REST endpoint (s) to indexer server **250**, where they are indexed for future utilization.

**[0137]** FIG. **3** is an architectural diagram illustrating the relationship **300** between a designer **310**, activities **320**, **330**, and drivers **340**, according to an embodiment of the present invention. Per the above, a developer uses designer **310** to develop workflows that are executed by robots. Workflows may include user-defined activities **320** and UI automation activities **330**. Some embodiments are able to identify non-textual visual components in an image, which is called computer vision (CV) herein. Some CV activities pertaining to such components may include, but are not limited to, click, type, get text, hover, element exists, refresh scope, highlight, etc. Click in some embodiments identifies an element using CV, optical character recognition (OCR), fuzzy text matching, and multi-anchor, for example, and clicks it. Type may identify an element using the above and types in the element. Get text may identify the location of specific text and scan it using OCR. Hover may identify an element and hover over it. Element exists may check whether an element exists on the screen using the techniques described above. In some embodiments, there may be hundreds or even thousands of activities that can be implemented in designer **310**. However, any number and/or type of activities may be available without deviating from the scope of the invention.

**[0138]** UI automation activities **330** are a subset of special, lower level activities that are written in lower level code (e.g., CV activities) and facilitate interactions with applications through the UI layer. In certain embodiments, UI automation activities **300** may simulate" user input through window messages or the like, for example. UI automation activities **330** facilitate these interactions via drivers **340** that allow the robot to interact with the desired software. For instance, drivers **340** may include OS drivers **342**, browser drivers **344**, VM drivers **346**, enterprise application drivers **348**, etc.

**[0139]** Drivers **340** may interact with the OS at a low level looking for hooks, monitoring for keys, etc. They may facilitate integration with Chrome®, IE®, Citrix®, SAP®, etc. For instance, the "click" activity performs the same role in these different applications via drivers **340**.

**[0140]** FIG. **4** is an architectural diagram illustrating an RPA system **400**, according to an embodiment of the present invention. In some embodiments, RPA system **400** may be or include RPA systems **100** and/or **200** of FIGS. **1** and/or **2**. RPA system **400** includes multiple client computing systems **410** running robots. Computing systems **410** are able to communicate with a conductor computing system **420** via a web application running thereon. Conductor computing system **420**, in turn, is able to communicate with a database server **430** and an optional indexer server **440**.

**[0141]** With respect to FIGS. **1** and **3**, it should be noted that while a web application is used in these embodiments, any suitable client and/or server software may be used without deviating from the scope of the invention. For instance, the conductor may run a server-side application that communicates with non-web-based client software applications on the client computing systems.

**[0142]** FIG. **5** is an architectural diagram illustrating a computing system **500** configured to provide UI descriptors, UI object libraries, UI object repositories, and/or object browsers for RPA, according to an embodiment of the present invention. In some embodiments, computing system **500** may be one or more of the computing systems depicted and/or described herein. Computing system **500** includes a bus **505** or other communication mechanism for communicating information, and processor(s) **510** coupled to bus **505** for processing information. Processor(s) **510** may be any type of general or specific purpose processor, including a Central Processing Unit (CPU), an Application Specific Integrated Circuit (ASIC), a Field Programmable Gate Array (FPGA), a Graphics Processing Unit (GPU), multiple instances thereof, and/or any combination thereof. Processor (s) **510** may also have multiple processing cores, and at least some of the cores may be configured to perform specific functions. Multi-parallel processing may be used in some embodiments. In certain embodiments, at least one of processor(s) **510** may be a neuromorphic circuit that includes processing elements that mimic biological neurons. In some embodiments, neuromorphic circuits may not require the typical components of a Von Neumann computing architecture.

**[0143]** Computing system **500** further includes a memory **515** for storing information and instructions to be executed by processor(s) **510**. Memory **515** can be comprised of any

combination of Random Access Memory (RAM), Read Only Memory (ROM), flash memory, cache, static storage such as a magnetic or optical disk, or any other types of non-transitory computer-readable media or combinations thereof. Non-transitory computer-readable media may be any available media that can be accessed by processor(s) **510** and may include volatile media, non-volatile media, or both. The media may also be removable, non-removable, or both.

**[0144]** Additionally, computing system **500** includes a communication device **520**, such as a transceiver, to provide access to a communications network via a wireless and/or wired connection. In some embodiments, communication device **520** may be configured to use Frequency Division Multiple Access (FDMA), Single Carrier FDMA (SC-FDMA), Time Division Multiple Access (TDMA), Code Division Multiple Access (CDMA), Orthogonal Frequency Division Multiplexing (OFDM), Orthogonal Frequency Division Multiple Access (OFDMA), Global System for Mobile (GSM) communications, General Packet Radio Service (GPRS), Universal Mobile Telecommunications System (UMTS), cdma2000, Wideband CDMA (W-CDMA), High-Speed Downlink Packet Access (HSDPA), High-Speed Uplink Packet Access (HSUPA), High-Speed Packet Access (HSPA), Long Term Evolution (LTE), LTE Advanced (LTE-A), 802.11x, Wi-Fi, Zigbee, Ultra-WideB and (UWB), 802.16x, 802.15, Home Node-B (HnB), Bluetooth, Radio Frequency Identification (RFID), Infrared Data Association (IrDA), Near-Field Communications (NFC), fifth generation (5G), New Radio (NR), any combination thereof, and/or any other currently existing or future-implemented communications standard and/or protocol without deviating from the scope of the invention. In some embodiments, communication device **520** may include one or more antennas that are singular, arrayed, phased, switched, beamforming, beamsteering, a combination thereof, and or any other antenna configuration without deviating from the scope of the invention.

**[0145]** Processor(s) **510** are further coupled via bus **505** to a display **525**, such as a plasma display, a Liquid Crystal Display (LCD), a Light Emitting Diode (LED) display, a Field Emission Display (FED), an Organic Light Emitting Diode (OLED) display, a flexible OLED display, a flexible substrate display, a projection display, a **4**K display, a high definition display, a Retina ° display, an In-Plane Switching (IPS) display, or any other suitable display for displaying information to a user. Display **525** may be configured as a touch (haptic) display, a three dimensional (3D) touch display, a multi-input touch display, a multi-touch display, etc. using resistive, capacitive, surface-acoustic wave (SAW) capacitive, infrared, optical imaging, dispersive signal technology, acoustic pulse recognition, frustrated total internal reflection, etc. Any suitable display device and haptic I/O may be used without deviating from the scope of the invention.

**[0146]** A keyboard **530** and a cursor control device **535**, such as a computer mouse, a touchpad, etc., are further coupled to bus **505** to enable a user to interface with computing system **500**. However, in certain embodiments, a physical keyboard and mouse may not be present, and the user may interact with the device solely through display **525** and/or a touchpad (not shown). Any type and combination of input devices may be used as a matter of design choice. In certain embodiments, no physical input device and/or display is present. For instance, the user may interact with computing system **500** remotely via another computing system in communication therewith, or computing system **500** may operate autonomously.

**[0147]** Memory **515** stores software modules that provide functionality when executed by processor(s) **510**. The modules include an operating system **540** for computing system **500**. The modules further include a UI object operations module **545** that is configured to perform all or part of the processes described herein or derivatives thereof. Computing system **500** may include one or more additional functional modules **550** that include additional functionality.

**[0148]** One skilled in the art will appreciate that a "system" could be embodied as a server, an embedded computing system, a personal computer, a console, a personal digital assistant (PDA), a cell phone, a tablet computing device, a quantum computing system, or any other suitable computing device, or combination of devices without deviating from the scope of the invention. Presenting the above-described functions as being performed by a "system" is not intended to limit the scope of the present invention in any way, but is intended to provide one example of the many embodiments of the present invention. Indeed, methods, systems, and apparatuses disclosed herein may be implemented in localized and distributed forms consistent with computing technology, including cloud computing systems.

**[0149]** It should be noted that some of the system features described in this specification have been presented as modules, in order to more particularly emphasize their implementation independence. For example, a module may be implemented as a hardware circuit comprising custom very large scale integration (VLSI) circuits or gate arrays, off-the-shelf semiconductors such as logic chips, transistors, or other discrete components. A module may also be implemented in programmable hardware devices such as field programmable gate arrays, programmable array logic, programmable logic devices, graphics processing units, or the like.

**[0150]** A module may also be at least partially implemented in software for execution by various types of processors. An identified unit of executable code may, for instance, include one or more physical or logical blocks of computer instructions that may, for instance, be organized as an object, procedure, or function. Nevertheless, the executables of an identified module need not be physically located together, but may include disparate instructions stored in different locations that, when joined logically together, comprise the module and achieve the stated purpose for the module. Further, modules may be stored on a computer-readable medium, which may be, for instance, a hard disk drive, flash device, RAM, tape, and/or any other such non-transitory computer-readable medium used to store data without deviating from the scope of the invention.

**[0151]** Indeed, a module of executable code could be a single instruction, or many instructions, and may even be distributed over several different code segments, among different programs, and across several memory devices. Similarly, operational data may be identified and illustrated herein within modules, and may be embodied in any suitable form and organized within any suitable type of data structure. The operational data may be collected as a single data set, or may be distributed over different locations including over different storage devices, and may exist, at least partially, merely as electronic signals on a system or network.

**[0152]** Some embodiments store object libraries of collections of UI descriptors corresponding to a screen from a certain version of an application in a database. The object library may be created by an RPA designer application (e.g., UiPath Studio™) when a user is developing an RPA UI automation. This may assist in creating a more extensible and adaptable collection of UI objects that can be used to accommodate post-design time changes, such as new versions of applications.

**[0153]** Consider the case where an employee uses one or more RPA robots to perform tasks on software applications running on his or her computer. The information technology (IT) department then upgrades software applications with which the RPA robot interacts. If the company's RPA team did not make changes to the modified UI descriptors called the RPA robot workflows in advance, some of the RPA processes may now be broken since the RPA robots can no longer find certain UI elements in the applications due to the changes in the new versions (e.g., changed UI element functionality and/or appearance, UI elements being removed entirely or moved to a new screen, etc.). If the UI descriptors for the UI elements for both versions already exist, the UI descriptors for the new version could be swapped with the UI descriptors for the previous version in the appropriate activities of the RPA workflows, and the RPA robots should then work on the new version.

**[0154]** FIG. **6**A is a screenshot illustrating an RPA designer application **600**, according to an embodiment of the present invention. RPA designer application **600** includes a main RPA development pane **610** that includes an RPA workflow **612** (in this example, a sequence). A "snippets" pane **620** includes reusable components or common automation items that are reusable and applicable in multiple workflows. A properties pane **640** shows properties of a selected activity **614** of RPA workflow **612**.

**[0155]** In this embodiment, RPA workflow **612** performs a sequence of actions on standard screen (or window) **670** of the Windows® 7 calculator. See FIG. **6**B. The user can select from different screens for different calculator settings using view tab **672**. The sequence of actions in RPA workflow **612** is clicking button 2, clicking the plus button, clicking button 3, clicking the equals button, getting the text for the result, clicking the clear button, and writing the result via a "write line" operation. An enlarged view of the sequence in outline pane **630** is shown in FIG. **6**C.

**[0156]** An enlarged view of snippets pane **620** is shown in FIG. **6**D. Snippets pane **620** includes workflow snippets, which may be ready-made workflows that the developer can invoke/include in his or her own workflows (e.g., RPA workflow **612**) in RPA designer application **600**. Snippets pane **620** may provide a sandbox where a team a company, all interested developers, or any other group of developers can save UI descriptors for elements to be automated in some embodiments. Snippets pane **620** includes UI descriptors **621**, which are arranged by application. Under calculator application **622**, the Windows® 10 selectors are organized under Windows® 10 version **623**, standard window **624**, target UI elements **625**, and respective UI element selectors **626**. The Windows® 7 selectors are organized under Windows® 7 version **623**A, standard window **624**A, target UI elements **625**A, and respective UI element selectors **626**A. While selectors are used in this embodiment, CV descriptors, unified target descriptors, or both, could be included in addition to or in lieu of the UI element selectors in some embodiments.

**[0157]** FIGS. **6**E and **6**F show activities of the sequence of RPA workflow **612**. Screen captures of the portions of the Windows 7° standard calculator screen that correspond with each of the activities are shown for that activity and highlighted, where applicable. The respective UI elements for the activities may have been selected using "indicate" functionality in UiPath Studio™, for example, as is discussed in more detail later herein with respect to using multiple UI descriptor types for an activity. In this manner, the user can visually verify that the RPA workflow should interact with the desired UI element. By clicking a button **615** for activities that interact with UI elements, a menu **616** appears. See FIG. **6**G. The user may add the respective UI object to an object browser by selecting add to UI objects option **618**.

**[0158]** FIG. **6**H illustrates RPA designer application **600** with properties for a click activity shown in a properties pane **640**. FIG. **6**I shows an enlarged view of properties pane **640**. At the bottom of properties pane **640**, the user can select a UI object browser via UI object browser tab **652**.

**[0159]** FIG. **6**J illustrates RPA designer application **600** with a UI descriptors view of UI object browser pane **650** and FIG. **6**K shows an enlarged view of UI object browser pane **650** with a UI descriptors view. The UI descriptors view includes project UI descriptors **654**A and UI object libraries **656**A. In FIG. **6**K, no UI descriptors have been selected yet for the project.

**[0160]** In order to add the UI descriptors, the developer may add these using snippets pane **620**. For instance, the developer may right click on Windows® 7 version **623**A in snippets pane **620**, which causes a menu **627** to appear. The developer may select to add these UI descriptors to the project, which causes them to appear under project UI descriptors **654**A in UI object browser pane **650**, which shows them as UI descriptors **658**A. See FIG. **6**L. In the UI activities view of UI object browser pane **650** shown in FIG. **6**M, the project **654**B and UI activities **656**B are shown. While an RPA workflow may have various activities of different types, the UI activities view lists UI activities **656**B so the developer can readily view them. UI activities **656**B can be extracted and have a similar structure to that shown in snippets pane **620**. In certain embodiments, all UI descriptors that have been developed and are shared in a library may be displayed in snippets pane **620** whereas only UI descriptors that are used by UI activities appear in the UI activities view of UI object browser pane **650**.

**[0161]** Once the selectors are in object browser pane **650**, the user can drag-and-drop a given selector into the desired activity, as shown in FIG. **6**N. This provides reusability at the project level. In some embodiments, other UI descriptors, such as CV descriptors, unified target descriptors, etc., may be dragged and dropped into desired activities in addition to or in lieu of selectors. Once the selectors have been dropped into the respective activities, RPA workflow **612** is ready to be execute by an RPA robot to interact with the respective UI elements.

**[0162]** Consider the case where the developer would like to perform the same RPA process for the Windows® 10 calculator (see Windows® 10 calculator **680** of FIG. **6**O). Running the RPA process as designed for the Windows® 7 calculator would likely fail for activities interacting with

various UI elements since the UI elements of the Windows® 10 calculator are substantially different from those of the Windows® 7 calculator. See FIG. **6**B. If selectors have already been developed for the Windows® 10 calculator and are available in a published library of UI descriptors in snippets pane **620**, as is the case in this example, the user may delete the selectors for the Windows® 7 calculator and add the selectors for the Windows® 10 calculator, which then appear in the UI activities view of UI object browser pane **650**. See FIG. with Windows® 10 calculator selectors, according to an embodiment of the present invention.

**[0163]** When the target application is set to the Windows® 10 calculator, the screenshot portions for each activity and the respective selectors are updated in RPA workflow **612**. See FIG. **6**Q. RPA workflow **612** will not execute correctly on the Windows® 10 calculator. This provides reusability at the project level. However, the selectors are inside this project specifically and are not yet available globally as a UI object library.

**[0164]** In order to "upgrade" the calculator application, the UI descriptors for the UI elements are changed to those for the new version of the application. For instance, a NuGet™ package that includes these UI descriptors may be created, uploaded, and then retrieved. Thus, when the dependency for the UI elements is changed, the UI descriptors will be updated.

**[0165]** In order to provide reusability at the global level such that all processes can use the UI descriptors, UI object libraries **656**A may be used. By clicking publish button **658** in this embodiment (see FIG. **6**P), a publish UI object library window **660** appears. See FIG. **6**R. This allows the selectors and/or other UI descriptors from the project to be published into a package (e.g., into a NuGet™ package) that can be accessed and utilized by other developers for other RPA processes after publication via a manage packages window **662**. See FIG. **6**S. Installing this package of calculator descriptors as a dependency for a project causes the selectors/UI descriptors to appear under libraries **656**A in UI object browser pane **650**. See FIG. **6**T. The UI object library may then be used for the given project. As a best practice, selectors and/or other UI descriptors for interacting with UI elements may be imported from UI object libraries as dependencies only if reuse is desired. However, if a given selector or other UI descriptor is specific to the given project and unlikely to be reused, certain selectors/UI descriptors may eb created locally for the project and others may be imported from UI object libraries.

**[0166]** FIG. **7**A is a screenshot illustrating an RPA designer application **700**, according to an embodiment of the present invention. RPA designer application **700** includes a main RPA development pane **702** that includes an RPA workflow **710** (in this example, a sequence that includes different UI element identification activities). A project pane **704** includes the dependencies for the current project. A UI descriptors pane **706** currently includes no selections for project UI descriptors and UI object libraries.

**[0167]** FIG. **7**B is an enlarged view illustrating RPA workflow **710**. Activity **720** will use selector-based identification, activity **730** will use CV-based identification, and activity **740** will use unified target-based identification. The configuration of activities **720**, **730**, **740** for this example is described below.

**[0168]** FIG. **7**C illustrates Windows® 10 calculator **750** as modifiable by UiPath Studio™. When the user selects "indicate on screen" **721** for selector-based identification activity **720** (see FIG. **7**B), recognized elements of the UI that the developer moves the mouse over are highlighted. For instance, in FIG. **7**C the 9 button **752** is highlighted. When the user clicks on 9 button **752**, a screenshot **722** including the selected UI element appears in selector-based identification activity **720**. See FIG. **7**D.

**[0169]** By clicking button **724** of selector-based identification activity **720**, a menu **725** appears. See FIG. **7**E. Choosing the "Edit Selector" option opens a selector editor **726**. See. FIG. **7**F. Selector editor **726** allows the developer to edit attributes of the selector and validate that the selector finds the respective UI element in Windows® 10 calculator **750** (i.e., 9 button **752**). Selecting "Highlight" causes the respective UI element to be highlighted on Windows® 10 calculator **750**. After the selector is created, the developer can click button **724** of selector-based identification activity **720** and choose the "Add to UI Objects" option on menu **725**, which causes an add to UI objects library window **728** to appear. See FIG. **7**G. The developer can then add the created selector for the 9 button to a UI object library for the project. The selector now appears in UI descriptors pane **706**. See FIG. **7**H.

**[0170]** In order to configure CV-based identification activity **730**, the user should first indicate the screen on which CV is to be performed in this embodiment. When the user selects "indicate on screen" **731** (see FIG. **7**B), the user clicks on the UI of Windows® 10 calculator **750**, which causes UiPath Studio™ to detect elements (using CV) and labels (using the selected OCR engine **732**—in this case, Microsoft® OCR), causing a message **733** to appear. See FIG. **7**I. Once the elements and labels in the UI of Windows® 10 calculator **750** are detected, a screenshot of detected UI elements **734** appears in CV-based identification activity **730**. See FIG. **7**K. A CV click activity **735** may be used that can be configured to use CV to identify the 9 button. This activity may be added as a nested activity within CV-based identification activity **730** using search interface **708**, which may appear when the developer clicks the plus icon in a given activity. See FIG. **7**J.

**[0171]** When the developer clicks indicate on scope **736** for CV click activity **735**, Windows® 10 calculator **750** appears with a CV click interface **754**. See FIG. **7**L. However, when the user clicks on 9 button **752**, this button is not uniquely recognized using CV. See FIG. **7**M. CV click interface **754** displays a message to the developer that duplicate matches were found and asks the developer to add an anchor. The developer then adds anchors for 9 button **752** (e.g., selected anchors **756**, **757** and candidate anchor **758** using anchor selection functionality) until button 9 **752** is uniquely identified as a target UI element based on its relation to other anchor UI elements in Windows® 10 calculator **750**. After the CV descriptor for 9 button **752** uniquely identifies it using the target and anchor(s), a screenshot **737** appears in CV click activity **735**. See FIG. **7**O. In FIG. **7**O, screenshot **737** shows a version without the target and anchors having been properly selected, but this is shown by way of example only. In certain embodiments, the CV descriptor may be saved without configuring it to uniquely identify the target UI element.

**[0172]** The developer may view the CV click with descriptor properties using a properties tab **760**. See FIG. **7**P. This provides various variables of the CV descriptor. However, unlike selectors, the underlying attributes of the selector for

the CV descriptor may be complex and pertain to the application of an AI/ML model to the image. Thus, while a CV selector is provided, it may not be readily accessible or modifiable by the developer in some embodiments. Instead, the developer may re-indicate the target UI element in order to edit the CV descriptor/selector. This also means that even non-technical users may indicate targets/anchors in some embodiments. A collection of UI elements on the screen and the UI element that the developer wishes to click may be saved as part of CV-based identification activity **730**.

**[0173]** With respect to unified target-based identification activity **740**, when the developer selects "Indicate Application" **741** (see FIG. **7**B), the user clicks on the UI of Windows® 10 calculator **750**, which causes UiPath Studio™ to capture a screenshot **743** of the UI and display screenshot **743** in unified target-based identification activity **740**. See FIG. **7**Q. An application path **744** for the application associated with screenshot **743** also is shown, and the developer may add application arguments **745**, if desired. A do activity **742** is nested in unified target-based identification activity **740**. When the developer clicks the plus icon, search interface **708** appears. See FIG. **7**R. The developer may then search for the desired click functionality.

**[0174]** The selected click option causes a nested click activity **746** to appear within do activity **742**. See FIG. **7**S. Click activity **746** includes an indicate on screen button **747** that enables the developer to indicate a target to be selected and clicked on the screen. The developer can also specify the click type and the mouse button to be clicked. In this case, a single left click is specified.

**[0175]** Clicking indicate on screen button **747** causes a unified target selection options window **770** to appear. See FIG. **7**T. Unified target adds targets and/or anchors based on images and uses a selector-based framework behind the scenes. Hovering the mouse over the 9 button causes a target UI element outline **772** to appear. When the user clicks on the 9 button, it is selected as the target, and this status is indicated on target UI element outline **772**. See FIG. **7**U. Various option icons also appear, including anchor designation icon **774**. In this embodiment, UiPath Studio™ attempted to find a suitable anchor automatically, but was unable to do so.

**[0176]** The developer designates an anchor **776** (in this case, the 8 button), and the combination of these elements allows the unified target logic to uniquely identify the target 9 button using the combination of the target and the anchor 8 button. See FIG. **7**V. This causes unified target selection options window **770** to confirm that the target and anchors are OK, and the designer can validate the target and anchor selectors, confirm the selections, or cancel. Here, the developer chooses to validate the target and anchor selectors, and unified target selection options window **770** confirms that the validation was successful with a validation accuracy score of 100% shown in validation score notification **778**. See FIG. **7**W. After indicating that the target and anchor selectors are OK, a screenshot **748** of the target and anchor appears. See FIG. **7**X. In certain embodiments, CV techniques may be used within the unified target framework.

**[0177]** In some embodiments, image matching may be employed to find UI elements. For instance, a click image activity **780** has been added in FIG. **7**Y. When the developer selects "indicate image on screen" **782**, the developer may define an image for image searching. In FIG. **7**Z, the developer drags a box **784** around the 9 button, and a screenshot **786** of the 9 button appears in click image activity **780**. Properties of click image activity appear in properties tab **760**. See FIG. **7***a*. A selector for the image is generated as well, as shown in selector editor **726** of FIG. **7***b*. The selector captures the application from which the developer took the snapshot.

**[0178]** In certain embodiments, a combination of a selector and OCR may be used. FIG. **7***c* shows a click OCR text activity **790** that includes a field **794** where a developer can manually input text to search for and an OCR engine **796**. In this embodiment, when the user clicks "Indicate on screen" **792**, the user selects a UI element in a similar manner to the selector-based approach (see FIG. **7**C). After the selection of the UI element, a screenshot **798** of the selected UI element appears in click OCR text activity **790**. See FIG. **7***d*. However, unlike the selector-based approach, the selector and OCR approach additionally employs OCR to identify the UI element. For instance, while many of the calculator buttons have the same shape, only one button has each number.

**[0179]** FIG. **8** is a flowchart illustrating a process **800** for generating a selector-based activity, according to an embodiment of the present invention. The process begins with generating a selector-based activity at **810**. The activity may click a button, enter text, open a menu and select an option, etc. An indicate on screen command is received at **820**, and the application is detected at **830**. This may include autodetecting an application, detecting a version of the application, and/or detecting a screen within the application in some embodiments. If the application is not autodetected, detecting the application may include requesting for a user to provide the application name and version. For instance, a dropdown list may be provided to the user to provide the application name and the application version if multiple applications are detected and/or the user may enter this information manually.

**[0180]** A series of activities may be provided that allow the developer to create the desired RPA process. Some activities may allow users use to indicate screens/applications. When a user wishes to perform an automation, the user may indicate a screen, a UI element on the screen, etc., that activities should interact with. Certain activities may open applications. This may include opening a desktop application, navigating using a URL, etc.

**[0181]** The UI elements on the application screen are detected at **840**. The detected elements may be highlighted for the user to generate a UI model in some embodiments. The detected UI elements may be organized as a taxonomy, or tree, as a model of the screen. However, in certain embodiments, a non-taxonomical approach may be used, such as an ontology. Ontologies may define certain structural and logical relationships between screens. For instance, if the "Submit" button is clicked on one screen, this may cause another screen to appear with at least some different UI elements. Also, certain UI elements and/or portions of the screen may be common to multiple screens. For instance, in Microsoft Outlook®, the left rail navigation subscreen typically does not change and may be reusable between screens. Knowing which subscreens and/or UI elements do not change may reduce processing time.

**[0182]** An indication of the UI element for the activity is received from the user at **850**. This may include clicking a desired UI element in some embodiments. An out-of-the-box selector is generated for the indicated UI element using

a driver (e.g., driver **340**) based on a best match for the UI element and the activity is configured accordingly at **860**.

**[0183]** FIG. **9** is a flowchart illustrating a process **900** for generating a CV descriptor-based activity, according to an embodiment of the present invention. The process begins with generating a CV descriptor-based activity at **910**. An indicate on screen command and a user selection of the screen to automate are received at **920**. For instance, the user may select an entire application interface in some embodiments. The application is detected at **930** and the UI elements on the application screen are detected at **940** using CV.

**[0184]** A command is received to designate UI elements for an interaction and the interface is displayed with selectable UI elements detected by CV at **950**. A selection of a target UI element is then received from the user at **960**. If the target can be uniquely identified at **970**, the CV descriptor is generated and the activity is configured accordingly at **980**. However, if the target cannot be uniquely identified at **970**, anchor designations are required and received from the user until the target can be uniquely identified at **990**. The process then proceeds to step **980** to generate the CV descriptor and configure the activity.

**[0185]** FIG. **10** is a flowchart illustrating a process **1000** for generating a unified target-based activity, according to an embodiment of the present invention. An indicate application command and a user selection of the screen to automate are received at **1020**. For instance, the user may select an entire application interface in some embodiments. The application is detected at **1030** and the UI elements on the application screen are detected at **1040** using the driver, for example.

**[0186]** A command is received to designate UI elements for an interaction and the interface is displayed with selectable UI elements detected by the driver at **1050**. A selection of a target UI element is then received from the user at **1060**. If the target can be uniquely identified at **1070** using the selector for that element alone, the unified target descriptor is generated (e.g., a selector) and the activity is configured accordingly at **1080**. However, if the target cannot be uniquely identified at **1070**, anchor designations are required and received from the user until the target can be uniquely identified at **1090**. In some embodiments, this may include validating the target and anchor(s) by determining a validation score. The process then proceeds to step **1080** to generate the unified target descriptor (e.g., selectors for the target and anchor(s) and positional/geometric relationships therebetween) and configure the activity.

**[0187]** In order to determine whether UI elements are uniquely identified, a strength computation (e.g., a validation score) may be used to determine how well the target UI element is believed to match based on the unified target UI descriptor. If the strength computation is below a threshold (e.g., below 97%, below 95%, etc.), it is possible that the UI element may not be determined as accurately as desired at runtime. The acceptable accuracy may vary based on task(s) being accomplished by the RPA workflow. UI element targets falling below the threshold may require anchors for unique identification. These anchors may be determined automatically and displayed to the user, or the user may mouse over UI elements to select anchors. Unified target descriptor strength due to adding a given anchor may be shown to the user in some embodiments. If the threshold still is not met after adding an anchor, the user may be required to continue adding additional anchors until the threshold is met for the target UI element.

**[0188]** Anchors are other UI elements on the screen that can be used to assist in uniquely identifying a target UI element on the screen. For instance, if multiple text fields are included on a screen, searching for a text field alone is insufficient to uniquely identify a given text field. Accordingly, some embodiments look for additional information in order to uniquely identify a given UI element. Using the text field example, a text field for entering a first name may appear to the right of the label "First Name". This first name label may be set as an "anchor" to help to uniquely identify the text field for the selector, which is the "target".

**[0189]** Various positional and/or geometric associations between the target and the anchor may be used in some embodiments, potentially within a tolerance, to uniquely identify the target. For instance, the center of a bounding box for the anchor and the target may be used to define a line segment. This line segment could then be required to have a certain length within a tolerance and/or slope within a tolerance to uniquely identify the target using the target/anchor pair.

**[0190]** In some cases, a single anchor may not be sufficient to uniquely identify a target element on a screen. For instance, consider the case where two text field for entering a first name appear to the right of respective labels "First Name" in different locations on the screen. In such cases, one or more additional anchors may be useful to uniquely identify a given target. The geometric properties between the anchors and the target (e.g., line segment lengths, angles, and/or relative locations with tolerances) may be used to uniquely identify the target. The user may be required to continue to add anchors until a match strength for the target exceeds the threshold.

**[0191]** In some embodiments, rather than marking and displaying the UI elements and anchor candidates to the user, one or anchors may automatically be assigned to until the strength computation exceeds the threshold. For instance, if the threshold is 97% and a given UI element has a match strength of 90%, the system may continue to add anchors until the match strength meets or exceeds the threshold. This may be accomplished in some embodiments by determining an anchor that increases the match strength the most for the selector, adding this anchor, if still below the threshold, determining match strength increases for other elements after adding the anchor, adding the anchor causing the highest increase in match strength, and repeating until the threshold is met.

**[0192]** FIG. **11** is a flowchart illustrating a process **1100** for generating an image matching activity, according to an embodiment of the present invention. The process begins with generating an image matching activity at **1110**. The activity may click a button, enter text, open a menu and select an option, etc. based on image matching techniques. An indicate on screen command is received at **1120**, and the application is detected at **1130**.

**[0193]** A selection of a region of the application on which image matching is to be performed is received at **1140**. This may include the user drawing a box around the UI element of interest, using a lasso tool, drawing a freeform selection, or any other selection mechanism without deviating from the scope of the invention. The image matching selector is then generated for the selected image and the activity is configured accordingly at **1150**.

**[0194]** FIG. **12** is a flowchart illustrating a process **1200** for generating a selector and OCR-based activity, according to an embodiment of the present invention. The process begins with generating a selector and OCR-based activity at **1210**. The activity may click a button, enter text, open a menu and select an option, etc. An indicate on screen command is received at **1220**, and the application is detected at **1230**. The UI elements on the application screen are also detected at **1240**.

**[0195]** An indication of the UI element for the activity is received from the user at **1250**. This may include clicking a desired UI element in some embodiments. An out-of-the-box selector is generated for the indicated UI element using a driver based on a best match for the UI element and the activity is configured accordingly at **1260**. A selection of an OCR engine is received and the activity is configured accordingly at **1270**. Rather than searching for the selector alone, the selector and OCR-based activity, when executed as part of an RPA process, checks both that the selector for the UI element is found and verifies that the text of the UI element matches text designated in the activity using OCR.

**[0196]** FIG. **13** is a flowchart illustrating a process **1300** for generating an RPA workflow that uses multiple identification techniques, according to an embodiment of the present invention. The process begins with generating UI element identification and interaction activities at **1310**. The activities may be one or more selector-based identification activities, CV-based identification activities, unified target identification activities, image matching identification activities, selector and OCR-based identification activities, any other suitable identification activities, any combination thereof, etc.

**[0197]** The UI element identification and interaction activities are then configured into a logical relationship at **1320**. The logical relationship may be sequential, conditional (e.g., if the first activity does not uniquely detect the UI element successfully, use the second, then the third, etc. until the UI element is uniquely identified or all activities have been attempted), in parallel, etc. An RPA robot implementing a workflow that includes the UI element identification and interaction activities is generated at **1330**, and the RPA robot is executed to detect and interact with the UI element at **1340**.

**[0198]** FIG. **14** is a flowchart illustrating a process **1400** for creating a UI object library and configuring a project to work with a new version of an application, according to an embodiment of the present invention. The process may begin with loading one or more UI object libraries from a UI object repository if these have been previously created at **1410**. UI descriptors for interacting with respective UI elements for the activities are then created and/or added from one or more UI object libraries at **1420** to interact with a new version of an application with a changed UI.

**[0199]** Once the appropriate UI descriptors have been updated, a UI object library including the UI descriptors is published in the UI object repository at **1430**. The UI object library may also include the application, screens, and least some UI elements from the application with which the activities interact. However, in certain embodiments, other UI elements and/or UI descriptors may be included that are not specifically used in the RPA workflow. The UI object library is then published or re-published in the UI object repository at **1440** for use in other RPA workflows and/or by other developers.

**[0200]** If UI objects are missing from the UI object library or UI descriptors for activities no longer work for a new version of an application, the user may thus add these. The created UI object library, and potentially other UI object libraries in the UI object repository, may be displayed to the user in the designer application. The publication of the object library may be performed as part of a global object library database (OLDB) or a local OLDB in some embodiments. The global OLDB UI object repository may be a globally shared database (Center of Excellence (CoE) level), for instance. The local OLDB UI object repository may be a locally shared database (local machine level). In some embodiments, the UI object libraries may be pushed and published to a service, such as a UiPath™ service or Go! service. This allows sharing of a set of UI object libraries with the world, if desired. The storage form for the UI object repository (e.g., an OLDB) should be decided at an architectural/technical level.

**[0201]** The process steps performed in FIGS. **8-14** may be performed by a computer program, encoding instructions for the processor(s) to perform at least part of the process(es) described in FIGS. **8-14** in accordance with embodiments of the present invention. The computer program may be embodied on a non-transitory computer-readable medium. The computer-readable medium may be, but is not limited to, a hard disk drive, a flash device, RAM, a tape, and/or any other such medium or combination of media used to store data. The computer program may include encoded instructions for controlling processor(s) of a computing system (e.g., processor(s) **510** of computing system **500** of FIG. **5**) to implement all or part of the process steps described in FIGS. **8-14**, which may also be stored on the computer-readable medium.

**[0202]** The computer program can be implemented in hardware, software, or a hybrid implementation. The computer program can be composed of modules that are in operative communication with one another, and which are designed to pass information or instructions to display. The computer program can be configured to operate on a general purpose computer, an ASIC, or any other suitable device.

**[0203]** It will be readily understood that the components of various embodiments of the present invention, as generally described and illustrated in the figures herein, may be arranged and designed in a wide variety of different configurations. Thus, the detailed description of the embodiments of the present invention, as represented in the attached figures, is not intended to limit the scope of the invention as claimed, but is merely representative of selected embodiments of the invention.

**[0204]** The features, structures, or characteristics of the invention described throughout this specification may be combined in any suitable manner in one or more embodiments. For example, reference throughout this specification to "certain embodiments," "some embodiments," or similar language means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, appearances of the phrases "in certain embodiments," "in some embodiment," "in other embodiments," or similar language throughout this specification do not necessarily all refer to the same group of embodiments and the described features, structures, or characteristics may be combined in any suitable manner in one or more embodiments.

**[0205]** It should be noted that reference throughout this specification to features, advantages, or similar language does not imply that all of the features and advantages that may be realized with the present invention should be or are in any single embodiment of the invention. Rather, language referring to the features and advantages is understood to mean that a specific feature, advantage, or characteristic described in connection with an embodiment is included in at least one embodiment of the present invention. Thus, discussion of the features and advantages, and similar language, throughout this specification may, but do not necessarily, refer to the same embodiment.

**[0206]** Furthermore, the described features, advantages, and characteristics of the invention may be combined in any suitable manner in one or more embodiments. One skilled in the relevant art will recognize that the invention can be practiced without one or more of the specific features or advantages of a particular embodiment. In other instances, additional features and advantages may be recognized in certain embodiments that may not be present in all embodiments of the invention.

**[0207]** One having ordinary skill in the art will readily understand that the invention as discussed above may be practiced with steps in a different order, and/or with hardware elements in configurations which are different than those which are disclosed. Therefore, although the invention has been described based upon these preferred embodiments, it would be apparent to those of skill in the art that certain modifications, variations, and alternative constructions would be apparent, while remaining within the spirit and scope of the invention. In order to determine the metes and bounds of the invention, therefore, reference should be made to the appended claims.

**1**. A non-transitory computer-readable medium storing a computer program, the computer program configured to cause at least one processor to:

scan a set of projects in a user interface (UI) object repository;

detect one or more processes in the scanned projects that are using one or more UI descriptors referenced in one or more respective activities of a robotic process automation (RPA) workflow that belong to an application and application version; and

automatically update at least one of the one or more UI descriptors in the RPA workflow with one or more respective UI descriptors from the detected processes.

**2**. The non-transitory computer-readable medium of claim **1**, wherein the computer program is further configured to cause the at least one processor to:

extract at least one UI descriptor from the RPA workflow; and

add the extracted at least one UI descriptor to a structured schema that groups the one or more UI descriptors by UI applications, screens, and graphical elements of the UI.

**3**. The non-transitory computer-readable medium of claim **1**, wherein

the one or more UI descriptors identify respective graphical elements in the UI for the respective activities in the RPA workflow at runtime,

the UI object repository comprises a plurality of UI descriptors corresponding to one or more screens from multiple application versions of an application, and

the plurality of UI descriptors comprise a UI element selector, an anchor selector, a computer vision (CV) descriptor, a unified target descriptor, a screen image capture, a graphical element image capture, or any combination thereof.

**4**. The non-transitory computer-readable medium of claim **1**, wherein the one or more UI descriptors are called via one or more web services.

**5**. The non-transitory computer-readable medium of claim **1**, wherein the RPA workflow comprises a selector-based identification activity, a computer vision (CV)-based identification activity, a unified target identification activity, an image matching identification activity, a selector and optical character recognition (OCR)-based identification activity, or a combination thereof.

**6**. The non-transitory computer-readable medium of claim **1**, wherein

the UI object repository comprises one or more UI object libraries, and

at least one of the one or more UI object libraries is an encapsulation of UI descriptors grouped by applications, application versions, and screens.

**7**. The non-transitory computer-readable medium of claim **1**, wherein an application shown in the UI is a web application and the one or more UI descriptors comprise HyperText Markup Language (HTML) paths to the respective graphical elements for the one or more corresponding UI descriptors.

**8**. A computing system, comprising:

memory storing computer program instructions; and

at least one processor configured to execute the computer program instructions, wherein the computer program instructions are configured to cause the at least one processor to:

scan a set of projects in a user interface (UI) object repository;

detect one or more processes in the scanned projects that are using one or more UI descriptors referenced in one or more respective activities of a robotic process automation (RPA) workflow that belong to an application and application version; and

automatically update at least one of the one or more UI descriptors in the RPA workflow with one or more respective UI descriptors from the detected processes.

**9**. The computing system of claim **8**, wherein the computer program instructions are further configured to cause the at least one processor to:

extract at least one UI descriptor from the RPA workflow; and

add the extracted at least one UI descriptor to a structured schema that groups the one or more UI descriptors by UI applications, screens, and graphical elements of the UI.

**10**. The computing system of claim **8**, wherein

the one or more UI descriptors identify respective graphical elements in the UI for the respective activities in the RPA workflow at runtime,

the UI object repository comprises a plurality of UI descriptors corresponding to one or more screens from multiple application versions of an application, and

the plurality of UI descriptors comprise a UI element selector, an anchor selector, a computer vision (CV)

descriptor, a unified target descriptor, a screen image capture, a graphical element image capture, or any combination thereof.

**11**. The computing system of claim **8**, wherein the one or more UI descriptors are called via one or more web services.

**12**. The computing system of claim **8**, wherein the RPA workflow comprises a selector-based identification activity, a computer vision (CV)-based identification activity, a unified target identification activity, an image matching identification activity, a selector and optical character recognition (OCR)-based identification activity, or a combination thereof.

**13**. The computing system of claim **8**, wherein

the UI object repository comprises one or more UI object libraries, and

at least one of the one or more UI object libraries is an encapsulation of UI descriptors grouped by applications, application versions, and screens.

**14**. The computing system of claim **8**, wherein an application shown in the UI is a web application and the one or more UI descriptors comprise HyperText Markup Language (HTML) paths to the respective graphical elements for the one or more corresponding UI descriptors.

**15**. A computer-implemented method, comprising:

scanning a set of projects in a user interface (UI) object repository, by a computing system;

detecting one or more processes in the scanned projects that are using one or more UI descriptors referenced in one or more respective activities of a robotic process automation (RPA) workflow that belong to an application and application version, by the computing system; and

automatically updating at least one of the one or more UI descriptors in the RPA workflow with one or more respective UI descriptors from the detected processes, by the computing system, wherein

the one or more UI descriptors identify respective graphical elements in the UI for the respective activities in the RPA workflow at runtime,

the UI object repository comprises a plurality of UI descriptors corresponding to one or more screens from multiple application versions of an application, and

the plurality of UI descriptors comprise a UI element selector, an anchor selector, a computer vision (CV) descriptor, a unified target descriptor, a screen image capture, a graphical element image capture, or any combination thereof.

**16**. The computer-implemented method of claim **15**, further comprising:

extracting at least one UI descriptor from the RPA workflow, by the computing system; and

adding the extracted at least one UI descriptor, by the computing system, to a structured schema that groups the one or more UI descriptors by UI applications, screens, and graphical elements of the UI.

**17**. The computer-implemented method of claim **15**, wherein the one or more UI descriptors are called via one or more web services.

**18**. The computer-implemented method of claim **15**, wherein the RPA workflow comprises a selector-based identification activity, a computer vision (CV)-based identification activity, a unified target identification activity, an image matching identification activity, a selector and optical character recognition (OCR)-based identification activity, or a combination thereof.

**19**. The computer-implemented method of claim **15**, wherein

the UI object repository comprises one or more UI object libraries, and

at least one of the one or more UI object libraries is an encapsulation of UI descriptors grouped by applications, application versions, and screens.

**20**. The computer-implemented method of claim **15**, wherein an application shown in the UI is a web application and the one or more UI descriptors comprise HyperText Markup Language (HTML) paths to the respective graphical elements for the one or more corresponding UI descriptors.

* * * * *