



Fork me on GitHub

Docs

Getting Started

Data Structure

Object Mapping

Collections

BsonDocument

Expressions

DbRef

Connection String

FileStorage

Indexes

Encryption

Pragmas

Collation

Expressions

Expressions are path or formulas to access and modify the data inside a document. Based on the concept of JSON path (<http://goessner.net/articles/JsonPath/>), LiteDB supports a similar syntax to navigate inside a document.

`BsonExpression` is the class that parses a path expression and compiles it into a Linq Expression to be evaluated by LiteDB.

- Path starts with `$` : `$.Address.Street`, where `$` represents the root document. The `$` symbol are optional and default in document navigation (`Address.Street` works too)
- Int values are defined by `[0-9]*` : `123`
- Double values are defined by `[0-9].[0-9]` : `123.45`
- Strings are represented with a single/double quote: `'Hello World'`
- Null is represented by `null`
- Bool is represented using `true` or `false` keywords.
- Document starts with `{ key1: <value|expression>, key2: ... }`
- Arrays are represented with `[<value|expression>, <value|expression>, ...]`
- Functions are represented with `FUNCTION_NAME(par1, par2, ...) : LOWER($.Name)`

Examples:

- `$.Price`
- `$.Price + 100`
- `SUM($.Items[*].Price)`

```
var expr = new BsonExpression("SUM($.Items[*].Unity * $.Items[*].Price)");
var total = expr.Execute(doc, true).First().AsDecimal;
```

Expressions can be used in many ways:

- Creating an index based on an expression:
 - `collection.EnsureIndex("idx_name", "LOWER($.Name)", false)`
 - `collection.EnsureIndex(x => x.Name.ToLower())`
- Querying documents inside a collection based on expression (full scan search)
 - `collection.Find("SUBSTRING($.Name, 0, 1) = 'T'")`
- Update using SQL syntax
 - `UPDATE customers SET Name = LOWER($.Name) WHERE _id = 1`
- Creating new document result in SELECT shell command
 - `SELECT { upper_titles: ARRAY(UPPER($.Books[*].Title)) } WHERE $.Name LIKE "John%"`
- Querying documents using the SQL syntax
 - `SELECT $.Name, $.Phones[@.Type = "Mobile"] FROM customers`

Path

- `$` - Root
- `$.Name` - Name field
- `$.Name.First` - First field from Name subdocument
- `$.Books` - Returns an array of books
- `$.Books[0]` - Returns the first book inside Books array
- `$.Books[*]` - Returns every book inside Books
- `$.Books[*].Title` Returns the title from every book in Books
- `$.Books[-1]` - Returns the last book inside Books array

Path also supports expressions to filter child nodes

- `$.Books[@.Title = 'John Doe']` - Returns all books where Title is 'John Doe'
- `$.Books[@.Price > 100].Title` - Returns all titles where Price is greater than 100

Inside an array, `@` acts as a sub-iterator, pointing to the current sub-document. It's possible use functions inside expressions too:

- `$.Books[SUBSTRING(LOWER(@.Title), 0, 1) = 't']` - Returns all books whose Title starts with 'T' or 't'.

Difference between `$` and `*`

In SQL query (at `SELECT` segment) is possible use both `$` and `*`. But they represent different things.

- `$` represent current document root. When use `$` (or omitted, because this symbol are optional and are default) you are referencing about root current document.
- `*` represent all grouped documents. It's not more about a single document but all documents in group (or in query result). Used when `GROUP BY` are present or when you want return a single value in query (like `SELECT COUNT(*) FROM customers`).

If you use `SELECT $ FROM customers` you will get `IEnumerable<BsonDocument>` result (N documents). If you use `SELECT * FROM customers` you will get a single value, a `BsonArray` with all documents result inside. Be careful because if your resultset are big you are creating a very large single array in memory.

Functions

Functions are used to manipulate data in expressions. A few examples will be provided for each category of functions. For a complete list of functions, check the API documentation.

Aggregate Functions

Aggregate functions take an array as input and return a single value.

- `COUNT(arr)` - Returns the number of elements in the array `arr`
- `AVG(arr)` - Returns the average value in the array `arr`
- `LAST(arr)` - Returns the last element in the array `arr`

Data Type Functions

DataType functions provide explicit data type conversion.

- `STRING(expr)` - Returns the result of `expr` converted to string
- `INT32(expr)` - Tries to convert the result of `expr` to an `Int32`, returning `null` if not possible
- `DATETIME(expr)` - Tries to convert the result of `expr` to a `DateTime`, returning `null` if not possible

Date Functions

- `YEAR(date)` - Returns the year value from `date`
- `DATEADD('year', 3, date)` - Returns a new date with 3 years added to `date`
- `DATEDIFF('day', dateStart, dateEnd)` - Returns the difference in days between `dateEnd` and `dateStart`

Math Functions

- `ABS(num)` - Returns the absolute value of `num`
- `ROUND(num, digits)` - Returns `num` rounded to `digits` digits
- `POW(base, exp)` - Returns `base` to the power of `exp`

String Functions

- `UPPER(str)` - Returns `str` in uppercase
- `TRIM(str)` - Returns a new string without leading and trailing white spaces
- `REPLACE(str, old, new)` - Returns a new string with every occurrence of `old` in `str` replaced by `new`

High-Order Functions

High-Order functions take an array and a lambda expression that is applied to every document in the array. Use `@` symbol to represent inner looped value.

- `MAP(arr => expr)` returns a new array with the map expression applied to each element
 - `MAP([1,2,3] => @*2)` returns `[2,4,6]`
 - `MAP([{'a':1, 'b':2}, {'a':3, 'b':4}] => @.a)` returns `[1,3]`
- `FILTER(arr => expr)` returns a new array containing only the elements for which the filter expression returns `true`
 - `FILTER([1,2,3,4,5] => @ > 3)` returns `[4,5]`

- `FILTER([{a:1, b:2}, {a:2}] => @.b != null)` returns `[{a:1, b:2}]`
- `SORT(arr => expr)` returns a new array sorted by the result of `expr` in ascending order - `SORT([3,2,5,1,4] => @)` returns `[1,2,3,4,5]` - `SORT([{a:2}, {a:1, b:2}] => @.a)` returns `[{a:1, b:2}, {a:2}]`
- `SORT(arr => expr, order)` returns a new array sorted by the result of `expr` with the order defined by `order` (ascending if `order` is 1 or 'asc', descending if `order` is -1 or 'desc') - `SORT([3,2,5,1,4] => @, 'desc')` returns `[5,4,3,2,1]` - `SORT([{a:1, b:2}, {a:2}] => @.a, -1)` returns `[{a:2}, {a:1, b:2}]`

Misc Functions

- `JSON(str)` - Takes a string representation of a JSON and returns a parsed `BsonValue` containing the document
- `CONCAT(arr1, arr2)` - Returns a new array containing the concatenation between arrays `arr1` and `arr2`
- `RANDOM(min, max)` - Returns a random `Int32` between `min` and `max`

Made with ♥ by LiteDB team - @mbdavid - MIT License