

User Stories — Preferred Custody Platform (PCP)

BRD Version: 1.1 (07/09/2019) **Project:** Preferred Custody Platform (PCP) **Work:** Preferred Custody Overdraft/Uninvested Cash Balance (2)

Module 1: Custody Overdraft Tracker

US-001 As an authenticated user, I want to click the logout option in the navigation bar, so that my session and credentials are cleared and I am safely logged out.

BRD §4.3.1.1, step 1

- When the user clicks the Logout button in the Navbar, the system must trigger `NavbarComponent.logout()` which calls `AuthService.logout()`.
- The `AuthService` must remove the JWT token from `localStorage`.
- The `AuthService` must clear current user information and update the authentication state (e.g., via `sessionBehaviorSubject/Observable`).
- Upon successful logout and state update, the Angular Router must navigate the user to the Login page.
- Once the token is removed, the user must no longer be treated as authenticated.

US-002 As a system administrator, I want protected pages to be guarded by an authentication guard, so that unauthenticated users are blocked and redirected.

BRD §4.3.1.1, step 1

- When a user attempts to navigate to a protected route (e.g., dashboard), the system must execute the `canActivate` guard prior to loading the component.
- The `AuthGuard` must check the user's authentication status using `AuthService`.
- If the user is authenticated, the guard must allow navigation to the requested component.
- If the user is not authenticated, the guard must block navigation and/or redirect the user away from the protected route.

US-003 As an API client/developer, I want an HTTP Interceptor to automatically attach the authentication token to outgoing requests, so that backend APIs can verify user identity seamlessly.

BRD §4.3.1.1, step 1

- The `AuthInterceptor` must intercept outgoing HTTP requests dispatched through Angular `HttpClient`.
- The interceptor must retrieve the authentication token and attach it to the outgoing request payload/headers sent to backend APIs.
- The HTTP Interceptor and `HttpClient` must be configured globally in the application via `provideHttpClient()` and `providers` array.

US-004 As a user, I want a responsive navigation bar that indicates active routes and displays session-dependent navigation options, so that I can easily navigate the application across different devices.

BRD §4.3.1.1, step 1

- The navigation bar must expand on large screens and collapse into a mobile menu on smaller screens using Bootstrap classes (`navbar-expand-lg`).
- The navigation items must use `RouterLink` for single-page component routing and `RouterLinkActive` with `exact` match option to highlight the active route.
- The navigation template must listen to `authService.session$` via `async` pipe to dynamically render session status and display relevant links or logout button.
- The navigation bar must include styling for brand/logo, dark background theme (`bg-dark`, `navbar-dark`), bottom margin spacing (`mb-4`), and shadow (`shadow-sm`).