


QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Overview

HP ProLiant DL380 Generation9 (Gen9)

The HP ProLiant DL380 Gen9 Server delivers the best performance and expandability in the HP 2P rack portfolio. Reliability, serviceability and near continuous availability, backed by a comprehensive warranty, make it ideal for any environment. Deploy the data center standard.



Front View - 8SFF Chassis with Optional Universal Media Bay shown

1. Quick removal access panel
2. Universal Media Bay, 2 USB 2.0 and VGA standard (8SFF) bays optional
3. Optional Optical drive. Requires Universal Media bay
Optional 2 SFF HDD, blank shown. Requires Universal Media bay
4. Drive Bay 2, Blank shown, 8SFF optional.
5. Drive Bay 2, Blank shown, 8SFF optional.
6. 8 SFF Drive Cage Bay
Power On/Standy button and system power LED button
7. Health LED
8. NIC status
10. UID button
11. USB 3.0
12. Serial label pull tag




1. PCI Slots (Slots 1-3 top to bottom, riser shipped standard)
2. PCI Slots (Slots 4-6 top to bottom, requires second riser card, and second processor)
3. Optional serial port
4. Optional rear 2 SFF HDD (supported in 24 SFF or 12 LFF front end)
5. HP Flexible Slot Power Supply bay 1 (800w shown)
6. Power supply Power LED
7. Power supply Power connection
8. HP Flexible Slot Power Supply bay 2 (800w shown)
9. Power supply Power LED
10. Power supply Power connection
11. VGA connector
12. Embedded 4x 1GbE Network Adapter
13. Dedicated iLO connector
14. USB 3.0 connectors (2)
15. Unit ID LED
16. Optional FlexiLoM ports (Shown: 4 x 1GbE)

QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Overview



Internal View

1. Fan cage shown with 6 standard Hot-plug fans (High Ambient temperature fans optional)
2. Processors, heatsink showing, with HP Smart Socket Guide
3. Optional HP Smart Storage Battery
4. Up to 24 DIMM slots. Shown fully populated in 24 slots (12 per node)
5. MicroSD card slot
6. Internal USB 3.0 connector
7. Optional HP Flexible Smart Array or Smart HBA (H240ar shown)
8. (Under) Hot Plug redundant HP Flexible Slot Power supplies
9. Connection for second (optional) riser (Required second CPU)
10. Embedded 4x1GbE NIC
11. Primary PCIe riser, standard (Optional double wide GPU riser)
12. Optional Flexible LOM slot
13. X4 SATA ports (1 and 2)

QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Standard Features

NOTE: For more information regarding Intel Xeon processors, please see the following URL:
<http://www.intel.com/xeon>

Intel® Xeon® processor E5-2600 v3 product family is designed to deliver the best combination of performance, built-in capabilities, and cost-effectiveness. One (or two) of the following Intel® Xeon® E5-2600 v3 processors based on the model:

Processor	Model	CPU Frequency	Cores	L3 Cache	Power	QPI	DDR4 Hz
Up to two of the following depending on Model	E5-2699v3	2.3GHz	18	45MB	145W	9.6GT/s	2133
	E5-2698v3	2.3GHz	16	40MB	135W	9.6GT/s	2133
	E5-2697v3	2.6GHz	14	35MB	145W	9.6GT/s	2133
	E5-2695v3	2.3GHz	14	35MB	120W	9.6GT/s	2133
	E5-2694v3	2.6GHz	12	30MB	135W	9.6GT/s	2133
	E5-2687Wv3	3.1GHz	10	25MB	160W	9.6GT/s	2133
	E5-2683v3	2.0GHz	14	35MB	120W	9.6GT/s	2133
	E5-2680v3	2.5GHz	12	30MB	120W	9.6GT/s	2133
	E5-2670v3	2.3GHz	12	30MB	120W	9.6GT/s	2133
	E5-2667v3	3.2GHz	8	25MB	135W	9.6GT/s	2133
	E5-2660v3	2.6GHz	10	25MB	105W	9.6GT/s	2133
	E5-2650v3	2.3GHz	10	25MB	105W	9.6GT/s	2133
	E5-2650LV2	1.8GHz	12	25MB	65W	9.6GT/s	2133
	E5-2643v3	3.4GHz	6	20MB	135W	9.6GT/s	2133
	E5-2640v3	2.6GHz	8	20MB	90W	8.0GT/s	1866
	E5-2637v3	3.5GHz	4	15MB	135W	9.6GT/s	2133
	E5-2630v3	2.4GHz	8	20MB	85W	8.0GT/s	1866
	E5-2630Lv3	1.8GHz	8	25MB	55W	8.0GT/s	1866
	E5-2623v3	3.0GHz	4	10MB	105W	8.0GT/s	1866
	E5-2620v3	2.4GHz	6	15MB	85W	8.0GT/s	1866
	E5-2609v3	1.9GHz	6	15MB	85W	8.0GT/s	1600
	E5-2603v3	1.6GHz	6	15MB	85W	6.4GT/s	1600

Note: that all processors above 120W use a high efficiency Heatsink. Doublewide PCIe cards are only supported with this Heatsink. For processors with a standard Heatsink that require double wide cards we would need to leverage the Graphics Enablement kit (719082-B21)

Chipset	Intel® C610 Series Chipset Intel® E5-2600v3 Processor Family
	NOTE: For more information regarding Intel chipsets, please see the following URL: http://www.intel.com/products/server/chipsets/ .

On System Management Chipset	HP iLO (Firmware HP iLO4 2.0) 4GB NAND NOTE: 1GB USB user space configurable via UEFI and accessible via iLO. Read and learn more in the iLO QuickSpecs .
------------------------------	---

Memory	Type:
One of the following depending on Model	HP SmartMemory
	DDR4 Registered (RDIMM) or Load Reduced (LRDIMM)
DIMM Slots Available	24 (12 DIMM slots per processor, 4 channels per processor, 3 DIMMs per channel)

Memory Protection	Advanced ECC	Advanced ECC uses single device data correction to detect and correct single and all multibit error that occurs within a single DRAM chip.
	Online spare	Memory online spare mode detects a rank that is degrading and switches operation to the spare rank.

Expansion Slots	Expansion Slots #	Technology	Bus Width	Connector Width	Bus Number	Form Factor	Notes
Primary Riser (Standard)	1	PCIe 3.0	x16	x8	7	Full-height, half-length Slot	Proc 1
	2	PCIe 3.0	x16	x8	10	Full-height, half-length Slot	Proc 1
	3	PCIe 3.0	x8	x8	13	Half Length, Full Height Slot	Chipset

- Default bus assignment (in decimal). Inserting cards with PCI bridges may alter the actual bus assignment number
- ** Indicates the number of physical electrical lanes running to the connector.

NOTE: All slots support up to 150w PCIe cards, but an additional Power Cord Option is required (PN 669777-B21). See Option Section below for offering.

Slot 2 PCIe Riser (Optional 3-slot) 719073-B21	Expansion Slots #	Technology	Bus Width	Connector Width	Bus Number	Device Number	Form Factor	Notes
	4	PCIe 3.0	x16	x16	16		Full Height, Full Length Slot	Proc 2
	5	PCIe 3.0	x16	x16	20		Full Height, Full Length Slot	Proc 2
	6	PCIe 3.0	x8	x8	23		Full-height, half-length Slot	Proc 2

* Default bus assignment (in decimal). Inserting cards with PCI bridges may alter the actual bus assignment number

** Indicates the number of physical electrical lanes running to the connector.

NOTE: When populating the second optional riser slot, the second processor must be installed.

NOTE: All slots support up to 150w PCIe cards, but an additional Power Cord Option is required (669777-B21). See Option Section below for offering.

Slot 1 PCIe Riser (Optional 2-slot) 719076-B21	Expansion Slots #	Technology	Bus Width	Connector Width	Bus Number	Device Number	Form Factor	Notes
	4	PCIe 3.0	x16	x16	16		Full Height, Full Length Slot	Proc 1
	5	PCIe 3.0	x8	x8	16		Full-height, half-length Slot	Proc 1

* Default bus assignment (in decimal). Inserting cards with PCI bridges may alter the actual bus assignment number

QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Standard Features

** Indicates the number of physical electrical lanes running to the connector.		
NOTE: When populating the second optional riser slot, the second processor must be installed.		
NOTE: All slots support up to 150w PCIe cards, but an additional Power Cord Option is required (669777-B21). See Option Section below for offering.		
Storage Controller One of the following depending on Model	Entry Models	HP Dynamic Smart Array B140i Controller NOTE: The embedded B140i controller will operate in UEFI only mode. For legacy support an additional controller will be needed, and for CTO orders please also select the Legacy mode settings part, 758959-B22.
<hr/>		
Base Models	HP Dynamic Smart Array B140i Controller HP Flexible Smart Array P440ar/2GB FIO Controller HP Flexible Smart Array P840ar/4GB	
Performance Models	HP Dynamic Smart Array B140i Controller HP Flexible Smart Array P440ar/2GB	
<hr/>		
Internal Storage Devices One of the following depending on Model	Optical Drive	Ships standard in Performance Models Optional: DVD-ROM, DVD-RW
	Hard Drives	None ship standard 8 SFF with optional Universal Media bay or 8SFF bay options 24 SFF plus optional 3 SFF drives rear 12 LFF plus optional 3 LFF drives rear 4 LFF drive bays total NOTE: The Universal Media Bay (724865-B21) not available with the LFF chassis or the 24SFF front end, and can only be populated in Bay1
	Hard Drive Bays	NOTE: The 8SFF can be upgraded with a drive cage to 16 or 24 SFF with field upgrades. NOTE: The LFF chassis cannot be upgraded to 12LFF in the field. NOTE: Pre-configured Chassis come with an embedded 10-Port SATA controller. Optional HP Flexible Smart Array and Smart SAS HBA Controllers can be added. NOTE: Only the 24SFF and 12LFF Chassis support rear drives. NOTE: Universal media bay is not supported in the LFF configurations. Optical support is offered via USB DVD-RW Drive (701498-B21)
<hr/>		
Maximum Internal Storage		CAPACITY CONFIGURATION
	Hot Plug SFF SAS	31.2TB 24+2 x 1.2TB (with optional rear SFF drive cage)
	Hot Plug SFF SATA	26.0TB 24+2 x 1TB (with optional SFF drive cage)
	Hot Plug LFF SAS	90.0TB 12+3 x 6TB (with optional rear LFF drive cage)
	Hot Plug LFF SATA	90.0TB 12+3 x 6TB (with optional rear LFF drive cage)
	Hot Plug SFF SAS SSD	31.2TB 24+2 x 1.6TB (with optional rear SFF drive cage)
	Hot Plug LFF SATA SSD	24.0TB 12+3 x 1.6TB (with optional rear LFF drive cage)
<hr/>		
Power Supply	HP 500W Flex Slot Platinum Hot Plug Power Supply HP 800W Flex Slot Platinum Hot Plug Power Supply HP 1400W Flex Slot Platinum Plus Hot Plug Power Supply HP Power On (Flex Slot) Power supplies have a common electrical and physical design that allows for hot plug, tool-less installation into HP ProLiant Gen9 Performance Servers. Flex Slot power supplies are certified for high-efficiency operation and offer multiple power output options, allowing users to "right-size" a power supply for specific server configurations. This flexibility helps to reduce power waste, lower overall energy costs, and avoid "trapped" power capacity in the data center.	
	NOTE: All pre-configured servers ship with a standard 6-foot IEC C-13/C-14 jumper cord (AOK02A). This jumper cord is also included with each standard AC power supply option kit. If a different power cord is required, please check the ProLiant Power Cables web page.	
	To review the power requirements for your selected system, please use the HP Power Advisor Tool located at www.hp.com/go/proliant/poweradvisor .	
	Power specifications and technical content for all HP Server power supplies can be found at www.hp.com/go/proliant/powersupply .	
	NOTE: Mixing of power supplies in the same server is not supported. All power supplies must be of the same input voltage, output rating, and efficiency rating. If non-matching power supplies are installed, you may receive an error message and/or experience operational issues with your server.	
<hr/>		
System Fans One of the following depending on Model		Non-redundant Redundant
	2P model	6 fans
	NOTE: 1P models typically ship with 4 standard fans. The second processor option kit contains 2 additional fans.	
	NOTE: High Performance Temperature Fan Kit is available to meet ambient temperature environments (719079-B21)	
	NOTE: the 12LFF and 24SFF chassis ship with 6 High Performance fans as standard	
	NOTE: High Performance Temperature Fan Kit is required for GPU support.	
	NOTE: Additional HP 12Gb SAS Expander Card (727250-B21) and the 8SFF Bay kit (719067-B21) will ship with 6 High efficiency fans	
<hr/>		
Interfaces	Serial	optional
	Video	2 (1 front, optional via Universal Media Bay, 724865-B21), 1 back not active simultaneously
	FlexibleLOM Network Ports	4 x 1Gb ports shipping standard with optional FlexibleLOM
	HP ILO Remote Management Network Port	1 Gb Dedicated
	Micro SD Slot	1 Micro SD
	NOTE: The Micro SD slot is not a hot-pluggable device. Customers should not attempt to plug an SD card into the SD slot while the server is powered.	
	USB 3.0	Up to 5 total: 1 front, 2 rear, 2 internal (secure), 2 optional USB 2.0 front via Universal Media Bay
	SID (Systems Insight Display)	Optional
	Not shipping as standard. Available as a CTO option or as a field upgrade (768900-B21)	



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Standard Features

Operating Systems and Virtualization	Microsoft Windows Server Canonical Ubuntu
Software Support for ProLiant Servers	Red Hat Enterprise Linux (RHEL) SUSE Linux Enterprise Server (SLES) Oracle Solaris VMware Citrix XenServer
	NOTE: For more information on HP's Certified and Supported ProLiant Servers for OS and Virtualization software and latest listing of software drivers available for your server, please visit our Support Matrix at: http://www.hp.com/go/ossupport and our driver download page: http://www.hp.com/support/DL380Gen9
Upgradability	Upgradeable to two processors (36 Cores) NOTE: Processor upgrade available from Intel® Xeon® Processors E5-2600v3. Please contact HP Technology Sales Up to 24 DIMM slots available by year (not by re-seller) Up to 24 DIMM slots available by high Memory capacity FlexibleLOM connector for 1 Gigabit or 10 Gigabit networking options HP Flexible Smart Array or Smart HBA Controllers Embedded 10-Port SATA, B140 as standard Optional 3 slot riser (x16, x8), or 2 slot (x16, x8) NOTE: To take advantage of the additional 3 PCI slot upgrade, the second processor must be installed. Redundant Power Supply Universal Media Bay NOTE: The Universal Media bay provides front VGA and 2xUSB, plus ability to add 2SFF and Optical. NOTE: Universal Media bay only available with 8 or 8+8SFF chassis & can be populated in Bay1 only. HP Legacy Mode (FIO only, 758959-B22) NOTE: UEFI is the default model for CTO and BTO skus. Can change default to legacy via CTO.
Industry Standard Compliance	ACPI 2.0b Compliant PCIe 3.0 Compliant PXE Support WOL Support Microsoft® Logo certifications USB 3.0 Support USB 2.0 Support NOTE: This support is on the optional Universal Media Bay Energy Star ASHRAE A3/A4 For details on configurations supporting ASHRAE A3/4 please see: www.hp.com/servers/ASHRAE UEFI (Unified Extensible Firmware Interface Forum) Note: UEFI is the default for the DL380 Gen9. Legacy model can be selected in the field, or as a CTO option (758959-B22)
Graphics	Integrated Matrox G200eH2 video standard with 16MB of Video RAM <ul style="list-style-type: none">• 1280 x 1024 (32 bpp)• 1920 x 1200 (16 bpp) HP ILO 4 on System Management Memory <ul style="list-style-type: none">• 16 MB Flash• 256 MB DDR 3 with ECC (112 MB after ECC and video)
HP Server UEFI/Legacy ROM	HP Server UEFI/Legacy ROM Unified Extensible Firmware Interface (UEFI) is an industry standard that provides better manageability and more flexibility for server management. HP ProLiant Gen9 platform defaults to UEFI and can be factory or field configured for legacy BIOS Boot Mode. NOTE: The UEFI System Utilities function is analogous to the HP ROM-Based Setup Utility (RBSU) of legacy BIOS. For more information, please visit http://www.hp.com/go/proliantuefi/docs . UEFI enables numerous new capabilities specific to HP ProLiant servers such as: <ul style="list-style-type: none">• Secure Boot• Operating system specific functionality• Support for > 2.2 TB (using GPT) boot drives• USB 3.0 Stack• Embedded UEFI Shell• Mass Configuration Deployment Tool - HP RESTful API.• PXE boot support for IPv6 networks• Boot support for option cards that only support a UEFI option ROM For more information please visit http://www.hp.com/go/proliant/uefi NOTE: For UEFI Boot Mode, boot environment and OS image installations should be configured properly to support UEFI. NOTE: Legacy model can be enabled with a CTO build (758959-B22). All standard skus ship with UEFI as default.
Form Factor One of the following depending on Model	2U Rack form factor 8 SFF & 2xSFF Drive Bay Version: 3.40 x 17.54 x 26.75 in (8.73 x 44.55 x 67.94 cm) 4 LFF & 12 LFF Drive Bay Version: 3.44 x 17.54 x 26.75 in (8.73 x 44.55 x 73.02 cm) NOTE: Dimensions without bezel
Embedded Management	HP Integrated Lights-Out (HP iLO) Monitor your servers for ongoing management, service alerting, reporting and remote management with iLO. Learn more at www.hp.com/go/ilo . UEFI Configure and boot your servers securely with industry standard Unified Extensible Firmware Interface (UEFI). Learn more at www.hp.com/go/proliantuefi . HP RESTful API RESTful API is an application programming interface. RESTful Web Service API served by iLO's web server www.hp.com/go/restfulapi . Intelligent Provisioning Provision servers by discovering and deploying 1 to few servers with Intelligent Provisioning. Learn more at www.hp.com/go/intelligentprovisioning .



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Standard Features

Embedded Remote Support	HP's embedded remote support, used with Insight Online direct connect or HP Insight Remote Support, allows HP ProLiant servers to transmit hardware events directly to HP or an HP Authorized Partner for automated phone home support. Learn more at www.hp.com/go/insightonline/info .
Server utilities	
HP Smart Update	Optimize firmware and driver updates with HP Smart Update solutions. Learn more at www.hp.com/go/smartsupdate .
HP Systems Insight Manager (HP SIM)	HP SIM allows you to monitor the health of your HP ProLiant Servers and HP Integrity Servers, and also provides you with basic support for non-HP servers. HP SIM also integrates with HP SUM to provide quick and seamless firmware updates. Learn more at www.hp.com/go/sim .
Scripting Tool Kit and Windows PowerShell	Provision 1 to many servers using your own scripts to discover and deploy them with HP Scripting Tool Kit for Windows and Linux or HP Scripting Tools for Windows PowerShell. Learn more at www.hp.com/go/ProLiantSTK or www.hp.com/go/powershell .
HP RESTful Interface Tool	HP RESTful Interface tool is a scripting tool to provision servers using RESTful API interface to discover and deploy servers at scale. Learn more at www.hp.com/go/restfulapi .
HP iLO Mobile Application	Enables the ability to access, deploy, and manage your server anytime from anywhere from select smartphones and mobile devices. For additional information please visit: www.hp.com/go/ilo/mobileapp .
HP Insight Online	HP Insight Online, available at no additional cost as part of your HP warranty, Care Pack or contractual support agreement with HP, is a personalized dashboard for simplified tracking of IT operations and support information from anywhere, anytime. Learn more at www.hp.com/go/insightonline/info .
Security	Power-on password Serial interface control Administrator's password UEFI ILO 4 (Integrated Lights-Out 4) has 12 customizable user accounts and SSL encryption Integrated Lights-Out can be disabled via a Global Setting ILO Advanced supports directory services integration TPM 1.2
Warranty	This product is covered by a global limited warranty and supported by HP Services and a worldwide network of HP Authorized Channel Partners resellers. Hardware diagnostic support and repair is available for three years from date of purchase. Support for software and initial setup is available for 90 days from date of purchase. Enhancements to warranty services are available through HP Care Pack services or customized service agreements. Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details. This product is covered by a limited warranty. The limited warranty period begins on the date of purchase. Warranty repairs may be accomplished through the use of Customer Self Repair (CSR) parts. These parts fall into two categories: 1) Mandatory CSR parts are designed for easy replacement. A travel and labor charge will result when customers decline to replace a Mandatory CSR part; 2) Optional CSR parts are also designed for easy replacement but may involve added complexity. Customers may choose to have HP replace Optional CSR parts at no charge. Additional information regarding worldwide limited warranty and technical support is available at: http://hp18004.www1.hp.com/products/servers/platforms/warranty/index.html



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Optional Features

Embedded Management	ILO Advanced HP ILO Advanced licenses offer smart remote functionality without compromise, for all HP ProLiant servers. The license includes the full integrated remote console, virtual keyboard, video, and mouse (KVM), multi-user collaboration, console record and replay, and GUI-based and scripted virtual media and virtual folders. You can also activate the enhanced security and power management functionality. Learn more about HP ILO Advanced at www.hp.com/go/iloadvanced .
Server Management	HP Insight Control HP Insight Control, lets you deploy, migrate, monitor, remote control, and optimize your IT infrastructure through a single, simple management console. For more information, see http://www.hp.com/go/insightcontrol . HP OneView Powerful converged management of servers, storage, and network for IT service automation and infrastructure simplicity, see www.hp.com/go/oneview .
	HP Insight Cluster Management Utility (CMU) HP Insight Cluster Management Utility is a hyperscale-optimized management framework that includes software for the provisioning, control, performance management and monitoring of groups of nodes and infrastructure. Learn more at www.hp.com/go/cmua .
Rack and Power Infrastructure	HP Rack and Power Infrastructure products and services create highly efficient and intelligent solutions for existing or new IT data centers. HP Rack and Power infrastructure solutions – rack infrastructure, power protection and management, performance optimized data centers (PODs) – are the foundation you are looking for to help secure long-term IT success. These products are designed to help you react to changes in the industry. They deliver efficient, easy-to-use capabilities to manage, monitor, deploy and provision infrastructure from entry to enterprise. As an industry leader, HP is uniquely positioned to address the key concerns of power, cooling, cable management and system access. Learn more at HP Rack and Power Infrastructure .
High Performance Clusters	HP Cluster Platforms are specifically engineered, factory-integrated large-scale ProLiant clusters optimized for High Performance Computing, with a choice of servers, networks and software. Operating system options include specially priced offerings for Red Hat Enterprise Linux and SUSE Linux Enterprise Server, as well as Microsoft Windows HPC Server. A Cluster Platform Configurator simplifies ordering. http://www.hp.com/go/clusters .
HPC Interconnects	NOTE: High Performance Computing (HPC) interconnect technologies are available for this server under the HP Cluster Platform product portfolio. These high-speed interconnects are fully supported by HP when they are part of these configure to order Clusters. Solutions can be defined with a lot of flexibility with the help of configuration tools. Please visit the following URL to configure HPC Clusters with InfiniBand Interconnects: http://www.hp.com/echservers/clusters/ucp/index.html
Storage Software	Whether you need to solve a specific data protection, archiving, or storage command and control challenge, or deliver on strategic consolidation, compliance, or continuity initiatives, look no further than HP storage software. Our storage software helps you reduce costs, simplify storage infrastructure, protect vital assets and respond faster to business opportunities. Storage software that gets the job done: <ul style="list-style-type: none">● Data Protection and Recovery Software Whether you're a large enterprise or a smaller business, HP data protection and recovery software will cost-effectively protect you against disaster and ensure business continuity.● Data Archive and Migration Software HP's storage software enables you to comply with data retention and retrieval requirements, improve application performance, and reduce costs by efficiently migrating infrequently accessed or less valuable data to lower cost storage.● Storage Resource Management Software (SRM) HP's storage resource management software reduces operational costs and provides the command and control foundation you need to efficiently manage and visualize your physical and virtual environments.● Data Replication Software HP offers array-based and host-based replication software for use in disaster recovery, testing, application development and reporting.● Storage Device Management Software Maximize your investment in HP storage and networking with software that enables hardware-specific configuration, performance tuning and connectivity management.● HP StoreVirtual VSA With HP StoreVirtual VSA you can use the power of virtualization to turn a set of heterogeneous and disconnected physical disk drives in your servers and storage devices into a single pool of logical storage capacity. NOTE: For more information available Storage Software including QuickSpecs, please see: www.hp.com/go/storage/software .
One Config Simple (SCE)	SCE is a guided self-service tool to help sales and non-technical people provide customers with initial configurations in 3 to 5 minutes. You may then send the configuration on for configuration help, or use in your existing ordering processes. If you require "custom" rack configuration or configuration for products not available in SCE, please contact HP's Customer Business Center or an Authorized Partner for assistance. http://www.hp.com/products/configurator .



Service and Support

HP Technology Services HP Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to HP to help prevent problems and solve issues faster. Our support technology lets you to tap into the knowledge of millions of devices and thousands of experts to stay informed and in control, anywhere, any time.

HP Care Pack Services enable you to order the right service level, length of coverage and response time as you Protect your business beyond purchase your new server, giving you full entitlement for the term you select.

warranty with HP Care Pack

Services

Optimized Support **HP Proactive Care** - Call to Repair commitment, 24x7 coverage, three year Care Pack Service

recommendation Prevent problems and stabilize IT by utilizing secure, real-time, predictive analytics and proactive consultations when your products are connected to HP. Includes enhanced escalation management and the industry's highest level of hardware support commitment – hardware will be returned to operating conditions within six (6) hours after you open your case. Comes with collaborative software call management with two hour call back to reduce troubleshooting.

As a leading global support provider for Microsoft, Red Hat, VMware, SUSE and other operating systems, HP is able to simplify and shorten your time to resolution with one call for hardware or software questions. <http://h20195.www2.hp.com/v2/GetPDF.aspx/4AA3-8855ENW.pdf>

HP ProLiant Server Hardware Installation

Help ensure your new HP ProLiant hardware is installed smoothly, efficiently and with minimal disruption to your IT and business operations. <http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf>

Standard Support **HP Proactive Care** - 24x7 coverage, three year Care Pack Service

recommendation This service helps prevent problems and stabilize IT by utilizing secure, real-time, predictive analytics and proactive consultations when your products are connected to HP. Includes four hour response for hardware, and collaborative call management for software with a two hour callback.

<http://h20195.www2.hp.com/v2/GetPDF.aspx/4AA3-8855ENW.pdf>

HP ProLiant ML350 Hardware Installation

Help ensure your new HP ProLiant hardware is installed smoothly, efficiently and with minimal disruption to your IT and business operations. <http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf>

Related Services Data Center Platform Consulting Services

These services help modernize key systems and leverage new technology to support a changing business climate and prepare you for the new style of IT. HP understands the needs of the data center of the future and will serve as your guide for the journey. www.hp.com/services/consulting

Data Privacy Services

Protect your data through better media management. HP Data privacy services help manage and protect sensitive data. www.hp.com/services/dataprivacy



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Service and Support

Factory Express for Servers and storage

HP Factory Express offers configuration, customization, integration and deployment services for HP servers and storage products. Choose how your factory solutions are built, tested, integrated, shipped and deployed. <http://www.hp.com/go/factory-express>

HP Foundation Care

Hardware and software support services provide easy connection to HP to resolve support issues quickly. Includes collaborative call management for industry leading software; full software support may also be purchased, giving you one place to call for help. www.hp.com/services/foundationcare

Additional HP Care Pack services can be found at: www.hp.com/go/cpc

Parts and Materials
HP will provide HP-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by HP due to malfunction.



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Pre-configured Models

- For the Standard Features shipped in the "Factory Integrated Models", please see the "Configuration Information - Factory Integrated Models" section.
 1. Pre-configured models ship with the configurations below. Options can be selected from the Core or Additional options section of this QuickSpecs.
 2. HP does not allow factory integration of options into pre-configured models. Any additional options purchased will be shipped separately.
 3. If you desire a custom configuration please see "Configuration Information - Factory Integrated Models" section of this QuickSpecs.
 4. Not all models are available in all regions. Check with your local country HP offices for availability.

NOTE: All Pre-configured Models come populated with some hard drive blanks installed. Should the customer need additional hard drive blanks, they can order more using either P/N 666987-B21: HP SFF Hard Drive Blank Kit or P/N 666986-B21: HP LFF Hard Drive Blank Kit.

NOTE: All pre-configured servers ship with a standard 6-foot IEC C-13/C-14 jumper cord (A0K02A). This jumper cord is also included with each standard AC power supply option kit. If a different power cord is required, please check the ProLiant Power Cables web page.

Caution: HP recommends that a minimum of two people are required for all Rack Server installations. Please refer to your installation instructions for proper tools and number of people to use for any installation.

Entry Models

(SKU Number)	766342-B21	752686-B21	752688-B21	752687-B21
Model Name	HP ProLiant DL380 Gen9 E5-2609v3 1P 8GB-R B140i 4LFF SATA 500W PS Entry Server	HP ProLiant DL380 Gen9 E5-2609v3 1P 8GB-R B140i 8SFF SATA 500W PS Entry Server	HP ProLiant DL380 Gen9 E5-2620v3 1P 16GB-R P440ar 12LFF 2x800W PS Base Server	HP ProLiant DL380 Gen9 E5-2620v3 1P 16GB-R P440ar 8SFF 500W PS Base Server
Processor	Intel® Xeon® E5-2609v3	Intel® Xeon® E5-2609v3	Intel® Xeon® E5-2620v3	
Number of Processors	One			
Memory	8GB (1x8GB Registered DIMMs, 2133 MHz) NOTE: with the E5-2609v3 this memory DIMM will only operate at 1600MHz	8GB (1x8GB Registered DIMMs, 2133 MHz) NOTE: with the E5-2609v3 this memory DIMM will only operate at 1600MHz	16GB (1x16GB Registered DIMMs, 2133 MHz) NOTE: with the E5-2620v3 this memory DIMM will only operate at 1866MHz	
Network Controller	HP Embedded 1Gb Ethernet 4-port 331i Adapter			
Storage Controller	HP Dynamic Smart Array B140i	HP Flexible Smart Array P440/4G Controller	HP Flexible Smart Array P440ar/2GB	
Hard Drive	None ship standard	None ship standard; includes 10LFF hard drive blanks	None ship standard	
Internal Storage	4 LFF HDD Bays	8 SFF HDD Bays	12 LFF HDD Bays	8 SFF HDD Bays
Optical Drive	Optional via HP Mobile USB DVD/RW Drive (701498-821)	Optional via Universal Media Bay	Optional via HP Mobile USB DVD/RW Drive (701498-821)	Optional via Universal Media Bay
Optical Drive Bay				
PCI-Express Slots	3 PCIe slots (+3 PCIe slots available with upgrade option, second processor required)			
Power Supply	(1) HP 500W Flex Slot Platinum Power Supply	(2) HP 800W Flex Slot Platinum Power Supply	(1) HP 500W Flex Slot Platinum Power Supply	
Fans	4 hot plug fans, redundant	4 hot plug fans, redundant	6 hot plug high performance temperature fans, redundant	4 hot plug fans, redundant
Management	iLO Management (standard), Intelligent Provisioning (standard), iLO Advanced (optional), Insight Control (optional), HP OneView (optional)	iLO Management (standard), Intelligent Provisioning (standard), iLO Advanced (optional), Insight Control (optional), HP OneView (optional)		
Energy Star				
Accessories				
Integrated Lights Out				
Form Factor	Rack (2U), HP Easy Install Rails	Rack (2U), HP Easy Install Rails with CMA		
Warranty	Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite support with next business day response			

Performance Models

(SKU Number)	752689-B21
Model Name	HP ProLiant DL380 Gen9 E5-2650v3 2P 32GB-R P440ar 8SFF 2x10Gb 2x800W Perf Server
Processor	Intel® Xeon® E5-2650v3
Number of Processors	Two
Memory	32GB (2x16GB Registered DIMMs, 2133 MHz)
Network Controller	HP Embedded 4x1Gb, plus 2x10Gb-T Flexible LOM
Storage Controller	HP Flexible Smart Array P440ar/2GB
Hard Drive	None ship standard
Internal Storage	8 SFF HDD Bays
Optical Drive Bay	---Request to add Override item or delete item
Optical Drive	HP Half-Height SATA DVD-RW Optical Drive
PCI-Express Slots	6 PCIe slots (includes second riser slot upgrade option)
Power Supply	(2) HP 800W Flex Slot Platinum Power Supply
Fans	4 hot plug fans, redundant
Management	iLO Management (standard), Intelligent Provisioning (standard), iLO Advanced (standard), HP OneView (optional)
Energy Star	Meets Energy Star requirements
Form Factor	Rack (2U), HP Easy Install Rails with CMA
Warranty	Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite support with next business day response



Pre-configured Models

Note that UEFI is the standard default for all Predefined models

Country Code Key	xx1 = B21	Worldwide
	xx1 = 291	Japan
	xx1 = A41	PRC



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Configuration Information - Factory Integrated Models

This section lists some of the steps required to configure a Factory Integrated Model. To ensure only valid configurations are ordered, HP recommends the use of an HP approved configurator. Contact your local sales representative for information on configurable product offerings and requirements.

1. Factory Integrated Models must start with a CTO Server.
2. FIO indicates that this option is only available as a factory installable option.
3. All Factory Integrated Models will be populated with sufficient hard drive bays based on the number of initial hard drives ordered with the server.
4. Some options may not be integrated at the factory. Contact your local sales representative for additional information.

Step 1: Base Configuration (choose one of the following configurable models)

[Chassis]	HP ProLiant DL380 Gen9 8SFF Configure-to-order Server	HP ProLiant DL380 Gen9 24SFF Configure-to-order Server	12LFF Configure-to-order Server
SKU Number	719064-B21	767032-B21	719061-B21
Processor	2 (optional) x HP Smart Socket Guides		
DIMMSlots	24 DIMM slots for RDIMM, LRDIMM DDR4 Memory		
Storage Controller	HP Dynamic Smart Array B140i, plus optional HP Flexible Smart Array or Smart HBA controller		
PCIe	3 PCIe slots (+3 PCI slots available with upgrade option, second processor required)		
Drive Cage	8SFF Hot Plug	24SFF Hot Plug	12LFF Hot Plug
Network Controller	HP Embedded 1Gb Ethernet 4-port 331i Adapter, plus optional HP Flexible LOM		
Fans	4 hot plug fans, redundant	6 hot plug high performance temperature fans, redundant	
Management	ILO Management (standard), Intelligent Provisioning (standard), ILO Advanced (optional), Insight Control (optional), HP OneView (optional)	ILO Management (standard), Intelligent Provisioning (standard), ILO Advanced (optional), Insight Control (optional), HP OneView (optional)	
USB	1 front, 1 internal, 2 rear, (2 front optional)	1 front, 1 internal, 2 rear	
Ears			HP Quick Release Ears

Step 2: Choose Required Options (only one of the following from each list unless otherwise noted)

HP Processors

Select one or two processors from Core options-Processor section below.

- If one processor is desired, select one xxxx-L21
- If two processors are desired, select one xxxx-L21 and one xxxx-B21.
- Up to 2 processors supported. Mixing different processor models is not supported.
- DDR4 speed is the maximum memory speed of the processor. Actual memory speed may depend on the quantity and type of DIMMs installed.
- For the Intel® C600 Chipset ES-2600 Series, the letter preceding the model number indicates the Product Line (E3, E5, E7); 2600xvt, 2 = number of CPUs in a Node, 4 is socket/segment designation, 00 = Processor SKU, x = L for low power SKUs and vt (not yet designated) = version number.

HP Memory

Select one or more memory from Core options-Memory section below.

- RDIMM, RDIMM are all distinct memory technologies and cannot be mixed within a server. The majority of ProLiant Gen9 servers support LRDIMM and RDIMM.
- HP memory from previous generation servers are not qualified or warranted with this HP ProLiant Server. HP SmartMemory is required to realize the memory performance improvements and enhanced functionality listed in this document for Gen9.
- If only one processor is installed, only half of the total DIMM slots are available. When populating with two processors all DIMM slots are available.
- Kits described as LP include Low Power DIMMs. For more information on ProLiant Energy Efficient Features, see: www.hp.com/go/proliant-energy-efficient.
- Depending on the memory configuration and processor model, the memory speed may run at 2133MHz, 1866MHz, 1600MHz or 1333MHz. Please see Memory Population Table or the Online Memory Configuration Tool at: www.hp.com/go/ddr4/memory-configurator

HP Power Supplies

Select one or more power supplies from Core Options-Power Supplies section below:

- Prior to selecting a power supply option, it is highly recommended that you review your server configuration in the HP Power Advisor tool to determine the right size power supply for your server configuration. The HP Power Advisor is located at: www.hp.com/go/hppoweradvisor.
- Mixing of power supplies in the same server is not supported. All power supplies must be of the same input voltage, output rating, and efficiency rating. If non-matching power supplies are installed, you may receive an error message and/or experience operational issues with your server.

Step 3: Choose Additional Factory Integratable Options

HP Unique Options

Select one or more Unique options from Core options section below.

- This section may contain FIO options, please see the Unique options section below.
- FIO indicates that this option is only available as a factory installable option.

HP I/O Expansion Options

Select one or more Riser Kit options from Core options section below.

- To take advantage of the additional PCI slot upgrade, the second processor must be installed.
- This section may contain FIO options, please see HP I/O Expansion Options section below.
- FIO indicates that this option is only available as a factory installable option.

HP Drives

Select one or more drives from Core options-HP Drives section below:

- The components of a storage subsystem (e.g. the drive, the HBA/controller, firmware, and the server backplane) should operate at the same data transfer rate or the system bandwidth will be negotiated down to an acceptable level for all components.
- Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.
- The HP ProLiant Gen9 Smart Storage solutions are equipped with re-designed Small Form Factor (SFF 2.5 in) and Large Form Factor (LFF 3.5 in) hot plug carriers for HP Qualified Hard Drives and Solid State Drives. These new carriers provide status and activity indicators as well as caution indicators for "Do Not Remove".



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Configuration Information - Factory Integrated Models

- HP Flexible LOM** Select a FlexibleLOM from Core options-Networking section below.
- Only one FlexibleLOM can be added to the server. These options are upgradeable and can be changed from the original configuration after the server is shipped.
 - For 10Gb adapters, a minimum of two Gigabytes (2 GB) of server memory is required per each adapter.
 - Please see the QuickSpecs for Technical Specifications and additional information: www.hp.com/go/ProLiantNICS
- HP Networking** Select a standup NIC adapter from Core options-Networking section below.
- Please see the QuickSpecs for Technical Specifications and additional information: www.hp.com/go/ProLiantNICS
 - These options are upgradeable and can be changed from the original configuration after the server is shipped.
 - For 10Gb adapters, a minimum of two Gigabytes (2 GB) of server memory is required per each adapter.
- HP Storage Controllers** Select one or more Storage options from Additional options section below.
- The embedded B140i controller will operate in UEFI only mode. For legacy support an additional controller will be needed, and for CTO orders please also select the Legacy mode settings part, 758959-B2Z
 - This section may contain FIO options, please see HP Storage Controllers section below.
 - FIO indicates that this option is only available as a factory installable option.
- HP Graphics Options** Select one or more graphics adapter from Additional options section below.
- Please see the HP Power Advisor for estimated power consumption of your individual system configuration prior to installing GPUs. The HP Power Advisor is located at: www.hp.com/go/hppoweradvisor
 - This section may contain FIO options, please see HP Computation & Graphics Accelerators section below.
- HP Cooling Options** Select one or more Fan Kits from Core options section below.
- This section may contain FIO options, please see HP Cooling Options section below.
 - FIO indicates that this option is only available as a factory installable option.
- HP Rail Kits** Select one type of rail kit from Additional options section below.
- Please take a moment to review the installation documentation that comes with the server to help you with the installation of your Gen9 server.
 - To assist in the installation of the server into the rack, an optional installation tool is available by contacting your local services representative (p/n 695539-001).
 - See HP Rack Options in Additional Options section of this QuickSpecs for more rack kit choices.
- Caution:** HP recommends that a minimum of two people are required for all Rack Server installations. Please refer to your installation instructions for proper tools and number of people to use for any installation.



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Core Options

NOTE: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, HP recommends the use of an HP approved configurator. Contact your local sales representative for additional information.

HP Unique Options	HP DL380 Gen9 Universal Media Bay Kit	724865-B21
	NOTE: The HP DL380 Gen9 Universal Media bay provides front VGA and 2xUSB 3.0, plus support for 2xSFF front drives (724864-B21) and ODD support (No included); and can only be located in Bay1 in either a 8SF or 8+BSFF front end.	
	NOTE: This can only be populated in Bay1	
	HP DL380 Gen9 Graphics Enablement Kit	719082-B21
	NOTE: This kit includes alternative 2 Heatsinks plus 6 cables to enable GPU support with a 2SF configuration. Other limitations apply, see Graphic section for more details.	
	HP DL380 Gen9 High Performance Temperature Fan Kit	719079-B21
	NOTE: This kit is required for specific Ambient temperature environments, more details here: www.hp.com/go/proliant-achieve	
	NOTE: This kit is required for some GPGPU options, please see Graphics section for more details by card.	
	HP DL380 Gen9 2SFF Front/Rear SAS/SATA Kit	724864-B21
	NOTE: For 2SFF front Universal Media Bay (724865-B21) is required.	
	NOTE: 2SFF in the rear is only supported with a 2SFF or 12LFF (719061-B21) front end.	
	HP DL380 Gen9 3LFF Rear SAS/SATA Kit	768856-B21
	NOTE: This is only supported in the 12LFF chassis (719061-B21)	
	NOTE: 3LFF rear drives will consume the 12LFF riser expansion slot.	
	HP DL380 Gen9 Primary 2 Slot GPU Ready Riser Kit	719076-B21
	Slot1: 1x Gen3 x16 FH/FL, 1xGen3 x8 FH/HI	
	HP DL380 Gen9 Secondary 3 Slot GPU Ready Riser Kit	719073-B21
	Slot2: 2xGen3 x16 FH/FL, 1xGen3 x8 FH/HI	
	HP DL380 Gen9 8SFF Bay1 Cage/Backplane Kit	719067-B21
	NOTE: To add an additional 8SFF drive cage in Bay1.	
	NOTE: This ships with 6 High Efficiency Fans.	
	NOTE: Selecting this option does not allow you to select the Universal Media Bay.	
	HP DL380 Gen9 Additional 8SFF Cage/Backplane Kit	768857-B21
	NOTE: Adds an additional 8SFF drive cage in Bay 2.	
	HP 12Gb SAS Expander Card with Cables for DL380 Gen9	727250-B21
	NOTE: SAS expander to enable 24SFF field upgrade	
	NOTE: This kit included 6 High Efficiency Fans.	
	HP DL380 Gen9 Systems Insight Display Kit	768900-B21
	NOTE: The Systems Insight Display no longer ships as standard, but is available as a Factory Integrated, or field upgrade option.	
	HP Legacy FIO Mode Setting	758959-B22
	NOTE: UEFI is the default, this FIO part can be used for CTO to enable Legacy mode.	
HP Processors	Entry Processors - E5-2600v3 series Processors	
	HP DL380 Gen9 Intel® Xeon® E5-2603v3 (1.6GHz/6-core/15MB/85W) FIO Processor Kit	719053-L21
	HP DL380 Gen9 Intel® Xeon® E5-2603v3 (1.6GHz/6-core/15MB/85W) Processor Kit	719053-B21
	HP DL380 Gen9 Intel® Xeon® E5-2609v3 (1.9GHz/6-core/15MB/85W) FIO Processor Kit	719052-L21
	HP DL380 Gen9 Intel® Xeon® E5-2609v3 (1.9GHz/6-core/15MB/85W) Processor Kit	719052-B21
	Base Processors - E5-2600v3 series Processors	
	HP DL380 Gen9 Intel® Xeon® E5-2620v3 (2.4GHz/6-core/15MB/85W) FIO Processor Kit	719051-L21
	HP DL380 Gen9 Intel® Xeon® E5-2620v3 (2.4GHz/6-core/15MB/85W) Processor Kit	719051-B21
	HP DL380 Gen9 Intel® Xeon® E5-2623v3 (3.0GHz/4-core/10MB/105W) FIO Processor Kit	779556-L21
	HP DL380 Gen9 Intel® Xeon® E5-2623v3 (3.0GHz/4-core/10MB/105W) Processor Kit	779556-B21
	HP DL380 Gen9 Intel® Xeon® E5-2630v3 (2.4GHz/8-core/20MB/85W) FIO Processor Kit	719050-L21
	HP DL380 Gen9 Intel® Xeon® E5-2630v3 (2.4GHz/8-core/20MB/85W) Processor Kit	719050-B21
	HP DL380 Gen9 Intel® Xeon® E5-2630L v3 (1.8GHz/8-core/20MB/55W) FIO Processor Kit	719069-L21
	HP DL380 Gen9 Intel® Xeon® E5-2630L v3 (1.8GHz/8-core/20MB/55W) Processor Kit	719060-B21
	HP DL380 Gen9 Intel® Xeon® E5-2637v3 (3.5GHz/4-core/15MB/35W) FIO Processor Kit	719058-L21
	Ships with a High Performance Heatsink	
	HP DL380 Gen9 Intel® Xeon® E5-2637v3 (3.5GHz/4-core/15MB/135W) Processor Kit	719058-B21
	Ships with a High Performance Heatsink	
	HP DL380 Gen9 Intel® Xeon® E5-2640v3 (2.6GHz/8-core/20MB/90W) FIO Processor Kit	719049-L21
	HP DL380 Gen9 Intel® Xeon® E5-2640v3 (2.6GHz/8-core/20MB/90W) Processor Kit	719049-B21
	Performance Processors - E5-2600v3 series Processors	
	HP DL380 Gen9 Intel® Xeon® E5-2643v3 (3.4GHz/6-core/20MB/135W) FIO Processor Kit	719057-L21
	Ships with a High Performance Heatsink	
	HP DL380 Gen9 Intel® Xeon® E5-2643v3 (3.4GHz/6-core/20MB/135W) Processor Kit	719057-B21
	Ships with a High Performance Heatsink	
	HP DL380 Gen9 Intel® Xeon® E5-2650v3 (2.3GHz/10-core/25MB/105W) FIO Processor Kit	719048-L21
	HP DL380 Gen9 Intel® Xeon® E5-2650v3 (2.3GHz/10-core/25MB/105W) Processor Kit	719048-B21
	HP DL380 Gen9 Intel® Xeon® E5-2650L v3 (1.8GHz/12-core/30MB/65W) FIO Processor Kit	719059-L21
	HP DL380 Gen9 Intel® Xeon® E5-2650L v3 (1.8GHz/12-core/30MB/65W) Processor Kit	719059-B21
	HP DL380 Gen9 Intel® Xeon® E5-2660v3 (2.6GHz/10-core/25MB/105W) FIO Processor Kit	762764-L21
	HP DL380 Gen9 Intel® Xeon® E5-2660v3 (2.6GHz/10-core/25MB/105W) Processor Kit	762764-B21
	HP DL380 Gen9 Intel® Xeon® E5-2660v3 (2.6GHz/10-core/25MB/135W) FIO Processor Kit	719056-L21
	Ships with a High Performance Heatsink	
	HP DL380 Gen9 Intel® Xeon® E5-2660v3 (2.6GHz/10-core/25MB/135W) Processor Kit	719056-B21
	Ships with a High Performance Heatsink	
	HP DL380 Gen9 Intel® Xeon® E5-2670v3 (3.2GHz/12-core/30MB/120W) FIO Processor Kit	719046-L21
	HP DL380 Gen9 Intel® Xeon® E5-2670v3 (3.2GHz/12-core/30MB/120W) Processor Kit	719046-B21
	HP DL380 Gen9 Intel® Xeon® E5-2680v3 (3.4GHz/14-core/35MB/120W) FIO Processor Kit	719046-B21
	HP DL380 Gen9 Intel® Xeon® E5-2680v3 (3.4GHz/14-core/35MB/120W) Processor Kit	719046-B21
	HP DL380 Gen9 Intel® Xeon® E5-2690v3 (2.6GHz/12-core/30MB/135W) FIO Processor Kit	719044-L21
	HP DL380 Gen9 Intel® Xeon® E5-2690v3 (2.6GHz/12-core/30MB/135W) Processor Kit	719044-B21



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Core Options

HP DL380 Gen9 Intel® Xeon® E5-2695v3 (2.3GHz/14-core/35MB/120W) FIO Processor Kit Ships with a High Performance Heatsink	762760-L21
HP DL380 Gen9 Intel® Xeon® E5-2695v3 (2.3GHz/14-core/35MB/120W) Processor Kit Ships with a High Performance Heatsink	762760-B21
HP DL380 Gen9 Intel® Xeon® E5-2697v3 (2.6GHz/14-core/35MB/145W) FIO Processor Kit Ships with a High Performance Heatsink	719054-L21
HP DL380 Gen9 Intel® Xeon® E5-2697v3 (2.6GHz/14-core/35MB/145W) Processor Kit Ships with a High Performance Heatsink	719054-B21
HP DL380 Gen9 Intel® Xeon® E5-2698v3 (2.3GHz/16-core/40MB/135W) FIO Processor Kit Ships with a High Performance Heatsink	781913-L21
HP DL380 Gen9 Intel® Xeon® E5-2698v3 (2.3GHz/16-core/40MB/135W) Processor Kit Ships with a High Performance Heatsink	781913-B21
HP DL380 Gen9 Intel® Xeon® E5-2699v3 (2.3GHz/18-core/45MB/145W) FIO Processor Kit Ships with a High Performance Heatsink	781915-L21
HP DL380 Gen9 Intel® Xeon® E5-2699v3 (2.3GHz/18-core/45MB/145W) Processor Kit Ships with a High Performance Heatsink	781915-B21
HP DL380 Gen9 Intel® Xeon® E5-2687Wv3 (3.1GHz/10-core/25MB/160W) FIO Processor Kit Ships with a High Performance Heatsink	762768-L21
HP DL380 Gen9 Intel® Xeon® E5-2687Wv3 (3.1GHz/10-core/25MB/160W) Processor Kit Ships with a High Performance Heatsink	762768-B21

NOTE: Up to 2 processors supported. Performance and Energy Star Model configurations include two processors.

NOTE: HT indicates that the processor model supports Intel® Hyper-Threading Technology

NOTE: Turbo2: Intel® Turbo Boost Technology 2.0 provides more computing power when you need it with performance that adapts to spikes in your workload and delivers more performance upside than previous generation turbo technology.

NOTE: DRAM speed is the maximum memory speed of the processor. Actual memory speed may depend on the quantity and type of DIMMs installed.

NOTE: The xxxxxx-L21 is the first processor shipped, the xxxxxx-B21 is the 2nd processor and ships with 2 additional FANS for factory of field installation.

NOTE: Double wide PCIe cards are only supported in risers with the Processors leveraging the High Performance Heatsink. For Processors requiring double wide GPU support please order the GPU enablement kit (719082-B21)

HP Memory

Registered DIMMs (RDIMMs) for E5-2600v3 Series

NOTE: The following memory is supported by the E5-2600v3 series Processors.

HP 8GB (1x8GB) Single Rank x4 DDR4-2133 CAS-15-15-15 Registered Memory Kit	726718-B21
HP 16GB (1x16GB) Dual Rank x4 DDR4-2133 CAS-15-15-15 Registered Memory Kit	726719-B21

NOTE: Depending on Processor selected this memory will run at 1600, 1866 or 2133MHz

Load Reduced DIMMs (LRDIMMs) for E5-2600v3 Series

NOTE: The following memory is supported by the E5-2600v3 series Processors.

HP 32GB (1x32GB) Quad Rank x4 DDR4-2133 CAS-15-15-15 Load Reduced Memory Kit	726722-B21
--	------------

NOTE: Depending on Processor selected this memory will run at 1600, 1866 or 2133MHz

HP Optical Drives

HP 9.5mm SATA DVD-ROM Jack/Black Gen9 Optical Drive

NOTE: The Universal Media Bay (724865-B21) is required for this option

HP 9.5mm SATA DVD-RW Jack/Black G9 Optical Drive	726537-B21
--	------------

NOTE: The Universal Media Bay (724865-B21) is required for this option

HP Mobile USB Non Leaded System DVD RW Drive	701498-B21
--	------------

HP Drives

SAS Hot Plug SFF (2.5-inch) Enterprise (ENT) Drives

HP 1.7TB 6G SAS 10K rpm SFF (2.5-inch) SC Dual Port Enterprise 3yr Warranty Hard Drive	718162-B21
HP 900GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652589-B21
HP 160GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	759212-B21
HP 600GB 12G SAS 15K rpm LFF (3.5-inch) SC Converter Enterprise 3yr Warranty Hard Drive	765424-B21
HP 600GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652593-B21
HP 450GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	759210-B21
HP 450GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652572-B21
HP 300GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	759208-B21
HP 300GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652564-B21
HP 146GB 6G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652605-B21

SAS Hot Plug SFF (2.5-inch) Midline (MDL) Drives

HP 1TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652749-B21
HP 500GB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652745-B21

SAS Hot Plug LFF (3.5-inch) Enterprise (ENT) Drives

HP 450GB 12G SAS 15K rpm LFF (3.5-inch) SC Converter Enterprise 3yr Warranty Hard Drive	737394-B21
HP 300GB 12G SAS 15K rpm LFF (3.5-inch) SC Converter Enterprise 3yr Warranty Hard Drive	737261-B21

SAS Hot Plug LFF (3.5-inch) Midline (MDL) Drives

HP 1TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	655710-B21
HP 3TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652766-B21
HP 2TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652757-B21
HP 1TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652753-B21

SATA Hot Plug SFF (2.5-inch) Midline (MDL) Drives

HP 1TB 6G SATA 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	655710-B21
HP 3TB 6G SATA 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	652766-B21
HP 2TB 6G SAS 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	652757-B21
HP 1TB 6G SAS 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	652753-B21

SATA Hot Plug LFF (3.5-inch) Midline (MDL) Drives

HP 1TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	655710-B21
HP 3TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652766-B21
HP 2TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652757-B21
HP 1TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652753-B21

SATA Hot Plug LFF (3.5-inch) Midline (MDL) Drives

HP 1TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	655710-B21
HP 3TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652766-B21
HP 2TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652757-B21
HP 1TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652753-B21

SATA Hot Plug SFF (2.5-inch) Enterprise Solid State Drives

HP 800GB 12G SAS High Endurance SFF 2.5-in SC Enterprise Performance 3yr Wty Solid State Drive	741159-B21
HP 400GB 12G SAS High Endurance SFF 2.5-in SC Enterprise Performance 3yr Wty Solid State Drive	741155-B21
HP 200GB 12G SAS High Endurance SFF 2.5-in SC Enterprise Performance 3yr Wty Solid State Drive	741151-B21



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Core Options

12G SAS Hot Plug SFF (2.5-inch) Enterprise Mainstream Solid State Drives	
HP 800GB 12G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	741146-B21
HP 400GB 12G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	741142-B21
HP 200GB 12G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	741138-B21
12G SAS Hot Plug SFF (2.5-inch) Enterprise Value Solid State Drives	
HP 1.6TB 12G SAS Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	762263-B21
HP 800GB 12G SAS Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	762261-B21
12G SAS Hot Plug LFF (3.5-inch) Enterprise Value Solid State Drives	
HP 1.6TB 12G SAS Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	762272-B21
HP 800GB 12G SAS Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	762270-B21
6G SATA Hot Plug SFF (2.5-inch) Enterprise Mainstream Solid State Drives	
HP 800GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691868-B21
HP 400GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691866-B21
HP 200GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691864-B21
HP 100GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691862-B21
6G SATA Hot Plug SFF (2.5-inch) Enterprise Value Solid State Drives	
HP 800GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	717973-B21
HP 600GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	739898-B21
HP 480GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	717971-B21
HP 300GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	739888-B21
HP 240GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	717969-B21
6G SATA Hot Plug SFF (2.5-inch) Enterprise Boot Solid State Drives	
HP 120GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Boot 3yr Wty Solid State Drive	717965-B21
HP 80GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Boot 3yr Wty Solid State Drive	734360-B21
6G SATA Hot Plug LFF (3.5-inch) Enterprise Mainstream Solid State Drives	
HP 800GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691860-B21
HP 400GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691856-B21
HP 200GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691854-B21
HP 100GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691852-B21
6G SATA Hot Plug LFF (3.5-inch) Enterprise Value Solid State Drives	
HP 800GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	718189-B21
HP 600GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	739900-B21
HP 480GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	718183-B21
HP 300GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	739890-B21
HP 240GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	718177-B21
6G SATA Hot Plug LFF (3.5-inch) Enterprise Boot Solid State Drives	
HP 120GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Boot 3yr Wty Solid State Drive	718171-B21
HP 80GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Boot 3yr Wty Solid State Drive	734362-B21
Hard Drive Blank Kits	
HP Large Form Factor Hard Drive Blank Kit	666998-B21
HP Small Form Factor Hard Drive Blank Kit	666997-B21
Disk Enclosures	
HP D2600 w/12 4TB 6G SAS 7.2K LFF Dual Port MDL HDD 48TB Bundle	E7W32A
Hard Drive Kits	
HP DL380 Gen9 8SFF Bay1 Cage/Backplane Kit	719067-B21
HP DL380 Gen9 Additional 8SFF Bay2 Cage/Backplane Kit	768857-B21
HP DL380 Gen9 2SFF Front/Rear SAS/SATA Kit	724864-B21
HP DL380 Gen9 3LFF Rear SAS/SATA Kit	768856-B21
Media Bay Kits	
HP DL380 Gen9 Universal Media Bay Kit	
NOTE: The Universal Media Bay offers front VGA and 2xUSB 3.0, plus ability to add optional Optical drive, or 2SFF.	724865-B21
NOTE: This is only compatible with the 8SFF or 8+8 SFF front end configurations.	
HP Networking	
1 Gigabit Ethernet adapters	
HP Ethernet 1Gb 4-port 311T Adapter	647594-B21
HP Ethernet 1Gb 2-port 311T Adapter	652497-B21
HP Ethernet 1Gb 2-port 323T Adapter	615732-B21
HP Ethernet 1Gb 4-port 366FLR FIO Adapter	684217-B21
HP Ethernet 1Gb 4-port 331FLR Adapter	629135-B22
10 Gigabit Ethernet adapters	
HP Ethernet 10Gb 2-port 530SFP Adapter	652503-B21
HP Ethernet 10Gb 2-port 530T Adapter	656596-B21



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Core Options

HP Ethernet 10Gb 2-port 560SFP+ Adapter	665249-B21
HP Ethernet 10Gb 2-port 561T Adapter	716591-B21
HP Ethernet 10Gb 2-port 570SFP+ Adapter	716904-B21
HP FlexFabric 10Gb 2-port 566FLR-SFP+ Adapter	727060-B21
HP StoreFabric 10Gb 2-port 566FLR-SFP+ Adapter	E7Y06A
NOTE: A minimum of two gigabytes (2 GB) of server memory is required per each adapter.	
NOTE: Direct Attach Cable (DAC) for copper environments or fiber transceivers and cables for fiber-optic environments must be purchased separately. Please see the related NIC QuickSpecs for Technical Specifications and additional information: www.hp.com/go/ProLiantNICs .	
FlexibleLOM Adapters	
HP Ethernet 1Gb 4-port 366FLR Adapter	665240-B21
HP FlexFabric 10Gb 2-port 533FLR-T Adapter	700759-B21
HP Ethernet 10Gb 2-port 560FLR-SFP+ Adapter	665243-B21
HP Ethernet 10Gb 2-port 561FLR-T Adapter	700699-B21
NOTE: Only one FlexibleLOM can be added to the server. These options are upgradeable and can be changed from the original configuration after the server is shipped.	
NOTE: Direct Attach Cable (DAC) for copper environments or fiber transceivers and cables for fiber-optic environments must be purchased separately. Please see the related NIC QuickSpecs for Technical Specifications and additional information: www.hp.com/go/ProLiantNICs .	
HP InfiniBand	
HP InfiniBand FDR 2-port 545QSFP Adapter	702211-B21
HP I/O Expansion Options	
HP DL380 Gen9 Primary 2 Slot GPU Ready Riser Kit	
NOTE: This is for slot 2 and supports double wide GPGPUs	719076-B21
Slot1: 1x Gen3 x16 FH/FL 1x Gen3 x8 FH/HL	
HP DL380 Gen9 Secondary 3 Slot GPU Ready Riser Kit	
NOTE: This is for slot 2 and supports double wide GPGPUs	719073-B21
Slot2: 2x Gen3 x16 FH/FL 1x Gen3 x8 FH/HL	
NOTE: To support Graphics cards please also order the DL380 Gen9 Graphics Enablement kit, 719082-B21 that ships with 2 Performance Heatsinks and 6 cables. 1 kit needed for a 2P unit.	
HP Power Supplies	
NOTE: Mixing of power supplies in the same server is not supported. All power supplies must be of the same input voltage, output rating, and efficiency rating. If non-matching power supplies are installed, you may receive an error message and/or experience operational issues with your server.	
NOTE: Prior to selecting a power supply option, it is highly recommended that you review your server configuration in the HP Power Advisor tool to determine the right size power supply for your server configuration. The HP Power Advisor is located at: www.hp.com/go/hppoweradvisor .	
HP Flex Slot Platinum Hot-Plug Power supplies	
HP 500W Flex Slot Platinum Hot Plug Power Supply Kit	720478-B21
HP 800W Flex Slot Platinum Hot Plug Power Supply Kit	720479-B21
HP 1400W Flex Slot Platinum Hot Plug Power Supply Kit	720620-B21
NOTE: The above power supply options are all 80Plus Platinum-certified with an efficiency rating of up to 94%. Support for HP Power Discovery Services is included with the 1400W Flex Slot option. Power specifications and technical content for all HP Server power supplies can be found at www.hp.com/go/proliant/powersupply .	
NOTE: Maximum of 2 Flex Slot PS per platform	
HP Computation and Graphics Accelerators	
HP DL380 2nd Graphics Enablement Kit	719082-B21
NOTE: This GPU enablement kit includes 2 Heatsinks and 6 cables to enable double wide GPUs to be supported.	
NOTE: For doublewide GPU support you are required to have at least 1x1400W Power Supply (720620-B21), per card.	
NOTE: There are limitations on the chassis and processor supported when adding Graphics accelerators	
NOTE: Some cards will require the addition of the High Performance Ambient Temperature Fan Kit (719079-B21)	
HP NVIDIA GRID K1 Quad GPU PCIe Graphics Accelerator	J0G94A
NOTE: This GPU enablement kit includes 2 Heatsinks and 6 cables to enable double wide GPU's to be supported.	
NOTE: Is supported in all chassis with either increased or Max cooling settings	
NOTE: The Primary GPU riser (719076-B21) is required to support this in slot1	
NOTE: The secondary GPU riser (719073-B21) is required to support this in slot2 (2nd processor required)	
NOTE: For doublewide GPU support you are required to have at least 1x1400W Power Supply (720620-B21), per card.	
NVIDIA GRID K2 Reverse Air Flow Dual GPU PCIe Graphics Accelerator	753958-B21
NOTE: This GPU enablement kit includes 2 Heatsinks and 6 cables to enable double wide GPU's to be supported.	
NOTE: For doublewide GPU support you are required to have at least 1x1400W Power Supply (720620-B21), per card.	
NOTE: There are limitations on the chassis and processor supported when adding Graphics accelerators	
NOTE: This card will require the addition of the High Performance Ambient Temperature Fan Kit (719079-B21)	
NVIDIA Tesla K40C 12GB Computational Accelerator	753960-B21
NOTE: This GPU enablement kit includes 2 Heatsinks and 6 cables to enable double wide GPUs to be supported.	
NOTE: This is supported in all chassis.	
NOTE: The Primary GPU riser (719076-B21) is required to support this in slot1	
NOTE: The secondary GPU riser (719073-B21) is required to support this in slot2 (2nd processor required)	
NOTE: For doublewide GPU support you are required to have at least 1x1400W Power Supply (720620-B21), per card.	
HP NVIDIA Quadro K2200 Graphics Accelerator	J0G89A
NOTE: This GPU enablement kit includes 2 Heatsinks and 6 cables to enable double wide GPUs to be supported.	
NOTE: Is supported in all chassis.	
NOTE: The Primary GPU riser (719076-B21) is required to support this in slot1	
NOTE: The secondary GPU riser (719073-B21) is required to support this in slot2 (2nd processor required)	
NOTE: For doublewide GPU support you are required to have at least 1x1400W Power Supply (720620-B21), per card.	
HP NVIDIA Quadro K4200 Graphics Accelerator	J0G90A
NOTE: This GPU enablement kit includes 2 Heatsinks and 6 cables to enable double wide GPUs to be supported.	
NOTE: Is supported in all chassis.	
NOTE: The Primary GPU riser (719076-B21) is required to support this in slot1	
NOTE: The secondary GPU riser (719073-B21) is required to support this in slot2 (2nd processor required)	



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Core Options

(processor required).
NOTE: For doublewide GPU support you are required to have at least 1x1400W Power Supply (720620-B21), per card.

NVIDIA Quadro K6000 PCI-E Graphics Adapter

730874-B21

NOTE: The GPU enablement kit includes 2 Heatsinks and 6 cables to enable double wide GPUs to be supported.

NOTE: This is supported in all chassis.

NOTE: The Primary GPU riser (719076-B21) is required to support this in slot1

NOTE: The secondary GPU riser (719073-B21) is required to support this in slot2 (2nd processor required).

NOTE: For doublewide GPU support you are required to have at least 1x1400W Power Supply (720620-B21), per card.

HP 150W PCI-E Power Cable Kit

669777-B21

NOTE: Each DL380 Gen9 server will accommodate up to three single-width or two double width PCIe cards for Computational Graphics support

NOTE: The NVIDIA Tesla, GRID and Quadro modules are supported only on 64-bit versions of Linux and Windows operating systems as well as on Virtual Machine client operating systems. The supported bare metal operating systems are RHEL6, SLES 11 and Windows Server 2012 R2

NOTE: There are limitations on fan types, setting, and chassis support by card.

HP Cooling Options

HP DL380 Gen9 High Performance Temperature Fan Kit

NOTE: The High Performance Temperature Fan kit consists of 6 fans, these will need to replace all the standard Fans in the unit, and fill all 6-Fan cages

NOTE: The 12LF and 24SF chassis (including field upgrades to 24SF) will already include 6 High Performance Fan kits.

NOTE: The High Performance Temperature Fan Kit is needed to support certain

GPGPU (Graphics cards) configurations; or ASHRAE operating environments.

NOTE: For elevated ambient temperature support please see:

www.hp.com/servers/ASHRAE

719079-B21



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Additional Options

NOTE: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, HP recommends the use of an HP approved configurator.

Contact your local sales representative for additional information.

HP Insight Software

HP Insight Control

HP Insight Control including 1yr 24x7 Technical Support and Updates Single Server License

CGN27A

HP Insight Control including 1yr 24x7 Technical Support and Updates Electronic License

CGN28ABE

NOTE: The Electronic software license is available in EMEA only.

HP Insight Control Server Provisioning Media Kit

HP Insight Management Media Kit

BD883A

NOTE: Electronic and Flexible-Quantity licenses can be used to purchase multiple licenses with a single activation key.

NOTE: Customer will receive a license entitlement certificate. The license entitlement certificate must be redeemed online or via fax in order to obtain a license activation key(s). Includes one year of 24 x 7 HP Software Technical Support and Update Service.

CGN31A

NOTE: This includes the physical media. The Insight Control Server Provisioning Media Kit can be ordered separately, or can be downloaded at: <http://www.hp.com/go/insightupdates>.

NOTE: For additional license options please see the QuickSpecs at:

http://h18000.www1.hp.com/products/quickspecs/12631_div/12631_div.html

HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL+bundle Single Server FIO License

CGN36A

HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL+bundle FIO Electronic License

CGN36ABE

HP ILO Advanced

HP ILO Advanced Electronic License with 3yr 24x7 Tech Support and Updates

BD0506AAE

Embedded Management

HP ILO Advanced including 1yr 24x7 Technical Support and Updates Single Server License

512485-B21

HP ILO Advanced with 3yr 24x7 Tech Support and Updates

BD505A

HP ILO Advanced including 1yr 24x7 Technical Support and Updates E-LTU

EGU59ABE

HP ILO Advanced including 3yr 24x7 Technical Support and Updates E-LTU

EGU64ABE

HP ILO Advanced including 1yr 24x7 Technical Support and Updates Electronic License

TA850AAE

High Performance Clusters

HP Cluster Management Utility

HP Insight Cluster Management Utility 1yr 24x7 Flexible License

QL803B

HP Insight Cluster Management Utility 3yr 24x7 Flexible License

BD476A

NOTE: These part numbers can be used to purchase one certificate for multiple licenses. Each certificate is good for one node (server). Each server will receive a printed end user license agreement and license entitlement certificate via physical shipment. The license entitlement certificate must be redeemed online in order to obtain a license key. Customer also will receive a support agreement.

HP Insight Cluster Management Utility Media

BD477A

NOTE: For additional license kits please see the QuickSpecs at:

http://h18000.www1.hp.com/products/quickspecs/12612_div/12612_div.html

HP Security

HP 2U Security Bezel Kit

666998-B21

HP Trusted Platform Module Option

488069-B21

NOTE: The TPM (Trusted Platform Module) is a microcontroller chip that can securely store artifacts used to authenticate the server platform. These artifacts can include passwords, certificates and encryption keys. Windows® BitLocker™ Drive Encryption (BitLocker) is a data protection feature available in Windows Server® 2008. BitLocker leverages the enhanced security capabilities of a Trusted Platform Module (TPM) version 1.2. The TPM works with BitLocker to help protect user data and to ensure that a server running Windows Server 2008 has not been tampered with while the system was offline. For more information about TPM, including a white paper, go to: www.hp.com/go/TPM.

NOTE: PreLiant OS pre-installed units will come with the partition required for TPM deployment.

NOTE: The TPM key is unique to every TPM deployed server and must be retained. Misplacing or losing the key could result in data loss.

HP Storage Controllers

SAS Controllers

HP Flexible Smart Array Controllers

726736-B21

HP Smart Array P440ar/2GB FBWC 12Gb 2-ports Int SAS Controller

749974-B21

NOTE: Includes the HP Smart Storage Battery

HP Smart Array P440ar/2GB FBWC 12Gb 2-ports Int FIO SAS Controller

726757-B21

NOTE: Includes the HP Smart Storage Battery

HP H240ar 12Gb 1-port Int Smart Host Bus Adapter

749976-B21

HP H240ar 12Gb 1-port Int FIO Smart Host Bus Adapter

HP Smart Array Controllers

HP Smart Array P440/4GB FBWC 12Gb 1-port Int SAS Controller

726821-B21

HP Smart Array P840/4GB FBWC 12Gb 2-ports Int SAS Controller

726897-B21

HP Smart Array P441/4GB FBWC 12Gb 2-ports Ext SAS Controller

726825-B21

HP Smart Array P440/4GB FBWC 12Gb 1-port Int FIO SAS Controller

761872-B21

HP Smart Array P840/4GB FBWC 12Gb 2-ports Int FIO SAS Controller

761874-B21

HP Cable Options

HP DL380 Gen9 P040/440 SAS Cable Kit

783007-B21

HP DL380 Gen9 25FF Front SAS x4 Cable Kit

783008-B21

HP DL380 Gen9 85FF SAS Cable Kit

783009-B21

HP DL380 Gen9 25FF x8 Front Cable Kit

785989-B21

HP DL380 Gen9 12LF1 SAS Cable Kit

785991-B21

HP DL380 Gen9 85FF H240 Cable Kit

786092-B21

HP DL380 Gen9 12LF1 H240 SAS Cable Kit

786215-B21

For details on cabling options, additional information available here: Cabling Matrix

Optional Upgrades

HP 96W Smart Storage Battery with 145mm Cable for DL/ML/SL Servers

727258-B21

NOTE: Provide backup power for multiple HP Smart Array controllers or other devices (up to 16)

HP 12Gb SAS Expander Card with Cables for DL380 Gen9

727250-B21

HP Tape Backup

NOTE: For the complete range of tape drives, autoloaders, libraries and media see: <http://www.hp.com/go/tape>. For hardware and software compatibility of HP tape backup products see: <http://www.hp.com/storage/SPOCK> and <http://www.hp.com/go/els>.

Tape Drives



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Additional Options

HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive	EH964A
HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader	COH19A
HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit	COL99A
HP StoreEver LTO-4 Ultrium 1760 SAS External Tape Drive	EH920B
HP StoreEver LTO-4 Ultrium 1760 SAS (1) in 1U Rack-mount Kit	EH946C
HP StoreEver LTO-5 Ultrium 3000 SAS External Tape Drive	EH958B
HP StoreEver LTO-5 Ultrium 3000 SAS Tape Drive in 1U Rack-mount	EJ014B
HP StoreEver LTO-5 Ultrium 3280 SAS External Tape Drive	EH900B
HP StoreEver LTO-5 Ultrium 3280 SAS Tape Drive in 3U Rack-mount	EJ013B
HP StoreEver LTO-6 Ultrium 6250 External Tape Drive	EH970A
HP StoreEver TU SAS Rack-mount Kit	AE459B
HP StoreEver LTO-4 Ultrium 1760 SCSI External Tape Drive	EH922B
HP Tape Storage Systems	
HP StoreEver MSL6480	
HP StoreEver MSL6480 Scalable Expansion Module	
NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18006.www1.hp.com/storage/saninfrastructure/hba.html (Worldwide).	QU626A
HP StoreEver MSL6480 Scalable Base Module	QU625A
HP MSL2024 0-Drive Tape Library	AK379A
HP MSL4048 0-Drive Tape Library	AK381A
HP MSL Library Extender Kit	AQ746A
HP Storage Options	
NOTE: For the complete listing of Fibre Channel Host Bus Adapters for Windows 2000, Windows Server 2003 and Linux, please see: http://h18006.www1.hp.com/storage/saninfrastructure/hba.html .	
Emulex Fibre Channel HBAs	
HP 81E 8Gb 1-port PCIe Fibre Channel Host Bus Adapter	AJ762B
HP 82E 8Gb 2-port PCIe Fibre Channel Host Bus Adapter	AJ763B
HP StoreFabric SNT100E 16Gb Single Port Fibre Channel Host Bus Adapter	C8R38A
HP StoreFabric SNT100E 16Gb Dual Port Fibre Channel Host Bus Adapter	C8R39A
QLogic Fibre Channel HBAs	
HP 81Q 8Gb 1-port PCIe Fibre Channel Host Bus Adapter	AK344A
HP 82Q 8Gb 2-port PCIe Fibre Channel Host Bus Adapter	AJ764A
HP StoreFabric SNT100Q 16Gb 1-port PCIe Fibre Channel Host Bus Adapter	QW971A
HP StoreFabric SNT100Q 16Gb 2-port PCIe Fibre Channel Host Bus Adapter	QW972A
Converged Network Adapter	
HP StoreFabric CN1100R Dual Port Converged Network Adapter	QW990A
HP Disk Storage Systems	
Disk Enclosures	
HP D6000 Dual 1/0 Module Disk Enclosure	QG695A
HP D6000 w/35 4TB 6G SAS 7.2K LFF Dual Port MDL HDD 140TB Bundle	E7W30A
HP D6000 w/70 4TB 6G SAS 7.2K LFF Dual Port MDL HDD 280TB Bundle	E7W31A
HP D6000 w/35 2TB 6G SAS 7.2K LFF Dual port MDL HDD 70TB Bundle	QG697A
HP D6000 w/70 2TB 6G SAS 7.2K LFF Dual port MDL HDD 140TB Bundle	QG698A
HP D6000 w/35 3TB 6G SAS 7.2K LFF Dual port MDL HDD 105TB Bundle	QG699A
HP D6000 w/70 3TB 6G SAS 7.2K LFF Dual port MDL HDD 210TB Bundle	QG700A
HP Data Center Racks	
HP 11000 G2 Series Racks	
HP 11648 1075mm Pallet Universal Rack	H6JB7A
HP 11648 1075mm Shock Universal Rack	H6JB8A
HP 11642 1075mm Pallet Universal Rack	H6J65A
HP 11642 1075mm Shock Universal Rack	H6J66A
HP 11642 1200mm Pallet Universal Rack	H6J67A
HP 11642 1200mm Shock Universal Rack	H6J68A
HP 11636 1075mm Pallet Universal Rack	H6J77A
HP 11636 1075mm Shock Universal Rack	H6J78A
HP 11622 G2 1075mm Pallet Universal Rack	H6JB3A
HP 11622 G2 1075mm Shock Universal Rack	H6JB4A
HP 11614 1075mm Shock Universal Rack	H6JB2A
NOTE: Please see the HP 11000 G2 Series Racks QuickSpec for information on additional racks options and rack specifications.	
HP Intelligent Series Racks	
HP 647 1075mm Pallet Intelligent Series Rack	BW911A
HP 647 1075mm Shock Intelligent Series Rack	BW912A
HP 647 1200mm Pallet Intelligent Series Rack	BW913A
HP 647 1200mm Shock Intelligent Series Rack	BW914A
HP 642 1075mm Pallet Intelligent Series Rack	BW903A
HP 642 1075mm Shock Intelligent Series Rack	BW904A
HP 642 1200mm Pallet Intelligent Series Rack	BW907A
HP 642 1200mm Shock Intelligent Series Rack	BW908A
HP 636 1075mm Pallet Intelligent Series Rack	BW895A
HP 636 1075mm Shock Intelligent Series Rack	BW896A
HP 842 1075mm Pallet Intelligent Series Rack	BW917A
HP 842 1075mm Shock Intelligent Series Rack	BW918A
NOTE: Please see the HP Intelligent Series Racks QuickSpec for information on additional racks options and rack specifications.	
HP Value Series Rack	
HP V1142 1075mm Deep Pallet 100 series Rack	AF046A
NOTE: Please see the HP Value Series Rack QuickSpec for information on additional racks options and rack specifications.	
HP Power Distribution Units (PDUs)	
HP Basic Power Distribution Unit (BPDU)	
HP 4.9kVA 24A High Voltage NA/JP Core Modular Power Distribution Unit	252663-D74
HP 8.3kVA 40A High Voltage NA/JP Core Modular Power Distribution Unit	252663-D75
HP 7.3kVA 32A High Voltage INTL Core Modular Power Distribution Unit	252663-B33
HP 17.3kVA 48A Three Phase NA/JP Modular Power Distribution Unit	AF511A
HP 22kVA 32A Three Phase INTL Core Modular Power Distribution Unit	AF518A
HP 3.6kVA 200-240 Volt Detachable C20 Input (12xC13) WW Basic PDU	HSMS6A



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Additional Options

HP 4.9kVA 208 Volt L6-30 Input (20xC13) NA/JP Basic PDU	H5M58A
HP 7.3kVA 230 Volt IEC309 32A Input (20xC13) INTL Basic PDU	H5M68A
HP 7.3kVA 230 Volt IEC309 32A Input (24xC13/6xC19) INTL Basic PDU	H5M70A
NOTE: To learn more about HP Basic Power Distribution Units (bPDU), please visit the HP website at www.hp.com/go/bpdu .	
HP Monitored Power Distribution Units (mPDU)	
HP 2.8kVA 120 Volt L5-30 Input (12xNEMA 5-20RINA)JP Monitored PDU	D9N43A
HP 3.6kVA 200-240 Volt Detachable C20 Input (16xC13) WW Monitored PDU	D9N45A
HP 4.9kVA 208 Volt L6-30 Input (20xC13/4xC19) NA/JP Monitored PDU	D9N47A
HP 7.3kVA 230 Volt IEC309 32A Input (20xC13/4xC19) INTL Monitored PDU	D9N48A
HP 7.3kVA 230 Volt IEC309 32A Input (3x2xC13/4xC19) INTL Monitored PDU	D9N50A
HP 11kVA 400 Volt IEC309 16A 3-Phase Input (18xC13/3xC19) INTL Monitored PDU	D9N55A
HP 11kVA 400 Volt IEC309 16A 3-Phase Input (30xC13/3xC19) INTL Monitored PDU	D9N57A
HP 7.3kVA 208 Volt IEC309 60A 3-Phase Input (12xC13/3x2xC19) NA/JP Monitored PDU	D9N59A
HP 22kVA 400 Volt IEC309 32A 3-Phase Input (30xC13/3xC19) INTL Monitored PDU	D9N56A
HP 22kVA 400 Volt IEC309 32A 3-Phase Input (12xC13/12xC19) INTL Monitored PDU	D9N60A
NOTE: Please see the HP Monitored Power Distribution Units QuickSpec for information on additional options and product specifications.	
HP Intelligent Power Distribution Units (iPDU)	
HP 4.9kVA 24A Single Phase NA/JP Core Intelligent Modular Power Distribution Unit	AF520A
HP 8.3kVA 40A Single Phase NA/JP Core Intelligent Modular Power Distribution Unit	AF521A
HP 8.6kVA 24A Three Phase NA/JP Core Intelligent Modular Power Distribution Unit	AF522A
HP 17.3kVA 48A Three Phase NA/JP Core Intelligent Modular Power Distribution Unit	AF523A
HP 17.3kVA 48A 208V Three Phase 12 Outlet Core NA/JP Intelligent Power Distribution Unit	AF535A
HP 4.9kVA 24A Single Phase NA/JP Intelligent Modular Power Distribution Kit	AF531A
HP 8.6kVA 24A Three Phase NA/JP Intelligent Modular Power Distribution Kit	AF532A
HP 7.3kVA 32A Single Phase INTL Core Intelligent Modular Power Distribution Unit	AF525A
HP 7.3kVA 32A Single Phase INTL Intelligent Modular Power Distribution Kit	AF534A
NOTE: Please see the HP Intelligent Power Distribution Units QuickSpec for information on additional options and product specifications.	
HP Rack Mount Consoles, KVM Switches, and Keyboards	
HP Rack Mount Consoles	
HP TFT7600 G2 KVM Console Rackmount Keyboard US Monitor	AZ870A
HP TFT7600 G2 KVM Console Rackmount Keyboard INTL Monitor	AZ884A
NOTE: Please see the HP Rack Console QuickSpec for information on additional options and product specifications.	
Rail Kits	
NOTE: Gen9 rail kits have changed significantly from prior generation rail kits. Please take a moment to review the installation documentation that comes with the server to help you with the installation of your Gen9 server.	
NOTE: Rail kits are optional for DL380 Gen9 and are no longer included standard with the server. Customers have the option to purchase their server without a rail kit.	
NOTE: Ball bearing and Easy Install rail kits contain telescoping rails which allow for in-rack serviceability.	
NOTE: Ball bearing rail assembly must be installed with the server into the rack an optional installation tool is available by contacting your local service representative (408-655-539-00).	
Caution: HP recommends that a minimum of two people are required for all Rack Server installations. Please refer to your installation instructions for proper tools and number of people to use for any installation.	
HP 2U Small Form Factor Easy Install Rail Kit	733660-B21
NOTE: Does not include CMA (733664-B21)	
HP 2U Large Form Factor Easy Install Rail Kit	733662-B21
NOTE: Does not include CMA (733664-B21)	
HP 2U Cable Management Arm for Easy Install Rail Kit	733664-B21
HP 2U Small Form Factor Ball Bearing Rail Kit	720865-B21
NOTE: Does not include CMA (720865-B21)	
HP 2U Large Form Factor Ball Bearing Rail Kit	720864-B21
NOTE: Does not include CMA (720865-B21)	
HP 2U Cable Management Arm for Ball Bearing Rail Kit	720865-B21
HP KVM Switches	
HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software	AF620A
HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software	AF621A
HP Server Console 0x2x8 Port Analog Switch	AF616A
HP Server Console 0x2x16 Port Analog Switch	AF617A
HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software	AF618A
HP 1x1US/PS2 KVM Console Switch	AF611A
NOTE: To learn more, please visit the HP KVM Switches web page.	
HP USB Keyboard and Mouse	
HP USB BFR with PVC Free US Keyboard/Mouse Kit	631341-B21
HP USB BFR with PVC Free INTL Keyboard/Mouse Kit	672097-B33
NOTE: Please see the HP USB Keyboard and Mouse QuickSpec for information on additional options and product specifications.	
HP 1U Rackmount Keyboard with USB	
HP 1U US Rackmount Keyboard with USB	AG072A
HP 1U INTL Rackmount Keyboard with USB	
NOTE: Please see the HP 1U Rackmount Keyboard QuickSpec for information on additional options and product specifications.	
HP Uninterruptible Power Systems (UPS)	
HP Rack-mountable UPS	
HP R1.5kVA G3 1U INTL Uninterruptible Power System	AF471A
HP R1.5kVA G3 1U JP/TW Uninterruptible Power System	AF470A
HP R/T3000 G2 2U L530 Low Voltage NA/JP Uninterruptible Power System	AF466A
HP R/T3000 G2 2U Detachable Cord High Voltage INTL Uninterruptible Power System	AF468A
HP R5KVA 3U IEC309-32A High Voltage INTL Uninterruptible Power System	AF461A
HP R7KVA 4U IEC-32A High Voltage INTL Uninterruptible Power System	AF463A
HP RP12000/3 6U International (INTL) Uninterruptible Power System Module	AF437A
NOTE: To learn more, please visit the HP Uninterruptible Power Systems (UPS) web page.	




QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Memory

Memory Subsystem Architecture Each Intel® Xeon® E5-2600v3 family processor socket contains four memory channels per installed processor with three DIMMs per channel for a total of twelve (12) DIMMs or a grand total of twenty-four (24) DIMMs for the server.

Memory Population guidelines



DIMM population order		
1st slot of channel	2nd slot of channel	3rd slot of channel
A B C D	E F G H	I J K L
Number of DIMMs to install	4	
of DIMMs	8	
to install	12	

General Memory Population Rules and Guidelines:

- White DIMM slots denote the first slot of a channel. For 1 DPC (DIMM per channel) populate white slots only.
- A minimum of one DIMM is required per server.
- Install DIMMs only if the corresponding processor is installed.
- If only one processor is installed in a two processor system, only half of the DIMM slots are available.
- To maximize performance, it is recommended to balance the total memory capacity between all installed processors and to load the channels similarly whenever possible.
- When two processors are installed, balance the DIMMs across the two processors.
- Populate DIMMs from heaviest load (quad-rank) to lightest load (single-rank) within a channel. Heaviest load (DIMM with most ranks) within a channel goes furthest from the processor.
- RDIMMs operating at either 1.35V or 1.5V may be mixed in any order, but the system will power them at the higher voltage.
- Do not mix RDIMMs or LRDIMMs.
- LRDIMMs are supported up to 3 DIMMs per channel.
- Using the HP RBSU, 1.35V DIMMs can be changed to operate at 1.5V.
- DIMMs of different speeds may be mixed in any order; the server will select a common optimal speed.
- The maximum memory speed is a function of the memory type, memory configuration, and processor model.
- The maximum memory capacity is a function of the memory type and number of installed processors.
- HP memory from previous generation servers is not compatible with the DL380 Gen9 Server. Certain HP SmartMemory features such as memory authentication and enhanced performance may not be supported.
- To realize the performance memory capabilities listed in this document, HP SmartMemory is required. For additional information, please see the HP SmartMemory QuickSpecs at: http://h18000.www1.hp.com/products/quickspecs/14223_div/14225_jdiv.html (Worldwide).
- For memory population rules and additional memory guidelines, please see the DL380 Gen9 user guide at: <http://www.hp.com/support>.
- There are four (4) Memory channels per processor; eight (8) channels per 2 processor server.
- There are three (3) DIMM slots for each memory channel; twenty four (24) total slots for 2 processor server.
- Memory channels 1 and 3 consists of the three (3) DIMMs that are furthest from the processor.
- Memory channel 2 and 4 consists of the three (3) DIMMs that are closest to the processor.

Intel Gen9 Supported Memory Bandwidth for HP ProLiant Gen8 Intel® Xeon®E5-2600v3 Series Processor Family

Memory Bandwidth and Capacity

[DIMM Type]	Registered DIMMs (RDIMMs)	Load Reduced (LRDIMMs)	
DIMM Rank	Single Rank	Dual Rank	Quad Rank
DIMM Capacity	8GB	16GB	32GB
DIMM Native Speed (MT/s)			
Voltage	Std Voltage 1.2V		

SLOTS THAT CAN BE POPULATED		
24 slot servers	24	
MAXIMUM CAPACITY (GB)		
192	384	768



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Memory

1 DIMM Per Channel	2133		
2 DIMM Per Channel	2133		
3 DIMM Per Channel	1600	1600	1600

DIMM slot and configuration diagram

DIMM slot and configuration diagrams

Basic memory slot & population diagram

- Population order; start with "A" first, "B" second, "C" third, etc.
 - When one processor is installed, install DIMMs in sequential alphabetic order: A, B, C, D, E, F
 - When two processors are installed, install DIMMs in sequential alphabetic order: CPU1-A, CPU2-A, CPU1-B, CPU2-B, CPU1-C, CPU2-C

CPU 1		CPU 2	
Slot #	population order	Slot #	population order
1		1	

Processor Model	Processor Models	Supported Memory Speeds
E5-2609v3, E5-2609v5		1600MHz
E5-2620v3, E5-2623v3, E5-2630v3, E5-2630Lv3, E5-2633v3		1866MHz
E5-2637v3, E5-2643v3, E5-2650v3, E5-2650Lv3, E5-2650Lv5, E5-2670v3, E5-2670Lv3, E5-2683v3, E5-2690v3, E5-2695v3, E5-2697v3, E5-2699v3, E5-2699Lv3, E5-2687Wv3,	2133MHz	


Standard and Maximum Memory Capacity (Pre-configured Models)

Pre-Configured Models	Standard Memory	Maximum Memory Plus Optional Memory	Standard Memory Replaced with Optional Memory
E5-2609v3	8GB (1x8GB)	376GB (2x16GB, 1x8GB)	768GB (2x32GB)
E5-2620v3	16GB (1x16GB)	384GB (2x16GB, 1x16GB)	768GB (2x32GB)
E5-2650v3	32GB (2x16GB)	384GB (2x216GB, 2x16GB)	768GB (2x32GB)

DDR4 memory options part number decoder

NOTE: Capacity references are rounded to the common gigabyte (GB) values.

- 2GB = 2,048MB
 - 4GB = 4,096MB
 - 8GB = 8,192MB
 - 16GB = 16,384MB
 - 32GB = 32,768MB




QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Storage


4LFF hot-plug drive model



1-4

4 x LFF SATA/SAS/SSD Hot Pluggable Hard Drive Bays

12 LFF + 3 rear LFF hot-plug drive model



1-12


12 x LFF SATA/SAS/SSD Hot Pluggable Hard Drive Bays



1-3

3 x LFF SATA/SAS/SSD Hot Pluggable Rear Hard Drive Bays

12 LFF + 2 rear SFF hot-plug drive model



1-12

12 x LFF SATA/SAS/SSD Hot Pluggable Hard Drive Bays



1-2

2 x SFF SATA/SAS/SSD Hot Pluggable Rear Hard Drive Bays

8 SFF (+2 SFF) hot-plug drive model with Universal Media Bay




1-8

8 x SFF SATA/SAS/SSD Hot Pluggable Hard drive bays

1-2

2 x SFF SATA/SAS/SSD Hot Pluggable Hard Drive Bays

16 SFF (+2 SFF) hot-plug drive model with Universal Media Bay



1-16

16 x SFF SATA/SAS/SSD Hot Pluggable Hard drive bays

1-2

2 x SFF SATA/SAS/SSD Hot Pluggable Hard Drive Bays

24 SFF + rear 2 SFF hot-plug drive model



1-24

24 x SFF SATA/SAS/SSD Hot Pluggable Hard drive bays



1-2

2 x SFF SATA/SAS/SSD Hot Pluggable Rear Hard Drive Bays

QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Technical Specifications

System Unit	Dimensions	SFF Drives: 3.44 x 17.54 x 26.75 in (8.73 x 44.55 x 67.94 cm) LFF Drives: 3.44 x 17.54 x 28.75 in (8.73 x 44.55 x 73.02 cm) NOTE: Dimensions without Bezel
Weight (approximate)	Minimum (Minimum = 8SFF chassis with 1xSFF HDD and 7xHDD blanks, 1x processor, 1x power supply (plus blank), 1x Flexible Smart Array, 1x Riser installed) Maximum (Maximum = 12 LFF hard drives (No rear drives), 2x processors, 2x power supplies, 1x Flexible Smart Array, 2x Risers installed)	32.6 lb (14.759 kg) 51.5 lb (23.6 kg)
Input Requirements (per power supply)	Range Line Voltage	100 to 120 VAC 200 to 240 VAC
BTU Rating	Maximum	For 800W Power Supply: 3207 BTU/hr (at 100 VAC), 3071 BTU/hr (at 200 VAC), 3112 BTU/hr (at 240 VAC) for China Only For 500W Power Supply: 1979 BTU/hr (at 100 VAC), 1911 BTU/hr (at 200 VAC), 1965 BTU/hr (at 240 VAC) for China Only
Power Supply Output (per power supply)	Rated Steady-State Power	For 1400W Power Supply: 1400W (at 100 VAC), 1400W (at 240 VAC), 1400W (at 240 VAC) For 800W Power Supply: 800W (at 100 VAC), 800W (at 240 VAC), 800W (at 240 VAC) input for China only For 500W Power Supply: 500W (at 100 VAC), 500W (at 240 VAC), 500W (at 240 VAC) input for China only
	Maximum Peak Power	For 1400W Power Supply: 1400W (at 100 to 127 VAC), 1400W (at 200 to 240 VAC), 1400W (at 240 VAC) input for China only For 800W Power Supply: 800W (at 100 to 127 VAC), 800W (at 200 to 240 VAC), 800W (at 240 VAC) input for China only For 500W Power Supply: 500W (at 100 to 127 VAC), 500W (at 200 to 240 VAC), 500W (at 240 VAC) input for China only
System Inlet Temperature	Standard Operating Support	10° to 35°C (50° to 95°F) at sea level with an altitude derating of 1.0°C per every 305 m (1.8°F per every 1000 ft) above sea level to a maximum of 40°C (104°F) at 3050 m (10,000 ft). The upper limit and rate of change is 20°C/hr (36°F/hr). The upper limit and rate of change may be limited by the type and number of options installed. For approved hardware configurations, the supported system inlet range is extended to be: 5° to 40°C (41° to 104°F) at sea level with an altitude derating of 1.0°C per every 175 m (1.8°F per every 574 ft) above 900 m (2953 ft) to a maximum of 3050 m (10,000 ft). The approved hardware configurations for this system are listed at the URL: www.hp.com/go/proliant/Ashrae . For unapproved hardware configurations, the supported system inlet range is extended to be: 5° to 45°C (41° to 113°F) at sea level with an altitude derating of 1.0°C per every 125 m (1.8°F per every 410 ft) above 900 m (2953 ft) to a maximum of 3050 m (10,000 ft). The approved hardware configurations for this system are listed at the URL: www.hp.com/go/proliant/Ashrae .
	Extended Ambient Operating Support	
	Non-operating	-30° to 60°C (-22° to 140°F). Maximum rate of change is 20°C/hr (36°F/hr).
Relative Humidity	Operating	Minimum to be the higher (more moisture) of -12°C (10.4°F) dew point or 8% relative humidity. Maximum to be the lower (less moisture) of 24°C (75.2°F) dew point or 90% relative humidity.
	(non-condensing)	5 to 95% relative humidity (RH), 38.7°C (101.7°F) maximum wet bulb temperature, non-condensing.
Altitude	Operating	3050 m (10,000 ft). This value may be limited by the type and number of options installed. Maximum allowable altitude change rate is 457 m/min (150 ft/min).
	Non-operating	9144 m (30,000 ft). Maximum allowable altitude change rate is 457 m/min (150 ft/min).
Acoustic Noise	Listed are the declared A-Weighted sound power levels (LWAd) and declared average bystander position A-Weighted sound pressure levels (LpAm) when the product is operating in a 23°C ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74) and declared in accordance with ISO 9296 (ECMA 109).	
	Idle	
LWAd	4.0 B Entry LFF 4.1 B Entry 4.2 B Base 5.7 B Base LFF 4.3 B Perf	
LpAm	23 dB(A) Entry LFF 24 dB(A) Entry 24 dB(A) Base 39 dB(A) Base LFF 25 dB(A) Perf	
Operating		
LWAd	4.3 B Entry LFF 4.6 B Entry 4.8 B Base 5.9 B Base LFF 5.6 B Perf	
LpAm	25 dB(A) Entry LFF 29 dB(A) Entry 30 dB(A) Base 31 dB(A) Base LFF 39 dB(A) Perf	

NOTE: The Listed sound levels apply to standard shipping configurations (Entry LFF, Entry,



QuickSpecs

HP ProLiant DL380 Generation9 (Gen9)

Technical Specifications

Emissions Classification (EMC)		Base, Base LFF and Performance models) Additional options may result in increased sound levels. The Base LFF model leverages our High Efficiency Fans, other models are shipping with standard fan options			
FCC Rating Class A		Normative Standards CISPR 22; EN55022; EN55024; FCC CFR 47, Pt 15; ICES-003; CNS13438; GB9254; K2.K2; EN 61000-3-2; EN 61000-3-3; EN 60950-1; IEC 60950-1			
NOTE: Product conformance to cited product specifications is based on sample (type) testing, evaluation, or assessment. This product or family of products is eligible to bear the appropriate compliance logos and statements.					
NOTE: The Listed sound levels apply to standard shipping configurations. Additional options may result in increased sound levels.					
<hr/>					
HP Dynamic Smart Array B140i Controller	Number of PCI links	Four			
PCI link rate	4 Gb/s				
Storage protocol support	SATA				
SAS/SATA peak data transfer rate	6 Gb/s				
Number of SAS/SATA links	10 links				
SAS/SATA connectivity	2x4 connectors; 2x1 connectors				
Expander support	No				
Drives supported (max)	Up to 10 Internal Drives				
RAID support	0, 1, 10, 5 SATA				
Software management	HP SSA, SMH, SIM				
Warranty	Server warranty				
HP Secure Encryption license	Not Supported				
HP SmartCache License	Not Supported				
HP Smart Storage Administrator	Supported				
<hr/>					
HP Ethernet 1Gb 4-port 331i Adapter	Network Interface	10Base-T/100Base-TX/1000Base-TX			
	Compatibility	IEEE 802.3 10Base-T IEEE 802.3ab 1000Base-T IEEE 802.3u 100Base-TX			
	Ports				
	Data Transfer Method	PCI Express, two lanes (x2)			
	Controller	BCM5719			
	10Base-T (Half-Duplex)	10 Mb/s per port, 40 Mb/s combined			
	10Base-T (Full-Duplex)	20 Mb/s per port, 80 Mb/s combined			
	100Base-TX (Half-Duplex)	100 Mb/s per port, 400 Mb/s combined			
	1000Base-TX (Full-Duplex)	200 Mb/s per port, 800 Mb/s combined			
	1000Base-TX (Half and Full-Duplex)	1000Mb/s per port, 4000 Mb/s combined			
	1000Base-TX (Full-Duplex)	2000Mb/s per port, 8000 Mb/s combined			
	Connector	Four RJ-45			
	Cable Support	10 Base-T	Categories 3, 4 or 5 UTP; up to 328 ft (100 m)		
		10/100/1000 Base-TX	Category 5 or higher UTP; up to 328 ft (100 m)		
<hr/>					

Environment-friendly Products and Approach Hewlett-Packard offers end-of-life HP product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: <http://www.hp.com/go/green>. To recycle your product, please go to: <http://www.hp.com/go/green> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/green>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.



© Copyright 2014 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel® and Xeon® are registered trademarks of Intel Corporation in the U.S. and other countries.

Microsoft®, Windows®, and Windows Server® are U.S. registered trademarks of the Microsoft group of companies.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less

