

R (programming language)


R is a programming language and free software environment for statistical computing and graphics. It is supported by the R Core Team and the R Foundation for Statistical Computing.^[7] It is widely used among statisticians and data miners for developing statistical software and data analysis. Polls, data mining surveys, and studies of scholarly literature databases show that R is highly popular;^[8] since August 2021, R ranks 14th in the TIOBE index, a measure of programming language popularity.^[9]

The official R software environment is a GNU package. It is written primarily in C, Fortran, and R itself (partially self-hosting) and is available under the GNU General Public License. Precompiled executables are provided for various operating systems. It has a command line interface. Multiple third-party graphical user interfaces are available, such as RStudio, an integrated development environment; and Jupyter, a notebook interface.


Contents

- History**
- Features**
 - Statistics
 - Programming
- Packages**
- Milestones**
- Interfaces**
- Implementations**
- Communities**
- useR! conferences
- The R Journal*
- Comparison with alternatives
- Commercial support
- Examples**
 - Basic syntax
 - Structure of a function
 - Modeling and plotting
 - Mandelbrot set

R



R terminal

Paradigms	Multi-paradigm: <u>procedural</u> , <u>object-oriented</u> , <u>functional</u> , <u>reflective</u> , <u>imperative</u> , <u>array</u> ^[1]
Designed by	<u>Ross Ihaka</u> and <u>Robert Gentleman</u>
Developer	R Core Team
First appeared	August 1993
Stable release	4.1.2 ^[2] / 1 November 2021
Typing discipline	<u>Dynamic</u>
License	<u>GNU GPL v2</u>
Filename extensions	<u>.r</u> ^[3] <u>.rdata</u> <u>.rds</u> <u>.rda</u> ^[4]
Website	<u>www.r-project.org</u> (<u>https://www.r-project.org</u>) 
Influenced by	<u>Common Lisp</u> ^[5] · <u>S</u> · <u>Scheme</u> · <u>XLispStat</u>
Influenced	<u>Julia</u> ^[6]
 <u>R Programming at Wikibooks</u>	

[See also](#)[Notes](#)[References](#)[External links](#)

History

R is an implementation of the [S programming language](#) combined with [lexical scoping](#) semantics. It is inspired by [Scheme](#).^[1] S was created by [John Chambers](#) in 1976 while at [Bell Labs](#). A commercial version of S was offered as [S-PLUS](#) starting in 1988. Many codes written for S-PLUS run unaltered in R.^[10]

In 1991 [Ross Ihaka](#) and [Robert Gentleman](#) at the [University of Auckland](#), New Zealand, embarked on an S implementation, independent of S-PLUS. They began publicizing it in 1993.^[11] It was named partly after the first names of the first two R authors and partly as a play on the name of S.^[12] In 1995, [Martin Maechler](#) convinced Ihaka and Gentleman to make R [free and open-source software](#) under the [GNU General Public License](#).^{[13][14]} The R Core Team was formed in 1997 to further develop the language.^[12] As of 2021, it consisted of Gentleman, Ihaka, and Maechler, plus [Douglas Bates](#), [John Chambers](#), [Peter Dalggaard](#), [Kurt Hornik](#), [Tomas Kalibera](#), [Michael Lawrence](#), [Friedrich Leisch](#), [Uwe Ligges](#), [Thomas Lumley](#), [Martin Morgan](#), [Paul Murrell](#), [Martyn Plummer](#), [Brian Ripley](#), [Deepayan Sarkar](#), [Duncan Temple Lang](#), [Luke Tierney](#), and [Simon Urbanek](#). [Heiner Schwarte](#), [Guido Masarotto](#), [Stefano Iacus](#), [Seth Falcon](#), and [Duncan Murdoch](#) were members.^[15]

The first official release came in 1995.^[11] The [Comprehensive R Archive Network](#) (CRAN) was officially announced 23 April 1997 with 3 mirrors and 12 contributed packages.^[16] The first official "stable beta" version (v1.0) was released on 29 February 2000.^{[17][18]}

Features

Statistics

R and its libraries implement various statistical and [graphical](#) techniques, including [linear](#) and [nonlinear](#) modeling, classical statistical tests, [spatial](#) and [time-series analysis](#), [classification](#), [clustering](#), and others. R is easily extensible through functions and extensions, and its community is noted for contributing packages. Many of R's standard functions are written in R, which makes it easy for users to follow the algorithmic choices made. For computationally intensive tasks, [C](#), [C++](#), and [Fortran](#) code can be [linked](#) and called at run time. Advanced users can write C, C++,^[19] [Java](#),^[20] [.NET](#)^[21] or [Python](#) code to manipulate R objects directly.^[22] R is highly extensible through the use of packages for specific functions and specific applications. Due to its S heritage, R has stronger [object-oriented programming](#) facilities than most statistical computing languages. Extending it is facilitated by its [lexical scoping](#) rules.^[23]

Another of R's strengths is static graphics; it can produce publication-quality graphs that include mathematical symbols. Dynamic and interactive graphics are available through additional packages.^[24]

Programming

R is an interpreted language; users typically access it through a command-line interpreter. If a user types `2+2` at the R command prompt and presses enter, the computer replies with 4.

Like languages such as APL and MATLAB, R supports matrix arithmetic. R's data structures include vectors, matrices, arrays, data frames (similar to tables in a relational database) and lists.^[25] Arrays are stored in column-major order.^[26] R's extensible object system includes objects for (among others): regression models, time-series and geo-spatial coordinates. R has no scalar data type.^[27] Instead, a scalar is represented as a length-one vector.^[28]

Many features of R derive from Scheme. R uses S-expressions to represent both data and code. Functions are first-class objects and can be manipulated in the same way as data objects, facilitating meta-programming that allows multiple dispatch. Variables in R are lexically scoped and dynamically typed.^[29] Function arguments are passed by value, and are lazy—that is to say, they are only evaluated when they are used, not when the function is called.^[30]

R supports procedural programming with functions and, for some functions, object-oriented programming with generic functions.^[31] A generic function acts differently depending on the classes of the arguments passed to it. In other words, the generic function dispatches the method implementation specific to that object's class. For example, R has a generic print function that can print almost every class of object in R with `print(objectname)`^[32]

Although used mainly by statisticians and other practitioners seeking an environment for statistical computation and software development, R can also operate as a general matrix calculation toolbox – with performance benchmarks comparable to GNU Octave or MATLAB.^[33]

Packages

R's capabilities are extended through user-created^[34] *packages*, which allow offer statistical techniques, graphical devices, import/export, reporting (RMarkdown, knitr, Sweave), etc. R's packages and the ease of installing and using them, has been cited as driving the language's widespread adoption in data science.^{[35][36][37][38][39]} The packaging system is also used by researchers to create compendia to organise research data, code and report files in a systematic way for sharing and archiving.^[40]

Multiple packages are included with the basic installation. As of September 2018 more than 15,000 additional packages were available at the Comprehensive R Archive Network (CRAN),^[41] Bioconductor, Omegahat,^[42] GitHub, and other repositories.^{[43][44][45]}

The "Task Views" on the CRAN website^[46] lists packages in fields including Finance, Genetics, High Performance Computing, Machine Learning, Medical Imaging, Social Sciences and Spatial Statistics. R has been identified by the FDA as suitable for interpreting data from clinical research.^[47] Microsoft maintains a daily snapshot of CRAN that dates back to Sept. 17, 2014.^[48]

Other R package resources include R-Forge,^[49] a platform for the collaborative development of R packages. The Bioconductor project provides packages for genomic data analysis, including object-oriented data-handling and analysis tools for data from Affymetrix, cDNA microarray, and next-generation high-throughput sequencing methods.^[50]

A group of packages called the Tidyverse, which can be considered a "dialect" of the R language, is increasingly popular among developers.^[note 1] It strives to provide a cohesive collection of functions to deal with common data science tasks, including data import, cleaning, transformation and visualisation (notably with the ggplot2 package).

R is one of 5 languages with an Apache Spark API, along with Scala, Java, Python, and SQL.^{[51][52]}

Milestones

A list of changes in R releases is maintained in various "news" files at CRAN.^[53] Some highlights are listed below for several major releases.

Release	Date	Description
0.16		This is the last alpha version developed primarily by Ihaka and Gentleman. Much of the basic functionality from the "White Book" (see S history) was implemented. The mailing lists commenced on 1 April 1997.
0.49	1997-04-23	This is the oldest source release which is currently available on CRAN. ^[54] CRAN is started on this date, with 3 mirrors that initially hosted 12 packages. ^[55] Alpha versions of R for Microsoft Windows and the classic Mac OS are made available shortly after this version.
0.60	1997-12-05	R becomes an official part of the GNU Project . The code is hosted and maintained on CVS .
0.65.1	1999-10-07	First versions of <code>update.packages</code> and <code>install.packages</code> functions for downloading and installing packages from CRAN. ^[56]
1.0	2000-02-29	Considered by its developers stable enough for production use. ^[57]
1.4	2001-12-19	S4 methods are introduced and the first version for Mac OS X is made available soon after.
1.8	2003-10-08	Introduced a flexible condition handling mechanism for signalling and handling condition objects.
2.0	2004-10-04	Introduced lazy loading , which enables fast loading of data with minimal expense of system memory.
2.1	2005-04-18	Support for UTF-8 encoding, and the beginnings of internationalization and localization for different languages.
2.6.2	2008-02-08	Last version to support Windows 95, 98, Me and NT 4.0 ^[58]
2.11	2010-04-22	Support for Windows 64-bit systems.
2.12.2	2011-02-25	Last version to support Windows 2000 ^[59]
2.13	2011-04-14	Adding a new compiler function that allows speeding up functions by converting them to byte-code.
2.14	2011-10-31	Added mandatory namespaces for packages. Added a new parallel package.
2.15	2012-03-30	New load balancing functions. Improved serialisation speed for long vectors.
3.0.0	2013-04-03	Support for numeric index values 2^{31} and larger on 64-bit systems.
3.3.3	2017-03-06	Last version to support Microsoft Windows XP.
3.4.0	2017-04-21	Just-in-time compilation (JIT) of functions and loops to byte-code enabled by default.
3.5.0	2018-04-23	Packages byte-compiled on installation by default. Compact internal representation of integer sequences. Added a new serialisation format to support compact internal representations.
3.6.0	2019-04-26	Improved sampling from a discrete uniform distribution, which was noticeably non-uniform on large populations. ^[60] New serialisation format supported since 3.5.0 becomes the default.
4.0.0	2020-04-24	R now uses a <code>stringsAsFactors = FALSE</code> default, and hence by default no longer converts strings to factors in calls to <code>data.frame()</code> and <code>read.table()</code> . Reference counting is used for tracking object sharing, which reduces the need for copying objects. New syntax for raw string constants.
4.1.0	2021-05-18	Introduced <code> ></code> as the pipe operator for base R syntax (similar to the <code>%>%</code> operator of the <code>magrittr</code> package) and the anonymous function shortcut syntax <code>\(x) x+1</code>

Interfaces

Various applications can be used to edit or run R code.^[61]

Early developers preferred to run R via the command line console,^[62] succeeded by those who prefer an IDE.^[63] IDEs for R include (in alphabetical order) Rattle GUI, R Commander, RKward, RStudio, and Tinn-R.^[62] R is also supported in multi-purpose IDEs such as Eclipse via the StatET plugin,^[64] and Visual Studio via the R Tools for Visual Studio.^[65] Of these, Rstudio is the most commonly used.^[63]

Editors that support R include Emacs, Vim (Nvim-R plugin),^[66] Kate,^[67] LyX,^[68] Notepad++,^[69] Visual Studio Code, WinEdt,^[70] and Tinn-R.^[71] Jupyter Notebook can also be configured to edit and run R code.^[72]

R functionality is accessible from scripting languages including Python,^[73] Perl,^[74] Ruby,^[75] F#,^[76] and Julia.^[77] Interfaces to other, high-level programming languages, like Java^[78] and .NET C#^{[79][80]} are available.

Implementations

The main R implementation is written in R, C, and Fortran.^[81] Several other implementations aimed at improving speed or increasing extensibility. A closely related implementation is pqR (pretty quick R) by Radford M. Neal with improved memory management and support for automatic multithreading. Renjin and FastR (<https://github.com/oracle/fastr>) are Java implementations of R for use in a Java Virtual Machine. CXXR, rho, and Riposte^[82] are implementations of R in C++. Renjin, Riposte, and pqR attempt to improve performance by using multiple cores and deferred evaluation.^[83] Most of these alternative implementations are experimental and incomplete, with relatively few users, compared to the main implementation maintained by the R Development Core Team.

TIBCO built a runtime engine called TERR, which is part of Spotfire.^[84]

Microsoft R Open (MRO) is a fully compatible R distribution with modifications for multi-threaded computations.^{[85][86]} As of 30 June 2021, Microsoft started to phase out MRO in favor of the CRAN distribution.^[87]

Communities

R has local communities worldwide for users to network, share ideas, and learn.^{[88][89]}

A growing number of R events bring users together, such as conferences (e.g. useR!, WhyR?, conectaR, SatRdays),^{[90][91]} meetups,^[92] as well as R-Ladies groups^[93] that promote gender diversity. The R Foundation taskforce focuses on women and other under-represented groups.^[94]

useR! conferences

The official annual gathering of R users is called "useR!".^[95] The first such event was useR! 2004 in May 2004, Vienna, Austria.^[96] After skipping 2005, the useR! conference has been held annually, usually alternating between locations in Europe and North America.^[97] History:^[95]

- useR! 2006, Vienna, Austria

- useR! 2007, Ames, Iowa, USA
- useR! 2008, Dortmund, Germany
- useR! 2009, Rennes, France
- useR! 2010, Gaithersburg, Maryland, USA
- useR! 2011, Coventry, United Kingdom
- useR! 2012, Nashville, Tennessee, USA
- useR! 2013, Albacete, Spain
- useR! 2014, Los Angeles, California, USA
- useR! 2015, Aalborg, Denmark
- useR! 2016, Stanford, California, USA
- useR! 2017, Brussels, Belgium
- useR! 2018, Brisbane, Australia
- useR! 2019, Toulouse, France
- useR! 2020, took place online due to COVID-19 pandemic
- useR! 2021, took place online due to COVID-19 pandemic

As of November 2021, no next event date has been set yet. ^[98]

The R Journal

The R Journal is an open access, refereed journal of the R project. It features short to medium length articles on the use and development of R, including packages, programming tips, CRAN news, and foundation news.

Comparison with alternatives

R is comparable to popular commercial statistical packages such as SAS, SPSS, and Stata. One difference is that R is available at no charge under a free software license.^[99]

In January 2009, the *New York Times* ran an article charting the growth of R, the reasons for its popularity among data scientists and the threat it poses to commercial statistical packages such as SAS.^[100] In June 2017 data scientist Robert Muenchen published a more in-depth comparison between R and other software packages, "The Popularity of Data Science Software".^[101]

R is more procedural than either SAS or SPSS, both of which make heavy use of pre-programmed procedures (called "procs") that are built-in to the language environment and customized by parameters of each call. R generally processes data in-memory, which limits its usefulness in processing larger files.^[102]

Commercial support

Although R is an open-source project, some companies provide commercial support and extensions.

In 2007, Richard Schultz, Martin Schultz, Steve Weston and Kirk Mettler founded Revolution Analytics to provide commercial support for Revolution R, their distribution of R, which includes components developed by the company. Major additional components include: ParallelR, the R Productivity Environment IDE, RevoScaleR (for big data analysis), RevoDeployR, web services framework, and the ability for reading and writing data in the SAS file format.^[103] Revolution

Analytics offers an R distribution designed to comply with established IQ/OQ/PQ criteria that enables clients in the pharmaceutical sector to validate their installation of REvolution R.^[104] In 2015, Microsoft Corporation acquired Revolution Analytics^[105] and integrated the R programming language into SQL Server, Power BI, Azure SQL Managed Instance, Azure Cortana Intelligence, Microsoft ML Server and Visual Studio 2017.^[106]

In October 2011, Oracle announced the *Big Data Appliance*, which integrates R, Apache Hadoop, Oracle Linux, and a NoSQL database with Exadata hardware.^[107] As of 2012, Oracle R Enterprise^[108] became one of two components of the "Oracle Advanced Analytics Option"^[109] (alongside Oracle Data Mining).

IBM offers support for in-Hadoop execution of R,^[110] and provides a programming model for massively parallel in-database analytics in R.^[111]

TIBCO offers a runtime-version R as a part of Spotfire.^[112]

Mango Solutions offers a validation package for R, ValidR,^{[113][114]} to comply with drug approval agencies, such as the FDA. These agencies required the use of validated software, as attested by the vendor or sponsor.^[115]

Examples

Basic syntax

The following examples illustrate the basic syntax of the language and use of the command-line interface. (An expanded list of standard language features can be found in the R manual, "An Introduction to R".^[116])

In R, the generally preferred assignment operator is an arrow made from two characters `<-`, although `=` can be used in some cases.^{[117][118]}

```
> x <- 1:6 # Create a numeric vector in the current environment
> y <- x^2 # Create vector based on the values in x.
> print(y) # Print the vector's contents.
[1] 1 4 9 16 25 36

> z <- x + y # Create a new vector that is the sum of x and y
> z # Return the contents of z to the current environment.
[1] 2 6 12 20 30 42

> z_matrix <- matrix(z, nrow=3) # Create a new matrix that turns the vector z into a 3x2 matrix object
> z_matrix
     [,1] [,2]
[1,]    2   20
[2,]    6   30
[3,]   12   42

> 2*t(z_matrix)-2 # Transpose the matrix, multiply every element by 2, subtract 2 from each element in
the matrix, and return the results to the terminal.
     [,1] [,2] [,3]
[1,]    2   10   22
[2,]   38   58   82

> new_df <- data.frame(t(z_matrix), row.names=c('A','B')) # Create a new data.frame object that contains
the data from a transposed z_matrix, with row names 'A' and 'B'
> names(new_df) <- c('X','Y','Z') # Set the column names of new_df as X, Y, and Z.
> print(new_df) # Print the current results.
  X Y Z
A 2 6 12
B 20 30 42

> new_df$Z # Output the Z column
```

```
[1] 12 42

> new_df$Z==new_df['Z'] && new_df[3]==new_df$Z # The data.frame column Z can be accessed using $Z,
['Z'], or [3] syntax, and the values are the same.
[1] TRUE

> attributes(new_df) # Print attributes information about the new_df object
$names
[1] "X" "Y" "Z"

$row.names
[1] "A" "B"

$class
[1] "data.frame"

> attributes(new_df)$row.names <- c('one','two') # Access and then change the row.names attribute; can
also be done using rownames()
> new_df
      X Y Z
one   2 6 12
two  20 30 42
```

Structure of a function

One of R's strengths is the ease of creating new functions. Objects in the function body remain local to the function, and any data type may be returned.^[119] Example:

```
# Declare function "f" with parameters "x", "y"
# that returns a linear combination of x and y.
f <- function(x, y) {
  z <- 3 * x + 4 * y
  return(z) ## the return() function is optional here
}
```

```
> f(1, 2)
[1] 11

> f(c(1,2,3), c(5,3,4))
[1] 23 18 25

> f(1:3, 4)
[1] 19 22 25
```

Modeling and plotting

The R language has built-in support for data modeling and graphics. The following example shows how R can easily generate and plot a linear model with residuals.

```
> x <- 1:6 # Create x and y values
> y <- x^2
> model <- lm(y ~ x) # Linear
regression model y = A + B * x.
> summary(model) # Display an in-
depth summary of the model.

Call:
lm(formula = y ~ x)

Residuals:
    1     2     3     4     5     6 
3.3333 -0.6667 -2.6667 -2.6667 
-0.6667  3.3333 

Coefficients:
```




```

      Estimate Std. Error t
value Pr(>|t|)
(Intercept) -9.3333      2.8441
-3.282 0.030453 *
x            7.0000      0.7303
9.585 0.000662 ***
---
Signif. codes:  0 '***' 0.001 '**'
0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 3.055 on 4
degrees of freedom
Multiple R-squared:  0.9583, Adjusted
R-squared:  0.9478
F-statistic: 91.88 on 1 and 4 DF, p-
value: 0.000662

> par(mfrow = c(2, 2)) # Create a 2
by 2 layout for figures.
> plot(model) # Output diagnostic
plots of the model.

```



Mandelbrot set

Short R code calculating Mandelbrot set through the first 20 iterations of equation $z = z^2 + c$ plotted for different complex constants c . This example demonstrates:


- use of community-developed external libraries (called packages), in this case `caTools` package
- handling of complex numbers
- multidimensional arrays of numbers used as basic data type, see variables `C`, `Z` and `X`.

```

install.packages("caTools") #
install external package
library(caTools)           #
external package providing write.gif
function
jet.colors <-
colorRampPalette(c("red", "blue",
"#007FFF", "cyan", "#7FFF7F",
"yellow", "#FF7F00", "red",
"#7F0000"))
dx <- 1500 #
define width
dy <- 1400 #
define height
C <- complex(real = rep(seq(-2.2,
1.0, length.out = dx), each = dy),
imag = rep(seq(-1.2,
1.2, length.out = dy), dx))
C <- matrix(C, dy, dx) #
reshape as square matrix of complex
numbers
Z <- 0 #
initialize Z to zero
X <- array(0, c(dy, dx, 20)) #
initialize output 3D array
for (k in 1:20) { # loop
with 20 iterations
Z <- Z^2 + C # the

```

Diagnostic plots from plotting "model" (q.v. "plot.lm()" function). Notice the mathematical notation allowed in labels (lower left plot).



"Mandelbrot.gif" – graphics created in R with 14 lines of code in Example 2

```

central difference equation
X[, , k] <- exp(-abs(Z)) #
capture results
}
write.gif(X, "Mandelbrot.gif", col =
jet.colors, delay = 100)

```

See also

- [S programming language](#)
- [R package](#)
- [Comparison of numerical-analysis software](#)
- [Comparison of statistical packages](#)
- [List of numerical-analysis software](#)
- [List of statistical software](#)
- [Rmetrics](#)
- [RStudio](#)
- [Tidyverse](#)

Notes

1. As of 13 June 2020, [Metacran \(https://www.r-pkg.org/downloaded\)](https://www.r-pkg.org/downloaded) listed 7 of the 8 core packages of the Tidyverse in the list of most download R packages.

References

1. Morandat, Frances; Hill, Brandon; Osvald, Leo; Vitek, Jan (11 June 2012). "Evaluating the design of the R language: objects and functions for data analysis" (https://doi.org/10.1007/978-3-642-31057-7_6). *European Conference on Object-Oriented Programming*. **2012**: 104–131. doi:10.1007/978-3-642-31057-7_6 (https://doi.org/10.1007%2F978-3-642-31057-7_6). Retrieved 17 May 2016 – via SpringerLink.
2. Peter Dalgaard (1 November 2021). "R 4.1.2 is released" (<https://stat.ethz.ch/pipermail/r-announce/2021/000677.html>). Retrieved 1 November 2021.
3. "R scripts" (http://mercury.webster.edu/aleshun/R_learning_infrastructure/R%20scripts.html). *mercury.webster.edu*. Retrieved 17 July 2021.
4. "R Data Format Family (.rdata, .rda)" (<https://www.loc.gov/preservation/digital/formats/fdd/fdd000470.shtml>). *www.loc.gov*. 9 June 2017. Retrieved 17 July 2021.
5. Khomtchouk, Bohdan B.; Weitz, Edmund; Karp, Peter D.; Wahlestedt, Claes (31 December 2016). "How the strengths of Lisp-family languages facilitate building complex and flexible bioinformatics applications" (<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5952920>). *Briefings in Bioinformatics*. **19** (3): 537–543. doi:10.1093/bib/bbw130 (<https://doi.org/10.1093%2Fbib%2Fbbw130>). ISSN 1467-5463 (<https://www.worldcat.org/issn/1467-5463>). PMC 5952920 (<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5952920>). PMID 28040748 (<https://pubmed.ncbi.nlm.nih.gov/28040748>).
6. "Introduction" (<https://web.archive.org/web/20180620172516/https://docs.julialang.org/en/stable/manual/introduction/#man-introduction-1#man-introduction-1>). *The Julia Manual*. Archived from the original (<https://docs.julialang.org/en/stable/manual/introduction/#man-introduction-1>) on 20 June 2018. Retrieved 5 August 2018.

7. R language and environment

- Hornik, Kurt (4 October 2017). "R FAQ" (https://cran.r-project.org/doc/FAQ/R-FAQ.html#What-is-R_003f). *The Comprehensive R Archive Network*. 2.1 What is R?. Retrieved 6 August 2018.

R Foundation

- Hornik, Kurt (4 October 2017). "R FAQ" (https://cran.r-project.org/doc/FAQ/R-FAQ.html#What-is-the-R-Foundation_003f). *The Comprehensive R Archive Network*. 2.13 What is the R Foundation?. Retrieved 6 August 2018.

The R Core Team asks authors who use R in their data analysis (<https://cran.r-project.org/doc/FAQ/R-FAQ.html#Citing-R>) to cite the software using:

- R Core Team (2016). R: A language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria. URL <http://www.R-project.org/>.

8. R's popularity

- David Smith (2012); *R Tops Data Mining Software Poll* (<https://www.r-bloggers.com/2012/05/r-tops-data-mining-software-poll/>), R-bloggers, 31 May 2012.
 - Karl Rexer, Heather Allen, & Paul Gearan (2011); *2011 Data Miner Survey Summary* (<http://www.kdnuggets.com/2012/07/rexer-analytics-2011-data-miner-survey-results.html>), presented at Predictive Analytics World, Oct. 2011.
 - Robert A. Muenchen (2012). "The Popularity of Data Analysis Software" (<http://r4stats.com/articles/popularity/>).
 - Tippmann, Sylvia (29 December 2014). "Programming tools: Adventures with R" (<https://doi.org/10.1038%2F517109a>). *Nature*. **517** (7532): 109–110. doi:10.1038/517109a (<https://doi.org/10.1038%2F517109a>). PMID 25557714 (<https://pubmed.ncbi.nlm.nih.gov/25557714/>).
9. "TIOBE Index - The Software Quality Company" (<https://www.tiobe.com/tiobe-index/>). *TIOBE*. Retrieved 16 August 2021.
 10. "R: What is R?" (<https://www.r-project.org/about.html>). *R-Project*. Retrieved 7 August 2018.
 11. Ihaka, Ross (1998). *R : Past and Future History* (<https://www.stat.auckland.ac.nz/~ihaka/downloads/Interface98.pdf>) (PDF) (Technical report). Interface '98: Statistics Department, The University of Auckland, Auckland, New Zealand.
 12. Kurt Hornik. *The R FAQ: Why R?* (https://cran.r-project.org/doc/FAQ/R-FAQ.html#Why-is-R-named-R_003f). ISBN 3-900051-08-9. Retrieved 29 January 2008.
 13. "R license" (<https://www.r-project.org/COPYING>). r-project. Retrieved 5 August 2018.
 14. GNU project
 - "GNU R" (<http://directory.fsf.org/project/gnur/>). Free Software Foundation (FSF) Free Software Directory. 23 April 2018. Retrieved 7 August 2018.
 - R Project (n.d.). "What is R?" (<https://www.r-project.org/about.html>). Retrieved 7 August 2018.
 15. "R: Contributors" (<https://www.r-project.org/contributors.html>). *R Project*. Retrieved 14 July 2021.
 16. Kurt Hornik (23 April 1997). "Announce: CRAN" (<https://stat.ethz.ch/pipermail/r-announce/1997/000001.html>). *r-help*. Wikidata Q101068595..
 17. "Over 16 years of R Project history" (<http://blog.revolutionanalytics.com/2016/03/16-years-of-r-history.html>). *Revolutions*. Retrieved 30 May 2016.
 18. Ihaka, Ross. "The R Project: A Brief History and Thoughts About the Future" (<https://www.stat.auckland.ac.nz/~ihaka/downloads/Massey.pdf>) (PDF). *stat.auckland.ac.nz*.
 19. Eddelbuettel, Dirk; Francois, Romain (2011). "Rcpp: Seamless R and C++ Integration" (<https://doi.org/10.18637/jss.v040.i08>). *Journal of Statistical Software*. **40** (8). doi:10.18637/jss.v040.i08 (<https://doi.org/10.18637/jss.v040.i08>).

20. "nution-j2r: Java library to invoke R native functions" (<https://gitlab.nuiton.org/nuiton/nuiton-j2r>). Retrieved 13 September 2018.
21. .NET Framework
 - "Making GUIs using C# and R with the help of R.NET" (<http://psychwire.wordpress.com/2011/06/19/making-guis-using-c-and-r-with-the-help-of-r-net/>). 19 June 2011. Retrieved 13 September 2018.
 - "R.NET homepage" (<http://r.dotnet.codeplex.com/>). Retrieved 13 September 2018.
 - Haynold, Oliver M. (April 2011). *An Rserve Client Implementation for CLI/.NET* (<https://web.archive.org/web/20151129223447/http://www.rinfinance.com/agenda/2011/OliverHaynold.pdf>) (PDF). *R/Finance 2011* (<http://www.rinfinance.com/RinFinance2011/agenda/>). Chicago, IL, USA. Archived from the original (<http://www.rinfinance.com/agenda/2011/OliverHaynold.pdf>) (PDF) on 29 November 2015. Retrieved 13 September 2018.
22. R manuals. "Writing R Extensions" (<https://cran.r-project.org/doc/manuals/r-release/R-exts.html>). *r-project.org*. Retrieved 13 September 2018.
23. Jackman, Simon (Spring 2003). "R For the Political Methodologist" (https://web.archive.org/web/20060721143309/http://polmeth.wustl.edu/tpm/tpm_v11_n2.pdf) (PDF). *The Political Methodologist*. Political Methodology Section, American Political Science Association. **11** (1): 20–22. Archived from the original (http://polmeth.wustl.edu/tpm/tpm_v11_n2.pdf) (PDF) on 21 July 2006. Retrieved 13 September 2018.
24. Lewin-Koh, Nicholas (7 January 2015). "CRAN Task View: Graphic Displays & Dynamic Graphics & Graphic Devices & Visualization" (<https://cran.r-project.org/web/views/Graphics.html>). The Comprehensive R Archive Network. Retrieved 13 September 2018.
25. Dalgaard, Peter (2002). *Introductory Statistics with R* (https://archive.org/details/introductorystat00dalga_885). New York, Berlin, Heidelberg: Springer-Verlag. pp. 10 (https://archive.org/details/introductorystat00dalga_885/page/n26)–18, 34. ISBN 0387954759.
26. *An Introduction to R*, Section 5.1: Arrays. Retrieved in 2010-03 from <https://cran.r-project.org/doc/manuals/R-intro.html#Arrays>.
27. Ihaka, Ross; Gentleman, Robert (September 1996). "R: A Language for Data Analysis and Graphics" (<https://www.stat.auckland.ac.nz/~ihaka/downloads/R-paper.pdf>) (PDF). *Journal of Computational and Graphical Statistics*. American Statistical Association. **5** (3): 299–314. doi:10.2307/1390807 (<https://doi.org/10.2307/1390807>). JSTOR 1390807 (<https://www.jstor.org/stable/1390807>). Retrieved 12 May 2014.
28. "Data structures · Advanced R." (<http://adv-r.had.co.nz/Data-structures.html>) *adv-r.had.co.nz*. Retrieved 26 September 2016.
29. Mount, John (25 February 2012). "Why I don't like Dynamic Typing" (<https://win-vector.com/2012/02/25/why-i-dont-like-dynamic-typing/>). *Win Vector LLC*. Retrieved 17 July 2021.
30. "Functions · Advanced R." (<http://adv-r.had.co.nz/Functions.html#lazy-evaluation>) *adv-r.had.co.nz*.
31. White, Homer. *14.1 Programming Paradigms | Beginning Computer Science with R* (<https://homerhanumat.github.io/r-notes/programming-paradigms.html>).
32. R Core Team. "Print Values" (<https://stat.ethz.ch/R-manual/R-devel/library/base/html/print.html>). *R Documentation*. R Foundation for Statistical Computing. Retrieved 30 May 2016.
33. "Speed comparison of various number crunching packages (version 2)" (<https://web.archive.org/web/20071016130210/http://www.sciviews.org/benchmark/>). SciView. 2003. Archived from the original (<http://www.sciviews.org/benchmark>) on 16 October 2007. Retrieved 3 November 2007.
34. Hadley, Wickham; Bryan, Jenny. "R packages: Organize, Test, Document, and Share Your Code" (<https://r-pkgs.org/>).

35. Chambers, John M. (2020). "S, R, and Data Science" (<https://journal.r-project.org/archive/2020/RJ-2020-028/index.html>). *The R Journal*. **12** (1): 462–476. doi:10.32614/RJ-2020-028 (<https://doi.org/10.32614%2FRJ-2020-028>). ISSN 2073-4859 (<https://www.worldcat.org/issn/2073-4859>).
36. Vance, Ashlee (6 January 2009). "Data Analysts Captivated by R's Power" (<https://www.nytimes.com/2009/01/07/technology/business-computing/07program.html>). *New York Times*.
37. Tippmann, Sylvia (29 December 2014). "Programming tools: Adventures with R" (<https://doi.org/10.1038%2F517109a>). *Nature News*. **517** (7532): 109–110. doi:10.1038/517109a (<https://doi.org/10.1038%2F517109a>). PMID 25557714 (<https://pubmed.ncbi.nlm.nih.gov/25557714>).
38. Thieme, Nick (2018). "R generation" (<https://doi.org/10.1111%2Fj.1740-9713.2018.01169.x>). *Significance*. **15** (4): 14–19. doi:10.1111/j.1740-9713.2018.01169.x (<https://doi.org/10.1111%2Fj.1740-9713.2018.01169.x>). ISSN 1740-9713 (<https://www.worldcat.org/issn/1740-9713>).
39. widely used
 - Fox, John & Andersen, Robert (January 2005). "Using the R Statistical Computing Environment to Teach Social Statistics Courses" (<https://socialsciences.mcmaster.ca/jfox/Teaching-with-R.pdf>) (PDF). Department of Sociology, McMaster University. Retrieved 6 August 2018.
 - Vance, Ashlee (6 January 2009). "Data Analysts Captivated by R's Power" (<https://www.nytimes.com/2009/01/07/technology/business-computing/07program.html>). *New York Times*. Retrieved 6 August 2018. "R is also the name of a popular programming language used by a growing number of data analysts inside corporations and academia. It is becoming their lingua franca..."
40. Marwick, Ben; Boettiger, Carl; Mullen, Lincoln (26 August 2017). "Packaging data analytical work reproducibly using R (and friends)" (<https://peerj.com/preprints/3192/?td=wk>). *PeerJ Preprints*. doi:10.7287/peerj.preprints.3192v1 (<https://doi.org/10.7287%2Fpeerj.preprints.3192v1>). ISSN 2167-9843 (<https://www.worldcat.org/issn/2167-9843>).
41. "The Comprehensive R Archive Network" (<https://cran.r-project.org/>). Retrieved 16 September 2018.
42. "Omegahat.net" (<http://www.omegahat.net/>). Omegahat.net. Retrieved 16 September 2018.
43. packages available from repositories
 - Robert A. Muenchen (2012). "The Popularity of Data Analysis Software" (<http://r4stats.com/articles/popularity/>).
 - Tippmann, Sylvia (29 December 2014). "Programming tools: Adventures with R" (<https://doi.org/10.1038%2F517109a>). *Nature*. **517** (7532): 109–110. doi:10.1038/517109a (<https://doi.org/10.1038%2F517109a>). PMID 25557714 (<https://pubmed.ncbi.nlm.nih.gov/25557714>).
 - "Search all R packages and function manuals | Rdocumentation" (<http://www.rdocumentation.org/>). *Rdocumentation*. 16 June 2014. Retrieved 16 September 2018.
44. Wickham, Hadley; Bryan, Jennifer. *Chapter 10 Object documentation | R Packages* (<https://r-pkgs.org/man.html>).
45. "Rd formatting" (<https://cran.r-project.org/web/packages/roxygen2/vignettes/rd-formatting.html>). *cran.r-project.org*. Retrieved 16 August 2021.
46. "CRAN Task Views" (<https://cran.r-project.org/web/views/>). *cran.r-project.org*. Retrieved 16 September 2018.
47. "FDA: R OK for drug trials" (<http://blog.revolutionanalytics.com/2012/06/fda-r-ok.html>). Retrieved 16 September 2018.
48. "CRAN Time Machine. MRAN" (<https://mran.microsoft.com/timemachine>). Retrieved 26 December 2019.
49. "R-Forge: Welcome" (<https://r-forge.r-project.org/>). Retrieved 16 September 2018.

50. Huber, W; Carey, VJ; Gentleman, R; Anders, S; Carlson, M; Carvalho, BS; Bravo, HC; Davis, S; Gatto, L; Girke, T; Gottardo, R; Hahne, F; Hansen, KD; Irizarry, RA; Lawrence, M; Love, MI; MacDonald, J; Obenchain, V; Oleś, AK; Pagès, H; Reyes, A; Shannon, P; Smyth, GK; Tenenbaum, D; Waldron, L; Morgan, M (2015). "Orchestrating high-throughput genomic analysis with Bioconductor" (<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4509590>). *Nature Methods*. Nature Publishing Group. **12** (2): 115–121. doi:10.1038/nmeth.3252 (<https://doi.org/10.1038%2Fnmeth.3252>). PMC 4509590 (<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4509590>). PMID 25633503 (<https://pubmed.ncbi.nlm.nih.gov/25633503>).
51. "Spark API Documentation" (<https://spark.apache.org/docs/latest/api.html>). *Spark*.
52. "SparkR (R on Spark)" (<https://spark.apache.org/docs/latest/sparkr.html>). *Spark*.
53. Changes in versions 3.0.0 onward: "R News" (<https://cran.r-project.org/src/base/NEWS>). *cran.r-project.org*. Retrieved 3 July 2014. Earlier change logs (by major release number):
 - "NEWS" (<https://cran.r-project.org/src/base/NEWS>). *cran.r-project.org*. Retrieved 28 June 2020.
 - "NEWS.3" (<https://cran.r-project.org/src/base/NEWS.3>). *cran.r-project.org*. Retrieved 28 June 2020.
 - "NEWS.2" (<https://cran.r-project.org/src/base/NEWS.2>). *cran.r-project.org*. Retrieved 8 April 2017.
 - "NEWS.1" (<https://cran.r-project.org/src/base/NEWS.1>). *cran.r-project.org*. Retrieved 8 April 2017.
 - "NEWS.0" (<https://cran.r-project.org/src/base/NEWS.0>). *cran.r-project.org*. Retrieved 8 April 2017.
54. "Index of /src/base/R-0" (<https://cran.r-project.org/src/base/R-0/>). *cran.r-project.org*.
55. "ANNOUNCE: CRAN" (<https://stat.ethz.ch/pipermail/r-announce/1997/000001.html>). *stat.ethz.ch*.
56. <https://cran.r-project.org/src/base/NEWS.0>
57. Peter Dalgaard. "R-1.0.0 is released" (<https://stat.ethz.ch/pipermail/r-announce/2000/000127.html>). Retrieved 6 June 2009.
58. "CHANGES IN R VERSION 2.7.0" (<https://cran-archive.r-project.org/bin/windows/base/old/2.7.0/CHANGES.R-2.7.0>).
59. "R FAQ" (https://cran.r-project.org/bin/windows/base/rw-FAQ.html#How-do-I-install-R-for-Windows_003f). Retrieved 20 March 2020.
60. Ottoboni, Kellie; Stark, Philip B. (2018). "Random problems with R". *arXiv:1809.06520* (<https://arxiv.org/abs/1809.06520>) [cs.MS (<https://arxiv.org/archive/cs/MS>)].
61. "Recommendations for Windows text editor for R (StackOverflow)" (<https://stackoverflow.com/questions/1173463/recommendations-for-windows-text-editor-for-r>). Retrieved 20 December 2020.
62. "Poll: R GUIs you use frequently (2011)" (<http://www.kdnuggets.com/polls/2011/r-gui-used.html>). *kdnuggets.com*. Retrieved 18 September 2018.
63. "R Programming - The State of Developer Ecosystem in 2020 Infographic" (<https://www.jetbrains.com/lp/devecosystem-2020/>). *JetBrains: Developer Tools for Professionals and Teams*. Retrieved 16 August 2021.
64. Stephan Wahlbrink. "StatET for R" (<https://marketplace.eclipse.org/content/statet-r>).
65. "Work with R in Visual Studio" (<https://docs.microsoft.com/en-us/visualstudio/rts/?view=vs-2017>). Retrieved 14 December 2020.
66. "Nvim-R - Plugin to work with R : vim online" (https://www.vim.org/scripts/script.php?script_id=2628). *www.vim.org*. Retrieved 6 March 2019.
67. "Syntax Highlighting" (https://web.archive.org/web/20080707062903/http://www.kate-editor.org/downloads/syntax_highlighting). Kate Development Team. Archived from the original (http://kate-editor.org/downloads/syntax_highlighting) on 7 July 2008. Retrieved 9 July 2008.

68. Paul E. Johnson & Gregor Gorjanc. "LyX with R through Sweave" (<http://wiki.lyx.org/LyX/LyXWithRThroughSweave>). Retrieved 4 April 2017.
69. "NppToR: R in Notepad++" (<http://sourceforge.net/projects/npptor/>). sourceforge.net. 8 May 2013. Retrieved 18 September 2013.
70. Uwe Ligges (5 January 2017). "RWinEdt: R Interface to 'WinEdt' " (<https://cran.r-project.org/web/packages/RWinEdt/index.html>). Retrieved 4 April 2017.
71. "Tinn-R" (<https://nbcgib.uesc.br/tinnr/en/>). Retrieved 5 March 2019.
72. "Using the R programming language in Jupyter Notebook" (<https://docs.anaconda.com/anaconda/navigator/tutorials/r-lang/>). *Anaconda*. Retrieved 14 September 2020.
73. Gautier, Laurent. "rpy2 - R in Python" (<https://rpy2.github.io>). Retrieved 30 November 2021.
74. Florent Angly. "Statistics::R - Perl interface with the R statistical program - metacpan.org" (<http://metacpan.org/module/Statistics::R>).
75. alexgutteridge (15 July 2021). "GitHub - alexgutteridge/rsruby: Ruby - R bridge" (<https://github.com/alexgutteridge/rsruby>). *GitHub*.
76. BlueMountain Capital. "F# R Type Provider" (<https://bluemountaincapital.github.io/FSharpRProvider/>).
77. "JuliaInterop/RCall.jl" (<https://github.com/JuliaInterop/RCall.jl>). 2 June 2021 – via GitHub.
78. "Rserve - Binary R server - RForge.net" (<https://www.rforge.net/Rserve/>). *www.rforge.net*.
79. "konne/RserveCLI2" (<https://github.com/konne/RserveCLI2>). 8 March 2021 – via GitHub.
80. "R.NET" (<https://jmp75.github.io/rdotnet/>).
81. "r-source: Read only mirror of R source code on GitHub" (<https://github.com/wch/r-source>). *GitHub*. Retrieved 14 September 2019.
82. Talbot, Justin; DeVito, Zachary; Hanrahan, Pat (1 January 2012). "Riposte: A Trace-driven Compiler and Parallel VM for Vector Code in R". *Proceedings of the 21st International Conference on Parallel Architectures and Compilation Techniques*. ACM: 43–52. doi:10.1145/2370816.2370825 (<https://doi.org/10.1145%2F2370816.2370825>). S2CID 1989369 (<https://api.semanticscholar.org/CorpusID:1989369>).
83. Neal, Radford (25 July 2013). "Deferred evaluation in Renjin, Riposte, and pqR" (<https://radfordneal.wordpress.com/2013/07/24/deferred-evaluation-in-renjin-riposte-and-pqr/>). *Radford Neal's blog*. Retrieved 6 March 2017.
84. Jackson, Joab (16 May 2013). TIBCO offers free R to the enterprise (<http://www.pcworld.com/article/2038944/tibco-offers-free-r-to-the-enterprise.html>). *PC World*. Retrieved 20 July 2015.
85. "Home" (<https://mran.microsoft.com/>). *mran.microsoft.com*. Retrieved 22 November 2021.
86. "Microsoft R Open: The Enhanced R Distribution" (<https://mran.microsoft.com/open>). Retrieved 30 June 2018.
87. "Looking to the future for R in Azure SQL and SQL Server" (<https://cloudblogs.microsoft.com/qlserver/2021/06/30/looking-to-the-future-for-r-in-azure-sql-and-sql-server/>). Retrieved 7 November 2021.
88. "Local R User Group Directory" (<http://blog.revolutionanalytics.com/local-r-groups.html>). *Revolutions Blog*. Retrieved 12 May 2018.
89. *A list of R conferences and meetings* (<https://jumpingrivers.github.io/meetingsR/index.html>). *Jumping Rivers*. Retrieved 12 May 2018.
90. "official website of WhyR? conference" (<http://whyr.pl/>). *WhyR?*. Retrieved 26 June 2019.
91. "SatRdays listing" (<https://satrdays.org/>). *SatRdays*. Retrieved 26 June 2019.
92. "R Project for Statistical Computing" (<https://www.meetup.com/topics/r-project-for-statistical-computing/>). *Meetup*. Retrieved 12 May 2018.
93. "R Ladies" (<https://rladies.org>). *R Ladies*. Retrieved 12 May 2018.
94. "Forwards" (<https://forwards.github.io/>). Retrieved 23 March 2020.
95. "R: Conferences" (<https://www.r-project.org/conferences/>). *r-project.org*. 1 November 2019. Retrieved 19 November 2019.

96. "useR! 2004 - The R User Conference" (<http://www.ci.tuwien.ac.at/Conferences/useR-2004/>). 27 May 2004. Retrieved 9 September 2018.
97. R Project (9 August 2013). "R-related Conferences" (<https://www.r-project.org/conferences>). Retrieved 15 August 2019.
98. "R: Conferences" (<https://www.r-project.org/conferences/>). *www.r-project.org*.
99. Burns, Patrick (27 February 2007). "Comparison of R to SAS, Stata and SPSS" (http://www.burns-stat.com/pages/Tutor/R_relative_statpack.pdf) (PDF). Retrieved 18 September 2013.
100. R as competition for commercial statistical packages
 - Vance, Ashlee (7 January 2009). "Data Analysts Are Mesmerized by the Power of Program R: [Business/Financial Desk]" (<https://www.nytimes.com/2009/01/07/technology/business-computing/07program.html>). *The New York Times*.
 - Vance, Ashlee (8 January 2009). "R You Ready for R?" (<http://bits.blogs.nytimes.com/2009/01/08/r-you-ready-for-r/>). *The New York Times*.
101. Muenchen, Robert (19 June 2017). "The Popularity of Data Science Software" (<http://r4stats.com/articles/popularity/>). Retrieved 21 November 2018.
102. "R vs. SPSS" (<https://www.educba.com/r-vs-spss/>).
103. Morgan, Timothy Prickett (2011-02-07). "'Red Hat for stats' goes toe-to-toe with SAS". *The Register*, 7 February 2011. Retrieved from https://www.theregister.co.uk/2011/02/07/revolution_r_sas_challenge/.
104. "Analyzing clinical trial data for FDA submissions with R" (<http://blog.revolutionanalytics.com/2009/01/analyzing-clinical-trial-data-with-r.html>). Revolution Analytics. 14 January 2009. Retrieved 20 September 2018.
105. Sirosh, Joseph. "Microsoft Closes Acquisition of Revolution Analytics" (<http://blogs.technet.com/b/machinelearning/archive/2015/04/06/microsoft-closes-acquisition-of-revolution-analytics.aspx>). *blogs.technet.com*. Microsoft. Retrieved 20 September 2018.
106. "Introducing R Tools for Visual Studio" (<https://blogs.msdn.microsoft.com/visualstudio/2016/03/22/introducing-r-tools-for-visual-studio-3/>). Retrieved 20 September 2018.
107. Oracle Corporation's Big Data Appliance
 - Doug Henschen (2012); *Oracle Makes Big Data Appliance Move With Cloudera* (<http://www.informationweek.com/software/information-management/oracle-makes-big-data-appliance-move-wit/232400021>), InformationWeek, 10 January 2012.
 - Jaikumar Vijayan (2012); *Oracle's Big Data Appliance brings focus to bundled approach* (http://www.computerworld.com/s/article/9223325/Oracle_s_Big_Data_Appliance_brings_focus_to_bundled_approach), ComputerWorld, 11 January 2012.
 - Timothy Prickett Morgan (2011); *Oracle rolls its own NoSQL and Hadoop Oracle rolls its own NoSQL and Hadoop* (https://www.theregister.co.uk/2011/10/03/oracle_big_data_appliance/), The Register, 3 October 2011.
108. Chris Kanaracus (2012); *Oracle Stakes Claim in R With Advanced Analytics Launch* (http://www.pcworld.com/article/249509/oracle_stakes_claim_in_r_with_advanced_analytics_launch.html), PC World, February 8, 2012.
109. Doug Henschen (2012); *Oracle Stakes Claim in R With Advanced Analytics Launch* (<http://www.informationweek.com/software/business-intelligence/oracle-makes-its-big-play-for-analytics/232800252>), InformationWeek, April 4, 2012.
110. "What's New in IBM InfoSphere BigInsights v2.1.2" (https://web.archive.org/web/20140906200802/http://www-01.ibm.com/software/data/infosphere/biginsights/whats_new.html). IBM. Archived from the original (http://www-01.ibm.com/software/data/infosphere/biginsights/whats_new.html) on 6 September 2014. Retrieved 8 May 2014.

111. "IBM PureData System for Analytics" (https://web.archive.org/web/20140517153029/http://mainline.com/_web/_shared/pdfs/brochures/IBM-PureData-System-Overview.pdf) (PDF). IBM. Archived from the original (http://mainline.com/_web/_shared/pdfs/brochures/IBM-PureData-System-Overview.pdf) (PDF) on 17 May 2014. Retrieved 8 May 2014.
112. Tibco. "Unleash the agility of R for the Enterprise" (<http://spotfire.tibco.com/discover-spotfire/what-does-spotfire-do/predictive-analytics/tibco-enterprise-runtime-for-r-terr>). Retrieved 15 May 2014.
113. "ValidR on Mango website" (<https://www.mango-solutions.com/products/validr/>). Retrieved 24 September 2018.
114. Andy Nicholls at Mango Solutions. "ValidR Enterprise: Developing an R Validation Framework" (<https://www.lexjansen.com/phuse/2016/ad/AD12.pdf>) (PDF). Retrieved 24 September 2018.
115. FDA. "Statistical Software Clarifying Statement" (<https://www.fda.gov/downloads/ForIndustry/DataStandards/StudyDataStandards/UCM587506.pdf>) (PDF). Retrieved 24 September 2018.
116. "An Introduction to R. Notes on R: A Programming Environment for Data Analysis and Graphics" (<https://cran.r-project.org/doc/manuals/R-intro.pdf>) (PDF). Retrieved 3 January 2021.
117. R Development Core Team. "Assignments with the = Operator" (<https://developer.r-project.org/equalAssign.html>). Retrieved 11 September 2018.
118. most used assignment operator in R is <-
 - R Development Core Team. "Writing R Extensions" (<https://cran.r-project.org/doc/manuals/R-exts.html#Tidying-R-code>). Retrieved 11 September 2018. "[...] we recommend the consistent use of the preferred assignment operator '`<-`' (rather than '`=`') for assignment."
 - "Google's R Style Guide" (<https://google.github.io/styleguide/Rguide.xml#assignment>). Retrieved 11 September 2018.
 - Wickham, Hadley. "Style Guide" (<http://stat405.had.co.nz/r-style.html>). Retrieved 11 September 2018.
 - Bengtsson, Henrik (January 2009). "R Coding Conventions (RCC) – a draft" (<https://docs.google.com/document/preview?id=1esDVxyWvH8AsX-VJa-8oqWaHLs4stGI1bk8kLc5VIII&pli=1>). Retrieved 11 September 2018.
119. Kabacoff, Robert (2012). "Quick-R: User-Defined Functions" (<http://www.statmethods.net/management/userfunctions.html>). *statmethods.net*. Retrieved 28 September 2018.

External links

- Official website (<https://www.r-project.org>)  of the R project
- R Technical Papers (<https://developer.r-project.org/TechDocs/>)

Retrieved from "[https://en.wikipedia.org/w/index.php?title=R_\(programming_language\)&oldid=1059346828](https://en.wikipedia.org/w/index.php?title=R_(programming_language)&oldid=1059346828)"

This page was last edited on 8 December 2021, at 22:56 (UTC).

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.