

产品型号: 7C-1 T
Model: 7C-1 T
产品名称: 手扶农用拖车
Name: Hold farm trailer
产品图片:
Picture:



产品特点: 手扶农用拖车可与国内的各种 8—18hp 手扶拖拉机配套, 适用于山区、沼泽、丘陵作业, 主要用于轻型运输。

结构简单合理, 操作灵活, 人工辅助自卸。减震形式: 弹性弓板。牵引形式: 三角架活牵引。表面处理: 大型抛丸机消除焊接应力、除锈、除氧化皮、防锈漆、面漆、烤漆处理。焊接工艺: CO2 工装焊接。运输形式: 散件运输、箱板软包装。

The trailer can match with all kinds of 8—18hp Walking tractor in China . It is fit for operation in mountain areas ,marsh and hills, it mainly used for light-duty transportation. It has the features of simple and reasonable structure ,nimble operation, dump with manual assistance .

The form of damping: leaf spring

The form of traction: tripod traction

Surface treatment: derusting with large shot blast machine, to change welding stress

Surface spray coating: antirusting paint, finishing paint , stoving varnish.

The process of welding: carbon dioxide jig welding.

The form of transportation: parts and components, flexible packing with the box plate

主要参数: Main parameter

Carriage (mm) 车厢尺寸	Outdimensions (mm) 外形尺寸	Upload (kg) 载重量	Structure weight (kg) 自重	Tyre 配套轮胎	Brake 刹车形式	Unload form 卸料形式
1800X900X350	3450X1200X1550	1000	220	6.00-16	Mechanical brake 脚踏机械刹车	人工或人工辅助 自卸 Manual or dump with manual assistance

Contact: Henry

Mobile: 86 13806461474

E-mail: agritractor@gmail.com

Skype: shanweituo

Address: Weifang City, Shandong province, China

产品型号: 7C-1.5 T

Model: 7C-1.5 T

产品名称: 农用拖车

Name: farm trailer

产品图片:

Picture:

产品特点:

Feature:



1.5 吨拖车

适用于国内外各种 12-18hp 的小型四轮拖拉机配套, 用于平原山区、农田作业, 适合于农户小家庭的购买。刹车形式可根据配套的拖拉机选机械刹车、撞刹或气刹, 可选择液压自卸形式。减震形式: 弹性弓板。牵引形式: 三角架活牵引。表面处理: 大型抛丸机消除焊接应力、除锈、除氧化皮、防锈漆、面漆、烤漆处理。焊接工艺: CO2 工装焊接。运输形式: 散件运输、箱板软包装。

1.5ton trailer mainly match with 12-18 hp Small **Four** Wheel Tractor home and abroad. It's used for field, moutain areas and farmland, is fit for the farmer and small family to purchase. The chosen brake with the matched tractor is mechanical , impact or air brake, can also choose hydraulic pressure dump .

The form of damping: leaf spring

The form of traction: tripod traction

Surface treatment: derusting with large shot blast machine, to change welding stress

Surface spray coating: antirusting paint, finishing paint , stoving varnish.

The process of welding: carbon dioxide jig welding.

The form of transportation: parts and components, flexible packing with the box plate

Main parameter:

Carriage(mm) 车厢尺寸	Out dimensions(mm) 外形尺寸	Load (kg) 载重	Structure weight(kg) 自重	Tyre 配套 轮胎	Brake 刹车 形式	Unload form 卸料形式
2000X1000X450	3000X1500X1500	1500	330	6.50-16	Select 可选	Manual 人工
2000X1000X450	3000X1500X1500	1500	380	6.50-16	Select 可选	Hydraulic dump 液压自卸

Contact: Henry

Mobile: 86 13806461474

E-mail: agritractor@gmail.com

Skype: shanweituo

Address: Weifang City, Shandong province, China

产品型号: 7C-2T

Model: 7C-2T

产品名称: 农用拖车

Name: farm trailer

产品图片:

Picture:



产品特点: 结构合理, 操作灵活, 适用于公路和田间运输作业。保养

维护方便、经久耐用

2吨拖车主要配套于 12-25 马力拖拉机, 刹车可选用撞刹、机械刹或气刹, 可选装自卸。减震形式: 弹性弓板。牵引形式: 三角架活牵引。表面处理: 大型抛丸机消除焊接应力、除锈、除氧化皮、防锈漆、面漆、烤漆处理。焊接工艺: CO2 工装焊接。运输形式: 散件运输、箱板软包装。

It has the features of simple and reasonable structure , nimble operation. It is used for road and field transportation. It's convenient to maintain and durable in use .

The two ton trailer mainly match with 12-25hp tractor .

The chosen brake with the matched tractor is mechanical , impact or air brake, can also choose hydraulic pressure dump .

The form of damping: leaf spring

The form of traction: tripod traction

Surface treatment: derusting with large shot blast machine, to change welding stress

Surface spray coating: antirusting paint, finishing paint , stoving varnish.

The process of welding: carbon dioxide jig welding.

The form of transportation: parts and components, flexible packing with the box plate

主要参数: Main parameter:

Carriage (mm) 车厢规格	Out dimensions (mm) 外形尺寸	Load (kg) 载重量	Structure weight (kg) 自重	Tyre 配套轮胎	Unload form 卸料形式	Brake 刹车形式
2100X1500X450	3100x1500x1900	2000	350	7.00-16	Manual 人工	select 选装
2100X1500X450	3100x1500x1900	2000	420	7.00-16	Dump 自卸	Select 选装
2400X1200X450	3500x1600x1600	2000	350	7.00-16	Manual 人工	select 选装
2400X1200X450	3500x1600x1600	2000	420	7.00-16	Dump 自卸	Select 选装

Contact: Henry

Mobile: 86 13806461474

E-mail: agritractor@gmail.com

Skype: shanweituo

Address: Weifang City, Shandong province, China

产品型号: 7C-3T

Model: 7C-3T

产品名称: 农用拖车

Name: farm trailer

产品图片:

Picture:



产品特点: 3 吨拖车一般采用 2 轮或 4 轮形式, 配套动力 25-40hp, 刹车采用充气刹车。可选装自卸。3 吨两轮自卸采取后翻, 4 轮自卸是采取双侧翻的形式, 4 轮车配备电路。适用于中载货物的中短途运输和田间作业。。转向形式: 无心转盘。减震形式: 弹性弓板。牵引形式: 三角架活牵引。自卸配置: 双油缸。后置尾灯、左右护栏。整车汽车线束。气路连接形式: 气管快接头。电路连接形式: 螺旋七芯线快插头。油路连接形式: 快换接头。表面处理: 大型抛丸机消除焊接应力、除锈、除氧化皮、防锈漆、面漆、烤漆处理。焊接工艺: CO2 工装焊接。运输形式: 散件运输、箱板软包装。

3 TON : 2 wheels or 4w heels ,matched with 25-40hp tractor, inflation brake , dump selected . For 2wheels it adopts rear dump, 4wheels trailer can dump left and right with circuit.It is used for half and short distance

transportaion and operation in the field .

The form of turning: centreless turntable.

The form of damping: leaf spring

The form of traction: tripod stand traction(cusion spring)

Postpositive tailight

Left and right barrier

Auto-circuitry of the whole trailer

The form of tipping: left or right tipping Provide with fuel tank (double fuel tank)

The form of air path connection: connectted with spiral tube

The form of oil pipe: nipple

The form of circuitry path :Connectted with 7 core spiral cable swift connector

Surface treatment: derusting with large size shot blast machine, to change welding stress

Surface spray coating: antirusting paint, finishing paint .

The process of welding: carbon dioxide MIG welding.

The form of transportation: parts and components, flexible packing with the box plate

Contact: Henry

Mobile: 86 13806461474

E-mail: agritractor@gmail.com

Skype: shanweituo

Address: Weifang City, Shandong province, China

Carriage(mm) 车箱尺寸	Out dimensions(mm) 外形尺寸	Load (kg) 载重	Structure weight (kg) 自重	Tyre 配套轮胎	Unload form 卸料形式	Brake 刹车形式
3000*1600*500	4000*1600*2000	3000	550	7.50-16	人工 Manual	两轮汽刹 2 wheels
3000*1600*500	4000*1600*2000	3000	700	7.50-16	液压自卸 Hydraulic dump	两轮汽刹 2 wheels
3400*1700*450	4700*1800*2100	3000	900	7.00-16	人工 Manual	四轮后汽刹 4 wheels , rear air brake
3400*1700*450	4700*1800*2100	3000	1100	7.00-16	液压自卸 Hydraulic dump	四轮后汽刹 4 wheels, rear air brake

产品型号: 7C-4T

Model: 7C-4T

产品名称: 农用拖车

Name: farm trailer

产品图片:

Picture:



产品特点: 4吨拖车一般采用4轮形式, 刹车采用充气刹车, 可选装自卸, 采取双侧翻的形式, 配备电路。适用于中载货物的中短途运输和田间牧场作业。配套动力25-50hp。转向形式: 无心转盘。减震形式: 弹性弓板。牵引形式: 三角架活牵引。后置尾灯、左右护栏。整车汽车线束。气路连接形式: 气管快接头。电路连接形式: 螺旋七芯线快插头。油路连接形式: 快换接头。表面处理: 大型抛丸机消除焊接应力、除锈、除氧化皮、防锈漆、面漆、烤漆处理。焊接工艺: CO2工装焊接。运输形式: 散件运输、箱板软包装。

4wheels ,matched with 25-50hp tractor, inflation brake , dump selected . it adopts left and right dump with circuit.It is used for half and short distance transportation and operation in the field .

The form of turning: centreless turntable.

The form of damping: leaf spring

The form of traction: tripod stand traction(cusion spring)

Postpositive taillight

Left and right barrier

Auto-circuitry of the whole trailer

The form of tipping: left or right tipping Provide with fuel tank (double fuel tank)

The form of air path connection: connected with spiral tube

The form of oil pipe: nipple

The form of circuitry path :Connected with 7 core spiral cable swift connector

Surface treatment: derusting with large size shot blast machine, to change welding stress

Surface spray coating: antirusting paint, finishing paint .

The process of welding: carbon dioxide MIG welding.

The form of transportation: parts and components, flexible packing with the box plate

Contact: Henry

Mobile: 86 13806461474

E-mail: agritractor@gmail.com

Skype: shanweituo

Address: Weifang City, Shandong province, China

Carriage(mm) 车箱尺寸	Out dimension(m m) 外形尺寸	Loa d (kg) 载重	Structure weight(kg) 自重	Tyre 配套 轮胎	Matched power(hp) 配套动力	Unload form 卸料形式	Brake 刹车形式
3800X1700X500	5200x1700x2300	4000	1200	7.50-16	25-50	人工 Manual	四轮后汽刹 4 wheels ,rear air brake
3800X1700X500	5200x1700x2300	4000	1500	7.50-16	25-50	液压自卸 Hydraulic dump	四轮后汽刹 4 wheels ,rear air brake

产品型号: 7C-5T
Model: 7C-5T
产品名称: 农用拖车
Name: farm trailer
产品图片:
Picture:



产品特点:

5 吨拖车适用于运输重载货物, 和远近途运输, 该车配置齐全, 行驶平稳、外型美观、经久耐用, 使用做业环境广泛, 装载效率高。配套动力 40—60hp. 转向形式: 无心转盘。减震形式: 弹性弓板。牵引形式: 三角架活牵引。自卸配置: 双油缸。后置尾灯、左右护栏。整车汽车线束。气路连接形式: 气管快接头。电路连接形式: 螺旋七芯线快插头。油路连接形式: 快换接头。表面处理: 大型抛丸机消除焊接应力、除锈、除氧化皮、防锈漆、面漆、烤漆处理。焊接工艺: CO2 工装焊接。运输形式: 散件运输、箱板软包装。

The 5ton trailer is fit for heavy-duty, far and near transportation, completely configure, it runs steadily. the outlook is artistic. durable in use, working environment is widespread The loading efficiency is high. Matched power is 40—60hp.

The form of turning: centreless turntable.

The form of damping: leaf spring

The form of traction: tripod stand traction(cusion spring)

Postpositive tailight

Left and right barrier

Auto-circuitry of the whole trailer

The form of tipping: left or right tipping Provide with fuel tank (double fuel tank)

The form of air path connection: connected with spiral tube

The form of oil pipe: nipple

The form of circuitry path :Connected with 7 core spiral cable swift connector

Surface treatment: derusting with large size shot blast machine, to change welding stress

Surface spray coating: antirusting paint, finishing paint .

The process of welding: carbon dioxide jig welding

The form of transportation: parts and components, flexible packing with the box plate

Contact: Henry

Mobile: 86 13806461474

E-mail: agritractor@gmail.com

Skype: shanweituo

Address: Weifang City, Shandong province, China

Carriage(mm) 车箱尺寸	Out dimensions(mm) 外形尺寸	Load (kg) 载重	Structur weight(kg) 自重	Tyre 配套轮胎	Matched power(hp) 配套动力	Unload form 卸料形式	Brake (4 wheels) 刹车形式
4000X2200X500	5800x2200x2400	5000	1300	8.25-16	40—60	人工 Manual	Rear air Brake 四轮后气刹
4000X2200X500	5800x2200x2500	5000	1600	8.25-16	40—60	自卸 dump	Rear air brake 四轮后气刹

产品型号: 7C-6T
Model: 7C-6T
产品名称: 农用拖车
Name: farm trailer
产品图片:

Picture:

产品特点:

6 吨农用挂车适用于运输重载货物, 和远近途运输, 该车配置齐全, 行驶平稳、外型美观、经久耐用, 使用做业环境广泛, 装载效率高。配套动力 50—90hp. 转向形式: 无心转盘。减震形式: 弹性弓板。牵引形式: 三角架活牵引。自卸配置: 双油缸。后置尾灯、左右护栏。整车汽车线束。气路连接形式: 气管快接头。电路连接形式: 螺旋七芯线快插头。油路连接形式: 快换接头。表面处理: 大型抛丸机消除焊接应力、除锈、除氧化皮、防锈漆、面漆、烤漆处理。焊接工艺: CO2 工装焊接。运输形式: 散件运输、箱板软包装。



The 6ton trailer is fit for heavy-duty, far and near transportation, completely configure, it runs steadily. the outlook is artistic, durable in use, working environment is widespread. The loading efficiency is high. Matched power is 50—90hp.

The form of turning: centreless turntable.

The form of damping: leaf spring

The form of traction: tripod stand traction(cusion spring)

Postpositive tailight

Left and right barrier

Auto-circuitry of the whole trailer

The form of tipping: left or right tipping Provide with fuel tank (double fuel tank)

The form of air path connection: connected with spiral tube

The form of oil pipe: nipple

The form of circuitry path :Connected with 7 core spiral cable swift connector

Surface treatment: derusting with large size shot blast machine, to change welding stress

Surface spray coating: antirusting paint, finishing paint .

The process of welding: carbon dioxide MIG welding

The form of transportation: parts and components, flexible packing with the box plate

Contact: Henry

Mobile: 86 13806461474

E-mail: agritractor@gmail.com

Skype: shanweituo

Address: Weifang City, Shandong province, China

Carriage(mm) 车箱尺寸	Out dimension s(mm) 外形尺寸	Load (kg) 载重	Structure weight(kg) 自重	Tyre 配套轮 胎	Unload form 卸料形 式	Brake (4 wheels) 刹车形式
4500X2200X50	6200x2300x2500	6000	1700	9.00-20	Manua l 人工	Rear air brake 四轮后气刹
4500X2200X50	6200x2300x2500	6000	2200	9.00-20	Dump 自卸	Rear air brake 四轮后气刹

产品型号: 7C-7T

Model: 7C-7T

产品名称: 农用拖车

Name: farm trailer

产品图片:

Picture:

产品特点:

7吨农用挂车适用于运输重载货物,和远近途运输,该车配置齐全,行驶平稳、外型美观、经久耐用,使用做业环境广泛,装载效率高。配套动力 50-90hp. 转向形式: 无心转盘。减震形式: 弹性弓板。牵引形式: 三角架活牵引。自卸配置: 双油缸。后置尾灯、左右护栏。整车汽车线束。气路连接形式: 气管快接头。电路连接形式: 螺旋七芯线快插头。油路连接形式: 快换接头。表面处理: 大型抛丸机消除焊接应力、除锈、除氧化皮、防锈漆、面漆、烤漆处理。焊接工艺: CO2 工装焊接。运输形式: 散件运输、箱板软包装。



The 7ton trailer is fit for heavy-duty, far and near transportation, completely configure, it runs steadily. the outlook is artistic, durable in use, working environment is widespread. The loading efficiency is high. Matched power is 50-90hp.

The form of turning: centreless turntable.

The form of damping: leaf spring

The form of traction: tripod stand traction(cusion spring)

Postpositive taillight

Left and right barrier

Auto-circuitry of the whole trailer

The form of tipping: left or right tipping Provide with fuel tank (double fuel tank)

The form of air path connection: connected with spiral tube

The form of oil pipe: nipple

The form of circuitry path :Connected with 7 core spiral cable swift connector

Surface treatment: derusting with large size shot blast machine, to change welding stress

Surface spray coating: antirusting paint, finishing paint .

The process of welding: carbon dioxide MIG welding

The form of transportation: parts and components, flexible packing with the box plate

Carriage(mm) 车箱尺寸	Out dimension s(mm) 外形尺寸	Load (kg) 载重	Structure weight(kg) 自重	Tyre 配套轮 胎	Unload form 卸料形 式	Brake (4 wheels) 刹车形式
4500X2200X50	6200x2300x2500	7000	2200	9.00-20	Dump 自卸	Rear air brake 四轮后气刹

Contact: Henry

Mobile: 86 13806461474

E-mail: agritractor@gmail.com

Skype: shanweituo

Address: Weifang City, Shandong province, China

产品型号: 7C-8T
Model: 7C-8T
产品名称: 农用拖车
Name: farm trailer
产品图片:

Picture:



产品特点:

适用于运输重载货物, 和远途运输, 该车配置齐全, 行驶平稳、外型美观、经久耐用, 使用做业环境广泛, 装载效率高。配套动力 80-120hp. 转向形式: 无心转盘。减震形式: 弹性弓板。牵引形式: 三角架活牵引。自卸配置: 双油缸。后置尾灯、左右护栏。整车汽车线束。气路连接形式: 气管快接头。电路连接形式: 螺旋七芯线快插头。油路连接形式: 快换接头。表面处理: 大型抛丸机消除焊接应力、除锈、除氧化皮、防锈漆、面漆、烤漆处理。焊接工艺: CO2 工装焊接。运输形式: 散件运输、箱板软包装。

The 8ton trailer is fit for heavy-duty, far and near transportation, completely configure, it runs steadily. the outlook is artistic, durable in use, working environment is widespread. The loading efficiency is high. Matched power is 80 - 120hp.

The form of turning: centreless turntable.

The form of damping: leaf spring

The form of traction: tripod stand traction(cusion spring)

Postpositive tailight

Left and right barrier

Auto-circuitry of the whole trailer

The form of tipping: left or right tipping Provide with fuel tank (double fuel tank)

The form of air path connection: connected with spiral tube

The form of oil pipe: nipple

The form of circuitry path :Connected with 7 core spiral cable swift connector

Surface treatment: derusting with large size shot blast machine, to change welding stress

Surface spray coating: antirusting paint, finishing paint .

The process of welding: carbon dioxide MIG welding

The form of transportation: parts and components, flexible packing with the box plate

Contact: Henry

Mobile: 86 13806461474

E-mail: agritractor@gmail.com

Skype: shanweituo

Address: Weifang City, Shandong province, China

Carriage(mm) 车箱尺寸	Out dimensions (mm) 外形尺寸	Load (kg) 载重	Structure weight(kg) 自重	Tyre 配套轮胎	Unload form 卸料形式	Brake (4 wheels) 刹车形式
5500X2200X5 50	7200x2300x2600	8000	2100	9.00-20	人工 Manual	Rear air brake 四轮后气刹
5500X2200X5 50	7200x2300x2600	8000	2600	9.00-20	Dump 自卸	Rear air brake 四轮后气刹



10 Metric ton hydraulic self-loading trailer

- 1) Trailer Loading :10 Metric ton ; Empty Weight:2700KGS
- 2) Four wheel air brake
- 3) Turn Over Double side, three oil point
- 4) Trailer box dimension: 6000*2100*550mm; Overall Dimension : 7600*2190*3040mm
High Hurdle: 1050mm, High Hurdle can take to pieces.
- 5) The height from the ground to the trailer box floor: 1440mm
- 6) The height from the ground to the trailer axle: 350mm
- 7) Max. Unload inclination :75°
- 8) Wheelbase: 4300mm; Tyre Space between: 1740mm
- 9) Air-pressure for brake: 0.45~ 0.8MPA
- 10) Max. Oil pressure: 16MPA
- 11) Tyre specification: 10.00-20
- 12) Include one spare wheel.
- 13)

Contact:Henry

Mobile:86 13806461474

E-mail:agritractor@gmail.com

Skype: shanweituo

Address:Weifang City, Shandong province, China