


11: Managing Multiple Nodes



This section's goal is to have you bootstrap another node, this time a web server, and add it to the proxy members.

Objectives



After completing this module, you should be able to

- Bootstrap, update the `run_list`, and run `chef-client` on a node
- Append values to an attribute within a recipe
- Version a cookbook and upload it to the Chef Server


In this module you will learn how to bootstrap, update the run list, and run `chef-client` on a node. You will also learn how to update a default attribute within a recipe, version and upload a cookbook.

Managing User Traffic



You already configured the load balancer and one web server node.

In this module you'll add another node to the load balancer's list of web server's it is serving.



After completing this module, you will have configured three nodes:

Node 1: A web server

Node 2: The load balancer

Node 3: Another web server



Lab: Another Web Node

- ☐ Bootstrap a new node
- ☐ Update the run list of the new node to include the web server cookbook
- ☐ Run chef-client on that system
- ☐ Verify that the node's web server is functional

Now it's time to create a third node. The third node will be the second web server node.

We will provide you with a new node for the following exercise.

Lab: Bootstrap the New Node



```
$ knife bootstrap FQDN -x USER -P PWD --sudo -N node3
```

```
Connecting to ec2-54-210-86-164.compute-1.amazonaws.com
ec2-54-210-86-164.compute-1.amazonaws.com Starting first Chef Client run...
ec2-54-210-86-164.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
ec2-54-210-86-164.compute-1.amazonaws.com resolving cookbooks for run list: []
ec2-54-210-86-164.compute-1.amazonaws.com Synchronizing Cookbooks:
ec2-54-210-86-164.compute-1.amazonaws.com Compiling Cookbooks...
ec2-54-210-86-164.compute-1.amazonaws.com [2015-09-16T17:36:14+00:00] WARN: Node
node3 has an empty run list.
ec2-54-210-86-164.compute-1.amazonaws.com Converging 0 resources
ec2-54-210-86-164.compute-1.amazonaws.com
ec2-54-210-86-164.compute-1.amazonaws.com Running handlers:
ec2-54-210-86-164.compute-1.amazonaws.com Running handlers complete
ec2-54-210-86-164.compute-1.amazonaws.com Chef Client finished, 0/0 resources
updated in
```

Bootstrap the new node and name it node3.

Lab: Verify the New Node



```
$ knife node show node3
```

```
Node Name:    node3
Environment:  _default
FQDN:         ip-172-31-0-127.ec2.internal
IP:           54.210.86.164
Run List:
Roles:
Recipes:
Platform:    centos 6.6
Tags:
```

Verify that you bootstrapped the node.

Lab: Set the Run List



```
$ knife node run_list add node3 "recipe[apache]"
```

```
node3:  
  run_list: recipe[apache]
```

Set the run list for this node by running the apache cookbook's default recipe.

Lab: Converge the Run List



```
$ knife ssh "*:*" -x USERNAME -P PWD "sudo chef-client"
```

```
ec2-54-175-46-24.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
ec2-54-210-192-12.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
ec2-54-210-86-164.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
ec2-54-175-46-24.compute-1.amazonaws.com resolving cookbooks for run list: ["apache"]
ec2-54-210-86-164.compute-1.amazonaws.com resolving cookbooks for run list: ["apache"]
ec2-54-210-86-164.compute-1.amazonaws.com Synchronizing Cookbooks:
ec2-54-210-192-12.compute-1.amazonaws.com resolving cookbooks for run list: ["myhaproxy"]
ec2-54-175-46-24.compute-1.amazonaws.com Synchronizing Cookbooks:
ec2-54-175-46-24.compute-1.amazonaws.com   - apache
ec2-54-175-46-24.compute-1.amazonaws.com Compiling Cookbooks...
ec2-54-175-46-24.compute-1.amazonaws.com Converging 3 resources
ec2-54-175-46-24.compute-1.amazonaws.com Recipe: apache::server
```

Apply that run list by logging into that node and running `sudo chef-client` or remotely administer the node with the 'knife ssh' command as shown here.

Verify that the New Node Serves the Page



Verify that the node serves up the default html page that contains the node's internal IP address and hostname.



Lab: Update the Load Balancer

- ☐ Update the wrapped proxy server cookbook to include the new web node as a member.
- ☐ Upload that cookbook to the Chef Server
- ☐ Run chef-client on that system
- ☐ Verify that the load balancer delivers traffic to both web server nodes.

Now that you have the third node, it is time to add that node to the member's list for the load balancer.

Lab: Capture Node's Public Host Name and IP



```
$ knife node show node3 -a cloud
```

```
node1:
  cloud:
    local_hostname: ip-172-31-8-64.ec2.internal
    local_ipv4: 172.31.8.64
    private_ips: 172.31.8.64
    provider: ec2
    public_hostname: ec2-54-176-64-173.us-west-1.compute.amazonaws.com
    public_ips: 54.175.46.48
    public_ipv4: 54.175.46.48
```

If you use 'knife node show' to display the 'cloud' attribute for node3, you will see the local, private, and public connection information.

Capture and write down the public hostname and the public ipv4 address of node3. You will need this in the recipe you are going to write.

Lab: Add the Other Web Server to LB

`~/chef-repo/cookbooks/myhaproxy/recipes/default.rb`

```
node.default['haproxy']['members'] = [{  
  'hostname' => 'ec2-52-8-71-11.us-west-1.compute.amazonaws.com',  
  'ipaddress' => '52.8.71.11',  
  'port' => 80,  
  'ssl_port' => 80  
}, {  
  'hostname' => 'ec2-54-176-64-173.us-west-1.compute.amazonaws.com',  
  'ipaddress' => '54.175.46.48',  
  'port' => 80,  
  'ssl_port' => 80  
}  
]  
  
include_recipe 'haproxy::default'
```

Add the second web server (node3) to the load balancer's (LB) members list. You may need to run 'knife node show node3 -a cloud' to get the hostname and ipaddress values.

Lab: Update the Version

```
~/chef-repo/cookbooks/myhaproxy/metadata.rb

name 'myhaproxy'
maintainer 'The Authors'
maintainer_email 'you@example.com'
license 'all_rights'
description 'Installs/Configures myhaproxy'
long_description 'Installs/Configures myhaproxy'
version '0.2.0'

depends 'haproxy', '~> 1.6.6'
```

Update the version number in myhaproxy cookbook's metadata.

Lab: CD and Then Run berks install



```
$ cd ~/chef-repo/cookbooks/myhaproxy  
$ berks install
```

```
Resolving cookbook dependencies...  
Fetching 'myhaproxy' from source at .  
Fetching cookbook index from https://supermarket.chef.io...  
Using build-essential (2.2.3)  
Using cpu (0.2.0)  
Using haproxy (1.6.6)  
Using myhaproxy (0.2.0) from source at .
```

Change into the 'myhaproxy' cookbook directory and then run 'berks install' to install any dependencies for the 'myhaproxy' cookbook.

Lab: Upload the Cookbook to Chef Server



\$ berks upload

```
Uploaded build-essential (2.2.3) to:
'https://api.opscode.com:443/organizations/steveessentials2'
Uploaded cpu (0.2.0) to: 'https://api.opscode.com:443/organizations/steveessentials2'
Uploaded haproxy (1.6.6) to: 'https://api.opscode.com:443/organizations/steveessentials2'
Uploaded myhaproxy (0.2.0) to: 'https://api.opscode.com:443/organizations/steveessentials2'
```

Run 'berks upload' to upload the myhaproxy cookbook to Chef Server.

Lab: Converge the Cookbook



```
$ knife ssh "*:*" -x USERNAME -P PWD "sudo chef-client"
```


```
ec2-54-210-192-12.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
ec2-54-175-46-24.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
ec2-54-210-86-164.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
ec2-54-210-192-12.compute-1.amazonaws.com resolving cookbooks for run list:
["myhaproxy"]
ec2-54-175-46-24.compute-1.amazonaws.com resolving cookbooks for run list:
["apache"]
ec2-54-175-46-24.compute-1.amazonaws.com Synchronizing Cookbooks:
ec2-54-175-46-24.compute-1.amazonaws.com   - apache
ec2-54-175-46-24.compute-1.amazonaws.com Compiling Cookbooks...
ec2-54-210-192-12.compute-1.amazonaws.com Synchronizing Cookbooks:
ec2-54-175-46-24.compute-1.amazonaws.com Converging 3 resources
ec2-54-175-46-24.compute-1.amazonaws.com Recipe: apache::server
ec2-54-210-192-12.compute-1.amazonaws.com   - build-essential
```

Converge the cookbook by logging into that node and running 'sudo chef-client' or remotely administer the node with the 'knife ssh' command as shown here.

Within the output you should see the haproxy configuration file will update with a new entry that contains the information of the second member (node3).

Slide 17


Lab: Test the Load Balancer



Point a web browser to the URL of your Proxy server and then click Refresh a few times. You should see each of your web server's HTML page as the Proxy server switches between each web server.

This is not a very scientific way of seeing that the proxy server is balancing requests between these two web nodes.


Lab: Test the Load Balancer




The image displays three browser windows, each showing a 'Hello, world!' message and associated IP address and hostname. A blue arrow points from the top window to the bottom-right window, indicating a redirect or load balancing action.

- Top Window:** `ec2-50-18-19-208.us-west-1.compute.amazonaws.com`
Hello, world!
ipaddress: 10.197.105.148
hostname: ip-10-197-105-148
- Bottom-Left Window:** `ec2-50-18-19-208.us-west-1.compute.amazonaws.com`
Hello, world!
ipaddress: 10.198.51.26
hostname: ip-10-198-51-26
- Bottom-Right Window:** `ec2-54-176-64-173.us-west-1.compute.amazonaws.com`
Hello, world!
ipaddress: 10.197.105.148
hostname: ip-10-197-105-148

©2015 Chef Software Inc. 11-18



DISCUSSION



Discussion


What is the process to setup a third web node?

What is the process for removing a web node?

What is the most manual part of the process?

©2015 Chef Software Inc.

11-19



CHEF

Answer these questions.

With your answers, turn to another person and alternate asking each other asking these questions and sharing your answers.

DISCUSSION

Q&A

What questions can we help you answer?





CHEF™