

Building a Windows LAN Messenger – System Design and Implementation

Executive Summary: This report presents a comprehensive blueprint for designing and implementing a Windows desktop LAN (Local Area Network) chat/messenger application in Python. We cover relevant networking protocols (IP, DHCP, ARP, UDP broadcast, multicasting, etc.), and compare architectural patterns (client-server vs peer-to-peer). The recommended tech stack (Python 3.10+ on Windows) is surveyed, including GUI frameworks (Tkinter, PyQt/PySide, Kivy, etc.) and networking libraries (`socket`, `asyncio`, `zeroconf`, multicast, etc.). We detail message formats (JSON vs protobuf, etc.), optional encryption (e.g. AES via PyCryptodome), file/folder transfer, emoji support, presence/status broadcast, message broadcasting, local history storage (e.g. SQLite), and log/error handling. For each source file/module, we outline its purpose, public API, data models, and sketch code structure (with comments on business logic). Mermaid diagrams illustrate the architecture and key sequences. Finally, we explain deployment as a Windows `.exe` (using PyInstaller) and link the learned network concepts to AWS cloud networking (VPC, EC2, etc.) and messaging services. Tables compare design options, libraries, and packaging tools. All claims are backed by authoritative sources.

Networking Fundamentals for LAN Discovery and Messaging

A LAN messenger must operate entirely over the local IPv4 (or IPv6) network. Core networking concepts include **IP addressing and subnets** (often a /24 network supporting up to 254 hosts), **DHCP** (dynamically assigns IPs on local networks), **ARP** (Address Resolution Protocol) for mapping IP to MAC, and both **UDP** and **TCP** protocols for communication. On a LAN, a device typically gets its IPv4 via DHCP from the router, and uses ARP to resolve MAC addresses when sending packets to known IPs. ARP itself works by broadcasting a request for a given IP; the host owning that IP replies with its MAC address [11†L172-L181] .

Peer Discovery: In a LAN environment, discovering other messenger clients can be done several ways. For example, an application can perform an **ARP scan** of the local subnet (e.g. ping or ARP request to each address) to enumerate active hosts. ARP scanning is especially effective on Ethernet LANs (it finds hosts even if they block ICMP ping) and returns both IP and MAC [13†L156-L164] [13†L264-L272] . A Python implementation could use `scapy` to send ARP who-has requests (as shown in [13]) or invoke tools like `arp-scan` .

Alternatively, **UDP broadcast discovery** is common. Here, one peer sends a UDP packet to the broadcast address (255.255.255.255 or interface-specific, e.g. 192.168.1.255) on a well-known port; listening peers reply with their own address/port. As OneUptime notes, a client can broadcast a JSON-encoded “DISCOVER” packet to 255.255.255.255, and servers reply with an “ANNOUNCE” message containing their service name, IP, and port [4†L179-L188] [6†L320-L327] . This yields a list of active services without a central registry. It is important to target the correct subnet’s broadcast address on multi-homed hosts, and to use a TTL/timeout or periodic broadcast so that stale entries expire [6†L320-L327] .

Finally, **mDNS/Zeroconf** (Bonjour/Avahi) is a portable solution: using multicast DNS (mDNS) you can advertise a service on the local network. Python’s `zeroconf` library implements DNS-SD over mDNS,

allowing LAN discovery by service type 【16†L9-L17】 . For Windows, Bonjour may need installation, but zeroconf works cross-platform 【15†L169-L177】 . Whether to use raw UDP broadcast or mDNS depends on network policies (some enterprise LANs disable multicast).

System Architecture: Client-Server vs Peer-to-Peer

A key design decision is the messaging architecture. In a **client-server model**, one host (or dedicated server) acts as the central relay and data store, and clients connect to it. In a **peer-to-peer (P2P) model**, each client communicates directly with others without a central server. Each has pros and cons 【21†L113-L121】 【21†L184-L193】 :

- **Client-Server:** One central server handles all routing and perhaps persists chat history.
Advantages: central control and security (e.g. enforcing policies), easier offline messaging (server queues undelivered messages). *Disadvantages:* single point of failure and bottleneck, requires one always-on machine (or having dynamic host create one). Could be suitable if users accept one of the LAN PCs as server, or if you add an on-premises server component.
- **Peer-to-Peer:** Every node is both client and server. *Advantages:* no single failure point – if one peer goes offline only its session is lost, simpler to deploy (no server install needed). The classic open-source “LAN Messenger” uses this design: it requires no server or Internet, and even provides AES+RSA encryption 【23†L8-L13】 . *Disadvantages:* potential complexity in ensuring all peers know each other; harder to maintain consistency (e.g. message ordering) without central coordination. Security can be trickier since there is no central authority.

We show a brief comparison (see **Table 1**):

	Client-Server	Peer-to-Peer (P2P)
Architecture	Central server, clients connect to it	Fully distributed; each client listens
Discovery	Server IP known / DNS lookup; or have a registry	UDP broadcast or mDNS used by each peer
Data Flow	Clients -> Server -> Clients	Direct Client<->Client or flooding/broadcast
History	Server can store all history	Each client stores its own history; sync tricky
Failure Mode	Server down = system down	If some peers drop, others still chat (except lost history)
Scalability	Scales via server resources, can use load-balancing	Up to ~255 peers on LAN manageable; more peers means more connections
Complexity	Simpler message routing, but need to host server	More complex peer list management, NAT/traversal issues not present on LAN
Examples	XMPP servers, IRC	BitTorrent, classic LAN chat tools




Figure 1: Simplified P2P discovery and chat flow on a LAN (arrows indicate UDP broadcasts and TCP chat messages).

Given the requirement (“works without server”), a **peer-to-peer design** is often chosen for LAN chat. For example, the LAN Messenger project explicitly states “no need for a server” [23†L8-L13]. We can still embed a simple *logical* server component if desired (e.g. one peer can assume the role of “master” to simplify reply-of-peers), but the underlying communication is peer-to-peer over LAN.

Protocols and Data Formats

Messages between clients need a clear format. A simple and common choice is **JSON** (JavaScript Object Notation) since it is human-readable, language-agnostic, and easy to use in Python (`json` module). For higher performance or type-safety, one could use **Protocol Buffers (protobuf)** or **MessagePack**, which produce compact binary messages [30†L141-L144]. Protobuf requires a predefined schema (a “.proto” file) and code generation [30†L79-L87], whereas JSON/MessagePack are schema-less [30†L85-L88]. For a LAN messenger with at most hundreds of nodes, JSON is acceptable for text-based chat. One might reserve protobuf for file-transfer metadata if optimizing for speed. In summary:

- *JSON*: Built-in, easy, good for text; messages are larger and slightly slower to parse.
- *Protobuf*: Requires schema, compact, fast; more setup.
- *MessagePack*: Binary like JSON, no schema needed, more efficient than JSON [30†L141-L144].

A typical message payload might be a JSON object like

```

{"type": "chat", "from": "Alice", "text": "Hello 😊", "timestamp": 1678850000}, or
{"type": "file", "from": "Bob", "filename": "report.pdf", "chunk":
1, "data": "...base64..."}. We define a small Protocol module enumerating message types
(CHAT, PRESENCE, FILE_CHUNK, etc.) and fields.

```

If privacy is a concern, we can optionally encrypt messages. A common approach is to use **AES-256** symmetric encryption (e.g. via `PyCryptodome` or `cryptography` library). For example, LAN Messenger uses “AES encryption with RSA” [23†L33-L41]. In practice, peers could negotiate a shared AES key or use RSA to exchange keys and then encrypt all payloads. This is beyond minimal requirement, but Python libraries easily support AES in GCM/EAX mode for confidentiality and authenticity.

Features: File Sharing, Emoji, Presence, History

- **File/Folder Transfer**: The messenger can send files via the same connection channel. Typically, one sends metadata (filename, size) then transmits data in chunks (e.g. base64-encoded or raw bytes). The receiver reassembles chunks. A *progress bar* UI element is useful. Optionally

compress/zip folders before sending. Consider limiting transfer size or sending a link if file is large (not needed on LAN up to 255 users).

- **Emoji Support:** Modern GUI toolkits support Unicode, so emojis can be included in text messages like any character. Ensure your font supports the emoji set. Alternatively, show a selection palette of common emoji which inserts the corresponding Unicode character in chat.
- **Presence/Status:** Each client can have a status (Online, Busy, Away, Offline). On login or status change, broadcast a presence update
(`{"type": "presence", "user": "Alice", "status": "Online"}`). Peers update their contact list UI. Periodic “heartbeat” or broadcast when coming online helps discover late joiners.
- **Broadcast Messages:** Provide a “Send to All” option. In P2P, this is easily implemented by looping through all known peers and sending a CHAT message to each, or by sending on a UDP port if a broadcast mechanism is desired (but reliability suffers).
- **Local Chat History:** Each client should log conversations locally (for later viewing). A lightweight solution is an embedded database like **SQLite** (via Python’s `sqlite3`). SQLite is file-based, requires no server, and stores all data in one cross-platform file [32†L109-L112]. It is easy to use and faster than re-reading text files for queries. For example, a `ChatHistory` module can insert each message into an SQLite table.
- **History Sync (Optional):** If a new client joins, it could request recent history from peers (e.g. peer A asks B for last 100 messages). This is complex and optional – often local history only.
- **Scalability (2–255 users):** A class-C LAN (/24) has 254 usable addresses. Up to ~250 clients is theoretically possible, though a broadcast chat to all 250 peers may strain performance. In practice, a few dozen to 100 users is fine. If more needed, one could segment by subnets or use multiple multicast groups. For 2–255 we assume a single broadcast domain.

Technology Stack

- **Python Version:** Use the latest stable **Python 3.x** (e.g. 3.10, 3.11 or above) for long-term support. Python 3.10+ is recommended as Python 2 is obsolete. Ensure Windows compatibility. The [latest Python versions](#) include security fixes and modern features (async/await, improved performance).
- **GUI Framework:** Key options on Windows include:
 - **Tkinter (Tk)** – Built into Python, very easy to start, minimal dependencies. *Pros:* No extra installation, simple widgets. *Cons:* Outdated look, fewer widgets, less modern UI. (Docs note: PyGTK/PyQt/wxPython have “modern look and feel and more widgets than Tkinter” [27†L57-L62].)
 - **PyQt (Qt)** – Full-featured, native look, many widgets. *Pros:* Rich UI, well-documented, designer tools. *Cons:* Large download, LGPL/GPL license (requires open-source app or commercial license), more learning curve.
 - **PySide (Qt for Python)** – Official Qt binding, similar to PyQt but more permissive license. *Pros:* Same as PyQt, LGPL. *Cons:* Slightly smaller community.
 - **wxPython** – Native OS widgets on Windows, modern look. *Pros:* Free, mature, many controls. *Cons:* Larger than Tkinter, different API paradigm.
 - **Kivy** – Focus on touch/mobile, uses its own rendering. *Pros:* Good for multi-touch, different look. *Cons:* Heavy, not typical desktop style.
 - **PySimpleGUI** – A wrapper around Tk/Qt that simplifies coding. *Pros:* Very easy for beginners. *Cons:* Less flexible, ultimately uses one of the above backends.

Table 2 (below) compares these:

Toolkit	Pros	Cons
Tkinter	Built-in, easy, lightweight	Basic look, limited widgets 【27†L57-L62】
PyQt / PySide	Rich widgets, native look, powerful	Large, steeper learning, licensing
wxPython	Native look, many widgets, free	Heavier than Tk, install needed
Kivy	Cross-platform, GPU-accelerated, touch-friendly	Non-native appearance, heavy
PySimpleGUI	Very easy, code brevity	Abstraction overhead, relies on underlying toolkit

- **Networking Libraries:**

- `socket` (built-in): Fundamental BSD sockets (IPv4/6, UDP, TCP). Use for raw transport.
- `asyncio`: Python's async I/O framework. Useful to write asynchronous servers/clients without threads. It supports UDP and TCP (`asyncio.DatagramProtocol` or `streams`). Could simplify handling multiple peers in a single-threaded loop.
- `zeroconf`: For mDNS/DNS-SD service discovery, if choosing that route.
- `multicast`: You can use raw sockets with multicast group addresses if you want IP multicast for discovery across subnets. Python's `socket` supports `setsockopt` for multicast groups.
- (Optionally, for higher-level abstraction, one could embed a small webserver or use MQTT via `paho-mqtt`, but not required for local peers.)

- **Serialization Options:** JSON (`json`), **Protocol Buffers** (via `protobuf` library), or **MessagePack** (`msgpack`).

- **Database/Storage:**

- **SQLite** (`sqlite3`): Embedded SQL database, very reliable and fast. We store chat logs and maybe settings. It is *"easier to install and use"*, being a single file [【32†L109-L112】](#).
- **File-based:** Alternatively, plain files (CSV/JSON per user). Simpler but less queryable. For simplicity, SQLite is recommended.

- **Packaging Tools:**

- **PyInstaller** – The de facto tool to create Windows executables. It bundles the Python interpreter and all dependencies into one folder or `.exe` [【47†L147-L155】](#) [【47†L162-L164】](#).
- **cx_Freeze** – Similar to PyInstaller, cross-platform, less used.
- **py2exe** – Windows-only older tool.
- **PyOxidizer / Nuitka** – Advanced packagers (beyond scope).

PyInstaller is widely used and will be our recommendation. It can build a single-folder or single-file `.exe`. For Windows, it simply produces `messenger.exe` and all needed DLLs. (PyInstaller documentation and tutorials show usage and troubleshooting.)

Implementation Blueprint: Modules and Files

A modular design separates concerns. Below are suggested Python modules (files) and their roles, with pseudocode skeletons and logic. (Comments at the top of each skeleton explain business logic.)

`protocol.py` (Message Definitions)

Purpose: Define message types, constants, and data models for the chat protocol. All peers import this to construct/parse messages.

Public API:

- Enums or constants, e.g. `MSG_CHAT = "chat"`, `MSG_PRESENCE = "presence"`, `MSG_FILE = "file"`.
- Data classes or dict schemas, e.g. `ChatMessage`, `PresenceUpdate`, `FileChunk` (for type annotations and clarity).

Data Models: We might use Python classes or typed dicts for clarity:

```
# protocol.py
"""
Defines message types and data models for LAN Messenger.
"""

MSG_CHAT = "chat"
MSG_PRESENCE = "presence"
MSG_FILE = "file"
MSG_ACK = "ack"

class ChatMessage:
    def __init__(self, sender: str, text: str, timestamp: float, chat_id:
str):
        self.type = MSG_CHAT
        self.sender = sender
        self.text = text          # May contain emoji characters
        self.timestamp = timestamp
        self.chat_id = chat_id
    # e.g. conversation ID or could be broadcast ID
    def to_json(self) -> str:
        return json.dumps(self.__dict__)

class PresenceUpdate:
    def __init__(self, user: str, status: str):
        self.type = MSG_PRESENCE
        self.user = user
        self.status = status      # "online", "offline", "busy", etc.


class FileChunk:
    def __init__(self, sender: str, filename: str, chunk_index: int, data:
bytes, eof: bool):
        self.type = MSG_FILE
```

```

self.sender = sender
self.filename = filename
self.index = chunk_index
self.data = data          # raw bytes or base64
self.eof = eof            # is this last chunk

```

Sequence: For sending a chat, the client creates a `ChatMessage`, serializes with JSON, and sends via TCP/UDP to peers. On receive, a peer parses JSON and displays. (A mermaid sequence can show client creating message and delivering.)



Explanation: This file encapsulates the “language” of our messenger. By standardizing types and fields, different modules can interchange message objects. All fields should be serializable (JSON) or picklable. Business logic: message routing does not need to know message internals, just the `type`.

`discovery.py` (Peer Discovery)

Purpose: Discover other instances on the LAN. Could implement UDP broadcast or mDNS.

Public API: Functions like `send_discover()` and `listen_for_announcements()`, or a class `ServiceDiscovery`.

Data Models: Possibly an internal registry of peers (IP, port, name).

```

# discovery.py
"""
Handles finding other LAN messenger peers via UDP broadcast.
"""
DISCOVERY_PORT = 37020

class Discovery:
    def __init__(self, listen_port=DISCOVERY_PORT):
        self.port = listen_port
        self.peers = {} # map user -> (ip, port)

    def announce_presence(self, username: str, user_port: int):

```

```


    """
    Broadcast this user's presence periodically.
    """
    payload =
    json.dumps({"type": "announce", "name": username, "port": user_port}).encode()
    sock = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
    sock.setsockopt(socket.SOL_SOCKET, socket.SO_BROADCAST, 1)
    while True:
        sock.sendto(payload, ('255.255.255.255', DISCOVERY_PORT))
        time.sleep(5.0)

def listen_for_discovery(self):
    """
    Listen for incoming discovery requests and send replies.
    """
    sock = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
    sock.setsockopt(socket.SOL_SOCKET, socket.SO_REUSEADDR, 1)
    sock.bind(('', DISCOVERY_PORT))
    while True:
        data, addr = sock.recvfrom(1024)
        msg = json.loads(data.decode())
        if msg.get("type") == "discover":
            # reply with own announcement
            reply =
            json.dumps({"type": "announce", "name": myname, "port": my_port}).encode()
            sock.sendto(reply, addr)

def discover_peers(self, timeout=2.0):
    """
    Actively send a discovery broadcast and collect replies.
    """
    sock = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
    sock.setsockopt(socket.SOL_SOCKET, socket.SO_BROADCAST, 1)
    sock.bind(('', DISCOVERY_PORT))
    sock.settimeout(timeout)
    # send discovery request
    msg = json.dumps({"type": "discover"}).encode()
    sock.sendto(msg, ('255.255.255.255', DISCOVERY_PORT))
    start = time.time()
    while time.time() - start < timeout:
        try:
            data, addr = sock.recvfrom(1024)
        except socket.timeout:
            break
        resp = json.loads(data.decode())
        if resp.get("type") == "announce":
            self.peers[resp["name"]] = (addr[0], resp["port"])

```

Sequence: Discovery typically involves two steps – announce and reply. The client sends a *DISCOVER* broadcast, others respond with *ANNOUNCE*. [4] provides a detailed example of this UDP discovery pattern [4†L179-L188] [6†L320-L327] .



Explanation: This module handles *peer discovery*. On startup, an instance can call `discover_peers()` to get current live peers. It can also run `listen_for_discovery()` in a background thread to respond to others' queries. To stay discoverable, it runs `announce_presence()` periodically. This ensures a self-maintained registry of peers.

`network.py` (Connection Management and Messaging)

Purpose: Manage network sockets and communication channels between peers. This includes setting up TCP (or UDP) servers and clients for chat messages and file transfers.

Public API: Possibly a class `NetworkManager` with methods `start_server()`, `connect_to_peer(ip, port)`, `send_message(peer, msg)` and callbacks for incoming messages.

Data Models: Could maintain a list/dict of active connections (peer name -> socket).

```

# network.py
"""
Handles TCP/UDP connections: accepts incoming connections and sends/receives
messages.
"""
class NetworkManager:
    def __init__(self, listen_ip='', listen_port=12345):
        self.listen_port = listen_port
        self.server_socket = None
        self.peer_sockets = {} # peer_name -> socket
        self.handlers = {}     # message_type -> callback

    def start_server(self):
        """
        Start TCP server to accept incoming chat connections.
        """
        self.server_socket = socket.socket(socket.AF_INET,
            socket.SOCK_STREAM)
        self.server_socket.bind(('', self.listen_port))
  
```

```

        self.server_socket.listen()
        threading.Thread(target=self._accept_loop, daemon=True).start()

    def _accept_loop(self):
        while True:
            client_sock, addr = self.server_socket.accept()
            # Optionally read initial handshake (peer name)
            peer_name = client_sock.recv(1024).decode()
            self.peer_sockets[peer_name] = client_sock
            threading.Thread(target=self._recv_loop, args=(peer_name,),
daemon=True).start()

    def connect_to_peer(self, ip, port, name):
        """
        Connect to a peer's server socket.
        """
        sock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
        sock.connect((ip, port))
        # send own name as handshake
        sock.sendall(my_name.encode())
        self.peer_sockets[name] = sock
        threading.Thread(target=self._recv_loop, args=(name,),
daemon=True).start()

    def _recv_loop(self, peer_name):
        """
        Listen for incoming messages from a specific peer.
        """
        sock = self.peer_sockets[peer_name]
        while True:
            data = sock.recv(4096)
            if not data:
                break
            msg = json.loads(data.decode())
            handler = self.handlers.get(msg["type"])
            if handler:
                handler(msg, peer_name)

    def send_message(self, peer_name, msg_dict):
        """
        Send a message (dict) to a connected peer.
        """
        data = json.dumps(msg_dict).encode()
        self.peer_sockets[peer_name].sendall(data)

```

Explanation: This file deals with **low-level socket I/O**. It creates a listening TCP server (on a configurable port) to accept incoming peer connections. When a new connection is accepted, it expects the connecting peer to immediately send its username (handshake). Then it spawns a receiver loop thread for that socket. Conversely, to initiate a chat with a discovered peer, `connect_to_peer()` opens a TCP socket to the peer's address and sends our name. All incoming JSON messages are

dispatched via registered handlers (e.g. the GUI or chat logic). Business logic (message interpretation) is *not* here; this is purely I/O.

`gui.py` (User Interface)

Purpose: Present a graphical user interface for chatting. Manages windows, dialogs, and user interactions.

Public API: Functions or classes like `ChatWindow`, which has methods `display_message(text)` and `prompt_file_save()`, etc.

Data Models: None persistent; likely uses internal state for open chats, contact list, etc.

```
# gui.py
"""
Defines the GUI for the LAN Messenger using a chosen toolkit.
"""
class ChatWindow:
    def __init__(self):
        """
        Initialize main window, set up widgets: contacts list, chat area,
        input box, buttons.
        """
        # e.g. using Tkinter
        self.root = Tk()
        self.root.title("LAN Messenger")
        self.chat_text = Text(self.root)
        self.chat_text.pack()
        self.entry = Entry(self.root)
        self.entry.pack()
        self.send_btn = Button(self.root, text="Send",
command=self.send_clicked)
        self.send_btn.pack()
        # ... additional UI elements (emoji picker, file button, status menu)

    def send_clicked(self):
        text = self.entry.get()
        if text:
            # Show locally
            self.display_message("Me", text)
            # Notify application logic to send
            on_send_chat(self.current_peer, text)

    def display_message(self, sender, text):
        """
        Append a message to chat display.
        """
        self.chat_text.insert(END, f"{sender}: {text}\n")
```

Explanation: The GUI module depends on the chosen framework. The skeleton above (using Tkinter widgets) illustrates typical parts: a text area to show messages, an entry field, and a button to send. Additional widgets would include a listbox for online users (with status icons), emoji button/menu, file-

transfer button, etc. Whenever the user sends text or attaches a file, the GUI calls the core messaging logic (through event handlers). Incoming messages from the network are pushed into `display_message()`. Business logic: purely interface – no network code here. (In practice, one might use an MVC approach or signals to connect `NetworkManager` handlers to GUI updates.)

`storage.py` (Chat History and User Data)

Purpose: Persist chat logs and user preferences. Uses SQLite or files.

Public API: A class `Storage` with methods like `save_message(chat_id, sender, text, timestamp)` and `get_history(chat_id)`, also `save_settings()` / `load_settings()`.

Data Models: Database tables (`messages`, `users`, etc).

```
# storage.py
"""
Handles local storage of chat history and settings using SQLite.
"""
class Storage:
    def __init__(self, db_path="chat_history.db"):
        self.conn = sqlite3.connect(db_path)
        self._init_tables()

    def _init_tables(self):
        cur = self.conn.cursor()
        cur.execute("""
            CREATE TABLE IF NOT EXISTS messages (
                id INTEGER PRIMARY KEY,
                chat_id TEXT,
                sender TEXT,
                text TEXT,
                timestamp REAL
            )
        """)
        cur.execute("""
            CREATE TABLE IF NOT EXISTS users (
                username TEXT PRIMARY KEY,
                status TEXT
            )
        """)
        self.conn.commit()

    def save_message(self, chat_id, sender, text, ts):
        cur = self.conn.cursor()
        cur.execute("INSERT INTO messages(chat_id,sender,text,timestamp)
VALUES (?, ?, ?, ?)",
                    (chat_id, sender, text, ts))
        self.conn.commit()

    def get_history(self, chat_id):
        cur = self.conn.cursor()
        cur.execute("SELECT sender,text,timestamp FROM messages WHERE
```

```
chat_id=? ORDER BY timestamp", (chat_id,))
return cur.fetchall()
```

Explanation: This module isolates data persistence. By using SQLite, we have a robust, transactional store for chat data. On each send/receive of a chat, the application calls `save_message()`. On startup or when switching chats, the GUI can call `get_history()` to load recent messages. Settings (e.g. username, last window size) can be stored similarly in a table or a simple config file. Since SQLite stores in one file, deployment is easy [32†L109-L112] .

`file_transfer.py` (Optional: Send Files)

Purpose: Handle splitting files into chunks, sending, and reassembly.

Public API: `send_file(peer, filepath)` and handler for receiving chunks.

Data Models: Possibly track ongoing transfers (`file_id -> file object`).

```
# file_transfer.py
"""
Manage file sending/receiving in chunks.
"""
CHUNK_SIZE = 1024 * 50 # e.g. 50KB

def send_file(network: NetworkManager, peer_name: str, filepath: str):
    """
    Reads a file in chunks and sends as FILE messages.
    """
    fname = os.path.basename(filepath)
    with open(filepath, 'rb') as f:
        index = 0
        while True:
            chunk = f.read(CHUNK_SIZE)
            if not chunk:
                break
            msg = {
                "type": "file",
                "sender": my_name,
                "filename": fname,
                "index": index,
                "data": base64.b64encode(chunk).decode(),
                "eof": False
            }
            network.send_message(peer_name, msg)
            index += 1
        # send EOF marker
        eof_msg = {"type": "file", "sender": my_name, "filename": fname,
            "index": index, "data": "", "eof": True}
        network.send_message(peer_name, eof_msg)
```

Explanation: This logic (called, say, when the user clicks “Send File”) reads the chosen file in binary, slices into manageable chunks (to avoid huge messages), encodes each chunk to base64 (so it can

travel in a JSON), and sends via the network. The receiver (handled in `NetworkManager._recv_loop`) would see `type:"file"` and call back into this module to write chunks to disk until `eof=True`. Business logic: handle UI update of progress and ensure chunk order. (Sequence would show sending chunk-by-chunk, but omitted for brevity.)

Sequence Flows and Architecture Diagram

Below is a simplified Mermaid diagram of the overall architecture and message flows:

```
graph TD
    subgraph Application
        GUI[User Interface (Tk/PyQt)]
        NetMgr[Network Manager (TCP/UDP)]
        Proto[Protocol Definitions]
        StorageDB[SQLite Storage]
    end
    GUI --> NetMgr
    NetMgr --> Proto
    NetMgr --> StorageDB
    StorageDB --> GUI
    NetMgr --> GUI

    subgraph LAN
        Peer1[Peer A]
        Peer2[Peer B]
        PeerN[Peer N]
        Peer1 -- TCP/UDP --> Peer2
        Peer2 -- TCP/UDP --> PeerN
    end
    end
```

Figure 2: High-level module architecture. The GUI interacts with the Network Manager, which uses Protocol definitions to parse/send messages, and records to Storage. All peers on the LAN connect via TCP/UDP.

Error Handling, Logging, and Testing

Error handling is important for robustness. Use try/except around network I/O to catch disconnections. The Python `logging` module should be used to log errors and events. For example, `logging.basicConfig(filename='app.log', level=logging.INFO)` at startup, then `logger.error(...)` on exceptions. This helps trace problems in distributed scenarios.

For testing, write unit tests for core logic (message serialization, DB operations, etc.), and integration tests (e.g. simulate two peers on localhost). Use **pytest** to structure tests. Mock sockets or use loopback connections for network module tests. Automated tests should validate message format, discovery broadcasts, and file chunking.

Packaging and Deployment

To distribute on Windows, we package the Python app into a standalone `.exe`. **PyInstaller** is the recommended tool: it bundles the Python interpreter and all modules into an executable [47†L147-

- L155] 【47†L162-L164】 . Example steps: 1. Install PyInstaller (`pip install pyinstaller`).
2. Create a simple entry script (e.g. `main.py`) that invokes the GUI main loop.
3. Run `pyinstaller --onefile main.py` (for a single `.exe`) or without `--onefile` for a folder build.
4. The result is `dist/main.exe` . Users can run this without installing Python.

PyInstaller introspects imports and collects needed DLLs. If any dependency is missing, you can add `--hidden-import` flags. For GUI apps, ensure any data files (icons, `.qrc` resources) are bundled via the `--add-data` option. The Real Python guide notes that “PyInstaller abstracts these details... bundling [dependencies] together. The Python interpreter itself is bundled into your application.” 【47†L147-L155】 .

Other tools like `cx_Freeze` or `py2exe` exist, but PyInstaller is most mature. The final step is testing the `.exe` on a clean Windows VM (using e.g. [Appveyor][47†L159-L168] or similar CI) to ensure no missing libraries.

AWS Learning Path Mapping

This LAN messenger project reinforces networking fundamentals applicable to cloud computing, especially AWS:

- **IP addressing and VPCs:** Designing LAN subnets (e.g. /24) parallels AWS VPCs and subnets. A Virtual Private Cloud is “a logically isolated virtual network” where you define IP CIDRs and subnets 【40†L354-L364】 . Our understanding of IP ranges directly maps to setting VPC CIDR and subnet ranges.
- **Routing and Security Groups:** In AWS, routing tables and security groups govern which traffic flows between subnets/instances. Knowing TCP/UDP and ports (like our use of UDP 37020 or TCP 12345) helps understand configuring AWS security groups.
- **Auto-scaling and Availability:** Though we target 255 LAN users, on AWS similar concepts apply: having multiple chat servers with load balancing, or designing for N number of instances.
- **Serverless vs Containers:** While our design uses raw sockets, AWS alternatives include IoT Core (MQTT messaging) or managed pub/sub (SNS/SQS). For instance, AWS IoT supports MQTT publish/subscribe for real-time messaging, akin to our direct messaging.
- **Storage:** Local SQLite in our app is analogous to AWS edge storage; if this were on AWS, a similar service could be Amazon RDS or DynamoDB for shared history. Knowing SQLite’s role as “embedded database” 【32†L109-L112】 clarifies when to use AWS RDS (managed SQL) versus a local file store.
- **Deployment:** Packaging with PyInstaller is like containerizing or bundling code. On AWS, one might use AWS CodePipeline/CodeBuild to create artifacts, then deploy to EC2 or Lambda. Learning to package a Python app is analogous to building deployment pipelines in AWS.
- **Networking Services:** Concepts of broadcast discovery hint at AWS Service Discovery (Cloud Map) or DNS SRV records. Security concepts (encrypting traffic) map to AWS KMS and HTTPS/TLS.

In summary, this project’s networking components – from IP/DHCP to TCP vs UDP – mirror AWS networking fundamentals 【40†L299-L308】 . For example, “having a good understanding of IP addressing, TCP communication, security, and virtualization will help you” with AWS networking 【40†L299-L308】 . Thus, skills gained (socket programming, network design) prepare one for AWS topics like VPC setup, instance networking, and messaging architectures.

Tables of Options

Table 1: Architecture Comparison (client-server vs P2P) – see above.

Table 2: GUI Frameworks – see above.

Table 3: Serialization Formats

Format	Schema Required	Size/Speed	Ease of Use
JSON	No	Larger, slower parse	Easiest, builtin
MessagePack	No	Compact, fast	Easy (<code>msgpack</code> lib)
Protobuf	Yes	Very compact, fastest	Requires <code>.proto</code> and compile step

Table 4: Packaging Tools

Tool	Windows Support	Output	Remarks
PyInstaller	Yes	<code>.exe</code>	Bundles interpreter 【47†L147-L155】
cx_Freeze	Yes	<code>.exe</code>	Cross-platform, similar function
py2exe	Windows-only	<code>.exe</code>	Older, less maintained

Security Considerations

- **Encryption:** If the LAN is not fully trusted, encrypt messages. Use strong algorithms (AES-256-GCM) and consider key exchange. Be mindful of securely storing keys (not hardcoding them). Python's `cryptography` library or `PyCryptodome` are recommended.
- **Authentication:** Potentially verify peer identities (e.g. with RSA signatures or TLS sockets) to prevent impersonation. On a small LAN, one might skip this or use known username tokens.
- **Input Sanitization:** If supporting file transfer, validate filenames to prevent path traversal.
- **OS-Level:** Use the Windows Firewall to open only necessary ports (e.g. UDP discovery port, and chosen TCP port). Encourage users to whitelist the app.
- **Sandboxing:** As a learning project, these measures might be optional, but are important in a product.

Summary

This blueprint covers the end-to-end design of a Python-based LAN messenger for Windows. It starts from low-level protocols (ARP, UDP broadcast) and goes through system design, implementation modules, and deployment. Mermaid diagrams and code skeletons illustrate how components interact. Comparisons of libraries and architectures (with sources) guide choices. Finally, the networking knowledge ties directly into AWS concepts (VPCs, EC2 networking, etc.) [【40†L299-L308】](#) [【40†L354-L364】](#). By following this guide, one can build and understand a fully-featured LAN chat app while reinforcing core network and software engineering skills.

Sources: Official documentation and authoritative articles were used throughout (see citations). Notable references include the OneUptime blog on UDP discovery [【4†L179-L188】](#) [【6†L320-L327】](#) and ARP scanning [【13†L156-L164】](#) [【13†L264-L272】](#), a Medium overview of P2P vs client-server [【21†L113-](#)

L121】 【21†L184-L193】 , the LANMessenger project page 【23†L8-L13】 , the Python docs on GUI toolkits 【27†L57-L62】 , and performance analyses of serialization 【30†L141-L144】 . These ensure our design is grounded in best practices.
