

Red Hat Lightspeed 1-latest

Deploy and run Red Hat Lightspeed services on Google Cloud

Last Updated: 2026-09-28

Legal Notice

Copyright © Red Hat.

Except as otherwise noted below, the text of and illustrations in this documentation are licensed by Red Hat under the Creative Commons Attribution–Share Alike 3.0 Unported license . If you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, the Red Hat logo, JBoss, Hibernate, and RHCE are trademarks or registered trademarks of Red Hat, LLC. or its subsidiaries in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

XFS is a trademark or registered trademark of Hewlett Packard Enterprise Development LP or its subsidiaries in the United States and other countries.

The OpenStack ® Word Mark and OpenStack logo are trademarks or registered trademarks of the Linux Foundation, used under license.

All other trademarks are the property of their respective owners.

Abstract

Connect to Red Hat Lightspeed with Gemini Enterprise and enable natural language interaction with the advisor, inventory, vulnerability and planning services.

Table of Contents

CHAPTER 1. MANAGE RHEL INFRASTRUCTURE ON GOOGLE CLOUD BY USING THE AI AGENT 3
1.1. OVERVIEW OF THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD 3
1.1.1. How the Red Hat Lightspeed Agent for Google Cloud works 3
1.1.2. Technical architecture and security 3
1.1.3. Supported capabilities 3
1.1.4. User access requirements 4
1.2. SUBSCRIBE TO THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD 4
1.3. ADD THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD 5
1.4. ENABLE USER PERMISSIONS FOR THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD 5
1.5. USE THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD 6
1.6. ADDITIONAL RESOURCES 7

CHAPTER 1. MANAGE RHEL INFRASTRUCTURE ON GOOGLE CLOUD BY USING THE AI AGENT

Deploy and run the Red Hat Lightspeed Agent for Google Cloud to enable Red Hat Lightspeed capabilities to Google Cloud Platform resources.

1.1. OVERVIEW OF THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD

The Red Hat Lightspeed Agent for Google Cloud is an enterprise-ready tool designed specifically for Red Hat Enterprise Linux to help Site Reliability Engineers (SREs) and IT administrators manage their Red Hat infrastructure on Google Cloud by using natural language.

1.1.1. How the Red Hat Lightspeed Agent for Google Cloud works

The Red Hat Lightspeed Agent for Google Cloud acts as a secure wrapper around the MCP server for Red Hat Lightspeed, permitting you to access Red Hat tools directly from Gemini Enterprise without installing local clients or navigating to the Red Hat Hybrid Cloud Console.

1.1.2. Technical architecture and security

The agent is designed for high security and seamless cloud integration:

Google Cloud Run deployment

The agent runs on Google Cloud Run to provide automatic scaling and a secure, production-ready footprint.

A2A protocol compliance

The agent communicates using Google's Agent-to-Agent (A2A) protocol specification.

Secure authentication

The agent integrates with Red Hat Single Sign-On (SSO) using the OAuth 2.0 protocol to give access to only authorized users.

1.1.3. Supported capabilities

You can query and analyze your registered Red Hat Enterprise Linux systems by using several specialized capabilities:

Advisor Recommendations

Analyze system configurations to proactively catch potential issues before they affect your production environments.

Vulnerability Analysis


Query and prioritize CVE remediation according to real-time risk.

System Inventory

Track and manage registered RHEL systems via basic text commands.

Lifecycle Planning

Query upgrade paths, deprecations, and lifecycle dates for your infrastructure.



IMPORTANT

The Red Hat Lightspeed Agent for Google Cloud currently relies on a read-only MCP server for Red Hat Lightspeed. You can query configurations and plan remediations, but you cannot execute playbooks or run remediation tasks directly through the Gemini interface.

1.1.4. User access requirements

To use the agent, you must meet the following access criteria:

- You have an active Gemini Enterprise subscription.
- You have an active Red Hat subscription.
- You authenticate using valid Red Hat login credentials.

1.2. SUBSCRIBE TO THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD

To use the Red Hat Lightspeed Agent for Google Cloud, locate and subscribe to the agent from the Google Cloud Marketplace.

Prerequisites

- You have valid Google Cloud Console credentials.
- You are logged in to the Google Cloud Marketplace with administrator privileges.

Procedure

1. Navigate to the Google Cloud Marketplace.
2. Search for the **Red Hat Lightspeed Agent for Google Cloud** and select the product.
3. Click **Subscribe**.
4. Follow the on-screen prompts to choose the **Plan** and what time frame you want the **Feature** to last for.
5. Accept the **Additional terms**.
6. Click **Subscribe**.

Verification

1. Click **go to product page**.
2. Click **Go to the Gemini Enterprise**
3. Click **Manage Orders** under **Pricing**.
4. Verify that the **Red Hat Lightspeed Agent for Google Cloud** order status is displayed as **Active** and is ready to use.

1.3. ADD THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD

To add the Red Hat Lightspeed Agent for Google Cloud, add and configure the agent in Gemini Enterprise.

Prerequisites

- You are logged in to the Gemini Enterprise Red Hat Marketplace with administrator privileges.
- You have subscribed to the agent from the Google Cloud Marketplace.

Procedure

1. Open the Gemini Enterprise Red Hat Marketplace.
2. Select **Agents**.
3. Select **Add agent**.
4. Click **Add** under **Agents via Marketplace**.
5. Select the **Red Hat Lightspeed Agent for Google Cloud by Red Hat**
6. Click **Next** to review the agent details.
7. Click **Next**.
8. Select **Use dynamic client registration for generating credentials**under **Authenticate agent**.



NOTE

- The **Use dynamic client registration for generating credentials**is what prompts you to log in to Red Hat SSO for authentication.
- Do not select **Enter credentials manually** because that workflow is not supported.

9. Click **Finish** to complete the agent configuration.

Verification

- The message to say **Your agent was created successfully**is displayed.
- The **Agent state** will display as **Enabled** for the Red Hat Lightspeed Agent for Google Cloud under the **Display name** column.

1.4. ENABLE USER PERMISSIONS FOR THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD

To enable all or specific users to have access to the Red Hat Lightspeed Agent for Google Cloud.

Prerequisites

- You are logged in to the Gemini Enterprise Red Hat Marketplace with administrator privileges.

- You have subscribed to the agent from the Google Cloud Marketplace.
- You have added the Red Hat Lightspeed Agent for Google Cloud.

Procedure

1. Log in to the Gemini Enterprise Red Hat Marketplace.
2. Select **Red Hat Lightspeed Agent for Google Cloud** under the **Display name** column.
3. Select the **User permissions** tab and click **Add user**.
4. Choose **All users** to grant access to all users in your organization or list individual users.
5. Click the **Role** drop-down and then select **Agent User**.
6. Click **Save**.

1.5. USE THE RED HAT LIGHTSPEED AGENT FOR GOOGLE CLOUD

To start using the Red Hat Lightspeed Agent for Google Cloud, select the agent in your Gemini Enterprise interface and run natural language queries to verify registered infrastructure connectivity. Authorizing using your Red Hat Single Sign-On (SSO) provides access to your inventory.

Prerequisites

- The agent is deployed and secured using OAuth 2.0.
- An active Gemini Enterprise subscription is available.
- You have valid Red Hat login credentials.

Procedure

1. Log in to the Gemini Enterprise Red Hat Marketplace.
2. Navigate to **Overview** and click the webapp page displayed.
3. Select **Agents** and choose the **Red Hat Lightspeed Agent for Google Cloud**
4. To initiate the authentication process, enter the following natural language query in the **Chats** input field:

   > How many systems are connected to Red Hat Lightspeed?

5. Click **Submit**.
6. Click **Authorize** to grant the agent access to the information.
7. Enter your Red Hat Single Sign-On (SSO) **username** and click **Next**.
8. Enter your **Password**.
9. Click **Log in**, and a query result from the agent is displayed.

Verification

1. Verify the agent is working as expected by entering the following natural language query in the **Chats** input field:

   > List the tools available for managing my inventory

2. Verify that the agent successfully connects to the Red Hat Lightspeed Agent for Google Cloud service and returns a list of tools available for managing your inventory.

3. Enter the following query to test vulnerability analysis:

   > What is the most critical CVE affecting system *<system_name>*?

   Replace *<system_name>* with a hostname or ID of a registered system in your fleet.

4. Verify that the agent returns the correct, real-time risk assessment and CVE prioritization details.

1.6. ADDITIONAL RESOURCES

- Unlock enterprise-ready, secure AI with Red Hat Lightspeed Agent for Google Cloud