

Red Hat Lightspeed 1-latest

Assessing security vulnerabilities in your OpenShift cluster using Red Hat Lightspeed

Using Red Hat Lightspeed vulnerability to assess cluster exposure to CVE vulnerabilities

Last Updated: 2026-09-02

Red Hat Lightspeed 1-latest Assessing security vulnerabilities in your OpenShift cluster using Red Hat Lightspeed

Using Red Hat Lightspeed vulnerability to assess cluster exposure to CVE vulnerabilities

Legal Notice

Copyright © Red Hat.

Except as otherwise noted below, the text of and illustrations in this documentation are licensed by Red Hat under the Creative Commons Attribution–Share Alike 3.0 Unported license . If you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, the Red Hat logo, JBoss, Hibernate, and RHCE are trademarks or registered trademarks of Red Hat, LLC. or its subsidiaries in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

XFS is a trademark or registered trademark of Hewlett Packard Enterprise Development LP or its subsidiaries in the United States and other countries.

The OpenStack ® Word Mark and OpenStack logo are trademarks or registered trademarks of the Linux Foundation, used under license.

All other trademarks are the property of their respective owners.

Abstract

Table of Contents

CHAPTER 1. OVERVIEW OF RED HAT LIGHTSPEED VULNERABILITY SERVICE 3
1.1. VULNERABILITY SERVICE COVERAGE AND LIMITATIONS 3
1.2. REQUIREMENTS TO USE THE VULNERABILITY DASHBOARD 3
1.3. CVE ASSESSMENT IN RED HAT LIGHTSPEED 4
1.4. DATA COLLECTION AND SECURITY 4
1.5. CVE AND CLUSTER VIEWS IN THE VULNERABILITY DASHBOARD 5
1.6. DASHBOARD VIEW NAVIGATION 5
1.7. ASSESS VULNERABILITY IMPACT USING DASHBOARD FIELDS 5
1.8. ADDITIONAL RESOURCES 6

CHAPTER 2. ASSESS CRITICAL VULNERABILITIES BY REVIEWING CVES AND CLUSTERS 7
2.1. CVE LIST VIEW FIELDS AND DEFAULT FILTERS 7
2.2. VIEW AND ASSESS VULNERABILITIES DETECTED ON YOUR CLUSTERS 7
2.3. IDENTIFY CRITICAL CVES BY REFINING THE LIST VIEW 8
2.3.1. CVE details page 9
2.3.2. Search for a specific CVE to assess impact 10
2.3.3. Access CVE details to understand cluster exposure 11
2.3.4. Filter CVE results to focus on priority vulnerabilities 12
2.3.5. Prioritize CVEs for remediation by filtering by severity rating 14
2.4. ADDITIONAL RESOURCES 15

CHAPTER 3. ASSESS CLUSTER VULNERABILITIES TO PRIORITIZE REMEDIATION 16
3.1. CLUSTERS LIST VIEW FIELDS AND ANALYSIS TECHNIQUES 16
3.2. ASSESS EXPOSURE OF YOUR CLUSTERS TO CVES 16
3.3. FILTER CLUSTER RESULTS TO FOCUS YOUR ASSESSMENT 17
3.4. PRIORITIZE CLUSTERS FOR REMEDIATION BY FILTERING BY CVE SEVERITY RATING 18
3.4.1. CVE severity indicators 19
3.4.2. CVE severity filtering by context 20

CHAPTER 1. OVERVIEW OF RED HAT LIGHTSPEED VULNERABILITY SERVICE

The Vulnerability dashboard provides information about the exposure of your Red Hat Lightspeed cluster infrastructure to Common Vulnerabilities and Exposures (CVEs). CVEs are security exposures or flaws identified in publicly-released software packages.

1.1. VULNERABILITY SERVICE COVERAGE AND LIMITATIONS

Red Hat Lightspeed analyzes data about your clusters and images to assess CVE exposure, with coverage focused on OpenShift Container Platform container components and known images from catalog.redhat.com.

Red Hat Lightspeed analyzes data that the Insights Operator collects about your clusters, images, and CVEs. The analysis results show how vulnerable your OpenShift Container Platform clusters are to CVEs. You can view these results in the Vulnerability dashboard in the Red Hat Hybrid Cloud Console.

You can use the Vulnerability dashboard to assess and monitor the exposure of your clusters and images to CVEs. This information helps you understand and rank the risks to your organization. The Vulnerability dashboard provides CVE data for:

- Red Hat Lightspeed components of OpenShift Container Platform running as containers
- Images from catalog.redhat.com



IMPORTANT

Red Hat Lightspeed components of OpenShift Container Platform running as containers are supported in the Vulnerability dashboard, but the operating system running under the cluster is not supported. For example, operators are supported.



NOTE

The Vulnerability dashboard provides CVE information about workloads running on the cluster if the workload is a known image to catalog.redhat.com. The service does not provide CVE data about custom workloads (completely custom images or images using catalog.redhat.com images as a base).

1.2. REQUIREMENTS TO USE THE VULNERABILITY DASHBOARD

To view cluster vulnerability data in Red Hat Lightspeed, your OpenShift Container Platform clusters must be connected and active by registering to Red Hat OpenShift Cluster Manager with remote health monitoring enabled. Telemetry and Insights Operator data must have been sent within the past 30 days for clusters to appear in the Vulnerability dashboard.

Clusters are considered connected and active when they are registered to Red Hat OpenShift Cluster Manager and are sending telemetry data.

To access the Vulnerability dashboard, your Red Hat account must be registered to the same organization as your clusters. You must also be logged into the Red Hat Hybrid Cloud Console to access the dashboard.

Registering to OpenShift Cluster Manager enables remote health monitoring by default, allowing telemetry and Insights Operator data to be sent to the Vulnerability dashboard.

In some cases, your clusters might be disconnected or stop sending data. For example, a cluster in an air-gapped environment is a disconnected cluster. In this example, you might need to register or upload your data in a different way than using the OpenShift Cluster Manager web console.

The Vulnerability dashboard provides two views for assessing security vulnerabilities in your OpenShift Container Platform environment:

CVEs list view

Displays all CVEs affecting your clusters and images. This view shows CVE severity ratings, CVSS scores, publish dates, and the number of exposed clusters and images for each vulnerability.


Clusters list view

Displays all vulnerable clusters (also referred to as exposed clusters) in your organization. This view shows cluster names, connection status, versions, CVE severity levels, cloud providers, and when the cluster last sent data.



NOTE

You will see a list of your clusters if the Insights Operator has sent information within the past 30 days.



IMPORTANT


Red Hat Lightspeed does not determine whether any of your connected clusters have been exploited. The Vulnerability dashboard identifies CVEs that might pose a risk to clusters and images in your OpenShift Container Platform environment.

Additional resources

- About remote health monitoring
- Registering OpenShift Container Platform clusters to OpenShift Cluster Manager

1.3. CVE ASSESSMENT IN RED HAT LIGHTSPEED

Red Hat Lightspeed identifies Common Vulnerabilities and Exposures (CVEs) affecting your OpenShift Container Platform clusters and helps you assess their security impact. This visibility enables you to prioritize remediation efforts based on which vulnerabilities pose the greatest risk to your environment.



IMPORTANT

Only CVEs with Red Hat-issued security advisories (RHSAs) are included in the Red Hat Lightspeed vulnerability dashboard.

Additional resources

- What is a CVE?
- Explaining Red Hat Errata (RHSA, RHBA, and RHEA)
- CVE™ Program Mission at mitre.org

1.4. DATA COLLECTION AND SECURITY

Red Hat Lightspeed gives you visibility into your operating environments, helping to identify and address operational and vulnerability risks before an issue results in downtime.

To achieve this, small pieces of system metadata are sent to the Red Hat Lightspeed service for processing and analysis. Red Hat Lightspeed does not collect identifying information, such as user names, passwords, or certificates.

Additional resources

- Red Hat Lightspeed data & application security
- About remote health monitoring
- Showing data collected by remote health monitoring
- Disabling remote health reporting

1.5. CVE AND CLUSTER VIEWS IN THE VULNERABILITY DASHBOARD

Choose between CVE list view and Clusters list view depending on whether you need vulnerability-focused or cluster-focused analysis to prioritize remediation efforts.

The Red Hat Lightspeed Vulnerability dashboard provides two primary views for assessing security vulnerabilities:

CVEs list view

Your starting point for getting information about a CVE and assessing vulnerability exposure across your clusters.

Clusters list view

Your starting point for getting information about a cluster and identifying which clusters CVEs affect.

1.6. DASHBOARD VIEW NAVIGATION

Navigate from CVE and Cluster list views to detail views to find information about a specific vulnerability and affected resources.

From the CVE and Cluster list views, you can navigate to the following views for more detailed information:

- CVE details view
- Cluster details view



NOTE

The names of these views are not shown in the UI. Use them as a framework to help guide you through the Red Hat Lightspeed Vulnerability dashboard.

1.7. ASSESS VULNERABILITY IMPACT USING DASHBOARD FIELDS

Use key vulnerability metrics displayed in each dashboard view to prioritize remediation by severity, affected clusters, and exposure scope.

After you access CVEs and Clusters in the Red Hat Lightspeed Vulnerability dashboard, you can find additional details about exposed clusters and images. You can view, filter, and sort information while looking at CVEs and Clusters. Changing the way you view your results can help you assess and prioritize the next steps for addressing the exposure to your clusters.

The following information is available in each dashboard view to help you analyze your results:

CVE list view

CVE ID, Publish date, Severity, CVSS score, Exposed clusters, Exposed images

CVE details view

Name, Status, Version, Provider, Exposed images

Cluster list view

Name, Status, Version, CVEs severity, Provider

Cluster details view

CVE ID, Publish date, Severity, CVSS score, Exposed images

1.8. ADDITIONAL RESOURCES

- OpenShift Cluster Manager
- About remote health monitoring

CHAPTER 2. ASSESS CRITICAL VULNERABILITIES BY REVIEWING CVES AND CLUSTERS

Use the CVE list view to assess vulnerabilities affecting your OpenShift Container Platform clusters and prioritize remediation efforts. You can filter and sort CVEs by severity, publish date, or number of affected clusters to focus on the most critical security threats. Click a CVE ID to see details about which clusters are exposed.

2.1. CVE LIST VIEW FIELDS AND DEFAULT FILTERS

The CVE list view displays vulnerability information including CVE ID, publish date, severity, CVSS score, exposed cluster and exposed image counts. Default filters show CVEs affecting one or more clusters in your organization.

In the CVE list view, you can assess the CVEs impacting your clusters so that you can take the appropriate actions to protect your organization. You can also focus on a single CVE by clicking a CVE ID to see details about which clusters that CVE exposes.

The default CVE list view includes the following details:

CVE ID

Shows details about the CVE, CVE ID number

Publish date

Shows the date the CVE was published

Severity

Shows the severity rating (Critical, Important, Moderate, Low, or Unknown) of the CVE

CVSS base score

Shows the Common Vulnerability Scoring System (CVSS) base score (0-10)

Exposed clusters

Shows the number of clusters currently affected by a CVE

Exposed images

Shows the number of images deployed in your clusters that are currently affected by a CVE

From this view, you can filter and sort using these details to help you focus on the most critical CVEs affecting your clusters and images.



IMPORTANT

The default view of the CVE list page shows a default filter selection of (**Exposed clusters** with **1 or More clusters**). The default filters show you CVEs that affect one or more clusters in your organization. To find all CVEs, including those that do not affect any clusters reported by Red Hat Lightspeed, you can click the **X** beside the filters to remove the filter.

Filters are persistent throughout your session in the Red Hat Hybrid Cloud Console.

2.2. VIEW AND ASSESS VULNERABILITIES DETECTED ON YOUR CLUSTERS

Use the CVE list view in the Vulnerability dashboard to review severity ratings and exposure counts, assess risk, and prioritize remediation for your OpenShift Container Platform clusters.

Prerequisites

- Your Red Hat account and your cluster are registered to the same organization.
- You have logged into the Red Hat Hybrid Cloud Console.
- Your cluster has been registered to Red Hat OpenShift Cluster Manager. For more information about registering clusters, see Registering OpenShift Container Platform clusters to OpenShift Cluster Manager.
- Your cluster must have sent data through Telemetry and the Insights Operator within the past 30 days. For more information about Telemetry and the Insights Operator, see About remote health monitoring.



NOTE

When the message "No CVEs found" displays, this means that Red Hat Lightspeed has not found any CVEs affecting your Red Hat Lightspeed infrastructure.

Procedure

1. Navigate to **OpenShift → Vulnerability Dashboard → CVEs** to view the CVEs that affect your clusters and images.
2. Verify the CVE list displays showing CVE IDs, severity ratings, and exposure counts.

Additional resources

- Identify critical CVEs by refining the list view
- Filter CVE results to focus on priority vulnerabilities
- About remote health monitoring

2.3. IDENTIFY CRITICAL CVES BY REFINING THE LIST VIEW

The CVE list view provides search, filter, and sort capabilities to help you focus on the most critical vulnerabilities affecting your OpenShift Container Platform clusters. Understanding these techniques helps you prioritize remediation based on severity, publish date, and cluster exposure.

Use the following techniques to refine CVE list view results:

Search

Locate specific CVEs by ID or description keywords

Filter

Narrow results by severity, publish date, CVSS score, or cluster exposure

Sort

Order results by clicking the sort arrow next to any column heading

Using these techniques in combination allows you to quickly identify the highest-priority vulnerabilities. For example, you might filter for Critical severity CVEs published in the last 30 days, then sort by exposed cluster count to see which vulnerabilities affect the most systems.

Additional resources

- Search for a specific CVE to assess impact
- Access CVE details to understand cluster exposure
- Filter CVE results to focus on priority vulnerabilities
- Prioritize CVEs for remediation by filtering by severity

2.3.1. CVE details page

The CVE details view displays vulnerability information, affected clusters, and exposed container images across three sections. Understanding these fields helps you assess CVE impact and prioritize remediation actions.

CVE information section

The CVE details page displays the following information about the vulnerability:

CVE ID
: The Common Vulnerabilities and Exposures identifier

Publish date
: The date the CVE was published

Description
: A detailed explanation of the vulnerability

Severity
: The severity rating (Critical, Important, Moderate, or Low)

CVSS base score
: The Common Vulnerability Scoring System score (0-10)

Exposed clusters tab

The **Exposed clusters** tab is selected by default and shows which clusters are affected by the CVE. The table displays:

Name
: The cluster name

Status
: The connection status of the cluster

Type
: The type of cluster

Version
: The OpenShift Container Platform version running on the cluster

Provider
: The cloud provider hosting the cluster (such as AWS)

Last seen

How long ago (in minutes, hours, or days) information was last uploaded from the cluster to the Red Hat Lightspeed vulnerability service

Exposed images tab

The **Exposed images** tab shows container images affected by the CVE. The table displays:

Name

The image name

Registry name

The registry where the image is stored

Version

The registry version

Clusters

The number of clusters running this vulnerable image. Clicking the number shows which clusters contain the image.

Additional resources

- Access CVE details to understand cluster exposure

2.3.2. Search for a specific CVE to assess impact

Search for specific CVEs in the CVE list view to quickly locate vulnerability details and assess their impact on your clusters.


Prerequisites

- Your Red Hat account and your cluster are registered to the same organization.
- You have logged into the Red Hat Hybrid Cloud Console.
- Your cluster has been registered to Red Hat OpenShift Cluster Manager. For more information about registering clusters, see Registering OpenShift Container Platform clusters to OpenShift Cluster Manager.
- Your cluster must have sent data through telemetry and the Insights Operator within the past 30 days. For more information about Telemetry and the Insights Operator, see About remote health monitoring.

Procedure

1. Navigate to **OpenShift → Vulnerability Dashboard → CVEs**.
2. Select **CVE** in the filter drop-down list.
3. Enter the CVE ID you want information about into the search field, for example, *CVE-2022-2526*.
4. Wait for the search results to populate or press Enter. You will see a list of CVE IDs that match what you entered in the search box. For this example, two CVEs (2022-2526 and 2022-25265) match because both contain numbers from the search. The search results also show you

information about the **Publish date**, **Severity**, **CVSS base score**, **Exposed clusters**, and **Exposed images** related to the CVE.



5. Click the CVE ID to get more details about the CVE. You will see details about the CVE. A list of clusters affected by the CVE is displayed by default in the **Exposed cluster** tab.

6. Optional: Click the **Exposed images** tab to see information about images affected by the CVE.

Verification

- In the search results, verify that the CVE you searched for is displayed in the list.

Additional resources

- Access CVE details to understand cluster exposure
- Prioritize CVEs for remediation by filtering by severity rating
- Red Hat CVE database


2.3.3. Access CVE details to understand cluster exposure

Access detailed information about specific CVEs to understand their impact on your OpenShift Container Platform clusters. The CVE details view shows severity ratings, affected clusters, and exposed container images, helping you assess risk and prioritize remediation.

Prerequisites

- Your Red Hat account and your cluster are registered to the same organization.
- You have logged into the Red Hat Hybrid Cloud Console.
- Your cluster has been registered to Red Hat OpenShift Cluster Manager. For more information about registering clusters, see Registering OpenShift Container Platform clusters to OpenShift Cluster Manager.

- Your cluster must have sent data through telemetry and the Insights Operator within the past 30 days. For more information about Telemetry and the Insights Operator, see About remote health monitoring.




NOTE

If your clusters are not affected by the CVE, you will see the message: "No matching clusters found."

Procedure

1. Navigate to **OpenShift → Vulnerability Dashboard → CVEs**.
2. Review the resulting list and find a CVE ID of interest (for example, 2022-2526).
3. Click the **CVE ID** to find additional details about the CVE.



Verification

- In the CVE details page, verify the CVE information displays including severity, CVSS score, and the Exposed clusters table.

Additional resources

- Official CVSS documentation
- Red Hat Product Security

2.3.4. Filter CVE results to focus on priority vulnerabilities

Apply filters to the CVE list view to focus on specific vulnerabilities by severity, publish date, or affected clusters. Filtering helps you prioritize remediation efforts by narrowing results to the CVEs that pose the greatest risk to your environment.

In the CVE list view, you can apply filters to focus on specific information. For example, filter by CVE severity level or Red Hat Lightspeed version. After selecting an individual CVE, you can apply primary and secondary filters to the resulting list of clusters.

The filters and options that you can apply are:

- **CVE ID**: Filter by ID or description.

- **Publish date**: Select from All, Last 7 days, Last 30 days, Last 90 days, Last year, or More than 1 year ago.
- **Severity**: Select one or more values: Critical, Important, Moderate, Low, or Unknown.
- **CVSS base score**: Enter a range from 0-10.
- **Exposed clusters**: Select to only show CVEs with clusters currently affected, or with no clusters affected.

Prerequisites

- Your Red Hat account and your cluster are registered to the same organization.
- You have logged into the Red Hat Hybrid Cloud Console.
- Your cluster has been registered to Red Hat OpenShift Cluster Manager. For more information about registering clusters, see Registering OpenShift Container Platform clusters to OpenShift Cluster Manager.
- Your cluster must have sent data through telemetry and the Insights Operator within the past 30 days. For more information about Telemetry and the Insights Operator, see About remote health monitoring.



NOTE

Your currently selected filters are visible to help you keep track of what you are filtering.

If the last action results in a message indicating "No matching CVEs found," this means your clusters are not affected by any CVEs.




IMPORTANT

Filters remain active until you remove them or leave the Red Hat Lightspeed session. Reset or remove unneeded filters to avoid unintended results. To deactivate filters, click the **X** next to each filter (or any default filters) you selected, as needed.

Procedure

1. Navigate to **OpenShift → Vulnerability Dashboard → CVEs**. The default view of the CVE list view shows a default filter selection of **1 or More clusters**.
2. Select a primary filter (for example, **Publish date**) from the drop-down list of filters.
3. Select a secondary filter from the drop-down list of filters. For this example, select **Last 30 days** from the **Filter by publish date** drop-down arrow.
4. Confirm your filter selection, and then review the resulting information. The following screen capture shows an example of CVEs from the last 30 days.



Verification

- In the CVE list, verify that only CVEs matching your filter criteria are displayed.

Additional resources

- Prioritize CVEs for remediation by filtering by severity rating
- Search for a specific CVE to assess impact
- Official CVSS documentation

2.3.5. Prioritize CVEs for remediation by filtering by severity rating

Filter CVEs by severity level to prioritize remediation by focusing on Critical and Important vulnerabilities that pose the greatest risk to your OpenShift Container Platform clusters.

Prerequisites

- Your Red Hat account and your cluster are registered to the same organization.
- You have logged into the Red Hat Hybrid Cloud Console.
- Your cluster has been registered to Red Hat OpenShift Cluster Manager. For more information about registering clusters, see Registering OpenShift Container Platform clusters to OpenShift Cluster Manager.
- Your cluster must have sent data through telemetry and the Insights Operator within the past 30 days. For more information about Telemetry and the Insights Operator, see About remote health monitoring.

Procedure

1. Navigate to **OpenShift → Vulnerability Dashboard → CVEs**.
2. Click the drop-down filter list.

3. Select **Severity**.
4. Click the drop-down arrow in the **Filter by Severity** field.
5. Select a filter (for example, **Critical**) to display all CVEs with that severity rating.
6. Click the CVE ID to get additional information.

Verification

- In the CVE list, verify that only CVEs at your selected severity level are displayed.

Additional resources

- Access CVE details to understand cluster exposure
- CVE severity indicators
- Red Hat security severity ratings

2.4. ADDITIONAL RESOURCES

- Severity Ratings
- Official CVSS documentation

CHAPTER 3. ASSESS CLUSTER VULNERABILITIES TO PRIORITIZE REMEDIATION

View and analyze vulnerable clusters (also referred to as exposed clusters) in the Red Hat Lightspeed Vulnerability dashboard. The dashboard helps you assess which OpenShift Container Platform clusters are affected by CVEs and prioritize remediation based on severity, version, and provider.

3.1. CLUSTERS LIST VIEW FIELDS AND ANALYSIS TECHNIQUES

The Clusters list view displays key information about vulnerable clusters including name, status, version, CVE severity, provider, and last data upload. You can filter and sort these fields to focus your analysis.

The following information is in the Clusters list:

Name

Shows the name of a vulnerable cluster that is affected by a CVE.

Status

Shows the connection status (Connected, Stale, Unknown, Active) of a cluster.

Version

Shows the Red Hat OpenShift Container Platform version (4.8+) of a cluster.

CVEs severity

Shows the severity level (Critical, Important, Moderate, Low) of the CVEs affecting the cluster.

Provider

Shows the name of the cluster's cloud provider.

Last seen

Shows the last time (in the form of minutes, hours, or days) since information was last uploaded from the cluster to the Red Hat Lightspeed service.

You can use the following techniques to analyze cluster data:

Filter

Narrow results by severity, version, provider, or status

Sort

Order results by clicking any column heading (Name, Status, Version, CVEs severity, Provider, Last seen)

3.2. ASSESS EXPOSURE OF YOUR CLUSTERS TO CVES

To assess which OpenShift Container Platform clusters are affected by CVEs, use the Clusters list view. You can sort and filter vulnerability data to focus on the clusters that require immediate attention.

Prerequisites

- Your Red Hat account and your cluster are registered to the same organization.
- You have logged into the Red Hat Hybrid Cloud Console.

- Your cluster has been registered to Red Hat OpenShift Cluster Manager. For more information about registering clusters, see Registering OpenShift Container Platform clusters to OpenShift Cluster Manager.
- Your cluster must have sent data through telemetry and the Insights Operator within the past 30 days. For more information about Telemetry and the Insights Operator, see About remote health monitoring.

Procedure

1. Navigate to **OpenShift → Vulnerability Dashboard → Clusters** to view clusters reporting CVE data.
2. Verify that the Clusters list displays cluster names, CVE severity ratings, and connection status.

Additional resources

- Filter cluster results to focus your assessment
- Prioritize clusters for remediation by filtering by CVE severity rating
- About remote health monitoring

3.3. FILTER CLUSTER RESULTS TO FOCUS YOUR ASSESSMENT

Apply filters to the Clusters list view to focus on specific vulnerability criteria such as CVE severity, cluster version, or cloud provider. Filtering helps you prioritize remediation by identifying clusters with the most critical security issues.

In the Clusters list view, apply filters to focus on specific information. For example, filter by cluster name (or UUID), CVE severity level, or cluster version. After selecting an individual cluster, you can apply filters to the resulting list of CVEs affecting that cluster.

The options for filtering in the Clusters list view are:

- **Name**: Filters on the name of a vulnerable cluster that is affected by a CVE.
- **Status**: Filters on the connection status (Connected, Disconnected, Stale, Unknown, Active) of a cluster.
- **Version**: Filters on the version (Red Hat OpenShift Container Platform 4.8+) of a cluster.
- **CVEs severity**: Filters on the severity level (All clusters, Critical, Important, Moderate, Low) of the security-related issue and the number of images affected in the cluster.
- **Provider**: Filters on the name of the cluster's cloud provider.

Prerequisites

- Your Red Hat account and your cluster are registered to the same organization.
- You have logged into the Red Hat Hybrid Cloud Console.
- Your cluster has been registered to Red Hat OpenShift Cluster Manager. For more information about registering clusters, see Registering OpenShift Container Platform clusters to OpenShift Cluster Manager.

- Your cluster must have sent data through telemetry and the Insights Operator within the past 30 days. For more information about Telemetry and the Insights Operator, see About remote health monitoring.



IMPORTANT

The default view is *All clusters* which shows all clusters, even those not vulnerable to any CVE. Remove this filter if you want to only show clusters that are affected by at least one CVE reported by Red Hat Lightspeed.

Filters remain active until you remove them or leave a Red Hat Lightspeed session. Reset or remove unneeded filters to avoid unintended results. To deactivate filters, click the **X** next to each filter (or any default filters) that you selected.

Procedure

1. Navigate to **OpenShift → Vulnerability Dashboard → Clusters**.
2. Select a primary filter (for example, **CVEs severity)** from the drop-down list of filters.
3. Select the secondary filter (for example, **Filter by CVEs severity**).
4. Select a severity rating (for example, **Critical**). The selected filters appear below the filter selection menu.
5. Review the resulting information. Clusters vulnerable to CVEs with a severity level of Critical show first in the list.

Verification

- In the Clusters list, verify only clusters matching your filter criteria are displayed.

3.4. PRIORITIZE CLUSTERS FOR REMEDIATION BY FILTERING BY CVE SEVERITY RATING

Filter clusters by CVE severity ratings to prioritize remediation efforts and focus on clusters with the most critical security vulnerabilities.

Red Hat applies severity ratings to CVEs by using a four-point scale of *Critical*, *Important*, *Moderate*, and *Low*. You can filter the CVEs, starting with the most critical, to help you begin to take actions to protect your organization.

In Red Hat Lightspeed, you can use the CVEs Severity filter to show clusters affected by CVEs with ratings of Critical, Important, Moderate, or Low. The default filter, **All clusters**, shows both vulnerable clusters with their CVE severity ratings and clusters not vulnerable to CVEs.

Prerequisites

- Your Red Hat account and your cluster are registered to the same organization.
- You have logged into the Red Hat Hybrid Cloud Console.

- Your cluster has been registered to Red Hat OpenShift Cluster Manager. For more information about registering clusters, see Registering OpenShift Container Platform clusters to OpenShift Cluster Manager.
- Your cluster must have sent data through telemetry and the Insights Operator within the past 30 days. For more information about Telemetry and the Insights Operator, see About remote health monitoring.

Procedure

1. Navigate to **OpenShift → Vulnerability Dashboard → Clusters**.
2. Click the drop-down filter list.
3. Select the **CVEs severity** primary filter.
4. Click the **Filter by CVEs severity** secondary filter.
5. Clear **All clusters**.
6. Select a severity level, for example, select **Critical**. You will see a list of clusters that have CVEs rated with the severity level of the option you selected.
7. Optional: To obtain more information about the CVEs that potentially affect that cluster, click any of the clusters shown in the **Name** column.
8. Optional: To see exposed images in the cluster, click the **Exposed images** tab.

Verification


- In the Clusters table, verify that only clusters affected by CVEs at your selected severity level are displayed.

Additional resources

- CVE severity filtering by context
- CVE severity indicators
- Red Hat security severity ratings

3.4.1. CVE severity indicators

CVE severity indicators use color-coded icons to show vulnerability severity from Critical to Low. This visual ranking helps you prioritize remediation by identifying which clusters have the most critical security issues requiring immediate attention.




Additional resources

- Severity Ratings: Understanding Red Hat security ratings


3.4.2. CVE severity filtering by context

CVE severity filtering in the Clusters view displays results by context, showing higher-severity vulnerabilities alongside your filtered selection. This context-aware approach helps you understand the full security posture of each cluster while focusing on specific severity levels.




For example, suppose you change the filter to *Important*. In the preceding example dashboard, the top cluster has 26 CVEs with a severity level of Important. You can also see the additional CVEs affecting the cluster and their severity levels.

The Critical CVEs are still filtered by the severity level of Important. The filter takes into account the importance of the Critical severity. It shows CVEs rated as Important along with Critical CVEs, as shown in the following image:



In this same filter session, results show a cluster with zero CVEs with a **Critical** severity rating. The cluster has 32 CVEs with a severity level of **Important**, as shown in the following image.



Filtering in this context helps you see the most important information first.