We thank all five reviewers for their careful reading and are encouraged that they find the work worthwhile — "sensible" (27Jx), "important"/"promising" (D8hx), and "a fair and interesting contribution" with "compelling" matched-setting results (wGgF). We take the presentation problems seriously and have completed a full language and formatting revision, verifying that no model, experiment, or reported result is affected by these edits.

Reviewer 27Jx (#1)—R1-1: Presentation. We sincerely apologize for the draft-stage errors, and we are very grateful for the reviewer's careful reading. We have carried out a thorough revision: resolved the dangling "Figure ??" to Fig. 1 (Sec. 3.2), corrected the flagged typos ("multi-granul"→"multi-granular", "Constrion"→"Construction", "Fame-level"→"Frame-level"), re-rendered Figs. 1–2 as vector graphics, and made a careful, line-by-line language pass over the entire manuscript. These were purely presentation issues, not substantive ones; no result, number, or claim was affected.

R1-2: Distinction from Vgent. We thank the reviewer. The distinction is paradigmatic and does not hinge on any single layer. Vgent is a *fixed* retrieve-then-read graph-RAG over frame and segment local relations. In contrast, our contribution is twofold: we build a multi-level scene-graph index over long video, and we design a modular, plug-and-play adaptive agent that uses the scene graph as its primary retrieval index, verifying each proposal against raw frames before answering (R2-3). Together they drive the +18.2-pp matched-setting gain on LVBench (54.8%→73.0%). We address the event layer's specific role, and its accuracy contribution, in R1-3.

R1-3: The role of the event graph. We agree with the observation. At a fixed backbone the event layer's measurable effect is efficiency: it cuts LLM and frame-inspection calls by 71.5% and 74.7% at unchanged accuracy (64.6%→64.4%). We read this as a capability gain, not a void: reaching the same answers with far less search is itself better reasoning. Still, efficiency need not carry the contribution alone. The flat accuracy reflects the conservative event-graph construction of the submitted version, not an intrinsic ceiling. In an additional experiment that strengthens the construction and queries the index *caption-free*, the agent reaches **68.5%** e2e accuracy on LVBench, a 3.9-pp gain over the segment-only version and a 13.7-pp gain over the caption-only baseline. A graph that answers 68.5% of questions with *no* captions is an answer-bearing reasoning substrate, so the distinction does *not* collapse. The same structured index lets the lighter `o4-mini` reach 73.0%, matching DVD's far stronger `o3` (74.2%) and beating DVD's own `o4-mini` (70.2%). Our continued experiments improve these results further; we will report fair, matched comparisons in the camera-ready.

Reviewer D8hx (#2)—R2-1: Offline construction cost. For all 103 LVBench videos (115.5h), construction costs $112.74 (12,360 `gpt-4.1` frame-graph calls at one keyframe per 5s, ≤120/video; 7.94h on four workers; the symbolic Stage 3 event build adds only 121s), i.e. $0.98 per video-hour. We reuse DVD's open-sourced captions rather than generating our own, so this is our only added offline cost. End-to-end VQA over all 1549 questions costs $279.54 (`o4-mini`) and $499.31 (`o3`), so this one-time construction is only 40% and 23% of the recurring online budget it serves.

R2-2: Cross-benchmark control. We agree not all entries are controlled. On LVBench the DVD comparison *is* fully controlled: the same `o3` backbone, DVD's own open-sourced captions, and the same video database. On the other three, DVD released no full reproduction setup, so we cannot match its pipeline; we still use its captions and report these as best-effort positions. Other commercial and open models have closed weights or fixed pipelines, so they are reference positions only. Our claims therefore rest on the fully controlled LVBench comparison and its matched-setting ablations.

R2-3: Direct graph quality. Direct evaluation is desirable, but intrinsic scene-graph metrics need a gold-annotated benchmark that does not exist at hour scale, and they would still miss what matters: extraction accuracy and the graph's net effect on answers. Comparable systems, DVD included, are judged the same way, not by intrinsic quality. We therefore measure the graph through the task: the caption-free graph-only setting is cleanest, since with captions removed the answer must come from the graph, yet accuracy holds at 68.5% on LVBench (R1-3), and the matched ablations isolate its gain. We will still add a small human-verified sample for entity and relation precision; the pipeline already shows 76.8% entity-mention absorption and a 5.0% invalid-relation rate. Propose–verify re-inspection of the raw frames further reduces how much frame-level error propagates into the event graph.

R2-4: Implementation details. To give the values asked for: entity alignment scores name, description, and type similarity with weights 0.7, 0.2, and 0.1, and merges above a threshold of 0.78; the entity blacklist removes artefacts and over-generic terms; segments merge into events at a 12s temporal gap with relation-overlap thresholds. The composite retrieval score and all remaining thresholds are fully specified in the appendix, which gives the alignment, gating, and event-construction algorithms; we will release a fully reproducible repository for the camera-ready.

R2-5: Presentation. Thanks; see R1-1.

R2-6: Isolating localization from FTT. Our reported answered accuracy (ans_acc) separates the two: the caption-only baseline scores 65.7% and SGDAgent 74.2% (+8.5 pp), independent of the answer rate, while the FTT drop (16.5%→1.6%) is itself a consequence of structured retrieval converging where open caption search loops for lack of locatable evidence.

Reviewer k56s (#3)—R3-1: Baseline data citation. Thank you for catching this. The correct DVD values are Video-MME 67.3 (we had mis-copied DVD's LongVideoBench(Long) entry, 68.6) and EgoSchema 76.6, both matching DVD's published numbers. The correction in fact widens our Video-MME margin to 69.0 vs. 67.3. We will present a carefully re-verified version, with a more general Fig. 1 example, in the camera-ready.

R3-2: Related works. Thank you; we will cite and discuss all three ([1] Mind Palace, [2] the Gaussian-token work, [3] GraphVideoAgent) in the camera-ready. They use the graph as an in-context representation or online entity memory, whereas we use it as the agent's primary retrieval index, gated to raw-frame verification before answering (see R1-2), a distinct design.

R3-3: Offline construction cost. Thanks; see R2-1.

R3-4: Error propagation & robustness. Two mechanisms limit it. First, propose–verify gates every graph hit to raw-frame re-inspection before answering (R2-3), so a hallucinated or mis-aligned node is caught at verification rather than read out as an answer, reducing upward propagation. Second, the caption-free graph-only system still reaches 68.5% (R1-3), evidence that the pipeline tolerates imperfect frame-level extraction. To quantify this we will add a robustness analysis that perturbs frame-graph quality and reports the accuracy sensitivity, and we will discuss [4].

Reviewer SSkz (#4)—R4-1: Over-strong coverage claim. We agree, and will revise the wording: the method improves *localization within the sampled frames*, and we will no longer claim to address incomplete sampling coverage, since the graph itself is built only from sparsely sampled keyframes.

R4-2: The role of the event graph. In the submitted table the event graph is not a fixed-backbone accuracy driver, and we present it as a higher-order layer that reduces the agent's search burden. A strengthened, caption-free run, however, shows it also carries accuracy, not only efficiency (see R1-3).

R4-3: Heuristic construction. For robustness see R2-3; we now fully specify the alignment, merging, and event thresholds (see R2-4).

R4-4: Presentation. See R1-1; we have already re-rendered Figures.

R4-5: Questions. Scene-graph accuracy: see R2-3. Repositioning the event graph as an efficiency layer: it does reduce search burden, but a strengthened caption-free run shows it is also accuracy-bearing (see R1-3). Full pipeline cost per video: see R2-1. Sampling interval: we currently sample one frame every 5s and will report 2s/5s/10s sensitivity in the revision.

Reviewer wGgF (#5)—R5-1: HIG & hierarchy novelty. Thank you; we agree HIG proposes a hierarchical video graph, and we will cite and contrast it. We will not claim the hierarchy concept as novel. Our work differs in task: HIG targets video scene-graph *generation*, whereas we use a graph index to *drive an adaptive agent* for long-video QA (see R1-2).

R5-2: Implementation details. The alignment, retrieval, gating, controller-signal, and event-construction rules are all specified operationally in the appendix as pseudocode; see R2-4 for the headline values.

R5-3: Graph-depth ablation. See R1-3: the segment graph drives fixed-backbone accuracy; the event graph reduces search burden and, under a stronger construction, also contributes accuracy (caption-free 68.5%).

R5-4: Efficiency evidence. Beyond online call counts we now also report dollar cost and construction time (see R2-1).

R5-5: Presentation. Thanks; see R1-1.