

# Working with Missing Data: Takeaways

by Dataquest Labs, Inc. - All rights reserved © 2019

## Syntax

- Replacing matching values with a single value:

```
s.mask(s == var, value_to_replace)
```

- Replacing matching values with corresponding values from a series:

```
s1.mask(s == var, series_to_replace)
```

- A function to create a null matrix

```
def plot_null_matrix(df, figsize=(18,15)):
    # initiate the figure
    plt.figure(figsize=figsize)

    # create a boolean dataframe based on whether values are null
    df_null = df.isnull()

    # create a heatmap of the boolean dataframe
    sns.heatmap(~df_null, cbar=False, yticklabels=False)

    plt.show()
```

- A function to create a null correlation heatmap

```
def plot_null_correlations(df):
    # create a correlation matrix only for columns with at least
    # one missing value
    cols_with_missing_vals = df.columns[df.isnull().sum() > 0]
    missing_corr = df[cols_with_missing_vals].isnull().corr()

    # create a triangular mask to avoid repeated values and make
    # the plot easier to read
    missing_corr = missing_corr.iloc[1:, :-1]
    mask = np.triu(np.ones_like(missing_corr), k=1)

    # plot a heatmap of the values
    plt.figure(figsize=(20,12))

    ax = sns.heatmap(missing_corr, vmin=-1, vmax=1,
                     cmap='RdBu', mask=mask, annot=True)

    # round the labels and hide labels for values near zero
    for text in ax.texts:
        t = float(text.get_text())
        if -0.05 < t < 0.01:
            text.set_text('')
```

## Concepts

```
else:  
    text.set_text(round(t, 2))  
  
plt.show()
```

- Imputation is the process of replacing missing values with other values.
- Imputing can be a better option than simply dropping values because you retain more of your original data.
- You might find values for imputation by:
  - Deriving the value from related columns.
  - Using the most common non-null value from a column.
  - Using a placeholder for missing values.
  - Augmenting factual data (e.g. location data) using an external resource.
- Using plots can help identify patterns in missing values which can help with imputation.

## Resources

- [pandas documentation](#)



Takeaways by Dataquest Labs, Inc. - All rights reserved © 2019