

```
In [1]: import matplotlib.pyplot as plt
from itertools import product
import numpy as np
from collections import Counter
from sklearn.base import BaseEstimator, RegressorMixin, ClassifierMixin
from sklearn.tree import DecisionTreeClassifier, DecisionTreeRegressor, export
from sklearn.ensemble import GradientBoostingClassifier, GradientBoostingRegressor
import graphviz

from IPython.display import Image

%matplotlib inline
```

Load Data

```
In [2]: data_train = np.loadtxt('svm-train.txt')
data_test = np.loadtxt('svm-test.txt')
x_train, y_train = data_train[:, 0: 2], data_train[:, 2].reshape(-1, 1)
x_test, y_test = data_test[:, 0: 2], data_test[:, 2].reshape(-1, 1)
```

```
In [3]: # Change target to 0-1 label
y_train_label = np.array(list(map(lambda x: 1 if x > 0 else 0, y_train))).res
```

Decision Tree Class

Problem 1

In [4]:

```

def compute_entropy(label_array):
    """
    Calculate the entropy of given label list

    :param label_array: a numpy array of binary labels shape = (n, 1)
    :return entropy: entropy value
    """
    # Your code goes here
    #Only considering binary classification
    entropy = 0 #Initialize entropy
    prob_one = label_array.sum() / len(label_array) #Calculate the probability
    prob_array = [1-prob_one,prob_one] #Likewise for class = 0

    #Make sure we don't bug out trying to take log_2(0)
    if prob_one == 0 or prob_one == 1:
        return 0

    #Calculate entropy sum(-log_2(prob)*prob)
    for i in [0,1]:
        entropy -= np.log2(prob_array[i]) * prob_array[i]

    #Return entropy
    return entropy

def compute_gini(label_array):
    """
    Calculate the gini index of label list

    :param label_array: a numpy array of labels shape = (n, 1)
    :return gini: gini index value
    """
    #Only considering binary classification
    gini = 0 #Initialize gini index
    prob_one = label_array.sum() / len(label_array) #Calculate the probability
    prob_array = [1-prob_one,prob_one] #Likewise for class = 0

    #Calculate gini index -> sum(prob_class(1-prob_class))
    for i in [0,1]:
        gini += prob_array[i]*(1-prob_array[i])
    return gini #Return gini index

```

Problem 2

In [5]:

```

class Decision_Tree(BaseEstimator):

    def __init__(self, split_loss_function, leaf_value_estimator,
                  depth=0, min_sample=5, max_depth=10):
        """
        Initialize the decision tree classifier

```

```

:param split_loss_function: method with args (X, y) returning loss
:param leaf_value_estimator: method for estimating leaf value from array
:param depth: depth indicator, default value is 0, representing root
:param min_sample: an internal node can be splitted only if it contains at least min_sample samples
:param max_depth: restriction of tree depth.
'''

self.split_loss_function = split_loss_function
self.leaf_value_estimator = leaf_value_estimator
self.depth = depth
self.min_sample = min_sample
self.max_depth = max_depth
self.is_leaf = False

#Add these variables to the constructor
self.right = None #Left child node
self.left = None #Right child node
self.split_id = None #Best column to split on
self.split_value = None #Best value to split on within best column
self.value = None #Value to return if leaf

def fit(self, x, y):
    '''
    This should fit the tree classifier by setting the values self.is_leaf,
    self.split_id (the index of the feature we want to split on, if we're not a leaf),
    self.split_value (the corresponding value of that feature where the split occurs),
    and self.value, which is the prediction value if the tree is a leaf node.
    When splitting the node, we should also init self.left and self.right to be
    objects corresponding to the left and right subtrees. These subtrees
    will contain the data that fall to the left and right, respectively, of self.split_id.
    This is a recursive tree building procedure.

    :param X: a numpy array of training data, shape = (n, m)
    :param y: a numpy array of labels, shape = (n, 1)

    :return self
    '''
    # Your code goes here

    #Check break condition, if we've exceeded max depth or are less than min_sample
    if self.depth >= self.max_depth or len(y) <= self.min_sample:
        self.is_leaf = True
        self.value = self.leaf_value_estimator(y)

        # If the majority class is 0
        if y.sum() / len(y) <= .5:
            self.value = 0
        else:
            self.value = 1

    else:
        #Calculate best splitting point
        self.find_best_feature_split(x,y)
        #Split data in two depending on criteria

```

```

all_data = np.append(x,y,axis=1) #Create one big matrix (easier to
#Filter data by split column / split point
left_data = all_data[all_data[:,self.split_id]<=self.split_value]
#Again but look for greater for right tree
right_data = all_data[all_data[:,self.split_id]>self.split_value]
left_x_node = left_data[:,0:-1]
left_y_node = left_data[:, -1].reshape(-1,1)
right_x_node = right_data[:,0:-1]
right_y_node = right_data[:, -1].reshape(-1,1)

#Create left and right nodes
self.left = Decision_Tree(self.split_loss_function, #Pass split f
                           self.leaf_value_estimator, #Pass leaf_va
                           depth=self.depth+1,        #Pass self.de
                           min_sample = self.min_sample, #Pass min
                           max_depth = self.max_depth
                           )
self.right = Decision_Tree(self.split_loss_function, #Pass split
                           self.leaf_value_estimator, #Pass leaf_va
                           depth=self.depth+1,        #Pass self.de
                           min_sample = self.min_sample, #Pass min
                           max_depth = self.max_depth
                           )

#Fit the left/right nodes
self.left.fit(left_x_node,left_y_node)
self.right.fit(right_x_node,right_y_node)

return self

def find_best_split(self, x_node, y_node, feature_id):
    """
    For feature number feature_id, returns the optimal splitting point
    for data X_node, y_node, and corresponding loss
    :param X: a numpy array of training data, shape = (n_node)
    :param y: a numpy array of labels, shape = (n_node, 1)
    """
    # Your code
    #x_copy = x_node.copy()
    y_copy = y_node.copy()
    feature_vals = x_node[:,feature_id].copy() #Grab the feature vals
    sorting = feature_vals.argsort() #Prepare index for arg sorting fe
    y_copy = y_copy[sorting] #Sort the y_node by x index
    feature_vals.sort() #Sort the feature grabbed from x

    #Initialize entropy variable
    best_loss = 100
    split_value = -1
    #Iterate over the feature vals
    for i in range(1,len(feature_vals)):
        #Seperate sorted (single) feature vals into two halves
        top_half = y_copy[:i]
        bottom_half = y_copy[i:]

```

```

        #Calculate weighted entropy for each half
        top_ratio = (len(top_half)/len(y_copy))
        bottom_ratio = (len(bottom_half)/len(y_copy))
        top_half_entropy = top_ratio * self.split_loss_function(top_half)
        bottom_half_entropy = bottom_ratio * self.split_loss_function(bottom_half)

        #Calculate Loss = Total Weighted Entropy
        loss = top_half_entropy + bottom_half_entropy

        #Check if we've reached a smaller loss
        if loss <= best_loss:
            best_loss = loss #Update smaller loss

            if i == 1:
                split_value = (feature_vals[i]+feature_vals[i+1])/2 #Take
                #Update the best split value via midpoint value
                #Take midpoint of point before after if best split point is found
            else:
                split_value = (feature_vals[i]+feature_vals[i-1])/2 #Take

        return split_value, best_loss

def find_best_feature_split(self, x_node, y_node):
    """
    Returns the optimal feature to split and best splitting point
    for data X_node, y_node.
    :param X: a numpy array of training data, shape = (n_node, 1)
    :param y: a numpy array of labels, shape = (n_node, 1)
    """
    best_feature_loss = 100
    #Iterate over all of the columns
    for i in range(x_node.shape[1]):
        #Use self.find_best_split to
        split_value, best_loss = self.find_best_split(x_node, y_node, i)

        #Check if we've found a column to split better on
        if best_loss <= best_feature_loss:
            best_feature_loss = best_loss #Update Loss Accordingly
            self.split_id = i #Update the column split id
            self.split_value = split_value #Update the column split value

def predict_instance(self, instance):
    """
    Predict label by decision tree

    :param instance: a numpy array with new data, shape (1, m)

    :return whatever is returned by leaf_value_estimator for leaf contained in instance
    """
    if self.is_leaf:
        return self.value

```

```

    if instance[self.split_id] <= self.split_value:
        return self.left.predict_instance(instance)
    else:
        return self.right.predict_instance(instance)

```

Decision Tree Classifier

In [6]:

```

def most_common_label(y):
    """
    Find most common label
    """
    label_cnt = Counter(y.reshape(len(y)))
    label = label_cnt.most_common(1)[0][0]
    return label

```

In [7]:

```

class Classification_Tree(BaseEstimator, ClassifierMixin):

    loss_function_dict = {
        'entropy': compute_entropy,
        'gini': compute_gini
    }

    def __init__(self, loss_function='entropy', min_sample=5, max_depth=10):
        """
        :param loss_function(str): loss function for splitting internal node
        """

        self.tree = Decision_Tree(self.loss_function_dict[loss_function],
                                   most_common_label,
                                   0, min_sample, max_depth)

    def fit(self, X, y=None):
        self.tree.fit(X,y)
        return self

    def predict_instance(self, instance):
        value = self.tree.predict_instance(instance)
        return value

```

Problem 3

Decision Tree Boundary

In [8]:

```

# Training classifiers with different depth
clf1 = Classification_Tree(max_depth=1, min_sample=2)
clf1.fit(x_train, y_train_label)

clf2 = Classification_Tree(max_depth=2, min_sample=2)
clf2.fit(x_train, y_train_label)

clf3 = Classification_Tree(max_depth=3, min_sample=2)
clf3.fit(x_train, y_train_label)

clf4 = Classification_Tree(max_depth=4, min_sample=2)
clf4.fit(x_train, y_train_label)

clf5 = Classification_Tree(max_depth=5, min_sample=2)
clf5.fit(x_train, y_train_label)

clf6 = Classification_Tree(max_depth=6, min_sample=2)
clf6.fit(x_train, y_train_label)

# Plotting decision regions
x_min, x_max = x_train[:, 0].min() - 1, x_train[:, 0].max() + 1
y_min, y_max = x_train[:, 1].min() - 1, x_train[:, 1].max() + 1
xx, yy = np.meshgrid(np.arange(x_min, x_max, 0.1),
                     np.arange(y_min, y_max, 0.1))

f, axarr = plt.subplots(2, 3, sharex='col', sharey='row', figsize=(10, 8))


for idx, clf, tt in zip(product([0, 1], [0, 1, 2]),
                        [clf1, clf2, clf3, clf4, clf5, clf6],
                        ['Depth = {}'.format(n) for n in range(1, 7)]):

    Z = np.array([clf.predict_instance(x) for x in np.c_[xx.ravel(), yy.ravel()]]
    Z = Z.reshape(xx.shape)

    axarr[idx[0], idx[1]].contourf(xx, yy, Z, alpha=0.4)
    axarr[idx[0], idx[1]].scatter(x_train[:, 0], x_train[:, 1], c=y_train_label)
    axarr[idx[0], idx[1]].set_title(tt)

plt.show()

```



Compare decision tree with tree model in sklearn

```
In [9]: clf = DecisionTreeClassifier(criterion='entropy', max_depth=3, min_samples_sp
clf.fit(x_train, y_train_label)
export_graphviz(clf, out_file='tree_classifier.dot')
```


In [10]:


```

# Plotting decision regions
x_min, x_max = x_train[:, 0].min() - 1, x_train[:, 0].max() + 1
y_min, y_max = x_train[:, 1].min() - 1, x_train[:, 1].max() + 1
xx, yy = np.meshgrid(np.arange(x_min, x_max, 0.1),
                     np.arange(y_min, y_max, 0.1))

Z = np.array([clf.predict(x[np.newaxis,:]) for x in np.c_[xx.ravel(), yy.ravel()]]
Z = Z.reshape(xx.shape)
plt.figure()
plt.contourf(xx, yy, Z, alpha=0.4)
plt.scatter(x_train[:, 0], x_train[:, 1],
            c=y_train_label[:,0], alpha=0.8)

```

Out[10]: <matplotlib.collections.PathCollection at 0x7ff5505a2670>




In [11]:

```

# Visualize decision tree
!dot -Tpng ./tree_classifier.dot -o tree_classifier.png
Image(filename='./tree_classifier.png')

```

Out [11]:



Problem 4

Decision Tree Regressor

In [12]:

```

# Regression Tree Specific Code
def mean_absolute_deviation_around_median(y):
    """
    Calculate the mean absolute deviation around the median of a given target

    :param y: a numpy array of targets shape = (n, 1)
    :return mae
    """
    # Initialize mae / median
    mae = 0
    median = np.median(y)
    # Iterate over y's and calculate absolute deviation from median
    for y_hat in y:
        mae += abs(y_hat - median)
    # Take average
    mae = mae / len(y)
    # Return mae
    return mae

```

In [13]:

```

class Regression_Tree():
    """
    :attribute loss_function_dict: dictionary containing the loss functions u
    :attribute estimator_dict: dictionary containing the estimation functions
    """

    loss_function_dict = {
        'mse': np.var,
        'mae': mean_absolute_deviation_around_median
    }

    estimator_dict = {
        'mean': np.mean,
        'median': np.median
    }

    def __init__(self, loss_function='mse', estimator='mean', min_sample=5, m
        """
        Initialize Regression_Tree
        :param loss_function(str): loss function used for splitting internal
        :param estimator(str): value estimator of internal node
        """

        self.tree = Decision_Tree(self.loss_function_dict[loss_function],
                                   self.estimator_dict[estimator],
                                   0, min_sample, max_depth)

    def fit(self, X, y=None):
        self.tree.fit(X,y)
        return self

    def predict_instance(self, instance):
        value = self.tree.predict_instance(instance)
        return value

```

Fit regression tree to one-dimensional regression data

In [14]:

```

data_krr_train = np.loadtxt('krr-train.txt')
data_krr_test = np.loadtxt('krr-test.txt')
x_krr_train, y_krr_train = data_krr_train[:,0].reshape(-1,1), data_krr_train[:,1]
x_krr_test, y_krr_test = data_krr_test[:,0].reshape(-1,1), data_krr_test[:,1]

# Training regression trees with different depth
clf1 = Regression_Tree(max_depth=1, min_sample=3, loss_function='mae', estim
clf1.fit(x_krr_train, y_krr_train)

clf2 = Regression_Tree(max_depth=2, min_sample=3, loss_function='mae', estim
clf2.fit(x_krr_train, y_krr_train)

clf3 = Regression_Tree(max_depth=3, min_sample=3, loss_function='mae', estim
clf3.fit(x_krr_train, y_krr_train)

clf4 = Regression_Tree(max_depth=4, min_sample=3, loss_function='mae', estim
clf4.fit(x_krr_train, y_krr_train)

clf5 = Regression_Tree(max_depth=5, min_sample=3, loss_function='mae', estim
clf5.fit(x_krr_train, y_krr_train)

clf6 = Regression_Tree(max_depth=10, min_sample=3, loss_function='mae', esti
clf6.fit(x_krr_train, y_krr_train)

plot_size = 0.001
x_range = np.arange(0., 1., plot_size).reshape(-1, 1)


f2, axarr2 = plt.subplots(2, 3, sharex='col', sharey='row', figsize=(15, 10))

for idx, clf, tt in zip(product([0, 1], [0, 1, 2]),
                        [clf1, clf2, clf3, clf4, clf5, clf6],
                        ['Depth = {}'.format(n) for n in range(1, 7)]):

    y_range_predict = np.array([clf.predict_instance(x) for x in x_range]).re

    axarr2[idx[0], idx[1]].plot(x_range, y_range_predict, color='r')
    axarr2[idx[0], idx[1]].scatter(x_krr_train, y_krr_train, alpha=0.8)
    axarr2[idx[0], idx[1]].set_title(tt)
    axarr2[idx[0], idx[1]].set_xlim(0, 1)
plt.show()

```



Compare with scikit-learn for debugging

In [15]:

```

# Training regression trees with different depth
clf1 = DecisionTreeRegressor(criterion='absolute_error', max_depth=1, min_sample_weight=0.001,
                             Regression_Tree(max_depth=1, min_sample=3, loss_function='mae', estimator='m
clf1.fit(x_krr_train, y_krr_train)

clf2 = DecisionTreeRegressor(criterion='absolute_error', max_depth=2, min_sample_weight=0.001,
                             Regression_Tree(max_depth=2, min_sample=3, loss_function='mae', estimator='m
clf2.fit(x_krr_train, y_krr_train)

clf3 = DecisionTreeRegressor(criterion='absolute_error', max_depth=3, min_sample_weight=0.001,
                             Regression_Tree(max_depth=3, min_sample=3, loss_function='mae', estimator='m
clf3.fit(x_krr_train, y_krr_train)

clf4 = DecisionTreeRegressor(criterion='absolute_error', max_depth=4, min_sample_weight=0.001,
                             Regression_Tree(max_depth=4, min_sample=3, loss_function='mae', estimator='m
clf4.fit(x_krr_train, y_krr_train)

clf5 = DecisionTreeRegressor(criterion='absolute_error', max_depth=5, min_sample_weight=0.001,
                             Regression_Tree(max_depth=5, min_sample=3, loss_function='mae', estimator='m
clf5.fit(x_krr_train, y_krr_train)

clf6 = DecisionTreeRegressor(criterion='absolute_error', max_depth=10, min_sample_weight=0.001,
                             Regression_Tree(max_depth=10, min_sample=3, loss_function='mae', estimator='m
clf6.fit(x_krr_train, y_krr_train)

#Compare Plots
plot_size = 0.001
x_range = np.arange(0., 1., plot_size).reshape(-1, 1)


f2, axarr2 = plt.subplots(2, 3, sharex='col', sharey='row', figsize=(15, 10))

for idx, clf, tt in zip(product([0, 1], [0, 1, 2]),
                        [clf1, clf2, clf3, clf4, clf5, clf6],
                        ['Depth = {}'.format(n) for n in range(1, 7)]):

    y_range_predict = clf.predict(np.array([x for x in x_range]).reshape(-1, 1))

    axarr2[idx[0], idx[1]].plot(x_range, y_range_predict, color='r')
    axarr2[idx[0], idx[1]].scatter(x_krr_train, y_krr_train, alpha=0.8)
    axarr2[idx[0], idx[1]].set_title(tt)
    axarr2[idx[0], idx[1]].set_xlim(0, 1)
plt.show()

```



Gradient Boosting Method

Problem 5

In [16]:

```
#Pseudo-residual function.

def pseudo_residual_L2(train_target, train_predict):
    """
    Compute the pseudo-residual based on current predicted value.
    """
    return train_target - train_predict
```

In [27]:

```
class gradient_boosting():
    """
    Gradient Boosting regressor class
    :method fit: fitting model
    """
    def __init__(self, n_estimator, pseudo_residual_func, learning_rate=0.01,
                  min_sample=5, max_depth=5):
        """
        Initialize gradient boosting class
```

```

:param n_estimator: number of estimators (i.e. number of rounds of gr
:param pseudo_residual_func: function used for computing pseudo-residual be
:param learning_rate: step size of gradient descent
'''

self.n_estimator = n_estimator
self.pseudo_residual_func = pseudo_residual_func
self.learning_rate = learning_rate
self.min_sample = min_sample
self.max_depth = max_depth

self.estimators = [] #will collect the n_estimator models

def fit(self, train_data, train_target):
    '''
    Fit gradient boosting model
    :train_data array of inputs of size (n_samples, m_features)
    :train_target array of outputs of size (n_samples,)
    '''
    #Initialize array of 0's of size = (len(train_target))
    base_grad = np.zeros(len(train_target))
    self.estimators.append(base_grad) #Append base case

    #Set up our base case - Sk Learns Regression Tree
    base_case = DecisionTreeRegressor(criterion='squared_error',
                                     min_samples_split=self.min_sample,
                                     max_depth=self.max_depth)

    #Fit regression model
    base_case.fit(train_data, train_target.flatten())
    #Append Estimators
    self.estimators.append(base_case)

    #Iterate for however many rounds of gradient boosting we're using
    for i in range(1, self.n_estimator):
        #Compute Predictions
        predictions = self.predict(train_data)

        #Compute Residuals
        residuals = train_target.flatten() - predictions

        #Fit regression model to -g
        base_case = DecisionTreeRegressor(criterion='squared_error',
                                          min_samples_split=self.min_sample,
                                          max_depth=self.max_depth)

        #Fit new function
        base_case.fit(train_data, residuals)
        #Append estimators
        self.estimators.append(base_case)
    return self

def predict(self, test_data):
    '''

```



```

    Predict value
    :train_data array of inputs of size (n_samples, m_features)
    '''

    #Initialize prediction
    test_predict = np.zeros(len(test_data))

    #Iterate over the estimators we have saved in our .fit method
    for i in range(1,len(self.estimators)):

        #Add estimator_i prediction to test_predict, but scale by step size
        test_predict += self.estimators[i].predict(test_data) * self.learning_rate

    return test_predict

```

1-D GBM visualization - KRR data

Question 6

In [28]:

```

plot_size = 0.001
x_range = np.arange(0., 1., plot_size).reshape(-1, 1)

f2, axarr2 = plt.subplots(2, 3, sharex='col', sharey='row', figsize=(15, 10))


for idx, i, tt in zip(product([0, 1], [0, 1, 2]),
                      [1, 5, 10, 20, 50, 100],
                      ['n_estimator = {}'.format(n) for n in [1, 5, 10, 20, 50, 100]]):

    gbm_1d = gradient_boosting(n_estimator=i, pseudo_residual_func=pseudo_residual_func,
                               max_depth=3, learning_rate=0.1)
    gbm_1d.fit(x_krr_train, y_krr_train[:,0])

    y_range_predict = gbm_1d.predict(x_range)

    axarr2[idx[0], idx[1]].plot(x_range, y_range_predict, color='r')
    axarr2[idx[0], idx[1]].scatter(x_krr_train, y_krr_train, alpha=0.8)
    axarr2[idx[0], idx[1]].set_title(tt)
    axarr2[idx[0], idx[1]].set_xlim(0, 1)

```



Sklearn implementation for Classification of images

Question 9

Gradient Boosting Classifier

In [29]:

```
from sklearn.datasets import fetch_openml
from sklearn.linear_model import LogisticRegression
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
from sklearn.utils import check_random_state
```

In [30]:

```
def pre_process_mnist_01():
    """
    Load the mnist datasets, selects the classes 0 and 1
    and normalize the data.
    Args: none
    Outputs:
        X_train: np.array of size (n_training_samples, n_features)
        X_test: np.array of size (n_test_samples, n_features)
        y_train: np.array of size (n_training_samples)
        y_test: np.array of size (n_test_samples)
    """
    X_mnist, y_mnist = fetch_openml('mnist_784', version=1,
                                     return_X_y=True, as_frame=False)
    indicator_01 = (y_mnist == '0') + (y_mnist == '1')
    X_mnist_01 = X_mnist[indicator_01]
    y_mnist_01 = y_mnist[indicator_01]
    X_train, X_test, y_train, y_test = train_test_split(X_mnist_01, y_mnist_01,
                                                         test_size=0.33,
                                                         shuffle=False)

    scaler = StandardScaler()
    X_train = scaler.fit_transform(X_train)
    X_test = scaler.transform(X_test)

    y_test = 2 * np.array([int(y) for y in y_test]) - 1
    y_train = 2 * np.array([int(y) for y in y_train]) - 1
    return X_train, X_test, y_train, y_test
```

In [31]:

```
X_train, X_test, y_train, y_test = pre_process_mnist_01()
```

In [32]:

```

#Initialize helper variables
loss_dict = {'train':[], 'test':[]}
estimators = [2,5,10,100,200,500,1000]

#Iterate over the estimators
for n in estimators:
    #Helper Print Statement to let me know it isn't dead
    print(f'Now fiitting GBC - {n} Estimators used')
    #Initliaze GBC Estimator
    gbc = GradientBoostingClassifier(n_estimators=n, loss='deviance', max_dep
    #Fit the GBC estimator
    gbc.fit(X_train, y_train)

    #Append results
    loss_dict['train'].append(gbc.score(X_train, y_train)) #Append Train Loss
    loss_dict['test'].append(gbc.score(X_test,y_test))      #Append Test Loss

#Plot our results
plt.plot(estimators, loss_dict['train'], label = 'train accuracy') #Plot Trai
plt.plot(estimators, loss_dict['test'], label = 'test accuracy')    #Plot Test
plt.legend()
plt.plot()


```

```

fitting gbc with 2 estimators
fitting gbc with 5 estimators
fitting gbc with 10 estimators
fitting gbc with 100 estimators
fitting gbc with 200 estimators
fitting gbc with 500 estimators
fitting gbc with 1000 estimators

```

Out[32]: []



Problem 11

Random Forest Classifier

In [36]:

```
#Initialize helper variables
loss_dict = {'train':[], 'test':[]}
estimators = [2,5,10,100,200,500,1000]

#Iterate over our estimators
for n in estimators:
    #Initialize and fit a Random Forest Classifier from sklearn
    gbrf = RandomForestClassifier(n_estimators=n, criterion = 'entropy', max_
    gbrf.fit(X_train, y_train)

    #Append our train / test loss
    loss_dict['train'].append(gbrf.score(X_train, y_train))
    loss_dict['test'].append(gbrf.score(X_test, y_test))

#Plot our results
plt.plot(estimators, loss_dict['train'], label = 'train accuracy') #Plot Train
plt.plot(estimators, loss_dict['test'], label = 'test accuracy') #Plot Test
plt.legend()
plt.plot()
```

Out[36]: []

