

Optimization of Projectile Range

Giulio Procopio

January 2024

1 Introduction

Given a projectile thrown with initial velocity \vec{v}_0 from a height y_0 , what is the optimal angle θ^* between such velocity and the horizontal plane in order to maximize its range?

We will show that the optimal angle is, more generally, not always 45° ; such angle is indeed dependent from the initial state of the projectile (i.e. its initial velocity and height).

2 Initial State

Let's consider a projectile with initial velocity \vec{v}_0 . We'll study its motion in the plane x, y from its initial position $(0, y_0)$ at time t_0 , with $y_0 > 0$, to the ground.

As such, $\vec{v}_0 = (v_{0x}, v_{0y})$ with $v_{0x} > 0$ and $v_{0y} > 0$. The angle θ between \vec{v}_0 and the horizontal plane is $\theta = \arctan\left(\frac{v_{0y}}{v_{0x}}\right)$.

The projectile will be subject to an uniform gravitational acceleration \vec{g} with $g \approx 9.81 \frac{m}{s^2}$ pointing downwards. We'll neglect other forces such as air resistance.

3 Equations of Motion

The equations of motion for the projectile are

$$\begin{cases} x(t) = v_{0x}t \\ y(t) = y_0 + v_{0y}t - \frac{1}{2}gt^2 \end{cases} \quad , \quad t \geq t_0 = 0 \quad (1)$$

From the system above we can derive the function of the projectile's trajectory $y(x)$. Remembering that $v_{0x} = v_0 \cos \theta$ and $v_{0y} = v_0 \sin \theta$, we get

$$y(x) = y_0 + \tan \theta \cdot x - \frac{g}{2v_0^2 \cos^2 \theta} x^2 \quad (2)$$

Let r be the range of the projectile. The point of contact with the ground is given by $(r, 0)$, thus

$$\begin{aligned} y(r) = 0 &\implies r = \frac{-\tan \theta + \sqrt{\tan^2 \theta + \frac{2gy_0}{v_0^2 \cos^2 \theta}}}{-\frac{g}{v_0^2 \cos^2 \theta}} \\ &= \frac{v_0^2}{g} \left(\sin \theta + \sqrt{\sin^2 \theta + \frac{2gy_0}{v_0^2}} \right) \cos \theta \end{aligned} \quad (3)$$

For the sake of simplicity, let $A = \frac{v_0^2}{g}$ and $B = \frac{2gy_0}{v_0^2}$. So that, writing r as a function of θ ,

$$r(\theta) = A \left(\sin \theta + \sqrt{\sin^2 \theta + B} \right) \cos \theta \quad (4)$$

4 Degenerate Case $y_0 = 0$

Let's first consider the degenerate case $y_0 = 0$. The term B goes to zero, thus $r(\theta)$ simplifies to

$$r(\theta) = A \sin 2\theta \quad (5)$$

The range is maximized when the sine is maximum, i.e. $\max r(\theta) = r(\theta^*) = A$ when $\theta^* = \frac{\pi}{4}$.

5 General Case $y_0 > 0$

Considering the general case $y_0 > 0$, we evaluate the derivative of $r(\theta)$

$$\begin{aligned} \frac{dr}{d\theta} &= A \left[-\sin \theta \left(\sin \theta + \sqrt{\sin^2 \theta + B} \right) + \cos \theta \left(\cos \theta + \frac{\sin \theta \cos \theta}{\sqrt{\sin^2 \theta + B}} \right) \right] \\ &= A \left(-\sin^2 \theta - \sin \theta \sqrt{\sin^2 \theta + B} + \cos^2 \theta + \frac{\sin \theta \cos^2 \theta}{\sqrt{\sin^2 \theta + B}} \right) \end{aligned} \quad (6)$$

Since $\max r(\theta) = r(\theta^*)$, the derivative must be zero when $\theta = \theta^*$.

$$\begin{aligned} \frac{dr}{d\theta}(\theta^*) = 0 &\implies A \left(-\sin^2 \theta^* - \sin \theta^* \sqrt{\sin^2 \theta^* + B} + \cos^2 \theta^* + \frac{\sin \theta^* \cos^2 \theta^*}{\sqrt{\sin^2 \theta^* + B}} \right) = 0 \\ &\implies -\sin^2 \theta^* \cdot \sqrt{\sin^2 \theta^* + B} - \sin \theta^* \cdot (\sin^2 \theta^* + B) \\ &\quad + \cos^2 \theta^* \cdot \sqrt{\sin^2 \theta^* + B} + \sin \theta^* \cos^2 \theta^* = 0 \\ &\implies (\cos^2 \theta^* - \sin^2 \theta^*) \sqrt{\sin^2 \theta^* + B} = \sin^3 \theta^* + B \sin \theta^* - \sin \theta^* \cos^2 \theta^* \\ &\implies (\cos^2 \theta^* - \sin^2 \theta^*)^2 (\sin^2 \theta^* + B) = (\sin^3 \theta^* + B \sin \theta^* - \sin \theta^* \cos^2 \theta^*)^2 \\ &\implies \sin^2 \theta^* \cos^4 \theta^* + B \cos^4 \theta^* + \sin^6 \theta^* + B \sin^4 \theta^* - 2 \sin^4 \theta^* \cos^2 \theta^* \\ &\quad - 2B \sin^2 \theta^* \cos^2 \theta^* = \sin^6 \theta^* + B^2 \sin^2 \theta^* + \sin^2 \theta^* \cos^4 \theta^* + 2B \sin^4 \theta^* \\ &\quad - 2B \sin^2 \theta^* \cos^2 \theta^* - 2 \sin^4 \theta^* \cos^2 \theta^* \\ &\implies B - 2B \sin^2 \theta^* \cos^2 \theta^* = B^2 \sin^2 \theta^* + 2B \sin^4 \theta^* \end{aligned} \quad (7)$$

Dividing both sides by B and remembering that $\cos^2 \theta^* = 1 - \sin^2 \theta^*$

$$\begin{aligned} 1 - 2 \sin^2 \theta^* (1 - \sin^2 \theta^*) &= B \sin^2 \theta^* + 2 \sin^4 \theta^* \\ \implies 1 - 2 \sin^2 \theta^* &= B \sin^2 \theta^* \\ \implies \theta^* &= \arcsin \sqrt{\frac{1}{B+2}} \end{aligned} \quad (8)$$

Note that by setting $B = 0$ we get $\theta^* = \frac{\pi}{4}$, as expected from the case $y_0 = 0$.

6 Conclusion

The optimal take-off angle θ^* to maximize the projectile range is given by

$$\theta^* = \arcsin \sqrt{\frac{1}{\frac{2gy_0}{v_0^2} + 2}} \quad (9)$$

For example, a baseball thrown with initial velocity $v_0 = 20 \frac{m}{s}$ from a $y_0 = 20m$ 5th floor window will have an optimal take-off angle of $\theta^* \approx 35.3^\circ$.