## TaDA workshop - VLDB 2024

Fast and accurate regional effect plots for automated tabular data analysis

Vasilis Gkolemis<sup>1,2</sup> Christos Diou<sup>2</sup> Eirini Ntoutsi<sup>3</sup> Theodore Dalamagas<sup>1</sup>

<sup>1</sup>ATHENA Research and Innovation Center

<sup>2</sup>Harokopio University of Athens

<sup>3</sup>University of the Bundeswehr Munich

August 2024

- Introduction
  - Problem Statement
  - Proposed Pipeline
  - Regional RHALE our contribution
- Regional RHALE advantages
  - It is fast
  - It treats well correlated features
- Effector Python package


- Introduction
  - Problem Statement
  - Proposed Pipeline
  - Regional RHALE our contribution
- Regional RHALE advantages
  - It is fast
  - It treats well correlated features
- 3 Effector Python package

### Problem Statement




I will try to convince you for 4 things!


- Introduction
  - Problem Statement
  - Proposed Pipeline
  - Regional RHALE our contribution
- Regional RHALE advantages
  - It is fast
  - It treats well correlated features
- 3 Effector Python package




Black box ML model + XAI = a good pipeline!



Black box ML model + Global effect methods = a good pipeline!



Black box ML model + Regional effect methods = a better pipeline!



Black box ML model + Regional RHALE = an even better pipeline!

# Bike-sharing dataset


- hourly count of bike-rentals (2011, 2012)
- Design-matrix X:
  - year, month, day, hour
  - working day vs. non-working day
  - temperature
  - humidity
  - windspeed
- Target variable Y:
  - bike-rentals per hour
    - $\star Y_{\mu} = 189.5$
    - ★  $Y_{\sigma} = 181.4$
- Decision Making: decide a discount policy
- Data Understanding: confirm/reject some ideas about bike rentals

## Proposed pipeline: Fit and Explain

- decide a discount policy
  - which hour of the day to apply the discount
  - how the feature x<sub>hour</sub> relates to y<sub>bike\_rentals</sub>
- Step 1: Fit a black-box ML model
  - Could be any ML model
  - ▶ a Neural Network achieves RMSE  $\approx$  45.35 counts (0.25 $Y_{\sigma}$ )
- Step 2: Use feature effect
  - Global effect: x<sub>hour</sub> vs y<sub>bike\_rentals</sub> globally
  - Regional effect: Xhour vs Ybike\_rentals regionally


Let's see!

### Global Effect: PDP and RHALE




RHALE paper (Gkolemis et al., 2023b): ALE + heterogeneity

## Regional Effect: Regional-PDP



- Introduction
  - Problem Statement
  - Proposed Pipeline
  - Regional RHALE our contribution
- Regional RHALE advantages
  - It is fast
  - It treats well correlated features
- Street Python package

## Regional Effect: Regional-RHALE



- Introduction
  - Problem Statement
  - Proposed Pipeline
  - Regional RHALE our contribution
- Regional RHALE advantages
  - It is fast
  - It treats well correlated features
- 3 Effector Python package

- Introduction
  - Problem Statement
  - Proposed Pipeline
  - Regional RHALE our contribution
- Regional RHALE advantages
  - It is fast
  - It treats well correlated features
- 3 Effector Python package

- Introduction
  - Problem Statement
  - Proposed Pipeline
  - Regional RHALE our contribution
- Regional RHALE advantages
  - It is fast
  - It treats well correlated features
- Street Python package

- Introduction
  - Problem Statement
  - Proposed Pipeline
  - Regional RHALE our contribution
- Regional RHALE advantages
  - It is fast
  - It treats well correlated features
- 3 Effector Python package

#### Thank You!

- If you find this package useful, we would appreciate your feedback and a star on GitHub
- https://arxiv.org/abs/2404.02629
- https://github.com/givasile/effector
- https://xai-effector.github.io/

### References I

- Apley, Daniel W. and Jingyu Zhu (2020). "Visualizing the effects of predictor variables in black box supervised learning models". In: Journal of the Royal Statistical Society. Series B: Statistical Methodology 82.4, pp. 1059–1086. ISSN: 14679868. DOI: 10.1111/rssb.12377. arXiv: 1612.08468.
- Friedman, Jerome H and Bogdan E Popescu (2008). "Predictive learning via rule ensembles". In: *The annals of applied statistics*. Publisher: JSTOR, pp. 916–954.
- Gkolemis, Vasilis, Theodore Dalamagas, and Christos Diou (Oct. 2022). "DALE: Differential Accumulated Local Effects for efficient and accurate global explanations". In: Asian Conference on Machine Learning (ACML).
  - Gkolemis, Vasilis et al. (2023a). "Regionally Additive Models: Explainable-by-design models minimizing feature interactions". In: arXiv preprint arXiv:2309.12215.

#### References II

- Gkolemis, Vasilis et al. (2023b). "RHALE: Robust and Heterogeneity-Aware Accumulated Local Effects". In: *ECAI 2023*. IOS Press, pp. 859–866.
- Goldstein, Alex et al. (Mar. 2014). Peeking Inside the Black Box: Visualizing Statistical Learning with Plots of Individual Conditional Expectation. en. arXiv:1309.6392 [stat]. URL:
  - http://arxiv.org/abs/1309.6392 (visited on 01/23/2023).
- Herbinger, Julia, Bernd Bischl, and Giuseppe Casalicchio (Feb. 2022). REPID: Regional Effect Plots with implicit Interaction Detection. arXiv:2202.07254 [cs, stat]. DOI: 10.48550/arXiv.2202.07254. URL: http://arxiv.org/abs/2202.07254 (visited on 06/11/2023).
- (2023). "Decomposing Global Feature Effects Based on Feature Interactions". In: arXiv preprint arXiv:2306.00541.

#### References III



Lundberg, Scott M and Su-In Lee (2017). "A unified approach to interpreting model predictions". In: *Advances in neural information processing systems* 30.