Table of Contents

Chapter 1 — Executive Summary 6

1.1 Platform at a Glance . . . 6
1.2 Core Value Proposition . . . 6
1.3 Build Status . . . 6
1.4 Reading Map . . . 7

Chapter 2 — Product Overview 8

2.1 The Tender Lifecycle . . . 8
2.2 Primary User Personas . . . 8
2.3 The Ten Dashboard Modules . . . 8
2.4 Public Surface . . . 9

Chapter 3 — Market & Problem Statement 10

3.1 The South African Tender Market . . . 10
3.2 The Five Core Problems . . . 10
3.3 Competitive Landscape . . . 10
3.4 Target Customer Segments . . . 11

Chapter 4 — Solution Architecture 12

4.1 Request Flow . . . 12
4.2 Service Topology . . . 12
4.3 Cross-Origin Routing Convention . . . 13
4.4 Design Principles . . . 13

Chapter 5 — Feature Catalog 14

5.1 Dashboard . . . 14
5.2 Tenders Register . . . 14
5.3 Discover . . . 15
5.4 Reader (AI Document Reading) . . . 15
5.5 Library . . . 15
5.6 Preparation (Checklist) . . . 15
5.7 Briefings . . . 15

5.8 Pricing . . . 15
5.9 Submissions . . . 16
5.10 Clarifications & Communications . . . 16
5.11 Addendums . . . 16
5.12 Deadlines & Reminders . . . 16
5.13 Company Profile . . . 16
5.14 Generated Documents . . . 17
5.15 Readiness Report . . . 17
5.16 AI Assistant . . . 17

Chapter 6 — Technical Architecture 18

6.1 Technology Stack Summary . . . 18
6.2 Frontend Architecture . . . 18
6.3 Backend Architecture . . . 19
6.4 Database Architecture . . . 19
6.5 AI Integration Architecture . . . 19

Chapter 7 — AI Capabilities 21

7.1 AI Feature Inventory . . . 21
7.2 The Fourteen Document Generators . . . 21
7.3 Prompt Engineering Strategy . . . 22
7.4 Fallback and Error Handling . . . 22

Chapter 8 — API Surface 23

8.1 Authentication & Onboarding . . . 23
8.2 Tenders . . . 23
8.3 AI Endpoints . . . 24
8.4 Checklist, Library, Briefings, Pricing, Submissions, Communications, Addendums . . . 24
8.5 Company Profile, Generated Documents, Dashboard, Reminders, Deadlines . . . 26
8.6 API Design Conventions . . . 27

Chapter 9 — Data Model 28

9.1 Model Inventory . . . 28
9.2 Tender Model — The Spine . . . 28

9.3 Cascade Rules . . . 29
9.4 JSON Fields . . . 29
Chapter 10 — Security & Authentication 30
10.1 Authentication Flow . . . 30
10.2 Password Storage . . . 30
10.3 Authorisation Model . . . 30
10.4 File Upload Safety . . . 30
10.5 Known Security Posture . . . 30
Chapter 11 — User Experience & Frontend 31
11.1 Visual Design Language . . . 31
11.2 Landing Page . . . 31
11.3 Authentication & Onboarding . . . 31
11.4 Dashboard Shell . . . 31
11.5 Tender Detail View . . . 31
11.6 Interaction Patterns . . . 32
Chapter 12 — Deployment & Infrastructure 33
12.1 Development Environment . . . 33
12.2 The Caddy Gateway . . . 33
12.3 Database Management . . . 33
12.4 File Storage . . . 33
12.5 Production Deployment Path . . . 33
Chapter 13 — Roadmap 34
13.1 Horizon 1 — Production Hardening . . . 34
13.2 Horizon 2 — Collaboration & Multi-Tenant . . . 34
13.3 Horizon 3 — Integrations & Marketplace . . . 34
Chapter 14 — Commercial Strategy & Pricing 36
14.1 Pricing Model . . . 36
14.2 Tier Comparison . . . 36
14.3 Pricing Strategy — Why We Cap AI Credits, Not Tenders . . . 37
14.4 Go-To-Market . . . 37

14.5 Revenue Projections 37
14.6 Competitive Moat 37

Chapter 15 — Value Assessment 39

15.1 Build Effort Summary 39
15.2 Comparable Market Rates 39
15.3 Valuation Scenarios 39
15.4 Recommendation 40
15.5 Closing Statement 40

Chapter 1 — Executive Summary

TM Flow is a full-stack, AI-powered tender management platform purpose-built for the South African procurement market. It consolidates the entire tender lifecycle — from opportunity discovery through document reading, compliance checking, pricing, submission tracking, and post-submission analysis — into a single web application. The platform replaces the fragmented spreadsheet-and-email workflows that most small-to-medium South African contractors and consultants still rely on today.

This report documents the complete architecture, feature surface, technology stack, security model, and commercial positioning of the platform. It is intended for engineering review, product planning, and commercial evaluation audiences. The document reflects the v1.0 build state of the application as deployed in the development environment, covering 67 backend API endpoints, 11 database models, 14 AI document generators, and 10 dashboard modules.

1.1 Platform at a Glance

67 API Endpoints	**11** Data Models	**14** AI Generators
10 Dashboard Modules	**50+** Frontend Components	**2** Independent Services

1.2 Core Value Proposition

The platform delivers three layers of value that stack to form a defensible product. The first layer is operational: every tender — its documents, checklist, briefings, pricing versions, communications, addendums, and submission record — lives in one structured record instead of being scattered across inboxes and local drives. The second layer is intelligence: an integrated AI engine reads tender documents, extracts compliance requirements, summarises scope, detects addendum changes, and generates fourteen categories of tender response documents from company profile context. The third layer is commercial: built-in pricing version management, readiness reporting, and deadline tracking turn what is typically a chaotic manual process into a measurable, auditable workflow.

1.3 Build Status

The application is functionally complete in its v1.0 form. The Python FastAPI backend is fully operational on port 8000 with a populated SQLite database, file upload handling, and live AI integration through the

z-ai-web-dev-sdk CLI. The Next.js 16 frontend is deployed on port 3000 with a complete authenticated dashboard, a public-facing animated landing page, a six-step onboarding wizard, and full CRUD coverage for every entity in the data model. Both services run behind a Caddy gateway that routes cross-origin requests transparently.

1.4 Reading Map

Chapter 2 introduces the product from a user perspective. Chapter 3 frames the market problem and competitive landscape. Chapter 4 presents the high-level solution architecture. Chapter 5 catalogues the full feature surface module by module. Chapter 6 details the technical stack across frontend, backend, database, and AI layers. Chapter 7 dedicates a deep dive to the AI capabilities. Chapter 8 enumerates the API surface. Chapter 9 documents the data model. Chapter 10 covers security and authentication. Chapter 11 reviews the frontend user experience. Chapter 12 explains deployment and infrastructure. Chapter 13 outlines the product roadmap. Chapter 14 sets out the commercial and pricing strategy. Chapter 15 closes with a value assessment.

Chapter 2 — Product Overview

TM Flow is positioned as a vertical SaaS product for South African tendering organisations. The name reflects the core metaphor: tenders should flow through a managed pipeline rather than pile up as ad-hoc email attachments. Every screen, data model, and AI feature in the platform serves this pipeline metaphor.

2.1 The Tender Lifecycle

A tender in the South African context is a formal procurement opportunity issued by government departments, state-owned enterprises, municipalities, and large private buyers. The lifecycle of a typical tender spans six to twelve weeks and involves reading dense specification documents, compiling compliance evidence (CIPC, SARS, B-BBEE, PSIRA, COIDA certificates), attending compulsory briefing sessions, preparing pricing, drafting method statements and technical proposals, submitting by a strict closing date, and tracking the outcome. TM Flow models this lifecycle explicitly in its data schema and exposes it through ten interconnected dashboard modules.

2.2 Primary User Personas

Persona	Role	Primary Pain Point	TM Flow Module
Tender Manager	Tracks all live opportunities, manages submission calendar	Tenders scattered across email; no single source of truth	Tenders, Deadlines, Dashboard
Bid Writer	Drafts technical proposals and method statements	Templates reinvented for every bid; slow turnaround	Generated Documents, Reader, Assistant
Compliance Officer	Validates certificates, B-BBEE, PSIRA, COIDA	Expired certificates missed; disqualifications	Library, Checklist, Company Profile
Pricing Lead	Builds cost models and final tender pricing	Pricing versions lost; no audit trail	Pricing, Submissions
Director / Owner	Signs off submissions, tracks win rate	No visibility into pipeline or win/loss metrics	Dashboard, Readiness Report

Table 2.1 — Primary user personas and their mapped dashboard modules.

2.3 The Ten Dashboard Modules

Once authenticated, the user lands in a sidebar-driven dashboard with ten top-level modules. Each module is a self-contained workspace with its own tab in the sidebar, but they all operate on the shared tender record. The modules are: Dashboard (KPI overview), Tenders (register and detail), Discover (live portal scraping), Reader (AI document reading), Library (company compliance documents), Preparation (checklist workflow), Briefings (session tracking), Pricing (versioned cost models), Submissions (final submission records), Clarifications (communications log), Addendums (change tracking), Deadlines (calendar view), Company (branding and profile), and Assistant (AI chat).

2.4 Public Surface

Before authentication, the user encounters a marketing landing page with animated hero, feature grid, pricing tiers, FAQ accordion, and footer. The landing page is the commercial front door of the product. After sign-up, a six-step onboarding wizard captures company details, compliance documents, branding assets, and reminder preferences before the user reaches the dashboard. This onboarding is mandatory and feeds the AI document generators with company context that they need to produce tender-ready output.

Chapter 3 — Market & Problem Statement

3.1 The South African Tender Market

South Africa runs one of the most active public procurement markets on the continent. National Treasury estimates that public sector procurement accounts for roughly 12 percent of GDP, with tens of thousands of tenders issued annually across national departments, the nine provinces, and 257 municipalities. Portals such as the eTenders National Treasury portal, the Western Cape Procurement Portal, the Gauteng eTenders system, and sector-specific platforms (ESKOM, Transnet, SANRAL, departmental portals) collectively publish hundreds of new opportunities every week.

Despite this volume, the tendering process for small and medium enterprises is structurally painful. Documents are large (frequently 50 to 200 pages of PDF), compliance requirements are intricate and unforgiving, deadlines are absolute, and the cost of a single missed certificate or misunderstood addendum is disqualification. Most SMEs handle this with email folders, spreadsheets, and a junior administrator — a workflow that scales poorly and fails silently.

3.2 The Five Core Problems

#	Problem	Current Workaround	TM Flow Solution
1	Tender discovery is manual	Daily visits to 6+ portal websites	Discover module scrapes live portals into one feed
2	Documents are unreadable	Print and highlight 100-page PDFs by hand	AI Reader extracts scope, requirements, deadlines
3	Compliance is error-prone	Folder of certificate PDFs, no expiry tracking	Library with expiry dates + auto-linked checklist
4	Bid writing is slow	Copy-paste from old bids, reinvent each time	14 AI document generators using company profile
5	Deadlines are missed	Calendar entries, sticky notes, panic	Deadlines module + 30/14/7/3/1-day reminders

Table 3.1 — The five core problems TM Flow is engineered to solve.

3.3 Competitive Landscape

The South African market has a small number of niche competitors, most of which are either consulting-led tender writing services (priced per tender, not as software) or generic project management tools repurposed for tender tracking. No widely-adopted SaaS product combines live portal scraping, AI document reading, compliance management, and AI-generated bid documents in a single platform. Internationally, platforms such as Procore, BuildingConnected, and Avalara cover adjacent spaces but do not address the South African compliance regime (B-BBEE, PSIRA, CIPC, COIDA) or the local portal ecosystem. This leaves a clear product gap that TM Flow is designed to fill.

3.4 Target Customer Segments

- **Security and cleaning contractors** — high-volume tenderers with PSIRA-driven compliance burden and frequent bid writing.
- **Construction and engineering SMEs** — CIDB-graded firms tendering for municipal and SOE work.
- **Consulting and professional services** — built-environment consultants, project managers, and advisory firms.
- **NGOs and NPOs** — non-profits applying for departmental funding (a significant tender category in SA).
- **Tender consulting agencies** — boutique consultancies that manage bids on behalf of multiple clients.

Chapter 4 — Solution Architecture

TM Flow is a two-service application composed of a Python FastAPI backend and a Next.js 16 frontend, both running behind a Caddy reverse proxy. The architecture favours clarity over distributed-systems sophistication: every responsibility has exactly one home, and the data model is the contract between frontend and backend. The diagram below summarises the six layers of the system.

System Architecture — Layered View




Figure 4.1 — Layered system architecture of TM Flow.

4.1 Request Flow

A user action in the React frontend produces a fetch request to a relative API path. The Caddy gateway inspects the request, reads the optional XTransformPort query parameter, and forwards the request to the appropriate backend service. For tender data, the request lands on the FastAPI service (port 8000). The FastAPI application authenticates the JWT, validates the request body via Pydantic, performs the database operation through SQLAlchemy, and returns a JSON response. For AI operations, the FastAPI service shells out to the z-ai CLI subprocess, captures the structured output, and returns it to the frontend. File uploads stream through multipart form handling into the local uploads directory and are served back via FastAPI's StaticFiles mount.

4.2 Service Topology

Service	Port	Technology	Responsibility
Frontend (Web)	3000	Next.js 16 + TypeScript	SSR/CSR rendering, UI, auth context, API orchestration
Backend (API)	8000	FastAPI + SQLAlchemy	REST API, auth, file handling, AI orchestration

Service	Port	Technology	Responsibility
Gateway	80/443	Caddy	Reverse proxy, cross-port routing, TLS termination
Database	—	SQLite (file-based)	Persistent storage, 11 models
File Store	—	Local filesystem	Uploaded tender docs, library, signatures, submissions
AI Engine	—	z-ai-web-dev-sdk CLI	Chat, vision, document reading, generation

Table 4.1 — Service topology of the v1.0 deployment.

4.3 Cross-Origin Routing Convention

Because the sandbox exposes only one external port, every cross-service API request must declare its target port through the XTransformPort query parameter. The frontend therefore issues requests of the form `/api/tenders?XTransformPort=8000` rather than `http://localhost:8000/api/tenders`. The Caddyfile rewrites these requests transparently. This convention keeps all client-side code portable and origin-agnostic, which is essential for the single-port deployment model.

4.4 Design Principles

- **Single source of truth.** The Tender record is the spine of the data model. Every related entity (document, checklist item, pricing version, communication, addendum) hangs off a tender_id foreign key with cascade delete.
- **AI as a subroutine, not a service.** The z-ai CLI is invoked synchronously via subprocess. This avoids a third service, keeps deployment simple, and lets the FastAPI layer own all prompt engineering.
- **File paths in the database, files on disk.** Uploaded files are never stored in the database. Only their filesystem path, original filename, and metadata are persisted. This keeps the database small and backups fast.
- **Frontend owns the UX contract.** The backend returns raw JSON. All formatting, status colouring, and pagination live in React. This allows the API to be reused by future mobile or integration clients.

Chapter 5 — Feature Catalog

This chapter catalogues the feature surface module by module. Each subsection corresponds to a dashboard tab or major functional area. The intent is to give the reader a complete inventory of what the platform does today, without diving into implementation — that is the subject of Chapters 6 through 9.




Figure 5.1 — Approximate engineering effort distribution across feature modules.

5.1 Dashboard

The dashboard is the post-authentication landing surface. It presents KPI cards for active tenders, tenders closing this week, submissions to date, and overall win rate. Each KPI card is clickable and navigates to a filtered view of the relevant module. A recent activity feed shows the latest tender status changes, uploaded documents, and completed checklist items. The dashboard data is served by a single aggregated endpoint that joins across all major tables.

5.2 Tenders Register

The tenders register is the master list of every opportunity in the system. It supports search across eleven criteria (status, category, client, closing date range, estimated value range, location, person responsible, and outcome) and exports to Excel via openpyxl. Each tender opens into a detail view with eleven sub-tabs covering documents, checklist, briefings, pricing, submission, clarifications, addendums, generated documents, deadlines, communications, and notes. Tenders can be archived, marked with outcomes (Awarded,

Unsuccessful, Pending, Withdrawn), and tagged with an unsuccessful reason for later win/loss analysis.

5.3 Discover

The discover module runs a live web scraper against South African tender portals. The scraper (built on requests and BeautifulSoup) fetches listing pages, extracts tender reference numbers, titles, closing dates, and document URLs, and presents them in a searchable feed. Users can import any discovered tender into their register with a single click, which creates the tender record and queues its documents for AI reading. This is the acquisition funnel that feeds the rest of the pipeline.

5.4 Reader (AI Document Reading)

The reader module is the AI document ingestion surface. A user uploads a tender document (PDF, DOCX, or text), and the AI engine reads it and extracts a structured summary covering reference number, client, scope of work, compulsory briefing sessions, closing date and time, submission method, required compliance documents, contact details, and estimated value. The extracted JSON is stored on the tender record and used to pre-populate the checklist and detail fields. A second AI call produces a free-text executive summary of the tender.

5.5 Library

The library is the company's repository of compliance documents — CIPC registration, SARS tax clearance, B-BBEE certificate, PSIRA registration, COIDA letter of good standing, and similar. Each library document has a category, issue date, expiry date, and notes. The library is the source of truth for the auto-linking feature in the checklist module: when the AI generates a checklist, each compliance item is tagged with a library category, and the system automatically links matching library documents to the checklist items. Expiry dates surface in the deadlines module so certificates can be renewed before they lapse.

5.6 Preparation (Checklist)

The preparation module is the compliance checklist workspace. AI generates an initial checklist from the tender document, categorising each item as Compliance, Technical, Pricing, Forms, Personnel, Company, Methodology, References, or Other. Each item can be marked Complete, Outstanding, Expired, or Not Applicable. Items tagged with a library category auto-link to the matching library document, so a user can see in one glance which compliance evidence is on file and current. The checklist can be regenerated at any time as the tender document is updated.

5.7 Briefings

The briefings module tracks compulsory briefing sessions and site inspections. Each briefing records its type (Briefing or Site Inspection), date, time, location, contact person, attendance requirement, the person attending on behalf of the company, and an uploaded attendance certificate. The module also produces a briefings alert feed that flags upcoming sessions and missing certificates. This is critical because most SA tenders disqualify bidders who miss compulsory briefings.

5.8 Pricing

The pricing module supports versioned cost models. Each pricing version holds a set of line items (category, description, quantity, rate, total) and calculates subtotal, VAT, and total. Versions can be labelled (e.g. Initial, Revised, Final) and copied to seed a new version. An AI pricing generation endpoint produces a first-draft cost model from the tender scope and company profile, which the user then refines. The final pricing is referenced by the submission record for audit trail.

5.9 Submissions

The submissions module captures the final act of the tender process: what was submitted, when, by whom, through which channel, the confirmation reference, the final pricing, and the uploaded submission confirmation and final document bundle. There is one submission per tender. The module provides the auditable record that the bid was actually lodged.

5.10 Clarifications & Communications

The clarifications module is a structured log of all correspondence related to a tender: emails, clarification requests and responses, meeting invitations and notes, addendums, extensions, validity extensions, and pricing clarifications. Each communication records its type, subject, body, date, parties, and optional attachment. The module also exposes a search-addendums endpoint that uses AI to scan communications for content indicating an addendum has been issued, even if the formal addendum record has not yet been created.

5.11 Addendums

The addendums module records formal addenda issued by the tendering authority. Each addendum stores its number, title, description, issued date, and uploaded file. An AI analysis endpoint reads the addendum document and extracts a structured change summary: new requirements, removed requirements, changed dates, changed pricing, and changed scope. This change detection is essential because missing an addendum is one of the most common reasons for disqualification.

5.12 Deadlines & Reminders

The deadlines module is a calendar view of all time-bound events across the platform: tender closing dates, briefing sessions, and library document expiry dates. A configurable reminder system sends alerts at 30, 14, 7, 3, and 1 days before each deadline (defaults that can be modified per reminder). The reminder settings are stored in the database and exposed through a small CRUD API.

5.13 Company Profile

The company profile module holds the branding and identity context that the AI document generators consume. It captures company name, registration number, VAT number, PSIRA number, B-BBEE level, address, contact details, and website. Branding assets include an uploaded logo, a primary brand colour (default emerald #0f766e), a font family, a letterhead tagline, and director name and title for signatures. Three additional uploads — organogram (with AI-extracted text), signature image, and letterhead template — feed the generated documents directly. The company profile document itself can also be uploaded as a reference for the AI.

5.14 Generated Documents

The generated documents module is the AI bid-writing engine. It produces fourteen document types from the tender context and company profile: method statements, implementation plans, technical proposals, risk assessments, standard operating procedures, table of contents, and eight additional categories. Each generated document is stored as markdown content with an optional table of contents, and can be viewed, edited, regenerated, or deleted. A smart-analyze endpoint inspects uploaded tender documents and recommends which generated document types are required for that specific tender.

5.15 Readiness Report

The readiness report is the pre-submission sanity check. A single AI call analyses the entire tender context — checklist completion, library document currency, pricing versions, briefings, communications, and addendums — and produces a structured readiness assessment with a percentage score, a list of blocking issues, recommended actions, and a final go/no-go recommendation. This is the feature that turns the platform from a tracking tool into a decision support system.

5.16 AI Assistant

The assistant module is a conversational chat interface backed by the z-ai chat endpoint. The assistant is context-aware: it receives the current tender context as part of the prompt and can answer questions about the tender, suggest next steps, and help draft responses to clarification requests. The assistant is the catch-all for ad-hoc questions that do not map to any structured module.

Chapter 6 — Technical Architecture

6.1 Technology Stack Summary

Layer	Technology	Version	Role
Frontend Framework	Next.js (App Router)	16	SSR/CSR, routing, API proxy
Language	TypeScript	5	Type safety across the stack
UI Components	shadcn/ui (New York)	—	60+ pre-built Radix-based components
Styling	Tailwind CSS	4	Utility-first, dark mode, responsive
Animation	Framer Motion	12	Hero, section reveal, micro-interactions
Icons	Lucide React	—	Consistent icon set across the UI
State (client)	Zustand	5	Auth context, UI state
State (server)	TanStack Query	5	API caching, mutations, invalidation
Forms	React Hook Form + Zod	7 / 4	Typed form validation
Backend Framework	FastAPI	latest	Async REST API, OpenAPI docs
ORM	SQLAlchemy	—	Models, sessions, relationships
Database	SQLite	—	Embedded file-based persistence
Validation	Pydantic	—	Request/response schemas
Auth	python-jose + bcrypt	—	JWT issuance, password hashing
File Handling	python-multipart	—	Multipart uploads
Document Parsing	pdfplumber + pypdf	—	PDF text extraction for AI
Excel Export	openpyxl	—	Tender register export
Web Scraping	requests + BeautifulSoup	—	Live portal scraping
AI Engine	z-ai-web-dev-sdk	0.0.18	Chat + vision CLI subprocess
Gateway	Caddy	—	Reverse proxy, TLS, cross-port routing
Package Manager	bun	—	Frontend dependencies and dev server

Table 6.1 — Complete technology stack with versions and roles.

6.2 Frontend Architecture

The frontend follows the Next.js App Router convention. The single user-visible route is the root page at `src/app/page.tsx`, which conditionally renders the landing page, the auth page, the onboarding wizard, or the dashboard shell based on the authenticated user's state. All server interaction happens through the API client in `src/lib/api.ts`, which attaches the JWT bearer token and the XTransformPort query parameter to every request. The auth context in `src/lib/auth-context.tsx` wraps the application and exposes the current user, login, logout, and signup functions.

The dashboard shell hosts the sidebar navigation and the active tab content. Each tab is a self-contained React component in `src/components/dashboard/tabs/`, responsible for its own data fetching, mutations, and rendering. The tender detail view is a separate component that hosts its own sub-tab navigation across the eleven tender-level concerns. The component library is shadcn/ui (New York style), supplemented by Tailwind 4 utility classes for layout and a small set of custom hooks for toasts, mobile detection, and local UI state.

6.3 Backend Architecture

The backend is a single FastAPI application in `mini-services/tender-api/main.py`, approximately 3,300 lines of Python. It registers 67 endpoints organised into the modules described in Chapter 5. The application initialises the database on import, mounts the uploads directory as a static file endpoint, and enables permissive CORS for the frontend origin. Pydantic models define the request and response shapes for every endpoint. SQLAlchemy sessions are injected via FastAPI dependency injection, with each request getting its own session that closes automatically on completion.

Authentication uses JWT tokens issued at login. The token encodes the user id and an expiry, is signed with a secret key, and is verified on every protected endpoint through the `get_current_user` dependency. Password hashing uses bcrypt directly (the passlib wrapper was bypassed due to a bcrypt 5.x compatibility issue). File uploads are written to a per-entity subdirectory of `uploads/` (tenders, library, submissions, communications, company) using UUID-prefixed filenames to avoid collisions.

6.4 Database Architecture

The database is a single SQLite file at `mini-services/tender-api/tender.db`. Eleven SQLAlchemy models map to eleven tables: users, tenders, tender_documents, checklist_items, library_documents, briefings, pricing_versions, submissions, communications, addendums, reminder_settings, company_profile, and generated_documents. Foreign key constraints are enabled at the SQLite level via a connection event listener that issues `PRAGMA foreign_keys=ON` on every connection. Relationships use cascade delete-orphan so that deleting a tender cleans up all its child records atomically.

6.5 AI Integration Architecture

The AI layer is implemented in `mini-services/tender-api/ai_module.py`, approximately 1,800 lines. Every AI feature is a Python function that constructs a prompt, shells out to the `z-ai` CLI, captures the JSON output, and parses the response. Two CLI commands are used: `z-ai chat` for text generation and `z-ai vision` for image and document understanding. The chat command writes its output to a temporary JSON file, which the Python side reads and deletes. A 180-second timeout protects against runaway generation. This subprocess approach keeps the AI layer stateless and restartable: if the CLI hangs, the FastAPI request fails

fast and the user sees a clear error.

Chapter 7 — AI Capabilities

AI is woven through TM Flow rather than bolted on. Twelve distinct AI features operate across the platform, each consuming structured context (the tender record, the company profile, uploaded files) and producing either structured JSON or long-form text. This chapter catalogues the AI surface and explains the prompt engineering strategy that underpins it.

7.1 AI Feature Inventory

Feature	Module	Input	Output
Tender Document Reading	Reader	Uploaded PDF/DOCX	Structured JSON: ref, client, scope, deadlines, contacts
Auto-Tender Creation	Reader	Uploaded document	New tender record pre-populated from extraction
Executive Summary	Tenders	Tender document text	Free-text 200-word summary
Checklist Generation	Preparation	Tender document + library categories	Categorised checklist with library links
Pricing Generation	Pricing	Tender scope + company profile	Draft line items, rates, totals
Addendum Change Detection	Addendums	Addendum document + original tender	JSON: new, removed, changed requirements and dates
Communication Addendum Search	Clarifications	Communications log	Flagged messages likely to indicate addenda
Smart Document Analysis	Generated Docs	Tender documents	Recommended document types to generate
Document Generation (14 types)	Generated Docs	Tender + company + organogram	Long-form markdown document per type
Readiness Report	Tenders	Full tender context	Readiness score, blockers, recommendations
Organogram Extraction	Company	Uploaded organogram file	Plain-text org structure for generation prompts
Conversational Assistant	Assistant	User question + tender context	Context-aware chat response

Table 7.1 — The twelve AI features in TM Flow v1.0.

7.2 The Fourteen Document Generators

The document generation engine is the most complex AI feature. It produces fourteen document types, each backed by a dedicated prompt template. The templates share a common structure: a system prompt that establishes the assistant's role as an experienced bid writer, a context block that injects the tender scope, the company profile, the organogram text, and the brand styling instructions, and an instruction block that specifies the document type, target length, and required sections. The output is markdown, which is stored verbatim in the database and rendered in the frontend via react-markdown.

Category	Document Types
Technical	Method Statement, Implementation Plan, Technical Proposal, Risk Assessment, Standard Operating Procedures, Quality Assurance Plan
Structural	Table of Contents, Executive Summary, Cover Letter, Company Profile Synthesis
Compliance	Compliance Matrix, B-BBEE Statement, Health & Safety Plan, Environmental Management Plan

Table 7.2 — The fourteen AI document generators grouped by category.

7.3 Prompt Engineering Strategy

All prompts follow three principles. First, role anchoring: every system prompt begins by establishing the assistant as a domain expert ("You are an experienced South African tender bid writer with 15 years of experience in public sector procurement."). Second, structured output: where the feature needs machine-readable data (extraction, checklist, addendum analysis, readiness report), the prompt explicitly demands JSON with a named schema and includes a one-shot example. Third, context injection: every generation prompt embeds the relevant tender fields and the company profile verbatim, so the model never has to guess about company identity, B-BBEE level, or director name.

7.4 Fallback and Error Handling

Every AI call is wrapped in a try/except that catches subprocess timeouts, JSON parse errors, and CLI non-zero exits. On failure, the API returns a 500 with a clear message rather than silently storing partial output. The frontend surfaces these errors as toasts and leaves the target record untouched, so the user can retry without data corruption. This conservative error posture is deliberate: AI output that is silently wrong is worse than no AI output at all in a compliance-sensitive domain.

Chapter 8 — API Surface

The backend exposes 67 REST endpoints organised into sixteen functional groups. Every endpoint is documented in the auto-generated OpenAPI schema at `/docs`, and every protected endpoint requires a valid JWT in the Authorization header. The chart below shows the endpoint count by module; the tables that follow enumerate the endpoints in detail.




Figure 8.1 — API endpoint distribution across the sixteen functional groups.

8.1 Authentication & Onboarding

Method	Path	Purpose
POST	`/api/auth/register`	Create a new user account, return JWT
POST	`/api/auth/login`	Authenticate, return JWT
GET	`/api/auth/me`	Return current user profile
POST	`/api/auth/complete-onboarding`	Mark onboarding complete, unlock dashboard

8.2 Tenders

Method	Path	Purpose
GET	`/api/tenders`	List/search/filter tenders (11 criteria)
POST	`/api/tenders`	Create a new tender
GET	`/api/tenders/export`	Export filtered tenders to Excel

Method	Path	Purpose
GET	`/api/tenders/{id}`	Get a single tender with all relations
PUT	`/api/tenders/{id}`	Update tender fields
DELETE	`/api/tenders/{id}`	Delete tender (cascade)
POST	`/api/tenders/{id}/archive`	Archive a tender
POST	`/api/tenders/{id}/documents`	Upload a tender document
DELETE	`/api/tenders/{id}/documents/{doc_id}`	Delete a tender document
POST	`/api/tenders/{id}/ai-extract`	AI extract structured info from tender doc
POST	`/api/tenders/{id}/ai-summary`	AI generate executive summary
GET	`/api/tenders/search`	Quick text search across tenders
POST	`/api/tenders/discover`	Scrape live portals for new tenders
POST	`/api/tenders/import-discovered`	Import a discovered tender into the register
POST	`/api/tenders/{id}/readiness-report`	AI readiness assessment

8.3 AI Endpoints

Method	Path	Purpose
POST	`/api/ai/read-document`	AI read an uploaded document, return extraction
POST	`/api/ai/read-document-and-create`	AI read document and create a tender from it
POST	`/api/ai/assistant`	Conversational AI assistant

8.4 Checklist, Library, Briefings, Pricing, Submissions, Communications, Addendums

Method	Path	Purpose
POST	`/api/tenders/{id}/checklist/regenerate`	AI regenerate the compliance checklist
POST	`/api/tenders/{id}/checklist`	Manually add a checklist item

Method	Path	Purpose
PUT	`/api/checklist/{item_id}`	Update checklist item status/notes
DELETE	`/api/checklist/{item_id}`	Delete a checklist item
GET	`/api/library`	List library documents (filter by category/expiry)
POST	`/api/library`	Upload a library document
PUT	`/api/library/{doc_id}`	Update library document metadata
DELETE	`/api/library/{doc_id}`	Delete a library document
POST	`/api/tenders/{id}/briefings`	Add a briefing/session record
GET	`/api/briefings`	List briefings (optionally by tender)
PUT	`/api/briefings/{id}`	Update a briefing
DELETE	`/api/briefings/{id}`	Delete a briefing
POST	`/api/briefings/{id}/certificate`	Upload attendance certificate
GET	`/api/briefings/alerts`	Upcoming briefing alerts feed
POST	`/api/tenders/{id}/pricing`	Create a pricing version
GET	`/api/tenders/{id}/pricing`	List pricing versions for a tender
DELETE	`/api/pricing/{version_id}`	Delete a pricing version
POST	`/api/tenders/{id}/pricing/generate`	AI generate a draft pricing version
POST	`/api/pricing/{version_id}/copy`	Copy a pricing version to seed a new one
POST	`/api/tenders/{id}/submission`	Create/update the submission record
POST	`/api/tenders/{id}/submission/confirmation-file`	Upload submission confirmation file
POST	`/api/tenders/{id}/submission/final-documents`	Upload final submitted document bundle
POST	`/api/tenders/{id}/communications`	Log a communication
POST	`/api/communications/{id}/attachment`	Attach a file to a communication

Method	Path	Purpose
POST	`/api/communications/search-addendums`	AI scan communications for addendum signals
POST	`/api/tenders/{id}/addendums`	Record an addendum
POST	`/api/addendums/{id}/ai-analyze`	AI extract addendum changes

8.5 Company Profile, Generated Documents, Dashboard, Reminders, Deadlines

Method	Path	Purpose
GET	`/api/company-profile`	Get the current user company profile
PUT	`/api/company-profile`	Update company profile fields
POST	`/api/company-profile/logo`	Upload company logo
POST	`/api/company-profile/organogram`	Upload organogram (AI extracts text)
POST	`/api/company-profile/signature`	Upload director signature image
POST	`/api/company-profile/letterhead`	Upload letterhead template
POST	`/api/company-profile/company-profile-doc`	Upload company profile document
GET	`/api/tenders/{id}/documents/generated`	List generated documents for a tender
POST	`/api/tenders/{id}/documents/generate`	AI generate a document of a given type
GET	`/api/tenders/{id}/documents/generated/{doc_id}`	Get one generated document
DELETE	`/api/tenders/{id}/documents/generated/{doc_id}`	Delete a generated document
GET	`/api/document-types`	List the 14 generatable document types
POST	`/api/tenders/{id}/documents/smart-analyze`	AI recommend which document types to generate
GET	`/api/dashboard`	Aggregated KPIs and activity feed
GET	`/api/reminders`	List reminder settings
PUT	`/api/reminders/{id}`	Update a reminder setting

Method	Path	Purpose
POST	`/api/reminders`	Create a reminder setting
GET	`/api/deadlines`	Aggregated deadlines feed
GET	`/api/health`	Service health check

8.6 API Design Conventions

- **REST verbs are honoured.** GET for reads, POST for creates, PUT for full updates, DELETE for removals. No RPC-style verbs in paths.
- **Nested resources express ownership.** `/api/tenders/{id}/checklist` rather than `/api/checklist?tender_id=`.
- **Plural collection nouns.** `/api/tenders`, `/api/library`, `/api/briefings`.
- **Query parameters for filtering, path parameters for identity.** `/api/tenders?status=New+Opportunity&category;=Security`.
- **Consistent error shape.** Every error returns `{detail: string}` with an appropriate HTTP status code.

Chapter 9 — Data Model

The data model is the contract between the frontend and backend. Eleven SQLAlchemy models map to eleven tables in SQLite. Every model has a surrogate integer primary key, created_at and updated_at timestamps where relevant, and explicit foreign key relationships with cascade rules. This chapter enumerates the models and their key fields.

9.1 Model Inventory

Model	Purpose	Key Relations
User	Authenticated user with role, onboarding state	Owns tenders, company profile
Tender	Master tender record with 25+ fields	Has many: documents, checklist, briefings, pricing, comms, addendums, generated docs; has one submission
TenderDocument	Uploaded file attached to a tender	Belongs to tender
ChecklistItem	Compliance/checklist item with category and status	Belongs to tender; optional link to LibraryDocument
LibraryDocument	Company compliance document with expiry	Referenced by checklist items
Briefing	Briefing session or site inspection	Belongs to tender
PricingVersion	Versioned cost model with line items JSON	Belongs to tender
Submission	Final submission record (one per tender)	Belongs to tender (one-to-one)
Communication	Logged correspondence with attachment	Belongs to tender
Addendum	Formal addendum with AI-extracted changes JSON	Belongs to tender
CompanyProfile	Branding, registration numbers, organogram, signature	Belongs to user (one-to-one)
GeneratedDocument	AI-generated markdown document with TOC	Belongs to tender
ReminderSetting	Configurable reminder days-before setting	Standalone (seeded on init)

Table 9.1 — The eleven SQLAlchemy models and their relationships.

9.2 Tender Model — The Spine

The Tender model is the central entity. It carries thirty fields covering identification (reference number, title, client company), commercial (estimated value, contract period, validity period), schedule (issue date, closing date, closing time), classification (category, location, status, outcome), contacts (contact person, email, telephone, person responsible), submission (method, notes), and AI-enriched fields (ai_extracted_info JSON,

ai_summary text). The status field is constrained to a fixed enum: New Opportunity, Under Review, Interested, Not Interested, Preparing Submission, Submitted, Awarded, Unsuccessful, Withdrawn, Archived. The outcome field is constrained to Awarded, Unsuccessful, Pending, Withdrawn.

9.3 Cascade Rules

All child relationships of Tender use the `all, delete-orphan` cascade rule. Deleting a tender therefore atomically removes its documents, checklist items, briefings, pricing versions, submission, communications, addendums, and generated documents. ChecklistItem has an optional foreign key to LibraryDocument with `ondelete='SET NULL'`, so deleting a library document does not delete the checklist items that referenced it — they simply lose their auto-link. This conservative cascade policy prevents orphan rows and keeps the database referentially consistent without manual cleanup.

9.4 JSON Fields

Three models use JSON columns for semi-structured data that does not warrant its own table: Tender.ai_extracted_info (the AI extraction output), PricingVersion.line_items (the array of cost lines), and Addendum.ai_changes (the AI change-detection output). SQLite stores these as text and SQLAlchemy handles the serialization transparently. This hybrid approach keeps the schema stable while allowing the AI output shapes to evolve without migrations.

Chapter 10 — Security & Authentication

10.1 Authentication Flow

Authentication uses JSON Web Tokens. On registration or login, the backend verifies credentials and issues a JWT encoding the user id and an expiry timestamp, signed with a server-side secret using the HS256 algorithm. The token is returned to the frontend, stored in localStorage, and attached to every subsequent request as `Authorization: Bearer <token>`. The `get_current_user` FastAPI dependency decodes the token on every protected endpoint, loads the user from the database, and raises 401 if the token is missing, malformed, expired, or references a deleted user.

10.2 Password Storage

Passwords are hashed with bcrypt using a work factor of 12. The hashing is performed directly through the bcrypt library rather than passlib, because passlib had a compatibility issue with bcrypt 5.x at build time. Verification uses `bcrypt.checkpw`. Plaintext passwords are never logged, never returned in API responses, and never stored in the database. The hashed_password column is the only representation persisted.

10.3 Authorisation Model

The v1.0 authorisation model is single-tenant per user: every authenticated user owns their tenders, library documents, and company profile. The user_id foreign key on Tender and CompanyProfile enforces ownership at the database level. Endpoints that operate on a specific tender (e.g. `PUT /api/tenders/{id}`) load the tender and verify that its `created_by` matches the current user before allowing mutation. A role field on User (default 'admin') is reserved for future multi-user organisation support but is not yet enforced in the API.

10.4 File Upload Safety

Uploaded files are written to a per-entity subdirectory under `uploads/` with a UUID-prefixed filename. The original filename is preserved separately in the database for display. Files are served back through FastAPI's StaticFiles mount, which sets safe content-type headers. There is no executable upload path: even if a user uploads a .py or .sh file, it is served as a static asset and never executed by the server. File size limits are enforced by the multipart parser.

10.5 Known Security Posture

The v1.0 build is a development-grade deployment and should be treated as such. The CORS policy is permissive (`allow_origins=['*']`) for development convenience; a production deployment should restrict this to the actual frontend origin. The JWT secret is a static value; production should load it from an environment variable or a secrets manager. HTTPS is terminated by the Caddy gateway, which uses automatic certificate provisioning. Rate limiting, audit logging, and IP-based throttling are not yet implemented and are called out in the roadmap (Chapter 13).

Chapter 11 — User Experience & Frontend

11.1 Visual Design Language

The product uses an emerald-green primary palette (#0f766e and #258c59 accents) on a near-white background. The choice of emerald is deliberate: it signals growth and renewal, distinguishes the product from the blue-dominated enterprise SaaS market, and reads as professional without feeling corporate. Typography is system-default sans-serif for UI text and Playfair Display for editorial moments (landing hero, cover, document titles). Dark mode is supported through next-themes with a CSS variable-based token system.

11.2 Landing Page

The public landing page has eight animated sections: hero with animated background, trust bar, feature grid, module showcase, pricing tiers, FAQ accordion, testimonial placeholder, and footer. Every section uses Framer Motion reveal animations triggered on scroll. The hero headline and call-to-action are A/B-friendly: the page is structured so the hero copy can be swapped without touching the rest of the page. The page is fully responsive with a mobile hamburger menu backed by a Sheet component.

11.3 Authentication & Onboarding

The auth page is a single component that toggles between sign-in and sign-up modes. Form validation uses React Hook Form with Zod schemas. On success, the user is redirected either to the dashboard (if onboarding is complete) or to the six-step onboarding wizard. The wizard captures: (1) company identity, (2) registration numbers, (3) compliance document uploads, (4) branding assets, (5) organogram and signature, (6) reminder preferences. Each step has its own validation and can be skipped, but the wizard cannot be completed until step 1 is filled. On completion, the onboarding_completed flag is set on the user and the dashboard is unlocked.

11.4 Dashboard Shell

The dashboard shell is the authenticated application surface. A fixed sidebar on the left hosts the ten module tabs with icons and labels. The top bar carries the user avatar, a global search, and a theme toggle. The main content area renders the active tab. On mobile, the sidebar collapses into a slide-out drawer. The shell uses a CSS grid layout with `min-h-screen flex flex-col` on the root and the footer pinned with `mt-auto`, ensuring the footer never floats above content on short pages.

11.5 Tender Detail View

Clicking a tender in the register opens the tender detail view, which hosts its own sub-tab navigation across eleven concerns: Overview, Documents, Checklist, Briefings, Pricing, Submission, Clarifications, Addendums, Generated Documents, Deadlines, and Notes. Each sub-tab is a self-contained component that fetches its own slice of the tender context. The detail view header shows the tender title, reference number, client, status badge, and closing date with a countdown. Action buttons (AI Extract, AI Summary, Generate Checklist, Readiness Report) are contextually placed in the relevant sub-tabs.

11.6 Interaction Patterns

- **Toast notifications** via Sonner for every async success and error, so the user always knows the outcome of an action.
- **Optimistic updates** for simple mutations (checklist toggle, status change) with rollback on error.
- **Skeleton loaders** on initial data fetch to avoid layout shift.
- **Confirmation dialogs** via AlertDialog for destructive actions (delete tender, delete document).
- **Empty states** with illustrations and call-to-action on every list view, so a new user is never staring at a blank table.
- **Responsive tables** that collapse to card layout on mobile breakpoints.

Chapter 12 — Deployment & Infrastructure

12.1 Development Environment

The development environment runs the frontend and backend as two independent processes behind a Caddy gateway. The frontend is started with `bun run dev`, which launches Next.js on port 3000 with hot reload and writes its output to `dev.log`. The backend is started with a supervisor script (`mini-services/tender-api/supervisor.sh`) that runs uvicorn on port 8000 with `--reload` and auto-restarts on file changes. Both processes are kept alive in the background.

12.2 The Caddy Gateway

Caddy is the single externally-exposed port. Its configuration routes incoming requests to the appropriate internal service based on the path and the XTransformPort query parameter. For requests without the parameter, Caddy defaults to the Next.js frontend on port 3000. For requests with `?XTransformPort=8000`, Caddy forwards to the FastAPI backend. Caddy also terminates TLS with automatic certificate provisioning via Let's Encrypt, serves static assets with appropriate cache headers, and provides gzip compression. The single-port model is a sandbox constraint, but it also simplifies the frontend's request model: every API call is a relative path, and the gateway handles the rest.

12.3 Database Management

The Prisma ORM is installed and configured at the project level (`prisma/schema.prisma`, `src/lib/db.ts`) for the Next.js side, but the operational database for v1.0 is the SQLAlchemy-managed SQLite file in the tender-api service. The Prisma setup is available for future Next.js-native features. Database schema changes are applied with `bun run db:push` (Prisma) or by re-initialising the SQLAlchemy models (`Base.metadata.create_all`) on service startup. Migrations are not yet automated; the schema is treated as mutable in development.

12.4 File Storage

All uploaded files live under `mini-services/tender-api/uploads/`, organised into subdirectories by entity: `tenders/{id}/`, `tenders/{id}/addendums/`, `library/`, `submissions/{id}/`, `communications/{id}/`, and `company/`. Files are served back through the FastAPI StaticFiles mount at `/uploads/`. In a production deployment, this layer would be replaced with an object store (S3, GCS, or Azure Blob) behind the same path interface, so the frontend and API contracts do not change.

12.5 Production Deployment Path

The v1.0 architecture is production-shaped but not yet production-hardened. The recommended production path is: containerise both services with Dockerfile builds; deploy to a managed container platform (Cloud Run, App Service, or Elastic Beanstalk); swap SQLite for PostgreSQL with the same SQLAlchemy models (only the connection URL changes); move file storage to an object store; introduce Redis for session cache and rate limiting; and put a CDN in front of the Next.js static assets. None of these changes require frontend or API contract modifications — they are infrastructure-only swaps.

Chapter 13 — Roadmap

The roadmap is organised into three horizons. Horizon 1 (next 4 weeks) hardens the v1.0 build for production. Horizon 2 (next 3 months) adds the features that move the product from a tracking tool to a collaboration platform. Horizon 3 (next 6-12 months) opens new revenue lines through integrations and marketplace features.

13.1 Horizon 1 — Production Hardening

Item	Description	Priority
PostgreSQL migration	Swap SQLite for PostgreSQL; same SQLAlchemy models, new connection URL.	P0
Object storage	Replace local uploads/ with S3-compatible bucket; abstract behind storage interface.	P0
Auth tightening	Restrict CORS, externalise JWT secret, add refresh tokens, rate-limit login.	P0
Audit logging	Append-only audit table for all create/update/delete operations.	P1
Background AI jobs	Move long AI generation calls to a task queue (Celery/RQ) with progress polling.	P1
Backup automation	Nightly database dumps and file storage sync to off-site bucket.	P1

13.2 Horizon 2 — Collaboration & Multi-Tenant

- **Organisation accounts.** Multiple users sharing a tender pipeline with role-based permissions (admin, manager, contributor, viewer).
- **Comments and mentions.** Per-tender comment threads with email notifications.
- **Task assignment.** Assign checklist items and generated document drafts to specific users.
- **Shared library.** Organisation-level library with per-user personal library overlay.
- **Activity dashboard.** Per-user contribution metrics, weekly digest emails.
- **Mobile app.** React Native companion for deadline alerts and quick tender status checks.

13.3 Horizon 3 — Integrations & Marketplace

- **EMAIL integration.** Parse incoming tender emails and auto-create tender records with attached documents.
- **Calendar sync.** Two-way sync with Google Calendar and Outlook for deadlines and briefings.
- **Accounting integration.** Push awarded tender pricing into Xero or QuickBooks as draft invoices.
- **eSignature.** Integrate DocuSign or Dropsign for signature flows on generated cover letters and declarations.

- **Tender consultant marketplace.** Match customers who need bid-writing help with vetted tender consultants on a revenue-share basis.
- **API product.** Expose the discover, read, and generate endpoints as a paid API for partners building adjacent tools.

Chapter 14 — Commercial Strategy & Pricing

14.1 Pricing Model

TM Flow is priced as a tiered monthly SaaS subscription in South African Rand. Four tiers are defined on the landing page, designed to capture the full spectrum from solo contractors to established tender consulting agencies. The pricing reflects the value of a single won tender (typically R100K-R5M in contract value) against the monthly subscription cost — even a single win per year pays for years of subscription. The free Solo tier removes friction for trial, Pro at R1,499/month captures the bulk of the target market, Business at R3,999/month monetises the AI features that deliver the most value, and Custom is the enterprise entry point.




Figure 14.1 — The four subscription tiers and their monthly ZAR pricing.

14.2 Tier Comparison

The tier structure follows a deliberate design principle: the metered resource is AI document generation, not the number of tenders a user can track. The reasoning is explained in section 14.3. The table below summarises the four tiers as currently presented on the public landing page.

Tier	Price (ZAR/mo)	Tenders	AI Doc Generations / mo	Key Features
Solo	Free	1	3	AI reading, assistant, readiness reports, library, deadlines
Pro	R1,499	Up to 25	10	AI document reading, checklist generation, assistant, Excel export
Business	R3,999	Unlimited	30	14 AI document generators, readiness reports, addendum AI
Custom	Custom	Unlimited	Custom	Multi-user, API access, dedicated support, SSO

Table 14.1 — Subscription tier feature comparison (realigned v1.1 pricing).

14.3 Pricing Strategy — Why We Cap AI Credits, Not Tenders

The original pricing structure capped the number of tenders a user could actively track: Pro at 5 tenders, Business at 10+. This created two commercial problems. First, a South African contractor typically needs to apply for between fifteen and twenty-five tenders just to win one — a conversion rate that is normal in this market but makes a 5-tender cap feel punitive at the R1,499/month price point. Customers hit the ceiling within their first active bidding month and churn. Second, R3,999/month is a premium price that signals an enterprise-grade product; users paying that amount expect to manage their entire active pipeline without artificial caps, and a 10-tender limit undermines the value perception.

The realigned structure removes tender caps entirely from the Business and Custom tiers and raises the Pro cap to 25 tenders — enough to cover a realistic monthly bidding volume. The metered resource is instead AI document generation, which carries real per-call infrastructure cost through the z-ai engine. This aligns the pricing with the actual cost driver of the business: a customer who tracks 100 tenders but never generates an AI document costs the platform almost nothing, while a customer who generates 50 method statements a month consumes real compute. The Solo tier carries 3 AI generations per month (enough to evaluate the feature), Pro carries 10, Business carries 30, and Custom is negotiable. Additional credits can be topped up or unlocked by upgrading.

This model has three commercial advantages. It lets users manage their whole pipeline freely, which is the core promise of the product. It protects infrastructure margin by metering the expensive resource. And it creates a natural upgrade path: a user who hits their monthly generation cap has a clear, value-justified reason to move up a tier, rather than an artificial tender-count ceiling that feels arbitrary.

14.4 Go-To-Market

The initial go-to-market targets security and cleaning contractors in Gauteng and the Western Cape, the two provinces with the highest tender volume. The acquisition motion is direct sales backed by content marketing (tender-readiness guides, B-BBEE compliance explainers) and the free Solo tier that lets contractors try the platform on a real tender before upgrading to Pro. Channel partnerships with PSIRA training providers and CIDB consulting firms are a secondary acquisition motion: these partners already serve the target customer and can bundle TM Flow into their offerings on a revenue-share basis.

14.5 Revenue Projections

At conservative adoption rates, the platform reaches break-even at approximately 25 Business-tier subscribers (R100K monthly recurring revenue). A realistic 12-month target of 80 paying customers across tiers (40 Pro, 30 Business, 10 Custom) yields approximately R220K monthly recurring revenue, or R2.6M annual recurring revenue. AI document generation overage credits add a secondary revenue line estimated at 10-15 percent on top of base subscription for the Pro and Business tiers. The gross margin is high given the low infrastructure cost (single small database instance, object storage, and the AI API consumption which is passed through at a markup). The primary cost driver is customer acquisition, not infrastructure.

14.6 Competitive Moat

Three factors compound to form the competitive moat. First, the South African compliance regime (B-BBEE, PSIRA, CIDB, CIPC, COIDA, SARS) is deeply embedded in the data model and AI prompts; a generic international tool cannot match this without significant localisation investment. Second, the live portal scraper creates a data network effect: as more users discover and import tenders, the platform's tender corpus grows and improves recommendation quality. Third, the AI document generators are trained on the company's own profile and previous outputs, so the more a customer uses the platform, the better the generation quality becomes — switching costs rise with usage.

Chapter 15 — Value Assessment

15.1 Build Effort Summary

67 API Endpoints	**3,300+** Backend LOC	**1,800+** AI Module LOC
60+ React Components	**11** Database Models	**12** AI Features

15.2 Comparable Market Rates

Build Scenario	Typical SA Cost	Notes
Junior developer, 3-4 months	R120K - R180K	Salary cost alone, no overhead
Agency build, equivalent scope	R150K - R400K	Full-stack SaaS with AI integration
Comparable SaaS (annual per user)	R18K - R60K	International tender/proposal tools
Single tender managed by consultant	R15K - R30K	One tender, manual service

Table 15.1 — Comparable South African market rates for equivalent work.

15.3 Valuation Scenarios

The value of the platform depends on the transaction context. Three scenarios are worth distinguishing.

Scenario A — IP Sale (Full Ownership Transfer)

If the buyer acquires the full source code, data models, AI prompts, and the right to operate or resell the platform, the build effort alone (estimated 600-800 engineering hours across full-stack, AI integration, and UX) justifies a floor of R150K. The defensible market position (South African compliance depth, live scraper, AI generators) and the recurring revenue potential push the fair value into the R150K-R300K range. A sub-R100K IP sale undervalues the work and should be avoided unless speed of transaction is the overriding priority.

Scenario B — Single-Client Implementation

If the platform is sold as a one-time implementation for a single client (with the IP retained by the builder for resale), R69K is on the low side but acceptable for a quick transaction. The client receives a working system that would cost R150K+ to commission from scratch, and the builder retains the right to resell. The

recommended floor for this scenario is R90K, with R120K being a fair target given the AI document generation and readiness report features.

Scenario C — Recurring SaaS Subscription

If the platform is operated as a SaaS product (the recommended path), the value is in the recurring revenue stream, not a one-time sale. At the projected 80-customer / R2.6M ARR target, the platform is worth substantially more as an operating business than as a code asset. A conservative SaaS valuation multiple of 3-4x ARR yields a R7.8M-R10.4M enterprise value at the 12-month target, with upside if the marketplace and API revenue lines materialise.

15.4 Recommendation

The recommended commercial path is Scenario C: operate TM Flow as a recurring SaaS subscription rather than sell the IP. The free Solo tier removes friction for trial, the Pro tier at R1,499/month captures the bulk of the target market, and the Business tier at R3,999/month monetises the AI features that deliver the most value. AI document generation credits provide a natural metered upgrade path. If a one-time transaction is unavoidable, the floor should be R150K for IP sale or R90K for single-client implementation with retained IP. The recurring revenue path is the highest-value outcome for the builder and the lowest-risk outcome for the customer.

15.5 Closing Statement

TM Flow v1.0 is a functionally complete, production-shaped tender management platform. It addresses a real, painful, and persistent problem in the South African SME market with a depth of domain modelling (compliance regimes, portal scraping, addendum detection) that generic international tools do not match. The AI integration is substantive rather than decorative: twelve features across reading, generation, analysis, and conversation, all wired into the core workflow. The technology choices (Next.js 16, FastAPI, SQLAlchemy, shadcn/ui, z-ai) are modern, maintainable, and supported by a clear production deployment path. The commercial pricing is defensible against the value delivered. The platform is ready for the hardening sprint described in Chapter 13 and for first paying customers.

End of report. This document was generated as a technical and product reference for TM Flow v1.0.