


Practice 7

- Convolution Lowering SW


Computing Memory Architecture Lab.

Final Project Overview: Matrix Multiplication IP



Final Project Overview: Matrix Multiplication IP

W5



Final Project Overview: Matrix Multiplication IP

- Our original application



One layer in MLP (Software running on CPU)

```
for(j=0; j<1024; j+=8) {  
  for(i=0; i<256; i+=8) {  
    MV function on Hardware  
    Output[i] += Input[j]*W[i,j] + Input[j+1]*W[i,j+1] + ...  
    Output[i+1] += Input[j]*W[i+1,j] + Input[j+1]*W[i+1,j+1] + ...  
    ...  
    Output[i+7] += Input[j]*W[i+7,j] + Input[j+1]*W[i+7,j+1] + ...  
  }  
}
```

- Advanced application

One layer in Convolution with Convolution Lowering

```
for(j=0; j<1024; j+=8) {  
  for(i=0; i<256; i+=8) {  
    MV function on Hardware  
    Output[i] += Input[j]*W[i,j] + Input[j+1]*W[i,j+1] + ...  
    Output[i+1] += Input[j]*W[i+1,j] + Input[j+1]*W[i+1,j+1] + ...  
    ...  
    Output[i+7] += Input[j]*W[i+7,j] + Input[j+1]*W[i+7,j+1] + ...  
  }  
}
```




Main Practice



Lab 7: Overview

■ Goal

- Implement convolution lowering in C++
- Integrate convolution lowering into the pretrained model(CNN)
 - On MNIST
- Example) Convolutional Neural Network




MNIST, CIFAR 10




Dataset	MNIST	CIFAR 10
Category	digits(0-9)	airplane, automobile, ..., truck
Image size	28x28	32x32
Color	Gray scale	RGB
# images (training/test)	60000/10000	60000/10000

(pretrained) Convolutional Network Network(CNN)

- Input: **28x28** pixels \rightarrow **6 3x3 Conv** \rightarrow **30** values \rightarrow **10** values
 - 1st Conv: **28x28** inputs \rightarrow 6 3x3 Conv \rightarrow 6 26x26 outputs
 - 2nd FC: $6 \cdot 26 \cdot 26 (=4056)$ inputs \rightarrow FC \rightarrow 30 outputs
 - 3rd FC: 30 inputs \rightarrow FC \rightarrow 10 outputs



Implementation Detail: 1st layer



1) Convolution → Convolution Lowering

$$\text{Output}[0][0, 0] = \sum_{i,j} \text{Input}[i,j] * W[0][i,j]$$

$$\text{Output}[0][0, 1] = \sum_{i,j} \text{Input}[i,j+1] * W[0][i,j]$$

...

$$\text{Output}[5][25, 25] =$$


$$\sum_{i,j} \text{Input}[i+25,j+25] * W[5][i,j]$$

2) Activation(ReLU)

$$\text{Output}[0][0, 0] = \max(0, \text{Output}[0][0, 0])$$


...

$$\text{Output}[5][25, 25] = \max(0, \text{Output}[5][25, 25])$$




Convolution: 3D Input Case

- A receptive field in input feature maps gives an output neuron
- Each output feature map has its own set of kernel weights




Convolution with Matrix Multiplication (called Convolution Lowering)

- Input: $3 \times 3 \times 3$
- Output: $2 \times 2 \times 2$
- Convolutional kernel: $3 \times 2 \times 2$



Implementation Detail: 2nd layer



1) (MV) Multiplication

$$\text{Output}[0] = \sum_j \text{Input}[j] * W[0,j]$$

$$\text{Output}[1] = \sum_j \text{Input}[j] * W[1,j]$$

...

$$\text{Output}[29] = \sum_j \text{Input}[j] * W[29,j]$$


2) Activation(ReLU)

$$\text{Output}[0] = \max(0, \text{Output}[0])$$


$$\text{Output}[1] = \max(0, \text{Output}[1])$$

...

$$\text{Output}[29] = \max(0, \text{Output}[29])$$



Implementation Detail: 3rd layer



1) (MV) Multiplication

$$\text{Output}[0] = \sum_j \text{Input}[j] * W[0,j]$$

$$\text{Output}[1] = \sum_j \text{Input}[j] * W[1,j]$$

...

$$\text{Output}[9] = \sum_j \text{Input}[j] * W[9,j]$$

2) Softmax

$$\text{Output}[0] = \text{softmax}(\text{Output}[0])$$

...

$$\text{Output}[9] = \text{softmax}(\text{Output}[9])$$

3) Argmax

$$\text{Prediction} = \text{argmax}_i (\text{Output}[i: 0 \sim 9])$$

Install

- **Connect to the Server we distributed in Lab02**
- Code download
 - \$ git clone https://github.com/tahsd/hsd20_lab07
 - \$ cd hsd20_lab07
- Dataset download
 - \$ bash download.sh

Skeleton Code

```
.
|- Makefile
|- src
| |- fpga_api.cpp          # IMPLEMENT THIS!(only convLowering)
| |- fpga_api_on_cpu.cpp  # IMPLEMENT THIS!(only convLowering)
| |- tf_dnn.cpp           # Lab 07, Note: Don't need to edit
| |- caffe_dnn.cpp        # Lab 02, Note: Don't need to edit
| `-- py_lib.cpp          # don't need to edit
|
|- eval.py                # Evaluate the pretrained model
|
|- download.sh
|- pretrainend_weights
| |- cnn_weights.txt       # Lab 07, CNN(28x28x1->6 3x3conv->fc30->fc10)
| `-- mlp_iter_10000.caffemodel # Lab 02, MLP(784-1200-1200-10)
|
|- include
`-- data
```

Implement Convolution Lowering

- Edit `./src/fpag_api.cpp`, `./src/fpag_api_on_cpu.cpp`


```
// src/fpag_api.cpp, src/fpag_api_on_cpu.cpp
void FPGA::convLowering(const vector<vector<vector<vector<float>>>>& cnn_weights,
                        vector<vector<float>>& new_weights,
                        const vector<vector<vector<float>>>& inputs,
                        vector<vector<float>>& new_inputs) {

    /*
     * Arguments:
     *
     * conv_weights: [conv_channel, input_channel, conv_height, conv_width]
     * new_weights: [?, ?]
     * inputs: [input_channel, input_height, input_width]
     * new_inputs: [?, ?]
     *
     */
    ...
}
```

- [Note] Fill the function `largeMV` that you implemented in Lab 02

Convolution Lowering

- Input: 3x3x3
- Output: 2x2x2
- Convolutional kernel: 3x2x2



Run

- Edit `./src/fpga_api.cpp`, `./src/fpag_api_on_cpu.cpp`
 - void convLowering(...)
- Build
 - \$ make
- Evaluate
 - \$ python eval.py --num_test_images 10 --m_size 64 --v_size 64 --network cnn --run_type cpu
- Options
 - num_test_images : 1~10000
 - m_size, v_size : 8, 16, 32, 64, ...
 - network: cnn, mlp
 - cnn(lab07), mlp(lab2)
 - run_type: cpu
 - We don't have FPGA now, so you have to write this option when you eval

Example: Download datasets

```
zed@debian-zynq:~/ :master$ bash download.sh
--2019-05-13 17:56:45-- https://dl.dropbox.com/s/mdwy0kzf57nfl5f/t10k
Resolving dl.dropbox.com (dl.dropbox.com)... 162.125.80.6, 2620:100:60
Connecting to dl.dropbox.com (dl.dropbox.com)|162.125.80.6|:443... con
HTTP request sent, awaiting response... 302 FOUND
Location: https://dl.dropboxusercontent.com/s/mdwy0kzf57nfl5f/t10k-ima
--2019-05-13 17:56:46-- https://dl.dropboxusercontent.com/s/mdwy0kzf5
Resolving dl.dropboxusercontent.com (dl.dropboxusercontent.com)... 162
Connecting to dl.dropboxusercontent.com (dl.dropboxusercontent.com)|16
HTTP request sent, awaiting response... 200 OK
Length: 7840016 (7.5M) [application/octet-stream]
Saving to: 'data/t10k-images.idx3-ubyte'

data/t10k-images.idx3-ubyte                               100%[=====
2019-05-13 17:56:49 (3.70 MB/s) - 'data/t10k-images.idx3-ubyte' saved
```

Example: Build your implementations

```
zed@debian-zynq:~/...:master$ make
protoc -I=./proto --cpp_out=./proto proto/caffe.proto
g++ -fPIC -std=c++11 -O3 -I ./include -I./proto -o build/py_lib.o
g++ -fPIC -std=c++11 -O3 -I ./include -I./proto -o build/caffe.pb
g++ -fPIC -std=c++11 -O3 -I ./include -I./proto -o build/caffe_dr
g++ -fPIC -std=c++11 -O3 -I ./include -I./proto -o build/tf_dnn.o
g++ -fPIC -std=c++11 -O3 -I ./include -I./proto -o build/fpga_api
g++ -shared -o build/libpylib_cpu.so build/py_lib.o build/caffe.
g++ -fPIC -std=c++11 -O3 -I ./include -I./proto -o build/fpga_api
g++ -shared -o build/libpylib_fpga.so build/py_lib.o build/caffe
```

Example: Evaluation

```
zed@debian-zynq:~/...:master$ sudo python eval.py --num_test_images 10 --m_size 8 --v_size 64 --network mlp --run_type cpu
[*] Arguments: Namespace(m_size=8, network='mlp', num_test_images=10, run_type='cpu', v_size=64)
[*] Read MNIST...
[*] The shape of image: (10, 28, 28)
[*] Load the network...
[*] Run tests...
[*] Statistics...
{'accuracy': 0.9,
 'avg_num_call': 4838,
 'm_size': 8,
 'total_image': 10,
 'total_time': 0.5971291065216064,
 'v_size': 64}
```

- Accuracy(10,000 images)
 - MLP(Lab 2): around 95%
 - CNN(Lab 11): around 98%

Checklists

- MLP(Lab 2)

- \$ sudo python eval.py --num_test_images 10 --m_size 64 --v_size 64 --
network mlp --run_type cpu

- MV

- \$ sudo python eval.py --num_test_images 10 --m_size 64 --v_size 64 --
network mlp **--run_type cpu**

- Convolution Lowering(Lab 7)

- \$ sudo python eval.py --num_test_images 10 --m_size 64 --v_size 64 --
network cnn --run_type cpu

- Other arguments

- num_test_images, m_size, v_size, ...

Example: Benchmark

- \$ bash benchmark.sh
- Please remove 'sudo' command in benchmark.sh file

```
zed@debian-zynq:~/ :master$ sudo bash benchmark.sh
[*] Arguments: Namespace(m_size=64, network='mlp', num_test_images=100, run_type='cpu', v_size=
[*] Read MNIST...
[*] The shape of image: (100, 28, 28)
[*] Load the network...
[*] Run tests...
[*] Statistics...
{'accuracy': 0.08,
 'avg_num_call': 627,
 'm_size': 64,
 'total_image': 100,
 'total_time': 3.223191022872925,
 'v_size': 64}

=> Accuracy should be 0.97

[*] Arguments: Namespace(m_size=64, network='mlp', num_test_images=100, run_type='fpga', v_size=
[*] Read MNIST...
[*] The shape of image: (100, 28, 28)
[*] Load the network...
[*] Run tests...
[*] Statistics...
{'accuracy': 0.07,
 'avg_num_call': 627,
 'm_size': 64,
 'total_image': 100,
 'total_time': 6.748210906982422,
 'v_size': 64}

=> Accuracy should be 0.97

[*] Arguments: Namespace(m_size=64, network='cnn', num_test_images=100, run_type='cpu', v_size=
[*] Read MNIST...
[*] The shape of image: (100, 28, 28)
[*] Load the network...
[*] Run tests...
[*] Statistics...
{'accuracy': 0.08,
 'avg_num_call': 741,
 'm_size': 64,
 'total_image': 100,
 'total_time': 3.8482890129089355,
 'v_size': 64}

=> Accuracy should be 1.0
```

Homework

■ Requirements

- Result

- Attach your codes(e.g., fpga_api.cpp, fpga_api_on_cpu.cpp)
 - Refer Lab02
- Attach your benchmark.sh results with [student_number, name]
 - Refer Lab02

- Report

- Explain Convolution Lowering that you implemented
- In your own words
- Either in Korean or in English
- # of pages does not matter
- **PDF only!!**

- **Result + Report to a .zip**

■ Upload (.zip) file on ETL

- Submit one (.zip) file
 - zip file name : [Lab07]name.zip (ex : [Lab07]홍길동.zip)
- Due: 5/5(TUE) 23:59
 - **No Late Submission**

```
// src/fpga_api.cpp
void FPGA::largeMV(const float* l
                    float* output
{
    // IMPLEMENT HERE
    ...
}
```