

2026 INTERNATIONAL B2B EDITION

PRO / MAX TRADE GUIDE

Modular outdoor kitchen systems for distributors, contractors, developers and hospitality projects.

CONTROLLED COMMERCIAL REFERENCE

- PRO 2300 mm and MAX 2900 mm defined formats
- 304 standard; 316 order-selected stainless upgrade
- System Shell, Appliance-Ready or Full Package supply paths
- Order-specific specifications, QC and compliance records

KAISTEEL LIMITED

Hong Kong contracting party | Foshan production base
sales@kaisteelkitchen.com | kaisteelkitchen.com



MATERIALS AND SUPPLY BOUNDARY

STRUCTURAL FRAME

Q235 galvanized-steel frame. Final section sizes, coating requirements and acceptance criteria are fixed in the approved BOM and drawings.

CABINET BODY AND DOORS

304 stainless steel is standard. 316 stainless steel is available as an order-selected upgrade. Panels use an aluminum honeycomb-filled core.

SINK, FAUCET AND WORKTOP

Project-selected 304 or 316 stainless steel. Worktop options: 6, 8 or 10 mm, subject to the approved configuration.

CHOOSE THE SUPPLY PATH BEFORE CHOOSING APPLIANCES

SYSTEM SHELL

Structural enclosure, cabinetry, agreed worktop and non-regulated components. Cooking, refrigeration and regulated equipment are sourced locally.

APPLIANCE-READY

Approved openings and documented service interfaces for buyer-selected, locally certified appliances and licensed destination installation.

FULL PACKAGE

Selected appliances are supplied only after exact model, certificate scope, voltage, gas type and destination requirements are reviewed.

CERTIFICATION BOUNDARY

KAISTEEL does not itself hold CE, UL, SAA or CSA marks for the complete outdoor kitchen system. Applicable marks belong to the exact regulated appliance or component and must match the approved model and destination market.

PRO 2300 MM



COMPACT TRADE FORMAT

- Overall reference: 2300 x 880 x 2400 mm
- Net weight reference: 578 kg per unit
- Assembled or modular delivery
- Residential, dealer and hospitality programs

CONFIGURATION BOUNDARY

The image shows a possible configured unit. Appliances, lighting, electrical parts and utility interfaces are included only when listed in the approved quotation and BOM.

40HQ PLANNING

13 assembled or up to 26 modular units. Preliminary only; final quantity follows the approved packing plan.

ASSEMBLY REFERENCE

A recorded trial used two people and approximately four hours per unit. Site conditions and final configuration control actual time.

MATERIAL OPTIONS

304 standard or 316 order-selected stainless cabinet body, doors, sink, faucet and worktop, as defined in the BOM.

MAX 2900 MM



EXTENDED FLIP-COVER FORMAT

- Overall reference: 2900 x 960 x 2400 mm
- Net weight reference: 682 kg per unit
- Expanded work area and open-canopy presentation
- Assembled or modular delivery

CONFIGURATION BOUNDARY

The image shows a possible configured unit. Lift mechanisms, appliances, lighting and utility interfaces are included only when listed in the approved quotation and BOM.

40HQ PLANNING

8 assembled or up to 16 modular units. Preliminary only; final quantity follows the approved packing plan.

ASSEMBLY REFERENCE

A recorded trial used two people and approximately four hours per unit. Site conditions and final configuration control actual time.

MATERIAL OPTIONS

304 standard or 316 order-selected stainless cabinet body, doors, sink, faucet and worktop, as defined in the BOM.

FROM BUYER BRIEF TO SHIPMENT RELEASE

01

BUYER BRIEF

Market, model, quantity, appliances and target date.

02

QUOTATION

Scope, Incoterm, packing method and document requirements.

03

TECHNICAL FREEZE

Approved drawings, BOM, interfaces and acceptance criteria.

04

PRODUCTION AND QC

Configuration checks and order-specific evidence collection.

05

PACKING AND RELEASE

Approved packing plan and Compliance Dossier index.

LIMITED WARRANTY

15-year structural coverage, 5-year surface-finish coverage and 1-year functional-component coverage, subject to the published Limited Warranty and its exclusions.

TRANSIT-DAMAGE REMEDY

Target production time for approved replacement parts is 7-10 working days after written claim approval, subject to part, material and finish confirmation. Product charge is waived; freight, insurance, duties, taxes and destination costs remain the buyer's responsibility unless agreed otherwise.

EVIDENCE POLICY

Material grades, tests and certificates must match the exact configuration, batch, regulated model and destination. Required records are defined at Technical Freeze.

TARGET FACTORY LEAD TIME

30 days after configuration approval and Technical Freeze is a planning target, not a fixed promise. Final production and shipment timing is confirmed in the quotation and order documents.

PACKING, LOADING AND PILOT ORDER

PRELIMINARY 40HQ LOADING REFERENCE

MODEL	FULLY ASSEMBLED	MODULAR	CONFIRMATION BASIS
PRO 2300	13 units	Up to 26 units	Approved configuration and packing plan
MAX 2900	8 units	Up to 16 units	Approved configuration and packing plan

These are preliminary planning references, not freight guarantees. Final loading depends on product configuration, external packing dimensions, weight distribution, handling limits and the approved loading plan.

STANDARD FIRST ORDER

A standard PRO or MAX evaluation unit can be ordered without a full container. CUSTOM projects and modular-delivery formats remain full-container programs.

SAMPLE CREDIT

Eligible sample product value may be credited against a qualifying 40HQ order within 180 days. A 20GP may qualify only when the quotation expressly approves the exception and available credit. Freight, duties, taxes and the fixed USD 150 LCL wooden-crate charge per sample unit are excluded.

PACKING METHOD

Full-container units use an approved pallet-based protection system. Loose or sample units use a wooden export crate. Final dimensions are confirmed in the packing plan.

REQUEST AN ORDER-SPECIFIC CONFIGURATION REVIEW

Send destination, buyer type, model, quantity, appliance market and target date.

sales@kaisteelkitchen.com