

CLI

Configuration

Configure the Agent CLI using the `cli-config.json` file.

File location

Type	Platform	Path
Global	macOS/Linux	<code>~/.cursor/cli-config.json</code>
Global	Windows	<code>\$env:USERPROFILE\.cursor\cli-config.json</code>
Project	All	<code><project>/.cursor/cli.json</code>

 Only permissions can be configured at the project level. All other CLI settings must be set globally.

Override with environment variables:

- `CURSOR_CONFIG_DIR` : custom directory path
- `XDG_CONFIG_HOME` (Linux/BSD): uses `$XDG_CONFIG_HOME/cursor/cli-config.json`

Schema

Required fields

Field	Type	Description
<code>version</code>	number	Config schema version (current: <code>1</code>)
<code>editor.vimMode</code>	boolean	Enable Vim keybindings (default: <code>false</code>)
<code>permissions.allow</code>	string[]	Permitted operations (see Permissions)
<code>permissions.deny</code>	string[]	Forbidden operations (see Permissions)

Optional fields

Field	Type	Description
<code>model</code>	object	Selected model configuration
<code>hasChangedDefaultModel</code>	boolean	CLI-managed model override flag
<code>network.useHttp1ForAgent</code>	boolean	Use HTTP/1.1 instead of HTTP/2 for agent connections (default: <code>false</code>)
<code>attribution.attributeCommitsToAgent</code>	boolean	Add "Made with Cursor" trailer to Agent commits (default: <code>true</code>)
<code>attribution.attributePRsToAgent</code>	boolean	Add "Made with Cursor" footer to Agent PRs (default: <code>true</code>)

Examples

Minimal config

```
1 {
2   "version": 1,
3   "editor": { "vimMode": false },
4   "permissions": { "allow": ["Shell(ls)", "deny": [] }
5 }
```

Enable Vim mode

```
1 {
2   "version": 1,
3   "editor": { "vimMode": true },
4   "permissions": { "allow": ["Shell(ls)", "deny": [] }
5 }
```

Configure permissions

```
1 {
2   "version": 1,
3   "editor": { "vimMode": false },
4   "permissions": {
5     "allow": ["Shell(ls)", "Shell(echo)",
6     "deny": ["Shell(rm)"]
7   }
8 }
```

See [Permissions](#) for available permission types and examples.

Troubleshooting

Config errors: Move the file aside and restart:

```
mv ~/.cursor/cli-config.json ~/.cursor/cli-config.json.bad
```

Changes don't persist: Ensure valid JSON and write permissions. Some fields are CLI-managed and may be overwritten.

Notes

- Pure JSON format (no comments)
- CLI performs self-repair for missing fields
- Corrupted files are backed up as `.bad` and recreated
- Permission entries are exact strings (see [Permissions](#) for details)

Models

You can select a model for the CLI using the `/model` slash command.

```
1 /model auto
2 /model gpt-5.2
3 /model sonnet-4.5-thinking
```

See the [Slash commands docs](#) for other commands.

Proxy configuration

If your network routes traffic through a proxy server, configure the CLI using environment variables and the config file.

Environment variables

Set these environment variables before running the CLI:

```
1 export HTTP_PROXY=http://your-proxy:port
2 export HTTPS_PROXY=http://your-proxy:port
3 export NODE_USE_ENV_PROXY=1
```

If your proxy performs SSL inspection (man-in-the-middle), also trust your organization's CA certificate:

```
export NODE_EXTRA_CA_CERTS=/path/to/corporate-ca-cert.pem
```

HTTP/1.1 fallback

Some enterprise proxies (like Zscaler) don't support HTTP/2 bidirectional streaming. Enable HTTP/1.1 mode in your config:

```
1 {
2   "version": 1,
3   "editor": { "vimMode": false },
4   "permissions": { "allow": [], "deny": [] },
5   "network": {
6     "useHttp1ForAgent": true
7   }
8 }
```

This switches agent connections to HTTP/1.1 with Server-Sent Events (SSE), which works with most corporate proxies.

See [Network Configuration](#) for proxy testing commands and troubleshooting.



English ▾