

CLI

Parameters

Global options

Global options can be used with any command:

Option	Description
<code>-v, --version</code>	Output the version number
<code>--api-key <key></code>	API key for authentication (can also use <code>CURSOR_API_KEY</code> env var)
<code>-H, --header <header></code>	Add custom header to agent requests (format: <code>Name: Value</code> , can be used multiple times)
<code>-p, --print</code>	Print responses to console (for scripts or non-interactive use). Has access to all tools, including write and shell.
<code>--output-format <format></code>	Output format (only works with <code>--print</code>): <code>text</code> , <code>json</code> , or <code>stream-json</code> (default: <code>text</code>)
<code>--stream-partial-output</code>	Stream partial output as individual text deltas (only works with <code>--print</code> and <code>stream-json</code> format)
<code>--resume [chatId]</code>	Resume a chat session
<code>--continue</code>	Continue the previous session (alias for <code>--resume=-1</code>)
<code>--model <model></code>	Model to use
<code>--mode <mode></code>	Set agent mode: <code>plan</code> or <code>ask</code> (agent is the default when no mode is specified)
<code>--plan</code>	Start in plan mode (shorthand for <code>--mode=plan</code>)
<code>--list-models</code>	List all available models
<code>-f, --force</code>	Force allow commands unless explicitly denied
<code>--yolo</code>	Alias for <code>--force</code>
<code>--sandbox <mode></code>	Set sandbox mode: <code>enabled</code> or <code>disabled</code>
<code>--approve-mcps</code>	Automatically approve all MCP servers
<code>--trust</code>	Trust the workspace without prompting (headless mode only)
<code>--workspace <path></code>	Workspace directory to use
<code>--plugin-dir <path></code>	Load a local plugin directory (can be specified multiple times)
<code>--worktree</code>	Run in a new Git worktree under <code>~/.cursor/worktrees</code> (see CLI worktrees)
<code>-h, --help</code>	Display help for command

Commands

Command	Description	Usage
<code>agent</code>	Start in agent mode (the default)	<code>agent agent</code>
<code>login</code>	Authenticate with Cursor	<code>agent login</code>
<code>logout</code>	Sign out and clear stored authentication	<code>agent logout</code>
<code>status</code> <code>whoami</code>	Check authentication status	<code>agent status</code>
<code>about</code>	Display version, system, and account info	<code>agent about</code>
<code>models</code>	List all available models	<code>agent models</code>
<code>mcp</code>	Manage MCP servers	<code>agent mcp</code>
<code>acp</code>	Start ACP server mode (advanced, hidden command)	<code>agent acp</code>
<code>update</code>	Update Cursor Agent to the latest version	<code>agent update</code>
<code>ls</code>	List previous chat sessions	<code>agent ls</code>
<code>resume</code>	Resume the latest chat session	<code>agent resume</code>
<code>create-chat</code>	Create a new empty chat and return its ID	<code>agent create-chat</code>
<code>generate-rule</code> <code>rule</code>	Generate a new Cursor rule interactively	<code>agent generate-rule</code>
<code>install-shell-integration</code>	Install shell integration to <code>~/.zshrc</code>	<code>agent install-shell-integration</code>
<code>uninstall-shell-integration</code>	Remove shell integration from <code>~/.zshrc</code>	<code>agent uninstall-shell-integration</code>
<code>help [command]</code>	Display help for command	<code>agent help [command]</code>



`agent acp` is intended for custom ACP clients and advanced integrations. It is hidden from default command help output.



When no command is specified, Cursor Agent starts in interactive agent mode by default.

MCP

Manage MCP servers configured for Cursor Agent.

Subcommand	Description	Usage
<code>login <identifier></code>	Authenticate with an MCP server configured in <code>.cursor/mcp.json</code>	<code>agent mcp login <identifier></code>
<code>list</code>	List configured MCP servers and their status	<code>agent mcp list</code>
<code>list-tools <identifier></code>	List available tools and their argument names for a specific MCP	<code>agent mcp list-tools <identifier></code>
<code>enable <identifier></code>	Enable an MCP server	<code>agent mcp enable <identifier></code>
<code>disable <identifier></code>	Disable an MCP server	<code>agent mcp disable <identifier></code>

All MCP commands support `-h, --help` for command-specific help.

Arguments

When starting in chat mode (default behavior), you can provide an initial prompt:

Arguments:

- `prompt` — Initial prompt for the agent

Getting help

All commands support the global `-h, --help` option to display command-specific help.



English

