SENECA III TAB DATA

PA-34-220T · Takeoff and landing · Test build

Zero-wind takeoff and landing distances from the digitized Seneca III POH charts (Report VB-1110, Section 5), the same data the Performance Card app uses.

- Pressure altitude rows, OAT columns. Interpolate between rows and columns; the values are rounded up to the next 10 ft.
- Apply wind with the factors on the last page.
- Conditions: paved, level, dry runway. Takeoff 2800 RPM, 40 in. MAP, cowl flaps ½ open. Landing: throttles closed, full stall touchdown, maximum braking.
- Landing ground roll is the same for normal and short field technique.
- Unfactored chart values. Add your own margin.

Built 13 Oct 2026. The calculator matches the POH takeoff examples within 2%. It reads 2–5% shorter than the POH's printed landing examples, because the example path drawn on those charts strays from the chart's own guide lines; the tables follow the guide lines.

Normal takeoff	2
Maximum effort takeoff	4
Accelerate-stop 0°	6
Accelerate-stop 25°	8
Normal landing	10
Short field landing	12
Wind correction	14

NORMAL TAKEOFF

0° flaps · 79 KIAS · 1/2

Bold over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,750 LB

PA \ OAT	-10°C	0°C	10°C	20°C	30°C	40°C
SL	—	**1,710** 1,400	**1,810** 1,490	**1,910** 1,580	**2,010** 1,660	**2,100** 1,750
2,000	—	**1,920** 1,580	**2,020** 1,680	**2,130** 1,780	**2,240** 1,870	**2,340** 1,970
4,000	—	**2,150** 1,790	**2,270** 1,900	**2,380** 2,010	**2,500** 2,120	—
6,000	**2,270** 1,900	**2,400** 2,020	**2,530** 2,150	**2,670** 2,270	**2,830** 2,400	—
8,000	**2,530** 2,150	**2,700** 2,290	**2,870** 2,430	**3,020** 2,570	—	—

4,500 LB

PA \ OAT	-10°C	0°C	10°C	20°C	30°C	40°C
SL	—	**1,640** 1,330	**1,720** 1,410	**1,810** 1,490	**1,910** 1,570	**2,000** 1,650
2,000	—	**1,820** 1,500	**1,930** 1,590	**2,030** 1,680	**2,120** 1,770	**2,220** 1,850
4,000	—	**2,040** 1,690	**2,150** 1,790	**2,260** 1,890	**2,370** 1,990	—
6,000	**2,150** 1,790	**2,270** 1,900	**2,400** 2,020	**2,510** 2,130	**2,640** 2,250	—
8,000	**2,400** 2,020	**2,530** 2,150	**2,690** 2,280	**2,840** 2,410	—	—

4,250 LB

PA \ OAT	-10°C	0°C	10°C	20°C	30°C	40°C
SL	—	**1,570** 1,270	**1,640** 1,340	**1,720** 1,410	**1,810** 1,490	**1,900** 1,560
2,000	—	**1,730** 1,420	**1,830** 1,500	**1,920** 1,590	**2,010** 1,660	**2,100** 1,740
4,000	—	**1,930** 1,600	**2,030** 1,690	**2,130** 1,780	**2,230** 1,870	—
6,000	**2,030** 1,690	**2,150** 1,790	**2,260** 1,890	**2,380** 2,000	**2,480** 2,110	—
8,000	**2,270** 1,900	**2,400** 2,020	**2,520** 2,140	**2,650** 2,250	—	—

NORMAL TAKEOFF

0° flaps · 79 KIAS · 2/2

Bold over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,000 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,500** 1,200	**1,570** 1,270	**1,640** 1,340	**1,720** 1,410	**1,800** 1,480
2,000	—	**1,650** 1,340	**1,730** 1,420	**1,820** 1,500	**1,900** 1,570	**1,980** 1,640
4,000	—	**1,830** 1,510	**1,920** 1,590	**2,010** 1,670	**2,110** 1,750	—
6,000	**1,920** 1,590	**2,020** 1,680	**2,130** 1,780	**2,240** 1,870	**2,340** 1,970	—
8,000	**2,140** 1,780	**2,260** 1,890	**2,370** 2,000	**2,480** 2,100	—	—

3,750 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,430** 1,140	**1,500** 1,200	**1,570** 1,260	**1,630** 1,330	**1,700** 1,390
2,000	—	**1,570** 1,270	**1,650** 1,340	**1,720** 1,410	**1,790** 1,470	**1,870** 1,540
4,000	—	**1,730** 1,420	**1,810** 1,490	**1,900** 1,560	**1,980** 1,640	—
6,000	**1,810** 1,490	**1,910** 1,570	**2,010** 1,660	**2,110** 1,750	**2,200** 1,840	—
8,000	**2,010** 1,670	**2,120** 1,770	**2,230** 1,860	**2,330** 1,960	—	—

3,500 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,370** 1,080	**1,430** 1,140	**1,490** 1,190	**1,550** 1,250	**1,610** 1,310
2,000	—	**1,500** 1,200	**1,570** 1,260	**1,630** 1,330	**1,690** 1,390	**1,760** 1,440
4,000	—	**1,640** 1,340	**1,710** 1,400	**1,780** 1,470	**1,860** 1,540	—
6,000	**1,710** 1,400	**1,800** 1,480	**1,890** 1,560	**1,980** 1,640	**2,070** 1,720	—
8,000	**1,890** 1,560	**2,000** 1,650	**2,090** 1,740	**2,180** 1,820	—	—

MAXIMUM EFFORT TAKEOFF

25° flaps · 64/66 KIAS · 1/2

Bold over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,750 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,060** 840	**1,140** 900	**1,230** 950	**1,300** 1,010	**1,370** 1,070
2,000	—	**1,230** 960	**1,310** 1,020	**1,390** 1,090	**1,470** 1,150	**1,550** 1,210
4,000	—	**1,400** 1,090	**1,490** 1,160	**1,580** 1,230	**1,670** 1,300	—
6,000	**1,500** 1,170	**1,600** 1,250	**1,710** 1,330	**1,810** 1,410	**1,920** 1,500	—
8,000	**1,710** 1,330	**1,830** 1,430	**1,950** 1,520	**2,070** 1,620	—	—

4,500 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**960** 770	**1,040** 830	**1,120** 880	**1,200** 940	**1,270** 990
2,000	—	**1,130** 880	**1,210** 950	**1,290** 1,010	**1,370** 1,070	**1,440** 1,130
4,000	—	**1,290** 1,010	**1,380** 1,080	**1,470** 1,150	**1,550** 1,210	—
6,000	**1,390** 1,080	**1,490** 1,160	**1,590** 1,240	**1,690** 1,320	**1,790** 1,400	—
8,000	**1,590** 1,240	**1,700** 1,330	**1,820** 1,420	**1,930** 1,510	—	—

4,250 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**880** 710	**950** 760	**1,020** 810	**1,090** 860	**1,170** 910
2,000	—	**1,020** 810	**1,110** 870	**1,190** 930	**1,260** 990	**1,340** 1,040
4,000	—	**1,190** 930	**1,280** 1,000	**1,360** 1,060	**1,440** 1,130	—
6,000	**1,290** 1,000	**1,380** 1,080	**1,480** 1,150	**1,570** 1,220	**1,660** 1,300	—
8,000	**1,480** 1,150	**1,580** 1,240	**1,690** 1,320	**1,800** 1,400	—	—

MAXIMUM EFFORT TAKEOFF

25° flaps · 64/66 KIAS · 2/2

Bold over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,000 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**800** 650	**860** 690	**920** 740	**990** 790	**1,060** 840
2,000	—	**930** 750	**1,000** 800	**1,080** 850	**1,160** 910	**1,240** 960
4,000	—	**1,080** 860	**1,170** 920	**1,260** 980	**1,340** 1,040	—
6,000	**1,180** 920	**1,280** 1,000	**1,370** 1,070	**1,450** 1,140	**1,540** 1,200	—
8,000	**1,370** 1,070	**1,470** 1,150	**1,570** 1,220	**1,670** 1,300	—	—

3,750 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**730** 590	**780** 630	**840** 680	**900** 720	**960** 770
2,000	—	**840** 680	**900** 730	**970** 780	**1,050** 830	**1,130** 890
4,000	—	**980** 780	**1,060** 840	**1,150** 900	**1,230** 960	—
6,000	**1,070** 850	**1,180** 920	**1,260** 980	**1,340** 1,050	**1,430** 1,110	—
8,000	**1,260** 980	**1,360** 1,060	**1,450** 1,130	**1,540** 1,210	—	—

3,500 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**650** 530	**710** 570	**760** 610	**810** 660	**860** 700
2,000	—	**760** 620	**820** 660	**880** 710	**950** 760	**1,020** 810
4,000	—	**880** 710	**960** 770	**1,040** 830	**1,120** 880	—
6,000	**970** 780	**1,070** 840	**1,150** 900	**1,240** 970	**1,310** 1,030	—
8,000	**1,150** 900	**1,250** 970	**1,340** 1,040	**1,420** 1,110	—	—

ACCELERATE-STOP

0° flaps (chart × 0.93) · 1/2

Accelerate-stop · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,750 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**3,340**	**3,490**	**3,650**	**3,800**	**3,950**
2,000	—	**3,660**	**3,820**	**3,980**	**4,140**	**4,310**
4,000	—	**4,000**	**4,180**	**4,360**	**4,530**	—
6,000	**4,200**	**4,390**	**4,590**	**4,780**	**4,980**	—
8,000	**4,620**	**4,830**	**5,040**	**5,260**	—	—

4,500 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**3,200**	**3,340**	**3,480**	**3,620**	**3,760**
2,000	—	**3,490**	**3,640**	**3,790**	**3,950**	**4,100**
4,000	—	**3,810**	**3,980**	**4,140**	**4,310**	—
6,000	**4,000**	**4,180**	**4,360**	**4,540**	**4,730**	—
8,000	**4,390**	**4,590**	**4,790**	**4,990**	—	—

4,250 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**3,050**	**3,180**	**3,310**	**3,450**	**3,580**
2,000	—	**3,320**	**3,460**	**3,610**	**3,750**	**3,890**
4,000	—	**3,620**	**3,780**	**3,930**	**4,090**	—
6,000	**3,800**	**3,960**	**4,130**	**4,300**	**4,470**	—
8,000	**4,160**	**4,340**	**4,530**	**4,720**	—	—

ACCELERATE-STOP

0° flaps (chart × 0.93) · 2/2

Accelerate-stop · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,000 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,900**	**3,020**	**3,150**	**3,270**	**3,390**
2,000	—	**3,150**	**3,290**	**3,420**	**3,550**	**3,680**
4,000	—	**3,430**	**3,580**	**3,720**	**3,860**	—
6,000	**3,590**	**3,750**	**3,910**	**4,060**	**4,220**	—
8,000	**3,930**	**4,100**	**4,280**	**4,460**	—	—

3,750 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,760**	**2,860**	**2,980**	**3,090**	**3,210**
2,000	—	**2,980**	**3,110**	**3,230**	**3,350**	**3,480**
4,000	—	**3,250**	**3,380**	**3,510**	**3,640**	—
6,000	**3,390**	**3,540**	**3,680**	**3,820**	**3,970**	—
8,000	**3,700**	**3,860**	**4,020**	**4,190**	—	—

3,500 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,610**	**2,700**	**2,810**	**2,910**	**3,020**
2,000	—	**2,810**	**2,930**	**3,040**	**3,160**	**3,270**
4,000	—	**3,060**	**3,180**	**3,300**	**3,420**	—
6,000	**3,190**	**3,330**	**3,460**	**3,590**	**3,720**	—
8,000	**3,480**	**3,620**	**3,770**	**3,930**	—	—

ACCELERATE-STOP

25° flaps (chart × 0.87) · 1/2

Accelerate-stop · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,750 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,930**	**2,030**	**2,120**	**2,210**	**2,310**
2,000	—	**2,120**	**2,220**	**2,320**	**2,410**	**2,510**
4,000	—	**2,330**	**2,430**	**2,540**	**2,640**	—
6,000	**2,410**	**2,530**	**2,650**	**2,770**	**2,890**	—
8,000	**2,670**	**2,800**	**2,930**	**3,060**	—	—

4,500 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,820**	**1,910**	**2,000**	**2,100**	**2,190**
2,000	—	**2,010**	**2,100**	**2,190**	**2,290**	**2,380**
4,000	—	**2,200**	**2,300**	**2,400**	**2,500**	—
6,000	**2,280**	**2,400**	**2,510**	**2,630**	**2,740**	—
8,000	**2,540**	**2,660**	**2,780**	**2,910**	—	—

4,250 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,720**	**1,800**	**1,890**	**1,980**	**2,060**
2,000	—	**1,890**	**1,980**	**2,070**	**2,160**	**2,250**
4,000	—	**2,080**	**2,170**	**2,270**	**2,360**	—
6,000	**2,150**	**2,260**	**2,370**	**2,490**	**2,600**	—
8,000	**2,400**	**2,520**	**2,640**	**2,750**	—	—

ACCELERATE-STOP

25° flaps (chart × 0.87) · 2/2

Accelerate-stop · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,000 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,610**	**1,690**	**1,770**	**1,860**	**1,940**
2,000	—	**1,770**	**1,860**	**1,950**	**2,030**	**2,110**
4,000	—	**1,960**	**2,040**	**2,130**	**2,230**	—
6,000	**2,030**	**2,130**	**2,240**	**2,350**	**2,450**	—
8,000	**2,260**	**2,380**	**2,490**	**2,600**	—	—

3,750 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,510**	**1,580**	**1,660**	**1,740**	**1,820**
2,000	—	**1,660**	**1,740**	**1,820**	**1,900**	**1,980**
4,000	—	**1,830**	**1,910**	**2,000**	**2,090**	—
6,000	**1,900**	**1,990**	**2,100**	**2,200**	**2,310**	—
8,000	**2,120**	**2,240**	**2,340**	**2,450**	—	—

3,500 LB						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,410**	**1,470**	**1,540**	**1,620**	**1,690**
2,000	—	**1,540**	**1,620**	**1,700**	**1,770**	**1,850**
4,000	—	**1,700**	**1,780**	**1,860**	**1,950**	—
6,000	**1,770**	**1,860**	**1,960**	**2,060**	**2,160**	—
8,000	**1,980**	**2,090**	**2,200**	**2,290**	—	—

NORMAL LANDING

40° flaps · 1/2

Bold over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,513 LB · BARRIER 90 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,580** 1,330	**2,670** 1,380	**2,760** 1,440	**2,850** 1,490	**2,930** 1,540
2,000	—	**2,770** 1,440	**2,850** 1,490	**2,930** 1,540	**3,010** 1,600	**3,090** 1,650
4,000	—	**2,930** 1,550	**3,020** 1,600	**3,100** 1,660	**3,190** 1,720	—
6,000	**3,010** 1,600	**3,100** 1,660	**3,200** 1,720	**3,290** 1,790	**3,390** 1,850	—
8,000	**3,190** 1,720	**3,290** 1,790	**3,400** 1,860	**3,500** 1,930	—	—

4,250 LB · BARRIER 88 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,460** 1,250	**2,540** 1,300	**2,630** 1,350	**2,710** 1,400	**2,790** 1,450
2,000	—	**2,630** 1,350	**2,710** 1,400	**2,790** 1,450	**2,860** 1,500	**2,940** 1,550
4,000	—	**2,790** 1,450	**2,870** 1,510	**2,950** 1,560	**3,040** 1,620	—
6,000	**2,860** 1,500	**2,950** 1,560	**3,040** 1,620	**3,130** 1,680	**3,230** 1,740	—
8,000	**3,040** 1,620	**3,140** 1,680	**3,230** 1,750	**3,330** 1,820	—	—

4,000 LB · BARRIER 85 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,340** 1,170	**2,420** 1,220	**2,490** 1,270	**2,570** 1,320	**2,650** 1,360
2,000	—	**2,500** 1,270	**2,570** 1,320	**2,650** 1,360	**2,720** 1,410	**2,800** 1,460
4,000	—	**2,650** 1,360	**2,730** 1,410	**2,810** 1,470	**2,890** 1,520	—
6,000	**2,720** 1,410	**2,810** 1,460	**2,900** 1,520	**2,980** 1,580	**3,070** 1,640	—
8,000	**2,890** 1,520	**2,980** 1,580	**3,080** 1,640	**3,170** 1,710	—	—

NORMAL LANDING

40° flaps · 2/2

Bold over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

3,750 LB · BARRIER 83 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,220** 1,100	**2,290** 1,150	**2,360** 1,190	**2,430** 1,230	**2,500** 1,280
2,000	—	**2,370** 1,190	**2,430** 1,230	**2,500** 1,280	**2,570** 1,320	**2,640** 1,360
4,000	—	**2,500** 1,280	**2,580** 1,320	**2,660** 1,370	**2,740** 1,420	—
6,000	**2,570** 1,320	**2,650** 1,370	**2,740** 1,420	**2,830** 1,480	**2,910** 1,530	—
8,000	**2,740** 1,420	**2,830** 1,480	**2,920** 1,540	**3,010** 1,600	—	—

3,500 LB · BARRIER 81 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,110** 1,030	**2,170** 1,070	**2,240** 1,110	**2,300** 1,150	**2,360** 1,190
2,000	—	**2,240** 1,110	**2,300** 1,150	**2,360** 1,190	**2,420** 1,220	**2,490** 1,270
4,000	—	**2,360** 1,190	**2,430** 1,230	**2,500** 1,270	**2,580** 1,320	—
6,000	**2,420** 1,220	**2,500** 1,270	**2,580** 1,320	**2,670** 1,380	**2,750** 1,430	—
8,000	**2,580** 1,320	**2,670** 1,380	**2,760** 1,430	**2,850** 1,490	—	—

3,250 LB · BARRIER 78 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,000** 950	**2,060** 990	**2,110** 1,030	**2,170** 1,060	**2,220** 1,100
2,000	—	**2,120** 1,030	**2,170** 1,060	**2,220** 1,100	**2,270** 1,130	**2,330** 1,170
4,000	—	**2,220** 1,100	**2,280** 1,140	**2,350** 1,180	**2,420** 1,220	—
6,000	**2,270** 1,130	**2,350** 1,180	**2,420** 1,230	**2,500** 1,270	**2,580** 1,320	—
8,000	**2,420** 1,220	**2,500** 1,280	**2,590** 1,330	**2,680** 1,380	—	—

SHORT FIELD EFFORT LANDING

40° flaps · 1/2

Bold over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

4,513 LB · BARRIER 82 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**2,080** 1,330	**2,140** 1,380	**2,210** 1,440	**2,270** 1,490	**2,340** 1,540
2,000	—	**2,210** 1,440	**2,280** 1,490	**2,340** 1,550	**2,400** 1,600	**2,460** 1,650
4,000	—	**2,340** 1,550	**2,410** 1,610	**2,470** 1,660	**2,530** 1,720	—
6,000	**2,400** 1,600	**2,470** 1,660	**2,530** 1,730	**2,600** 1,790	**2,670** 1,850	—
8,000	**2,530** 1,720	**2,610** 1,790	**2,680** 1,860	**2,760** 1,930	—	—

4,250 LB · BARRIER 80 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,980** 1,250	**2,040** 1,300	**2,110** 1,350	**2,160** 1,400	**2,220** 1,450
2,000	—	**2,110** 1,350	**2,170** 1,400	**2,230** 1,450	**2,290** 1,500	**2,350** 1,550
4,000	—	**2,230** 1,450	**2,290** 1,510	**2,360** 1,560	**2,420** 1,610	—
6,000	**2,290** 1,500	**2,360** 1,560	**2,420** 1,620	**2,490** 1,680	**2,550** 1,740	—
8,000	**2,420** 1,620	**2,490** 1,680	**2,560** 1,750	**2,630** 1,810	—	—

4,000 LB · BARRIER 77 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,890** 1,180	**1,950** 1,220	**2,010** 1,270	**2,060** 1,310	**2,120** 1,360
2,000	—	**2,010** 1,270	**2,070** 1,320	**2,120** 1,360	**2,170** 1,410	**2,230** 1,450
4,000	—	**2,120** 1,360	**2,180** 1,410	**2,240** 1,460	**2,300** 1,510	—
6,000	**2,180** 1,410	**2,240** 1,460	**2,310** 1,520	**2,380** 1,580	**2,440** 1,630	—
8,000	**2,310** 1,520	**2,380** 1,580	**2,450** 1,640	**2,510** 1,700	—	—

SHORT FIELD EFFORT LANDING

40° flaps · 2/2

Bold over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — outside chart (ISA −15 to +30°C)

3,750 LB · BARRIER 75 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,800** 1,100	**1,850** 1,150	**1,910** 1,190	**1,960** 1,230	**2,010** 1,270
2,000	—	**1,910** 1,190	**1,960** 1,230	**2,010** 1,270	**2,060** 1,310	**2,110** 1,360
4,000	—	**2,010** 1,270	**2,070** 1,320	**2,120** 1,370	**2,180** 1,410	—
6,000	**2,060** 1,320	**2,130** 1,370	**2,190** 1,420	**2,250** 1,470	**2,320** 1,530	—
8,000	**2,190** 1,420	**2,260** 1,480	**2,330** 1,540	**2,400** 1,600	—	—

3,500 LB · BARRIER 73 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,710** 1,030	**1,760** 1,070	**1,810** 1,110	**1,850** 1,140	**1,900** 1,180
2,000	—	**1,810** 1,110	**1,860** 1,150	**1,900** 1,180	**1,950** 1,220	**2,000** 1,260
4,000	—	**1,900** 1,190	**1,950** 1,230	**2,010** 1,270	**2,060** 1,310	—
6,000	**1,950** 1,220	**2,010** 1,270	**2,070** 1,320	**2,130** 1,370	**2,190** 1,420	—
8,000	**2,070** 1,320	**2,130** 1,370	**2,200** 1,430	**2,270** 1,490	—	—

3,250 LB · BARRIER 70 KIAS						
PA \ OAT	**-10°C**	**0°C**	**10°C**	**20°C**	**30°C**	**40°C**
SL	—	**1,610** 950	**1,660** 990	**1,710** 1,030	**1,750** 1,060	**1,790** 1,090
2,000	—	**1,710** 1,030	**1,750** 1,060	**1,790** 1,090	**1,830** 1,130	**1,880** 1,170
4,000	—	**1,790** 1,100	**1,840** 1,130	**1,890** 1,170	**1,940** 1,220	—
6,000	**1,830** 1,130	**1,890** 1,170	**1,950** 1,220	**2,000** 1,270	**2,060** 1,320	—
8,000	**1,940** 1,220	**2,010** 1,270	**2,070** 1,320	**2,140** 1,380	—	—

WIND CORRECTION

Multiply the zero-wind table value by the factor

Multiply by	HW 5	HW 10	HW 15	TW 2.5	TW 5
Normal takeoff, over 50 ft	**0.97**	**0.93**	**0.88**	**1.11**	**1.22**
Normal takeoff, ground roll	**0.96**	**0.92**	**0.88**	**1.13**	**1.25**
Max effort, over 50 ft	**0.95**	**0.90**	**0.86**	**1.19**	**1.37**
Max effort, ground roll	**0.95**	**0.91**	**0.87**	**1.18**	**1.35**
Accel-stop, 0° flaps	**0.96**	**0.92**	**0.88**	**1.11**	**1.21**
Accel-stop, 25° flaps	**0.95**	**0.89**	**0.84**	**1.14**	**1.28**
Landing, over 50 ft (normal)	**0.95**	**0.90**	**0.85**	**1.12**	**1.23**
Landing, over 50 ft (short field)	**0.96**	**0.91**	**0.86**	**1.12**	**1.24**
Landing, ground roll	**0.94**	**0.88**	**0.82**	**1.16**	**1.31**

Headwind and tailwind components in knots, as charted (no extra factoring). Each factor is the least favorable one across the whole table, so it never gives less distance than the chart. For the 50% headwind / 150% tailwind practice, enter half the headwind or 1.5× the tailwind. Charts stop at 15 kt headwind and 5 kt tailwind.

Example. Normal takeoff, 4,000 lb, 2,000 ft, 20°C, 10 kt headwind: table over 50 ft × HW 10 factor.