N600NJ TAB DATA

Aerostar 600 · S/N 60-0199-088 · Takeoff and landing

Zero-wind takeoff, accelerate-stop and landing distances for N600NJ (Aerostar 600, S/N 60-0199-088), from the digitized charts in its 1976 Owner's Manual, Section 7. It's the same data the N600NJ Performance Card app uses.

- Pressure altitude rows, OAT (°F) columns. Interpolate between rows and columns; values are rounded up to the next 10 ft.
- Apply wind with the factors on the last page.
- Conditions: level, hard surface runway. Takeoff at maximum power. Landing with 45° flaps, power for a 3° approach and heavy braking.
- Ground roll from the chart notes: 78% of total flaps up, 80% (4,000 lb) to 72% (5,500 lb) flaps 20°, about 37% landing.
- Maximum takeoff and landing weight is 5,700 lb (AFMS ER94105). The charts stop at 5,500 lb, so the 5,700 lb tables are extended from the 5,000 and 5,500 lb lines. Treat them as estimates.
- Speeds are KIAS, converted from the chart's mph IAS and rounded up. Unfactored chart values; add your own margin.

Built 17 Oct 2026, speeds in KIAS 29 Oct 2026. The calculator matches the manual's worked examples within 1.6%.

Takeoff, flaps 20°	2
Takeoff, flaps up	4
Accelerate-stop	6
Normal landing	8
Wind correction	10

TAKEOFF · FLAPS 20°

Maximum power · 1/2

Bold total over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — off the chart

5,700 LB · T.O. 83 KIAS · EXTRAPOLATED							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,330** 960	**1,390** 1,000	**1,470** 1,060	**1,550** 1,120	**1,620** 1,170	**1,720** 1,240
2,000	**1,480** 1,060	**1,560** 1,120	**1,630** 1,180	**1,720** 1,240	**1,800** 1,300	**1,900** 1,370	**2,010** 1,450
4,000	**1,750** 1,260	**1,830** 1,320	**1,930** 1,390	**2,040** 1,470	**2,150** 1,550	**2,280** 1,650	**2,420** 1,740
6,000	**2,130** 1,530	**2,250** 1,620	**2,380** 1,710	**2,530** 1,820	**2,690** 1,940	**2,880** 2,080	**3,110** 2,240
8,000	**2,630** 1,890	**2,810** 2,020	**3,020** 2,170	**3,260** 2,350	**3,560** 2,560	**3,950** 2,840	**4,750** 3,420
10,000	**3,590** 2,580	**4,010** 2,890	**4,880** 3,510	—	—	—	—

5,500 LB · T.O. 83 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,270** 910	**1,320** 950	**1,400** 1,010	**1,470** 1,060	**1,540** 1,110	**1,630** 1,170
2,000	**1,400** 1,010	**1,480** 1,070	**1,550** 1,120	**1,630** 1,180	**1,710** 1,230	**1,800** 1,300	**1,890** 1,360
4,000	**1,650** 1,190	**1,740** 1,250	**1,830** 1,320	**1,930** 1,390	**2,030** 1,460	**2,150** 1,550	**2,270** 1,640
6,000	**2,000** 1,440	**2,120** 1,520	**2,230** 1,610	**2,370** 1,710	**2,520** 1,810	**2,690** 1,940	**2,880** 2,080
8,000	**2,460** 1,770	**2,620** 1,890	**2,810** 2,020	**3,020** 2,180	**3,280** 2,360	**3,610** 2,600	**4,250** 3,060
10,000	**3,310** 2,380	**3,660** 2,640	**4,350** 3,130	—	—	—	—

5,250 LB · T.O. 82 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,190** 870	**1,240** 910	**1,310** 960	**1,370** 1,010	**1,440** 1,060	**1,510** 1,110
2,000	**1,310** 960	**1,380** 1,010	**1,440** 1,060	**1,520** 1,110	**1,590** 1,170	**1,670** 1,220	**1,750** 1,290
4,000	**1,540** 1,130	**1,620** 1,190	**1,690** 1,240	**1,780** 1,310	**1,870** 1,370	**1,980** 1,450	**2,080** 1,530
6,000	**1,850** 1,360	**1,950** 1,430	**2,050** 1,510	**2,170** 1,590	**2,300** 1,690	**2,440** 1,790	**2,610** 1,910
8,000	**2,250** 1,650	**2,390** 1,750	**2,540** 1,870	**2,720** 2,000	**2,930** 2,150	**3,190** 2,340	**3,630** 2,670
10,000	**2,950** 2,170	**3,230** 2,370	**3,690** 2,710	—	—	—	—

TAKEOFF · FLAPS 20°

Maximum power · 2/2

Bold total over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — off the chart

5,000 LB · T.O. 82 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,110** 830	**1,160** 870	**1,210** 910	**1,270** 950	**1,330** 1,000	**1,400** 1,050
2,000	**1,220** 910	**1,280** 960	**1,340** 1,000	**1,400** 1,050	**1,470** 1,100	**1,530** 1,150	**1,610** 1,200
4,000	**1,420** 1,060	**1,500** 1,120	**1,560** 1,170	**1,640** 1,220	**1,720** 1,280	**1,800** 1,350	**1,900** 1,420
6,000	**1,700** 1,270	**1,780** 1,330	**1,870** 1,400	**1,970** 1,470	**2,080** 1,550	**2,200** 1,640	**2,330** 1,740
8,000	**2,040** 1,520	**2,160** 1,610	**2,280** 1,700	**2,430** 1,810	**2,590** 1,930	**2,780** 2,070	**3,010** 2,250
10,000	**2,600** 1,940	**2,800** 2,090	**3,030** 2,260	**3,320** 2,480	**3,710** 2,770	—	—

4,500 LB · T.O. 81 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	—	**1,010** 780	**1,060** 820	**1,110** 860	**1,160** 900	**1,220** 940
2,000	**1,060** 820	**1,110** 860	**1,160** 900	**1,220** 940	**1,270** 980	**1,330** 1,030	**1,390** 1,080
4,000	**1,230** 950	**1,290** 1,000	**1,350** 1,040	**1,410** 1,090	**1,480** 1,140	**1,540** 1,190	**1,610** 1,250
6,000	**1,460** 1,130	**1,520** 1,180	**1,590** 1,230	**1,660** 1,290	**1,740** 1,350	**1,830** 1,420	**1,920** 1,490
8,000	**1,710** 1,330	**1,800** 1,390	**1,890** 1,460	**2,000** 1,550	**2,100** 1,630	**2,230** 1,730	**2,400** 1,860
10,000	**2,120** 1,640	**2,250** 1,740	**2,410** 1,870	**2,600** 2,010	**2,850** 2,210	—	—

4,000 LB · T.O. 80 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	—	—	—	—	**1,000** 800	**1,030** 820
2,000	—	—	**1,000** 800	**1,030** 830	**1,090** 870	**1,140** 910	**1,190** 950
4,000	**1,050** 840	**1,110** 890	**1,150** 920	**1,210** 970	**1,270** 1,010	**1,320** 1,060	**1,390** 1,110
6,000	**1,250** 1,000	**1,310** 1,050	**1,370** 1,090	**1,430** 1,140	**1,500** 1,200	**1,560** 1,250	**1,620** 1,300
8,000	**1,470** 1,180	**1,530** 1,220	**1,600** 1,280	**1,670** 1,340	**1,750** 1,400	**1,840** 1,470	**1,940** 1,550
10,000	**1,760** 1,410	**1,850** 1,480	**1,950** 1,560	**2,050** 1,640	**2,190** 1,750	—	—

TAKEOFF · FLAPS UP

Maximum power · 1/2

Bold total over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — off the chart

5,700 LB · T.O. 95 KIAS · EXTRAPOLATED							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,820** 1,420	**1,910** 1,490	**2,010** 1,570	**2,140** 1,670	**2,260** 1,760	**2,390** 1,870
2,000	**1,990** 1,550	**2,100** 1,640	**2,230** 1,740	**2,370** 1,850	**2,500** 1,950	**2,660** 2,070	**2,840** 2,210
4,000	**2,370** 1,850	**2,500** 1,950	**2,650** 2,070	**2,830** 2,210	**3,020** 2,360	**3,230** 2,520	**3,500** 2,730
6,000	**2,840** 2,210	**3,030** 2,360	**3,250** 2,530	**3,520** 2,750	**3,840** 3,000	**4,190** 3,270	**4,640** 3,620
8,000	**3,610** 2,820	**3,920** 3,060	**4,290** 3,340	**4,750** 3,710	**5,320** 4,150	**6,030** 4,700	**7,020** 5,480
10,000	**4,670** 3,650	**5,240** 4,090	**5,930** 4,630	**6,880** 5,360	—	—	—

5,500 LB · T.O. 93 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,680** 1,310	**1,770** 1,380	**1,860** 1,450	**1,980** 1,540	**2,090** 1,630	**2,210** 1,720
2,000	**1,840** 1,440	**1,940** 1,520	**2,050** 1,600	**2,180** 1,710	**2,310** 1,800	**2,440** 1,910	**2,600** 2,030
4,000	**2,180** 1,710	**2,300** 1,800	**2,440** 1,910	**2,600** 2,030	**2,770** 2,160	**2,970** 2,310	**3,200** 2,500
6,000	**2,600** 2,030	**2,780** 2,170	**2,980** 2,320	**3,220** 2,510	**3,500** 2,730	**3,810** 2,970	**4,190** 3,270
8,000	**3,300** 2,570	**3,570** 2,780	**3,890** 3,030	**4,280** 3,340	**4,760** 3,710	**5,360** 4,180	**6,180** 4,820
10,000	**4,220** 3,290	**4,690** 3,660	**5,270** 4,120	**6,060** 4,730	—	—	—

5,250 LB · T.O. 91 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,510** 1,180	**1,590** 1,240	**1,670** 1,310	**1,770** 1,380	**1,870** 1,460	**1,970** 1,540
2,000	**1,650** 1,290	**1,740** 1,360	**1,840** 1,440	**1,950** 1,520	**2,060** 1,610	**2,180** 1,700	**2,320** 1,810
4,000	**1,950** 1,520	**2,060** 1,610	**2,180** 1,700	**2,310** 1,810	**2,470** 1,920	**2,630** 2,050	**2,830** 2,200
6,000	**2,320** 1,810	**2,470** 1,930	**2,640** 2,060	**2,840** 2,220	**3,070** 2,400	**3,330** 2,600	**3,630** 2,830
8,000	**2,900** 2,270	**3,130** 2,440	**3,390** 2,650	**3,700** 2,890	**4,070** 3,170	**4,520** 3,530	**5,130** 4,000
10,000	**3,650** 2,850	**4,010** 3,130	**4,460** 3,480	**5,040** 3,940	**5,820** 4,540	—	—

TAKEOFF · FLAPS UP

Maximum power · 2/2

Bold total over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — off the chart

5,000 LB · T.O. 89 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,340** 1,050	**1,410** 1,100	**1,490** 1,160	**1,560** 1,220	**1,650** 1,290	**1,740** 1,350
2,000	**1,460** 1,140	**1,540** 1,200	**1,630** 1,270	**1,710** 1,340	**1,820** 1,420	**1,920** 1,500	**2,030** 1,580
4,000	**1,710** 1,340	**1,810** 1,420	**1,920** 1,500	**2,020** 1,580	**2,160** 1,680	**2,300** 1,790	**2,450** 1,910
6,000	**2,030** 1,580	**2,160** 1,690	**2,310** 1,800	**2,470** 1,920	**2,640** 2,060	**2,840** 2,220	**3,060** 2,390
8,000	**2,510** 1,960	**2,690** 2,100	**2,900** 2,260	**3,110** 2,430	**3,370** 2,630	**3,680** 2,870	**4,070** 3,180
10,000	**3,080** 2,410	**3,330** 2,600	**3,640** 2,840	**4,030** 3,140	**4,480** 3,490	**5,010** 3,910	—

4,500 LB · T.O. 85 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,080** 840	**1,130** 880	**1,190** 930	**1,260** 980	**1,320** 1,030	**1,390** 1,090
2,000	**1,180** 920	**1,240** 970	**1,310** 1,020	**1,370** 1,070	**1,440** 1,130	**1,510** 1,180	**1,600** 1,250
4,000	**1,370** 1,070	**1,440** 1,130	**1,510** 1,180	**1,600** 1,250	**1,690** 1,320	**1,780** 1,390	**1,890** 1,470
6,000	**1,600** 1,250	**1,690** 1,320	**1,790** 1,400	**1,900** 1,480	**2,010** 1,570	**2,140** 1,670	**2,290** 1,790
8,000	**1,920** 1,500	**2,040** 1,590	**2,170** 1,700	**2,320** 1,810	**2,480** 1,940	**2,660** 2,070	**2,860** 2,230
10,000	**2,300** 1,790	**2,460** 1,920	**2,630** 2,060	**2,830** 2,210	**3,060** 2,390	**3,330** 2,600	—

4,000 LB · T.O. 82 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	—	—	—	—	—	**1,000** 780
2,000	—	—	—	**1,000** 780	**1,030** 800	**1,090** 850	**1,130** 890
4,000	**1,000** 780	**1,030** 800	**1,080** 850	**1,130** 880	**1,190** 930	**1,260** 980	**1,320** 1,030
6,000	**1,130** 890	**1,200** 930	**1,260** 990	**1,330** 1,040	**1,410** 1,100	**1,490** 1,160	**1,580** 1,240
8,000	**1,350** 1,050	**1,430** 1,110	**1,510** 1,180	**1,600** 1,250	**1,700** 1,330	**1,800** 1,400	**1,900** 1,480
10,000	**1,590** 1,240	**1,690** 1,320	**1,780** 1,390	**1,890** 1,470	**2,000** 1,560	**2,140** 1,670	—

ACCELERATE-STOP

Flaps up chart, use for both flap settings · 1/2

Accelerate-stop · feet, zero wind, rounded up to 10 ft · — off the chart

5,700 LB · EXTRAPOLATED							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	**2,730**	**2,830**	**2,960**	**3,090**	**3,230**	**3,380**	**3,530**
2,000	**3,020**	**3,160**	**3,290**	**3,450**	**3,590**	**3,740**	**3,910**
4,000	**3,440**	**3,570**	**3,730**	**3,890**	**4,050**	**4,220**	**4,410**
6,000	**3,920**	**4,070**	**4,250**	**4,420**	**4,610**	**4,830**	**5,140**
8,000	**4,410**	**4,610**	**4,820**	**5,130**	**5,430**	**5,860**	—

5,500 LB							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	**2,580**	**2,680**	**2,800**	**2,920**	**3,040**	**3,180**	**3,320**
2,000	**2,850**	**2,980**	**3,100**	**3,240**	**3,370**	**3,510**	**3,660**
4,000	**3,230**	**3,350**	**3,500**	**3,640**	**3,790**	**3,960**	**4,130**
6,000	**3,670**	**3,810**	**3,980**	**4,140**	**4,320**	**4,520**	**4,790**
8,000	**4,140**	**4,310**	**4,520**	**4,780**	**5,060**	**5,430**	—

5,250 LB							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	**2,400**	**2,490**	**2,590**	**2,700**	**2,810**	**2,930**	**3,050**
2,000	**2,640**	**2,750**	**2,860**	**2,980**	**3,100**	**3,220**	**3,350**
4,000	**2,970**	**3,090**	**3,210**	**3,330**	**3,480**	**3,630**	**3,780**
6,000	**3,360**	**3,500**	**3,640**	**3,790**	**3,960**	**4,140**	**4,360**
8,000	**3,790**	**3,950**	**4,130**	**4,350**	**4,590**	**4,890**	—

ACCELERATE-STOP

Flaps up chart, use for both flap settings · 2/2

Accelerate-stop · feet, zero wind, rounded up to 10 ft · — off the chart

5,000 LB							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	**2,220**	**2,300**	**2,390**	**2,490**	**2,580**	**2,680**	**2,790**
2,000	**2,430**	**2,520**	**2,620**	**2,720**	**2,830**	**2,940**	**3,040**
4,000	**2,710**	**2,820**	**2,920**	**3,030**	**3,160**	**3,300**	**3,440**
6,000	**3,050**	**3,180**	**3,310**	**3,450**	**3,590**	**3,760**	**3,930**
8,000	**3,440**	**3,590**	**3,750**	**3,920**	**4,120**	**4,350**	**4,650**

4,500 LB							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,950**	**2,030**	**2,110**	**2,200**	**2,290**	**2,380**
2,000	**2,070**	**2,150**	**2,230**	**2,310**	**2,410**	**2,510**	**2,600**
4,000	**2,300**	**2,400**	**2,500**	**2,590**	**2,690**	**2,790**	**2,910**
6,000	**2,610**	**2,700**	**2,800**	**2,910**	**3,030**	**3,150**	**3,290**
8,000	**2,910**	**3,020**	**3,150**	**3,290**	**3,430**	**3,590**	**3,770**

4,000 LB							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	**1,670**	**1,720**	**1,790**	**1,850**	**1,920**	**1,990**
2,000	**1,750**	**1,810**	**1,880**	**1,940**	**2,010**	**2,090**	**2,160**
4,000	**1,930**	**2,010**	**2,080**	**2,160**	**2,230**	**2,310**	**2,400**
6,000	**2,170**	**2,240**	**2,320**	**2,410**	**2,500**	**2,590**	**2,680**
8,000	**2,400**	**2,490**	**2,580**	**2,680**	**2,770**	**2,880**	**2,980**

NORMAL LANDING · FLAPS 45°

3° approach, heavy braking · 1/2

Bold total over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — off the chart

5,700 LB · APPROACH 98 KIAS · EXTRAPOLATED							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	—	**2,460** 910	**2,530** 940	**2,600** 960	**2,670** 990	**2,740** 1,020
2,000	**2,450** 910	**2,520** 940	**2,590** 960	**2,660** 990	**2,730** 1,010	**2,820** 1,040	**2,900** 1,080
4,000	**2,580** 960	**2,640** 980	**2,720** 1,010	**2,800** 1,040	**2,890** 1,070	**2,990** 1,110	**3,090** 1,150
6,000	**2,710** 1,010	**2,790** 1,040	**2,890** 1,070	**2,980** 1,100	**3,080** 1,140	**3,210** 1,190	**3,310** 1,230
8,000	**2,860** 1,060	**2,960** 1,100	**3,060** 1,140	**3,180** 1,180	**3,300** 1,220	—	—
10,000	**3,060** 1,140	**3,160** 1,170	**3,270** 1,210	**3,370** 1,250	—	—	—

5,500 LB · APPROACH 96 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	—	**2,360** 880	**2,430** 900	**2,490** 930	**2,560** 950	**2,630** 980
2,000	**2,350** 870	**2,420** 900	**2,480** 920	**2,550** 950	**2,620** 970	**2,700** 1,000	**2,790** 1,040
4,000	**2,470** 920	**2,540** 940	**2,610** 970	**2,690** 1,000	**2,780** 1,030	**2,870** 1,060	**2,970** 1,100
6,000	**2,600** 970	**2,680** 990	**2,770** 1,030	**2,860** 1,060	**2,960** 1,100	**3,070** 1,140	**3,170** 1,180
8,000	**2,750** 1,020	**2,840** 1,060	**2,940** 1,090	**3,050** 1,130	**3,160** 1,170	**3,280** 1,220	**3,390** 1,260
10,000	**2,940** 1,090	**3,030** 1,130	**3,140** 1,160	**3,230** 1,200	**3,330** 1,240	—	—

5,250 LB · APPROACH 94 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	—	**2,240** 830	**2,300** 860	**2,360** 880	**2,420** 900	**2,490** 920
2,000	**2,240** 830	**2,300** 850	**2,350** 870	**2,420** 900	**2,480** 920	**2,560** 950	**2,650** 980
4,000	**2,340** 870	**2,410** 890	**2,470** 920	**2,550** 950	**2,630** 980	**2,720** 1,010	**2,810** 1,040
6,000	**2,460** 910	**2,540** 940	**2,620** 970	**2,710** 1,010	**2,800** 1,040	**2,900** 1,080	**3,000** 1,110
8,000	**2,610** 970	**2,700** 1,000	**2,790** 1,040	**2,890** 1,070	**2,990** 1,110	**3,100** 1,150	**3,210** 1,190
10,000	**2,790** 1,030	**2,870** 1,070	**2,960** 1,100	**3,060** 1,130	**3,150** 1,170	—	—

NORMAL LANDING · FLAPS 45°

3° approach, heavy braking · 2/2

Bold total over 50 ft · light ground roll · feet, zero wind, rounded up to 10 ft · — off the chart

5,000 LB · APPROACH 92 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	—	**2,130** 790	**2,180** 810	**2,230** 830	**2,290** 850	**2,350** 870
2,000	**2,120** 790	**2,170** 810	**2,220** 830	**2,280** 850	**2,340** 870	**2,420** 900	**2,500** 930
4,000	**2,210** 820	**2,270** 840	**2,330** 870	**2,410** 900	**2,490** 920	**2,570** 950	**2,650** 990
6,000	**2,330** 860	**2,400** 890	**2,470** 920	**2,560** 950	**2,650** 980	**2,740** 1,020	**2,830** 1,050
8,000	**2,460** 910	**2,550** 950	**2,640** 980	**2,730** 1,010	**2,820** 1,050	**2,920** 1,080	**3,030** 1,120
10,000	**2,630** 980	**2,710** 1,010	**2,790** 1,040	**2,880** 1,070	**2,970** 1,100	**3,090** 1,150	—

4,500 LB · APPROACH 87 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	—	**1,900** 710	**1,950** 720	**2,000** 740	**2,040** 760	**2,100** 780
2,000	**1,900** 700	**1,940** 720	**1,990** 740	**2,040** 760	**2,090** 780	**2,150** 800	**2,220** 820
4,000	**1,980** 730	**2,030** 750	**2,080** 770	**2,140** 790	**2,200** 820	**2,270** 840	**2,340** 870
6,000	**2,080** 770	**2,130** 790	**2,190** 810	**2,260** 840	**2,330** 870	**2,420** 900	**2,500** 930
8,000	**2,180** 810	**2,250** 840	**2,320** 860	**2,410** 900	**2,500** 930	**2,600** 960	**2,690** 1,000
10,000	**2,320** 860	**2,400** 890	**2,470** 920	**2,560** 950	**2,640** 980	**2,740** 1,020	—

4,000 LB · APPROACH 82 KIAS							
PA \ OAT	**0°F**	**20°F**	**40°F**	**60°F**	**80°F**	**100°F**	**120°F**
SL	—	—	—	**1,720** 640	**1,760** 650	**1,800** 670	**1,850** 690
2,000	—	**1,710** 640	**1,750** 650	**1,800** 670	**1,840** 680	**1,890** 700	**1,940** 720
4,000	**1,740** 650	**1,790** 660	**1,830** 680	**1,880** 700	**1,930** 720	**1,990** 740	**2,050** 760
6,000	**1,820** 680	**1,870** 700	**1,930** 720	**1,980** 740	**2,050** 760	**2,120** 790	**2,190** 810
8,000	**1,920** 710	**1,980** 730	**2,040** 760	**2,110** 780	**2,180** 810	**2,270** 840	**2,350** 870
10,000	**2,040** 760	**2,100** 780	**2,160** 800	**2,230** 830	**2,310** 860	**2,410** 890	—

WIND CORRECTION

Multiply the zero-wind table value by the factor

Multiply by	HW 10	HW 20	HW 30	TW 5
Takeoff flaps 20°, total	**0.87**	**0.73**	**0.60**	**1.11**
Takeoff flaps up, total	**0.88**	**0.76**	**0.64**	**1.10**
Accelerate-stop	**0.87**	**0.74**	**0.61**	**1.11**
Landing, total	**0.90**	**0.79**	**0.68**	**1.08**

Headwind and tailwind components in knots, as charted. Each factor is the least favorable one across the whole table, so it never gives less distance than the chart. Ground roll scales with the total. For the 50% headwind / 150% tailwind practice, use half the headwind or 1.5× the tailwind. The charts stop at 30 kt headwind and 5 kt tailwind. The accelerate-stop chart has no tailwind lines; its TW 5 factor borrows the flaps-up takeoff chart's ratio.

Example. Flaps 20° takeoff, 5,500 lb, 2,000 ft, 60°F, 20 kt headwind: table total over 50 ft × HW 20 factor.