




MT50e
CHASSIS

Models 2021 to Present


Emergency Response Guide






EMERGENCY RESPONSE GUIDE

MT50e: Models 2021 to Present



NOTE: Representative schematic of vehicle exterior is shown. Various door opening points are possible

 Electric Propulsion	 Charging Port	 High Voltage Li-Ion Battery	 High Voltage Component
 Low Voltage Battery	 High Voltage Power Cable	 Access to Occupants	 Disconnect High Voltage

 WARNING

For extrication purposes, the MT50e is expected to contain at least one and potentially two occupants or more occupants, depending on cab type and other factors. This vehicle contains:

1. High-Voltage (HV) components and cabling primarily routed between the frame rails and beneath the floor; and
2. Charge ports on the right-hand side and routed below the floor level, which are only energized during charging.

The HV system can be safely disabled using either the primary shut-off switch located on the left side of the battery or the secondary switch positioned under the hood on the right-hand side, as shown in the diagram. Responders should confirm the exact location of all components before cutting or piercing, as the vehicle may have been altered from its original design.



EMERGENCY RESPONSE GUIDE

MT50e: Models 2021 to Present

1. Identification



Electric Van with charging port

2. Immobilization / stabilization / lifting



Use only these lifting points

3. Disable direct hazards / safety regulations



Shutdown high voltage possible in two places

4. Access to the Occupants



There are three door exits: one located at the rear and two located at the front, one on each side of the vehicle.

NOTE: Representative schematic of vehicle exterior is shown. Various door opening points are possible.

5. Stored energy / liquids / gases / solids



High voltage charge port



EMERGENCY RESPONSE GUIDE

MT50e: Models 2021 to Present

6. In case of fire

WARNING

Always wear appropriate PPE when fighting vehicle fires.

For fighting vehicle fires with lithium-ion batteries, use PPE at least as protective as used when fighting conventional vehicle fires, including but not limited to SCBA and full-body protective clothing.

7. In case of submersion

	Disable direct hazards from section 3 once out of the water.
---	--

8. Towing / transportation / storage

		Check battery temperature
---	---	---------------------------