

# Pattern matching exhaustiveness for GADTs

George Karachalias

School of Electrical and Computer Engineering  
National Technical University of Athens

December 27, 2013

- 1 Introduction
- 2 Algebraic Data Types
- 3 Generalized Algebraic Data Types
- 4 Exhaustiveness of Pattern Matching
- 5 Extending the Mechanism
- 6 Future Work

Today we are going to talk about:

Today we are going to talk about:

- Algebraic Data Types

Today we are going to talk about:

- Algebraic Data Types
- Generalized Algebraic Data Types

Today we are going to talk about:

- Algebraic Data Types
- Generalized Algebraic Data Types
- The Glasgow Haskell Compiler

Today we are going to talk about:

- Algebraic Data Types
- Generalized Algebraic Data Types
- The Glasgow Haskell Compiler
- Exhaustiveness of GADT Matches

- 1 Introduction
- 2 Algebraic Data Types**
- 3 Generalized Algebraic Data Types
- 4 Exhaustiveness of Pattern Matching
- 5 Extending the Mechanism
- 6 Future Work



# What is an Algebraic Data Type?

## What is an Algebraic Data Type?

An ordered pair, consisting of:

## What is an Algebraic Data Type?

An ordered pair, consisting of:

- A *Type Constructor*, i.e. a type-level function that results to the type we are defining.

## What is an Algebraic Data Type?

An ordered pair, consisting of:

- A *Type Constructor*, i.e. a type-level function that results to the type we are defining.
- A set of *Data Constructors*, i.e. a set of value-level functions that have as result values of the declared type.

## What is an Algebraic Data Type?

An ordered pair, consisting of:

- A *Type Constructor*, i.e. a type-level function that results to the type we are defining.
- A set of *Data Constructors*, i.e. a set of value-level functions that have as result values of the declared type.

```
1 data TypeConstructor  type_variables_list
2   = DataConstructor1 type_parameter_list1
3   | DataConstructor2 type_parameter_list2
4   | ...
5   | DataConstructorN type_parameter_listN
```

# Some ADT Examples

# Some ADT Examples

## 1 Enumeration Types

```
data Bool = True | False
```

## Some ADT Examples

### 1 Enumeration Types

```
data Bool = True | False
```

### 2 Wrapper Types

```
data Height = Height Float  
data Width  = Width  Float
```



## Some ADT Examples

### 1 Enumeration Types

```
data Bool = True | False
```

### 2 Wrapper Types

```
data Height = Height Float  
data Width  = Width  Float
```

### 3 Polymorphism

```
data Tuple a b = MkTuple a b
```

## Some ADT Examples

### 1 Enumeration Types

```
data Bool = True | False
```

### 2 Wrapper Types

```
data Height = Height Float  
data Width  = Width  Float
```

### 3 Polymorphism

```
data Tuple a b = MkTuple a b
```

### 4 Recursive Types

```
data List a = Nil | Cons a (List a)
```

# A Larger Example

Suppose we want to create an interpreter for a simply typed expression language with integers, booleans and pairs. For this purpose, we are going to need:

Suppose we want to create an interpreter for a simply typed expression language with integers, booleans and pairs. For this purpose, we are going to need:

- A data type to represent terms/expressions

Suppose we want to create an interpreter for a simply typed expression language with integers, booleans and pairs. For this purpose, we are going to need:

- A data type to represent terms/expressions
- A simple lexer/parser

Suppose we want to create an interpreter for a simply typed expression language with integers, booleans and pairs. For this purpose, we are going to need:

- A data type to represent terms/expressions
- A simple lexer/parser
- An evaluating function

# Representing Terms

For starters, let us concern ourselves only with the data type for the representation of terms.



# Representing Terms

For starters, let us concern ourselves only with the data type for the representation of terms.

A possible definition would look like the following:

# Representing Terms

For starters, let us concern ourselves only with the data type for the representation of terms.

A possible definition would look like the following:

```
1 data Term
2   = Lit Int
3   | Inc Term
4   | IsZ Term
5   | If Term Term Term
6   | Pair Term Term
7   | Fst Term
8   | Snd Term
```

# Representing Terms

Or, with explicit typing:

# Representing Terms

Or, with explicit typing:

```
1 data Term where
2   Lit  :: Int  -> Term
3   Inc  :: Term -> Term
4   IsZ  :: Term -> Term
5   If   :: Term -> Term -> Term -> Term
6   Pair :: Term -> Term -> Term
7   Fst  :: Term -> Term
8   Snd  :: Term -> Term
```

# Evaluation of Terms

The evaluation of a term can result to an integer, a boolean, or a pair of two values:

## Evaluation of Terms

The evaluation of a term can result to an integer, a boolean, or a pair of two values:

```
1 eval (Lit 7)                = 7      -- :: Int
2 eval (IsZ (Lit 7))          = False -- :: Bool
3 eval (Pair (Lit 6) (Lit 7)) = (6,7) -- :: (Int, Int)
```

## Evaluation of Terms

The evaluation of a term can result to an integer, a boolean, or a pair of two values:

```
1 eval (Lit 7)                = 7      -- :: Int
2 eval (IsZ (Lit 7))          = False -- :: Bool
3 eval (Pair (Lit 6) (Lit 7)) = (6,7) -- :: (Int, Int)
```

Hence, we have to define one more ADT for values:

## Evaluation of Terms

The evaluation of a term can result to an integer, a boolean, or a pair of two values:

```
1 eval (Lit 7)                = 7      -- :: Int
2 eval (IsZ (Lit 7))          = False -- :: Bool
3 eval (Pair (Lit 6) (Lit 7)) = (6,7) -- :: (Int, Int)
```

Hence, we have to define one more ADT for values:

```
1 data Value
2   = VI Int      -- Integer Value
3   | VB Bool     -- Boolean Value
4   | VP Value Value -- Pair Value
```



# Evaluation of Terms

Now we can write the `eval` function:

## Evaluation of Terms

Now we can write the `eval` function:

```
eval :: Term -> Value
eval (Lit x) = VI x
eval (Inc t)
  | VI x <- eval t = VI (x+1)
  | otherwise = error "Inc: Not an Int"
eval (IsZ t)
  | VI x <- eval t = VB (x==0)
  | otherwise = error "IsZ: Not a Bool"
eval (If t x y)
  | VB b <- eval t = if b then eval x
                    else eval y
  | otherwise = error "If: Not a Bool"
```

# Evaluation of Terms

..and the rest of it:

```
eval (Pair x y) = VP (eval x) (eval y)
eval (Fst t)
  | VP v1 _ <- eval t = v1
  | otherwise = error "Fst: Not a Pair"
eval (Snd t)
  | VP _ v2 <- eval t = v2
  | otherwise = error "Snd: Not a Pair"
```

Introduction

**Algebraic Data Types**

Generalized Algebraic Data Types

Exhaustiveness of Pattern Matching

Extending the Mechanism

Future Work

# Issues

# Issues

- 1 **The ADT does not enforce type-checking**

# Issues

## 1 The ADT does not enforce type-checking

Nothing prevents the formation of ill-typed terms like the following:

```
1 IsZ (IsZ (Lit 42))
```

```
2 Fst (Lit 5)
```

# Issues

## 1 The ADT does not enforce type-checking

Nothing prevents the formation of ill-typed terms like the following:

```
1 IsZ (IsZ (Lit 42))
```

```
2 Fst (Lit 5)
```

## 2 Evaluator's run-time checks

# Issues

## 1 The ADT does not enforce type-checking

Nothing prevents the formation of ill-typed terms like the following:

- 1 `IsZ (IsZ (Lit 42))`
- 2 `Fst (Lit 5)`

## 2 Evaluator's run-time checks

Due to (1), we have to manually check that the recursive calls to `eval` return the expected type of value (hence the guards).



# Issues

## 1 The ADT does not enforce type-checking

Nothing prevents the formation of ill-typed terms like the following:

- 1 `IsZ (IsZ (Lit 42))`
- 2 `Fst (Lit 5)`

## 2 Evaluator's run-time checks

Due to (1), we have to manually check that the recursive calls to `eval` return the expected type of value (hence the guards).

- Tiresome for the programmer

# Issues

## 1 The ADT does not enforce type-checking

Nothing prevents the formation of ill-typed terms like the following:

- 1 `IsZ (IsZ (Lit 42))`
- 2 `Fst (Lit 5)`

## 2 Evaluator's run-time checks

Due to (1), we have to manually check that the recursive calls to `eval` return the expected type of value (hence the guards).

- Tiresome for the programmer
- Additional overhead

How can we make our solution more elegant?

How can we make our solution more elegant?

With the expressive power of

**Generalized Algebraic Data Types**

- 1 Introduction
- 2 Algebraic Data Types
- 3 Generalized Algebraic Data Types**
- 4 Exhaustiveness of Pattern Matching
- 5 Extending the Mechanism
- 6 Future Work

1) Each data constructor may return a different instantiation of the abstract type:

1) Each data constructor may return a different instantiation of the abstract type:

```
1 data Term a where
2   Lit   :: Int -> Term Int
3   Inc   :: Term Int -> Term Int
4   IsZ   :: Term Int -> Term Bool
5   If    :: Term Bool -> Term a -> Term a -> Term a
6   Pair  :: Term a -> Term b -> Term (a,b)
7   Fst   :: Term (a,b) -> Term a
8   Snd   :: Term (a,b) -> Term b
```

2) Alternatively, all data constructors have the same return type, but their type may quantify over constraints (*qualified types*):



2) Alternatively, all data constructors have the same return type, but their type may quantify over constraints (*qualified types*):

```
1 data Term a where
2   Lit  :: forall a. (a ~ Int)  => Int  -> Term a
3   Inc  :: forall a. (a ~ Int)  => Term Int -> Term a
4   IsZ  :: forall a. (a ~ Bool) => Term Int -> Term a
5   If   :: forall a. Term Bool -> Term a -> Term a -> Term a
6   Pair :: forall a b c. (a ~ (b,c)) => Term b -> Term c -> Term a
7   Fst  :: forall a b. (a ~ b)   => Term (b,c) -> Term a
8   Snd  :: forall a c. (a ~ c)   => Term (b,c) -> Term a
```

Now, the implementation of the evaluating function is absolutely straightforward and its type trivial:

Now, the implementation of the evaluating function is absolutely straightforward and its type trivial:

```
1 eval :: Term a -> a
2 eval (Lit i)      = i
3 eval (Inc t)      = eval t + 1
4 eval (IsZ t)      = eval t == 0
5 eval (If t a b)   = if eval t then eval a else eval b
6 eval (Pair a b)   = (eval a, eval b)
7 eval (Fst t)      = fst (eval t)
8 eval (Snd t)      = snd (eval t)
```

## One More Example: Vectors

```
data Vec a n where
  VNil  :: Vec a Zero
  VCons :: a -> Vec a n -> Vec a (Succ n)
```

## One More Example: Vectors

```
data Vec a n where
  VNil  :: Vec a Zero
  VCons :: a -> Vec a n -> Vec a (Succ n)

vhead :: Vec a (Succ n) -> a
vhead (VCons x _) = x
```

## One More Example: Vectors

```
data Vec a n where
```

```
  VNil  :: Vec a Zero
```

```
  VCons :: a -> Vec a n -> Vec a (Succ n)
```

```
vhead :: Vec a (Succ n) -> a
```

```
vhead (VCons x _) = x
```

```
vmap :: (a -> b) -> Vec a n -> Vec b n
```

```
vmap f VNil      = VNil
```

```
vmap f (VCons x xs) = VCons (f x) (vmap f xs)
```

- 1 Introduction
- 2 Algebraic Data Types
- 3 Generalized Algebraic Data Types
- 4 Exhaustiveness of Pattern Matching**
- 5 Extending the Mechanism
- 6 Future Work

```
data Vec a n where
```

```
  VNil  :: Vec a Zero
```

```
  VCons :: a -> Vec a n -> Vec a (Succ n)
```

```
vhead :: Vec a (Succ n) -> a
```

```
vhead (VCons x _) = x
```

```
vmap :: (a -> b) -> Vec a n -> Vec b n
```

```
vmap f VNil      = VNil
```

```
vmap f (VCons x xs) = VCons (f x) (vmap f xs)
```



```
data Vec a n where
  VNil  :: Vec a Zero
  VCons :: a -> Vec a n -> Vec a (Succ n)

vhead :: Vec a (Succ n) -> a
vhead (VCons x _) = x
vhead VNil        = error "Inaccessible Code!"

vmap :: (a -> b) -> Vec a n -> Vec b n
vmap f VNil      = VNil
vmap f (VCons x xs) = VCons (f x) (vmap f xs)
```

## A tedious situation

## A tedious situation

```
vzip :: Vec a n -> Vec b n -> Vec (a,b) n  
vzip VNil          VNil          = VNil  
vzip (VCons x xs) (VCons y ys) = VCons (x,y) (vzip xs ys)
```

## A tedious situation

```
vzip :: Vec a n -> Vec b n -> Vec (a,b) n
vzip VNil          VNil          = VNil
vzip (VCons x xs) (VCons y ys) = VCons (x,y) (vzip xs ys)
```

ghc complains with the following warning:

```
Warning: Pattern match(es) are non-exhaustive
In an equation for `vzip':
  Patterns not matched:
    VNil (VCons _ _)
    (VCons _ _) VNil
```

## A tedious situation

```
vzip :: Vec a n -> Vec b n -> Vec (a,b) n
vzip VNil          VNil          = VNil
vzip (VCons x xs) (VCons y ys) = VCons (x,y) (vzip xs ys)
vzip VNil          (VCons _ _ ) = error "Inaccessible Code!"
vzip (VCons _ _ ) VNil          = error "Inaccessible Code!"
```

## A tedious situation

```
vzip :: Vec a n -> Vec b n -> Vec (a,b) n
vzip VNil          VNil          = VNil
vzip (VCons x xs) (VCons y ys) = VCons (x,y) (vzip xs ys)
vzip VNil          (VCons _ _ ) = error "Inaccessible Code!"
vzip (VCons _ _ ) VNil          = error "Inaccessible Code!"
```

ghc complains with the following error:

```
Couldn't match type `Zero' with `Succ n1'
Inaccessible code in
  a pattern with constructor
    VCons :: forall a (n :: Nat). a -> Vec a n
          -> Vec a (Succ n)
```

## Suppressing the warning

```
vzip :: Vec a n -> Vec b n -> Vec (a,b) n
vzip VNil          VNil          = VNil
vzip (VCons x xs) (VCons y ys) = VCons (x,y) (vzip xs ys)
vzip _             _             = error "Inaccessible Code!"
```

- 1 Introduction
- 2 Algebraic Data Types
- 3 Generalized Algebraic Data Types
- 4 Exhaustiveness of Pattern Matching
- 5 Extending the Mechanism**
- 6 Future Work



# Identifying the problem

# Why missing?

## Why missing?

GHC does not take into account local constraints when detecting missing patterns.

## Why missing?

GHC does not take into account local constraints when detecting missing patterns.

Recall the definition of vectors:

```
data Vec a n where
```

```
  VNil  :: forall a n.   (n~Zero)    => Vec a n
```

```
  VCons :: forall a n m. (n~Succ m) => a -> Vec a m -> Vec a n
```

## Why missing?

GHC does not take into account local constraints when detecting missing patterns.

Recall the definition of vectors:

```
data Vec a n where
```

```
  VNil  :: forall a n.   (n~Zero)    => Vec a n
```

```
  VCons :: forall a n m. (n~Succ m) => a -> Vec a m -> Vec a n
```

and the type of function vhead:

```
vhead :: Vec a (Succ n) -> a
```

## Why missing?

GHC does not take into account local constraints when detecting missing patterns.

Recall the definition of vectors:

```
data Vec a n where
```

```
  VNil  ::
```

```
  VCons ::
```

```
Vec a n
```

```
a -> Vec a m -> Vec a n
```

and the type of function vhead:

```
vhead :: Vec a (Succ n) -> a
```

# Why is it an error then?

## Why is it an error then?

The type checker of GHC takes into account the local constraints introduced by data constructors (as it should!).



## Why is it an error then?

The type checker of GHC takes into account the local constraints introduced by data constructors (as it should!).

```
data Vec a n where
```

```
  VNil  :: forall a n.   (n~Zero)    => Vec a n
```

```
  VCons :: forall a n m. (n~Succ m) => a -> Vec a m -> Vec a n
```

```
vhead :: Vec a (Succ n) -> a
```

```
vhead (VCons x _)      = x
```

```
vhead VNil              = error "Inaccessible Code!"
```

# Why can we overcome it?

## Why can we overcome it?

GHC's mechanism for the detection of overlapping patterns is also incomplete.

```
vhead :: Vec a (Succ n) -> a
vhead (VCons x _)      = x
vhead _                 = error "Inaccessible Code!"
```

# A Solution

# Idea

# Idea

- 1 Call the previous mechanism to detect the (possibly more than actual) missing patterns.

# Idea

- 1 Call the previous mechanism to detect the (possibly more than actual) missing patterns.
- 2 For every missing pattern collect the constraints that would introduce, if it appeared.

# Idea

- 1 Call the previous mechanism to detect the (possibly more than actual) missing patterns.
- 2 For every missing pattern collect the constraints that would introduce, if it appeared.
- 3 Call the constraint solver for each set of constraints (taking into consideration the program constraints) and, depending on the result:



# Idea

- 1 Call the previous mechanism to detect the (possibly more than actual) missing patterns.
- 2 For every missing pattern collect the constraints that would introduce, if it appeared.
- 3 Call the constraint solver for each set of constraints (taking into consideration the program constraints) and, depending on the result:
  - If the solver fails, the pattern under examination *cannot* really appear (with respect to the context) and we should not issue a warning.

# Idea

- 1 Call the previous mechanism to detect the (possibly more than actual) missing patterns.
- 2 For every missing pattern collect the constraints that would introduce, if it appeared.
- 3 Call the constraint solver for each set of constraints (taking into consideration the program constraints) and, depending on the result:
  - If the solver fails, the pattern under examination *cannot* really appear (with respect to the context) and we should not issue a warning.
  - If the solver succeeds, the pattern could appear in the specific context and a warning should be issued, since the pattern is actually missing.

# Key Points

## Key Points

- The missing patterns that **GHC issues warnings for** are always a **superset** of the patterns that **are actually missing**.

## Key Points

- The missing patterns that **GHC issues warnings for** are always a **superset** of the patterns that **are actually missing**.
- GHC's type checker (via constraint solving) detects inaccessible patterns.

# Advantages

## Advantages

**Simplicity** Based on mechanisms that are supported by most (if not all) languages that support ADTs:

- 1 Constraint Solving
- 2 Non-Exhaustiveness Check

## Advantages

**Simplicity** Based on mechanisms that are supported by most (if not all) languages that support ADTs:

- 1 Constraint Solving
- 2 Non-Exhaustiveness Check

**Efficiency** Patterns usually introduce only a few constraints.



## Advantages

**Simplicity** Based on mechanisms that are supported by most (if not all) languages that support ADTs:

- 1 Constraint Solving
- 2 Non-Exhaustiveness Check

**Efficiency** Patterns usually introduce only a few constraints.

**Consistency** Preserves the properties of the type system. We consider a pattern missing, only if the typechecker *allows* us to. If the semantics change, so does the behaviour of our mechanism.

# Disadvantage

## Disadvantage

**Recovery** In the cases of GADT constructors that are not actually missing, the constraint solver **must** fail and recover. Hence, the compilation for programs that make heavy use of GADTs may delay a bit.

# Implementation Results

## Performance (Part 1)

## Performance (Part 1)

- **GHC Build**

Both about 1 hour and 47 minutes. (22 secs faster)

## Performance (Part 1)

- **GHC Build**

Both about 1 hour and 47 minutes. (22 secs faster)

- **Testsuite Build**

Both about 4 hours and 58 minutes. (17 secs slower)

## Performance (Part 2)

```
1 data F :: * -> * -> * -> * where
2   MkF1  :: Int  -> Int  -> Int  -> F Int  Int  Int
3   MkF2  :: Int  -> Int  -> Char -> F Int  Int  Char
4   MkF3  :: Int  -> Int  -> Bool -> F Int  Int  Bool
5   ...
6   MkF27 :: Bool -> Bool -> Bool -> F Bool Bool Bool
```



## Performance (Part 2)

```
1 data F :: * -> * -> * -> * where
2   MkF1  :: Int  -> Int  -> Int  -> F Int  Int  Int
3   MkF2  :: Int  -> Int  -> Char -> F Int  Int  Char
4   MkF3  :: Int  -> Int  -> Bool -> F Int  Int  Bool
5   ...
6   MkF27 :: Bool -> Bool -> Bool -> F Bool Bool Bool
```

### ● Non Exhaustive

```
func1 :: F a b c -> Int
```

## Performance (Part 2)


```
1 data F :: * -> * -> * -> * where
2   MkF1  :: Int  -> Int  -> Int  -> F Int  Int  Int
3   MkF2  :: Int  -> Int  -> Char -> F Int  Int  Char
4   MkF3  :: Int  -> Int  -> Bool -> F Int  Int  Bool
5   ...
6   MkF27 :: Bool -> Bool -> Bool -> F Bool Bool Bool
```


- **Non Exhaustive**

```
func1 :: F a b c -> Int
```

- **Exhaustive**

```
func1 :: F a a a -> Int
```





# Correctness

## ● Testsuite Results

	Adjusted GHC	Vanilla GHC
expected passes	11122	11126
expected failures	141	141
unexpected passes	2	2
unexpected failures	72	68

## • Testsuite Results

	Adjusted GHC	Vanilla GHC
expected passes	11122	11126
expected failures	141	141
unexpected passes	2	2
unexpected failures	72	68

## • GHC Tickets

- #366
- #2006
- #3927
- #4139 (half)

## Other Examples



## Case Expressions

```
data T :: * -> * -> * where
  T1 :: Int -> Int -> T Int Int
  T2 :: Char -> Int -> T Char Int
  T3 :: Int -> Char -> T Int Char

f :: T a a -> Int
f x = case x of
  T1 i j -> i+j
```

-- should not issue warning

## Pattern Matching

```
data T :: * -> * -> * where
  T1 :: Int -> Int -> T Int Int
  T2 :: Char -> Int -> T Char Int
  T3 :: Int -> Char -> T Int Char

f :: T a a -> Int
f (T1 i j) = i+j      -- should not issue warning
```

## Let Bindings

```
data T :: * -> * -> * where
  T1 :: Int    -> Int    -> T Int  Int
  T2 :: Char   -> Int    -> T Char Int
  T3 :: Int    -> Char   -> T Int  Char
```

```
f :: T a a -> Int
f x = let T1 i j = x -- should not issue warning
      in i+j
```

## Where Bindings

```
data T :: * -> * -> * where
  T1 :: Int -> Int -> T Int Int
  T2 :: Char -> Int -> T Char Int
  T3 :: Int -> Char -> T Int Char
```

```
f :: T a a -> Int
f x = i+j           -- should not issue warning
  where T1 i j = x
```

## Nested Patterns

```
data X :: * -> * -> * where
```

```
  X1 :: X Char Char
```

```
  X2 :: X Int  Char
```

```
data Y :: * -> * -> * where
```

```
  Y1 :: Int  -> Char -> Y Int  Char
```

```
  Y2 :: Char -> Char -> Y Char Char
```

```
  Y3 :: a     -> b     -> Y a     b
```

```
fxy :: Y (X a a) (X a a) -> a
```

```
fxy value = case value of
```

```
    Y3 X1 X1 -> 'a'
```

## A Tricky Example

```
data T a where
```

```
  T1 :: T Int
```

```
  T2 :: T Bool
```

```
f1 :: T a -> T a -> Bool
```

```
f1 T1 T1 = True
```

```
f1 T2 T2 = False
```

```
f2 :: T a -> T a -> Bool
```

```
f2 T1 (T1 :: T Int) = True
```

```
f2 T2 (T2 :: T Bool) = False
```

## Data Kinds & Type Classes

```
data Vec v a where
```

```
  Nil :: Vec '[] a
```

```
  Vec :: a -> Vec v a -> Vec (() ': v) a
```

```
instance Eq a => Eq (Vec v a) where
```

```
  Nil == Nil = True
```

```
  (Vec x xs) == (Vec y ys) = x == y && xs == ys
```

- 1 Introduction
- 2 Algebraic Data Types
- 3 Generalized Algebraic Data Types
- 4 Exhaustiveness of Pattern Matching
- 5 Extending the Mechanism
- 6 Future Work**



## What's Next?

- Forthcoming version of GHC (7.8.1)
- Overlapping Patterns (#595 and at least 8 more tickets)



# Questions?