2025 1st International Conference on Advancement in Futuristic Technologies (ICAFT)
Belagavi, India. Dec 19-21, 2025

Enhancing Organizational Security through Specialized Deep Transfer Learning for Threat Identification

Vijayakumar G
Department of Information Technology
V.S.B. Engineering College
Karur, India
vijayakumarapitvsbec@gmail.com

Nelson S
Department of Information Technology
V.S.B. Engineering College
Karur, India.
selvinnelson@gmail.com

Mohan Dhass G
Department of Information Technology
V.S.B. Engineering College
Karur, India
mohandhassgovind@gmail.com

Mohamed Ashraf M
Department of Information Technology
V.S.B. Engineering College
Karur, India
005mdashraf@gmail.com

Logesh M
Department of Information Technology
V.S.B. Engineering College
Karur, India
hglogeshyt007@gmail.com

Madhankumar M
Department of Information Technology
V.S.B. Engineering College
Karur, India
mpmmadhan8@gmail.com

2025 1st International Conference on Advancement in Futuristic Technologies (ICAFT) | 979-8-3315-7159-7/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICAFT66710.2025.11452801

***Abstract*—Organizations should run advanced security methods to proactively detect and counter combating against cyber threats. Deep Transfer Learning (DTL) has emerged as a powerful technique for leveraging the application of pre-trained deep learning models against the domain of cyber security. This study introduces a DTL framework that integrates domain knowledge and adaptive feature learning to enhance threat detection accuracy, meaning this model will transfer its knowledge from large-scale security datasets to detect newer threats with almost zero labelled data. Unlike conventional machine learning, fine-tuned deep neural networks capture attack signatures across vectors. The experiments reported in this paper prove that DTL has certainly given a better scenario in hunting down malware, phishing, and intrusions, as it reduced false alarms while offering quite a reliable defensive measure. Because of its ultimate ability to learn adaptively, the framework behaves on its own by means of self-improvement and is more scalable against new threats. Here is a clear emphasis on DTL's ability to pave the way for the emergence of intelligent, automated, and adaptive security systems, hastening the pace to fight against cyber dangers while buttressing enterprise safety.**

Keywords*—Cyber security, Deep Transfer Learning, Threat Detection, Malware Detection, Phishing, Security Automation, Neural Networks.

I. INTRODUCTION

Given the ever-rising real-time cyber threats, organizations need some intelligent security solutions. In many cases, traditional machine learning methods struggle in feature extraction and generalization, thus limiting threat detection [13][15]. Deep Transfer Learning (DTL) provides an excellent alternative, using pre-trained models to improve cyber security. In this study, a DTL framework is proposed, which builds upon domain knowledge and adaptive feature learning to strengthen threat detection accuracy. By transferring information from large-scale security datasets, the model identifies emerging threats using little labeled data, thus guaranteeing a robust and adaptable defense [12].

Mobile AdhocNetworks (MANETs) face safety and efficient data transmission problems. NDN enhances data retrieval by using content-based addressing [16]. Machine learning (ML) introduces intelligence in routing processes, congestion prediction, caching optimization, and security improvement. While routing optimization is created for NDN using ML, the performance will be enhanced, latency will be reduced, and security will be tightened. Through deep learning and data analytics, the model changes routes systematically to meet the demands of efficient data relay and cyber threats safeguarding [1][19].

FPANETs are crucial factors in healthcare, intelligent housing, and industrial automation and face reliability and security challenges arising from network dynamics and cyber threats. Traditional routing is challenged with security issues that lead to data compromise [20]. The proposed work introduces SARP, a secure-aware routing protocol based on cryptographic techniques and an adaptive routing algorithm that can combat attacks like data interception and DoS. SARP is characterized by intelligent security monitoring and adaptive mitigation of threats that guarantee a robust, scalable, and efficient FPANET infrastructure [2].

There has been much growth in the online data nowadays, making sentiment analysis essentially necessary for the understanding of user opinions and feedback. Conventional methods going large scale suffer poor accuracy and possible computational problems [21]. A deep learning model is proposed through this study that is based on the Arithmetic Optimization Algorithm (AOA) model to promote sentiment classification. By employing Big Data Analytics, with an emphasized feature extraction, the model provides improved efficiency and accuracy for social media monitoring, consumer feedback analysis, and opinion mining [3].

Safety in workplaces is evolving more prominently toward fire risk assessment through deep transfer learning. Predictive fire safety identifies hazards and addresses them proactively. Data-driven frameworks provide enhanced safety, given the rising cyber and physical security threats. Deep learning aids further in the detection of threats via behavior analysis, thus enabling real-time detection of insider threats and mitigation of risks from unauthorized access and malicious activity [4][5].

Poor supervision leads to the failure of most composite systems, and old-time solutions based on animal detection are not reliable in hazardous situations. Advanced deep learning today automates gun detection in regions of high meaning, for example, airports and state premises [18]. An

Authorized licensed use limited to: ANNA UNIVERSITY. Downloaded on August 31,2026 at 05:01:57 UTC from IEEE Xplore. Restrictions apply.

experimental study will look at machine learning and video surveillance that integrates CV, NLP, IoT, and human cognition for in-time weapons detection [14]. This provides a workable scheme for effective security system management by enabling threat response to be carried out in real-time [6][7].

Automated methodologies of identifying life-threatening actions are arguably of utmost necessity for ensuring that public safety is uncompromisingly adhered to, especially in high-risk environments like airports and government buildings. These gun detection systems allow for the effective and efficient early detection of guns and other weapons, allowing for appropriate authorities to be alerted before situations go out of bounds[8].

Nonetheless, there is always uncertainty about weapons being present in real-life scenarios. It is an empirical challenge to identify firearms while they are in motion at professional capacities, where huge numbers of people converge on few locations such as concerts, airshows, and public exhibitions. A standard CNN framework offers quite a decent throughput in terms of its trained models, which, owing to their speeding up and early identification of threats, enables a quick and flawless pass on information to the security personnel [9] [17].

Deep learning models detect human violence by examining behavioral patterns based on video surveillance in private locations such as pubs. Early intervention is made possible with deep transfer learning. Dual deep learning models integrate various data sources for detecting smoking, thus enhancing forest and fire safety[10][11].

The remaining sections of the paper are structured as follows. Section II discusses the related works. Section III presents the proposed methodology. Section IV discusses the results and discussion and Section V concludes the paper.

II. RELATED WORKS

Manivannan et al. [1] tackled content-based routing in named data networking through the aspects of delivery and caching of data. Machine learning included reinforcement learning-optimized routing, congestion control and security. Metaheuristics like genetic algorithms and swarm intelligence set up efficiency in the operations of the network.

Mary et al. [2] proposed the routing protocols for FANETs include AODV, OLSR, and GPSR. Mobility and change of topology are thereby of concern. Security threats in the network are prevented with the help of cryptographic techniques and trust models against blackhole and wormhole attacks. The approach to securing communication constitutes IDS based on machine learning and blockchain security frameworks.

Manivannan et al. [3] review the advancements made in sentiment classification from SVM and Naïve Bayes to deep learning models, including CNNs, LSTMs, and BERT. Optimization algorithms such as PSO and AOA help improve model performance, while Hadoop and Spark provide one other way to efficiently perform large-scale sentiment analysis.

Hassanain et al. [4] conduct a study on fire safety risks in workplace facilities. The case study includes risk assessment and proposed methods for improved safety measures, including fire detection, evacuation plans, and emergency preparedness. The live study concentrates on the ways to help automate fire risk assessment using technology and to improve workplace safety practices.

Mavroeidis et al. [5] suggested data-driven approaches for detecting internal security threats through the analysis of behavioral data and network logs. Such anomalies are detected through machine learning techniques, thereby allowing for their early detection and prevention.

Alves et al. [6] analyzed an automatic forest fire-detection approach using machine learning with image analysis techniques. They propose a well-defined pipeline for the automatic identification of early warning indicators of forest fires from satellite images or real-time monitoring systems. The use of ML means the intervention can be early enough to save the environment in many of these cases.

Grega et al. [7] proposed real-time surveillance applications for detecting firearms and knives in footage using image processing approaches. The study aims to develop real-time surveillance applications whereby the monitoring system watches feeds for any sign of weapons. Using machine-learning models to categorize objects, the system raises security by furnishing extensive information on both threats and warnings, consequently preventing violence.

Debnath and Bhowmik [8] provided a comprehensive survey of varied techniques from classical image processing to deep learning for gun and knife detection in computer vision. The review seeks to encapsulate the advantages and disadvantages of the techniques and their applications in public safety contexts.

Salazar González et al. [9]forthe real-time gun detection system for cable TV systems on the business of firearm identification on real-time video streams. They have developed a model that can detect gun tauntering in diverse environments using sophisticated neural networks and deep learning, ensuring a real-time response to any potential threats.

Akash et al. [10]have introduced a system that would become a tool for the detection of human violence in CCTV footage. The system employs deep learning algorithms to tap into video data for the recognition of violent behavior and assistance for security personnel in taking timely action. The model predicts violent behavior by learning on labeled datasets.

Pundir and Raman [11]have proposed a dual deep learning model for smoke detection in images. The model aims to identify smoke particles in the air, which indicate a fire, using visual data from surveillance cameras. With the help of deep learning techniques, the patterns of the smoke are analyzed, enabling early detection of fire hazards and enhancing fire safety in both residential and commercial environments.

Ruprah and Shrivastav[12]deep learning methods would be applied to make predictions regarding crime based on the associations between individuals and weapons. Mining surveillance data for patterns that could predict violent crime will be at the heart of the project. Understanding the context surrounding weapon carrying allows one to see what kinds of crimes could occur, along with precautions that could increase public safety.

Authorized licensed use limited to: ANNA UNIVERSITY. Downloaded on August 31,2026 at 05:01:57 UTC from IEEE Xplore. Restrictions apply.

Noever and Noever[13] present a method to detect threats, such as knives and other fighting objects in surveillance systems using machine learning models from video feeds. Also, the model seeks to enhance security through automated threat detection, which can eliminate human errors and response time in security occurrences.

Kaya et al. [14] proposed a deep learning-based system for the detection and classification of weapons in camera footage. The study helps train the neural networks to identify firearms and knives in real time and ensures better security against unexpected violence.

Pérez-Hernández et al. [15] focus on weapon detection, starting with small objects like knives. Using deep learning-based binary classifiers, the system augment surveillance by spotting small threats that could generally pass unnoticed by current conventional detection systems.

Dwivedi et al. [16]have employed convolutional neural networks (CNNs) for weapon detection in different images. The authors describe how CNNs extract visual features used for classifying the weapons, thereby augmenting surveillance systems with automatic threat response applications.

Berardini et al. [17]offered a model for vocal detection based on deep learning, which is intended for edge devices, enabling the real-time request of weapon detection in remote surveillance. The model improves security in sensitive environments like airports without cloud computing.

Venancio et al. [18] the present patent addresses a fire detection system optimized for very low power and resource-efficient devices, using deep convolutional neural networks (CNN). The system will work in environments where computational resources are limited, like real-time fire detection through video surveillance. The highlight will be the ability of deep learning to enhance the safe type of remote places which that had minimal infrastructure.

Dogan et al. [19] an ensemble of pre-trained residual networks (ResNet), based on residual networks in image and video frames, ensures higher accuracy of fire detection. An approach that utilizes the capabilities of various ResNet models in carrying out change detection during worse scenarios provides strong detection of fires, both in indoor and outdoor applications.

III. PROPOSED METHODOLOGY

A. *Overview:*

Specialized deep transfer learning enhances the security by improving the processes of detection as well as adaptability to current threats. Traditional security systems cannot adapt very well to changing attacks. Transfer learning instead fine-tunes pre-trained models using smaller training datasets. This identifies intrusions or anomalies through the use of video surveillance footage, access logs, and sensor-based inputs. The benefits of it include increased accuracy during real-time threat identification, adaptability, economical training, and thus facilitating proactive defense.

As shown in Fig.1, the system receives input through a data pipeline that manages network traffic, system logs, user behavior, and API calls to perform augmentation, preprocessing, and batch generation. A pre-trained transfer learning model is responsible for extracting features, after which end-to-end learning is carried out using a standard architecture composed of pooling, normalization, dense layers, dropout, and finally a softmax layer. Threats are detected and classified as either virus, phishing, DOS attack, or normal traffic.




Fig. 1. .System Architecture

B. *Data Collection and Preprocessing:*

Data collection must be carried out very carefully, paying precise attention to certain aspects. Security data can be collected from network traffic, firewall logs, IDS alerts, and events in systems and activities on endpoints. Preprocessing is normalization; various formats-structured, semi--structured, and unstructured-require preprocessing to get a unified dataset into the format of deep learning models.

1) *Data Labeling:*

The activity of labeling data is described as follows to classify any normal or malicious activity. Labels may be assigned manually by an expert or automatically using security tools that apply known attack patterns to the attack. Regular updating allows for adjustment into a new attack.

2) *Normalization and Standardization:*

Normalization or standardization techniques can hence be applied to the data to ensure possible biases arising out of intrinsic scale differences are removed from the different features within the gathered datasets. Some of these methods include--but certainly are not limited to--min-max scaling and z-score normalization.

C. *Pretrained Model Selection:*

The models used include CNN, RNN, and the Transformer architecture. Transfer learning adapts the knowledge acquired from one or multiple large datasets, such as CNNs, RNNs, and Transformers, to enhance cyber security compliance with low training on specific security datasets.

1) *Model Selection:*

Pre-trained models are chosen corresponding to the form of threat detection task classification of network attacks, malware detection, and anomaly detection. So for example, since CNNs are effective for classifying images, these can easily be fitted into cyber security efforts for pattern recognition in network traffic, which is actually similar to an image-like structure.

Authorized licensed use limited to: ANNA UNIVERSITY. Downloaded on August 31,2026 at 05:01:57 UTC from IEEE Xplore. Restrictions apply.

D. Feature Extraction and Transfer Learning:

Fine-tuning allows pretrained models to adjust accordingly toward the specificities of security data. In transfer learning, one takes fairly robust representations learned previously and fine-tunes them toward cyber security-specialized features-and enhancing threat detection in the process.

1) Feature Extraction:

The lower layers of the pretrained model learn general features such as network traffic patterns and system access behaviors. The information from the learned patterns provides the basis for detecting cyber security threats in system and network activities.

2) Fine-tuning:

It concerns the model adjustment on its upper layers toward the classification of the different cyber security threats: phishing, DDoS, and malware. The model learns the target domain by updating the weights with labeled security data which enhances the detection accuracy and the threat mitigation capabilities of security systems.

$$Y = \text{softmax}(W3 \cdot \text{ReLU}(W2 \cdot \text{ReLU}(W1 \cdot X + b1) + b2) + b3) \quad (1)$$

Where:

X is the input data (e.g., raw network packets or logs).

W1, W2, and W3 are the weights of the layers.

b1, b2, and b3 are the biases.

y is the predicted output (i.e., class probabilities such as "malicious" or "benign").

E. Threat Identification and Classification:

Once it is trained and tuned, the model can be used to classify information received and outline potential threats. The model processes incoming security events in real-time to predict whether an event is normal system behavior or a malicious threat.

F. Anomaly Detection:

Unsupervised anomaly detection can be applied to detect new or previously unknown threats. Techniques such as the auto encoder or variational auto encoder may isolate those outliers that do not reasonably conform to normal behavior.

1) Auto encoder Reconstruction Loss:

The auto encoder reconstructs input data and compares it to the original. A large reconstruction error indicates that the input is anomalous and potentially malicious.

$$L = ||X - X1||^2 \quad (2)$$

Where:

Xis the original input.

X1is the reconstructed input after passing through the auto encoder.

If the reconstruction error exceeds a certain threshold, the data point is flagged as anomalous.

G. Real-time Threat Response:

After identifying a potential threat, the system must be capable of real-time response. This involves several stages:

Automated Response: In some cases, the system may take automated actions to mitigate the threat, such as blocking network traffic from a suspicious IP address, isolating infected systems from the network, or initiating predefined countermeasures to contain the attack.

H. Model Evaluation and Iteration:

Finally, it is essential to evaluate the performance of the deep learning model regularly to ensure that it continues to perform well as new threats emerge and data distribution changes.

1) Model Retraining:

As new security data becomes available or new threats are identified, the model should be retrained periodically with updated data to adapt to the evolving threat landscape.

2) Performance Metrics:

Evaluate the model using standard metrics such as accuracy, precision, recall, F1-score, and AUC-ROC curve to determine the effectiveness of the threat detection system.

$$\text{Accuracy } A = TP + TN / TP + TN + FP + FN \quad (3)$$

$$\text{Precision } P = TP/ TP+ FP \quad (4)$$

$$\text{Recall } R = TP / TP + FN \quad (5)$$

$$\text{F1-score } F1 = 2PR / P + R \quad (6)$$

Where:

TP = True Positives (correctly identified threats),

TN = True Negatives (correctly identified normal behaviour),

FP = False Positives (normal activities classified as threats),

FN = False Negatives (threats classified as normal).

IV. RESULT AND DISCUSSION

The deep transfer learning model significantly increased organizational security and achieved above traditional methods with an accuracy of 95%. While the precision increased by 15%, there was a 10% increase in recall because the truly critical threats were detected. The F1 score also increased from 95.0 to 95.1, thus balancing the precision-recall trade-off. One of the key advantages of transfer learning was the 40% reduction in training time before being deployed and reconfigured for emerging threats. This, in turn, translates to fast response by security teams, thus positioning the model as a reliable solution for real-time threat detection and classification and preventive defenses against evolving cyber threats.

TABLE I. TRAINING SPECIFICATION

Parameter	Original Value	Updated Value
Base Model	exception	MobileNetV2
Learning Rate	1×10^{-4}	3×10^{-4}
Batch Size	16	24
Epochs	50	55
Optimizer	Adam	SGD
Loss Function	Categorical Cross-Entropy	Categorical Cross-Entropy
Dropout Rate	0.5	0.3
GPU Used	NVIDIA Tesla T4	NVIDIA V100
NVIDIA V100	Patience 3	Patience 6
Data Augmentation	Enabled (rotation, flip, zoom)	Enabled (brightness, shear, contrast)

Authorized licensed use limited to: ANNA UNIVERSITY. Downloaded on August 31,2026 at 05:01:57 UTC from IEEE Xplore. Restrictions apply.

TABLE I, to improve efficiency, the model applied MobileNetV2 architecture in place of exception, with a higher learning rate and batch size for speed of training. Instead of Adam, SGD was chosen that is supposed to improve generalization. The dropout probability is lowered to 0.3, and NVIDIA V100 was used. Optimizations of data augmentation efforts targeted building in robustness.

Fig. 2.the model successfully detected known and unknown threats, including phishing, malware, DDoS, and zero-day exploits. The anomaly detection recognized abnormal network traffic, user actions, and deviations within system logs indicating APT activity. Real-time alerts prioritized threats for an efficient response, which improved site security. Timely and precise predictions enabled the security team to respond to critical events 30% faster.

TABLE II. DATASET DETAILS

Dataset Name	No. of Images	Classes	Purpose
Threat Monitoring Dataset	6500	Fire, Gun, Knife, Anomalies	Security Threat Detection
Industrial Risk Dataset	1800	Fire, Smoke, Hazardous Gas	Industrial Hazard Detection
Public Safety Dataset	5300	Fire, Violence, Emergency	Emergency Classification

In TABLE II the Threat Monitoring Dataset comprises 6,500 images relating to different types of security threats, such as fire, weapons, and anomalies. The Industrial Risk Dataset includes 1,800 images for detecting fire, smoke, and dangerous gases. Public Safety consists of 5,300 images and includes the field of emergency classification.

Using transfer learning allows threat detection to be improved via pre-trained models offering quick and customized implementation. A hybrid dataset provides the means for generalization, allowing detection of known and unknown attacks. However, issues encountered comprise limited labeled data, evolution of threats, and quality assessment of the data for effective detection. Ensuring diversity in the training datasets is very useful for avoiding gaps in the identification of advanced or rare cyber threats.

Deep learning model deployment in security systems facilitates threat detection but requires high-performance computing that limits small organizations. The other challenge is real-time scaling in scenarios where heavy traffic is encountered. Optimization via edge computing or distributed processing may facilitate broader deployment.




Fig. 2. Comparison of Training Specification




Fig. 3. Dataset Details

Fig.3.by real-time threat detection, deep transfer learning increases the organizational security, therefore minimizing false positives and making better use of other resources. This automation will provide improvements to incident prioritization and speed of response. Future improvements could include continuous learning for adaptive threat management and adversarial training to reinforce defenses against AI-targeted attacks.

V. CONCLUSION

Deep Transfer Learning (DTL) is the ability to borrow what is already extracted and fine-tuned to perform faster reasoning for the detection of new or emerging threats. DTL gives an upper hand for the real-time detection of threats, with comparatively lower consumption of CPU and their energy. Knowledge transfer also heightens the accuracy and efficacy while dealing with threats and enhances the whole framework of security. The incorporation of DTL in centers would safeguard the key assets and pre-empt potential threats that emerge in a much-developing trend. The future studies may seek optimal means for the fusion of these models with a huge variety of representations that can capture multimodal information to inform the improved mitigation of information security vulnerability. DTL assures itself of the capability to the scalable and linear threat response and risk mitigation.

REFERENCES

[1] Manivannan, K., Mary, P.A., Jino, R.F., Dineshkumar, P., Harivisva, M.S. and Harikrishnan, P., "Machine Learning Driven Routing Optimization for Named Data Networking in Mobile Adhoc Network," in 2024 8th International Conference on Computational System and Information Technology for Sustainable Solutions (CSITSS) (pp. 1-6). IEEE, 2024.

[2] Mary, P.A., Maalini, D., Manivannan, K., Umamaheswari, K., Balaji, S. and Deepak, R., "A Secure Aware Routing Protocol for Efficient and Reliable FPANETS," in 2024 First International Conference on Software, Systems and Information Technology (SSITCON) (pp. 1-6). IEEE, 2024.

[3] K. Manivannan, T. Suresh, M. Parthiban, "Big Data Analytics Assisted Arithmetic Optimization with Deep Learning Model for Sentiment Classification," International Journal of Engineering Trends and Technology, vol. 71, no. 12, pp. 50-60, 2023.

[4] M. A. Hassanain, M. Al-Harogi, and A. M. Ibrahim, "Fire safety risk assessment of workplace facilities: A case study," Frontiers Built Environ., vol. 8, Mar. 2022, Art. no. 861662.

[5] V. Mavroeidis, K. Vishi, and A. Jøsang, "A framework for data-driven physical security and insider threat detection," in Proc. IEEE/ACM Int. Conf. Adv. Social Netw. Anal. Mining (ASONAM), Aug. 2018, pp. 1108–1115.

[6] J. Alves, C. Soares, J. M. Torres, P. Sobral, and R. S. Moreira, "Automaticforest fire detection based on a machine learning and

Authorized licensed use limited to: ANNA UNIVERSITY. Downloaded on August 31,2026 at 05:01:57 UTC from IEEE Xplore. Restrictions apply.

image analysis pipeline,'' in New Knowledge in Information Systems and Technologies, vol. 2. USA: Springer, 2019, pp. 240–251.

[7] M. Grega, A. Matilanski, P. Guzik, and M. Leszczuk, ''Automated detection of firearms and knives in a CCTV image,'' Sensors, vol. 16, no. 1, p. 47, Jan. 2016.

[8] R. Debnath and M. K. Bhowmik, ''A comprehensive survey on computer visionbased concepts, methodologies, analysis and applications for automatic gun/knife detection,'' J. Vis. Commun. Image Represent., vol. 78, Jul. 2021, Art. no. 103165.

[9] J. L. Salazar González, C. Zaccaro, J. A. Álvarez-García, L. M. Soria Morillo, and F. Sancho Caparrini, ''Real-time gun detection in CCTV: An open problem,'' Neural Netw., vol. 132, pp. 297–308, Dec. 2020.

[10] S. A. A. Akash, R. S. S. Moorthy, K. Esha, and N. Nathiya, ''Human violence detection using deep learning techniques,'' J. Phys., Conf., vol. 2318, no. 1, Aug. 2022, Art. no. 012003.

[11] A. S. Pundir and B. Raman, ''Dual deep learning model for imagebased smoke detection,'' Fire Technol., vol. 55, no. 6, pp. 2419–2442, Nov. 2019.

[12] T. Ruprah and H. Shrivastav, ''Crime prediction based on person-weapons relation using deep learning techniques,'' Eur. Chem. Bull., vol. 12, pp. 984–994, Jun. 2023.

[13] D. A. Noever and S. E. M. Noever, ''Knife and threat detection,'' 2020, arXiv:2004.03366.

[14] V. Kaya, S. Tuncer, and A. Baran, ''Detection and classification of different weapon types using deep learning,'' Appl. Sci., vol. 11, no. 16, p. 7535, Aug. 2021.

[15] F. Pérez-Hernández, S. Tabik, A. Lamas, R. Olmos, H. Fujita, and F. Herrera, ''Object detection binary classifiers methodology based on deep learning to identify small objects handled similarly: Application in video surveillance,'' Knowl--Based Syst., vol. 194, Apr. 2020, Art. no. 105590.

[16] N. Dwivedi, D. K. Singh, and D. S. Kushwaha, ''Employing data generation for visual weapon identification using convolutional neural networks,'' Multimedia Syst., vol. 28, no. 1, pp. 347–360, Feb. 2022.

[17] D. Berardini, L. Migliorelli, A. Galdelli, E. Frontoni, A. Mancini, and S. Moccia, ''A deep-learning framework running on edge devices for handgun and knife detection from indoor video-surveillance cameras,'' Multimedia Tools Appl., vol. 83, no. 7, pp. 19109–19127, Jul. 2023.

[18] P. V. A. B. de Venancio, A. C. Lisboa, and A. V. Barbosa, ''An automatic ˇ fire detection system based on deep convolutional neural networks for low-power, resource-constrained devices,'' Neural Comput. Appl., vol. 34, no. 18, pp. 15349–15368, Sep. 2022.

[19] S. Dogan, P. Datta Barua, H. Kutlu, M. Baygin, H. Fujita, T. Tuncer, and U. R. Acharya, ''Automated accurate fire detection system using ensemble pretrained residual network,'' Exp. Syst. Appl., vol. 203, Oct. 2022, Art. no. 117407.

[20] Mary, P.A. and Radhakrishnan, M., ''An Aggregated Trust Model To Isolate Free Riders In P2p Network'' International Journal of Applied Engineering Research, 10(1), pp.371-384, 2015.

[21] Mary, P.A. and Radhakrishnan, M., ''Efficient File Sharing Mechanism In P2P Using Energy Efficient Clustering Mechanism,'' Appl. Math, 11(6), pp.1779-1787, 2017.

Authorized licensed use limited to: ANNA UNIVERSITY. Downloaded on August 31,2026 at 05:01:57 UTC from IEEE Xplore. Restrictions apply.