PrusaSlicer Settings - Sovol SV06 Plus (300×300), 0.2mm, 1 Perimeter Shell

Printer: Sovol SV06 Plus (300×300) | **Nozzle:** 0.4mm | **Layer Height:** 0.2mm
Filament: eSun PLA+ / eSun LW-PLA | **Mode:** Single Perimeter

Note: These are PrusaSlicer slicing recommendations for this specific machine. GCODECrunch is printer-agnostic and can process any Marlin-compatible G-code regardless of build volume.

Settings

Setting	PLA+	LW-PLA
Filament > Cooling > Slow down if layer print time is below	4-5s	6-8s
Filament > Cooling > Minimum print speed	28-30 mm/s	25-28 mm/s
Filament > Cooling > Enable auto cooling	Checked	Checked
Filament > Cooling > Min fan speed	100%	30%
Filament > Cooling > Max fan speed	100%	50%
Filament > Cooling > Disable fan for the first	1 layer	1 layer
Filament > Cooling > Full fan speed at layer	2-3	3-4
Filament > Cooling > Bridge fan speed	100%	50%
Print Settings > Speed > First layer speed	20 mm/s	20 mm/s
Print Settings > Speed > External perimeters	30-35 mm/s	25-30 mm/s
Print Settings > Speed > Perimeters	35-40 mm/s	30-35 mm/s
Print Settings > Speed > Small perimeters	30 mm/s	25-30 mm/s
Print Settings > Speed > Travel	150-180 mm/s	140-150 mm/s
Print Settings > Layers and perimeters > Perimeters	1	1
Print Settings > Layers and perimeters > Seam	Aligned/Rear	Aligned/Rear

position		
Printer Settings > **Extruder 1** > **Retraction** > **Lift Z (Z-hop)**	0 - 0.2mm	0.2 - 0.3mm
Printer Settings > **Extruder 1** > **Retraction** > **Length**	0.4-0.6mm	0.6-0.8mm
Printer Settings > **Extruder 1** > **Retraction** > **Speed**	30-40 mm/s	25-30 mm/s
Printer Settings > **General** > **Firmware** > **G-code flavor**	Marlin 2	Marlin 2
Printer Settings > **General** > **Firmware** > **Use relative E distances**	Checked (M83)	Checked (M83)
Print Settings > **Output options** > **Arc fitting**	Disabled	Disabled
Filament > **Advanced** > **Extrusion multiplier**	1.0	1.0