PrusaSlicer Settings - Sovol SV06 Plus (300×300), 0.2 mm, 1 Perimeter Shell

Printer: Sovol SV06 Plus (300×300) | **Nozzle:** 0.4mm | **Layer Height:** 0.2mm
Mode: Single Perimeter

GCODECrunch is printer-agnostic and processes any Marlin-compatible G-code, regardless of filament type. The travel optimiser itself works with all filament types. The table below gives the slicer settings for a regular filament (PLA/PLA+ and similar) alongside the adjustments needed for foaming LW filament.

Settings

Setting	Regular filament	LW-PLA
Filament > Cooling > Slow down if layer print time is below	4-5s	6-8s
Filament > Cooling > Minimum print speed	28-30 mm/s	25-28 mm/s
Filament > Cooling > Enable auto cooling	Checked	Checked
Filament > Cooling > Min fan speed	100%	30%
Filament > Cooling > Max fan speed	100%	50%
Filament > Cooling > Disable fan for the first	1 layer	1 layer
Filament > Cooling > Full fan speed at layer	2-3	3-4
Filament > Cooling > Bridge fan speed	100%	50%
Print Settings > Speed > First layer speed	20 mm/s	20 mm/s
Print Settings > Speed > External perimeters	30-35 mm/s	25-30 mm/s
Print Settings > Speed > Perimeters	35-40 mm/s	30-35 mm/s
Print Settings > Speed > Small perimeters	30 mm/s	25-30 mm/s
Print Settings > Speed > Travel	150-180 mm/s	140-150 mm/s
Print Settings > Layers and perimeters > Perimeters	1	1
Print Settings >		

Layers and perimeters > Seam position	Aligned/Rear	Aligned/Rear
Printer Settings > Extruder 1 > Retraction > Lift Z (Z-hop)	0 - 0.2 mm	0.2 - 0.3 mm
Printer Settings > Extruder 1 > Retraction > Length	0.4-0.6 mm	0.6-0.8 mm
Printer Settings > Extruder 1 > Retraction > Speed	30-40 mm/s	25-30 mm/s
Printer Settings > General > Firmware > G-code flavor	Marlin 2	Marlin 2
Printer Settings > General > Firmware > Use relative E distances	Checked (M83)	Checked (M83)
Print Settings > Output options > Arc fitting	Disabled	Disabled
Filament > Advanced > Extrusion multiplier	1.0	1.0