NIMBUS-9¾ BROOM

Manned eVTOL — 1 rider, 8 ducted fans, fly-by-intent

Project NIMBUS-9¾ · Real Quidditch · hardware full-stack

ISOMETRIC

SIDE

TOP

CUTAWAY — internal drive revealed

KEY DIMENSIONS & SPEC

(every number ties back to the flight software)

Overall length `core/params.py LEN = 2.4 m`	**2400 mm**
Lift fans `_default_fan_layout (exact x/y)`	**8 × EDF (internal)**
Thrust-to-weight `analysis/flight_thermal.py`	**2.45 (hover @ 41%)**
All-up mass `rider ~80 + airframe ~40`	**120 kg**
Hover endurance `2600 Wh — a sprinter, pit doctrine`	**~89 s / charge**
Cooling margin `lift air = coolant + heat pipes`	**17× waste heat**
Soft fence `fence_ceiling / fence_floor`	**ceiling 18 m / floor 3 m**
Control core `rust/nimbus_core + firmware/hal.py`	**Cortex-M4F @ 400 Hz**

NOTE
A bare stick has no disc area, so it's a ~90 s sprinter (hence the F1-style hot-swap pits the software already enforces). Fans are fully internal — prop exposure 0; the lift air doubles as motor coolant, with heat pipes spreading the rest over the 2.4 m shaft. Budget closes: FLIGHT + THERMAL both PASS.

BILL OF MATERIALS — BRM (31 line items, prototype qty 1)

REF	PART	SPEC	QTY	$ EA	$ EXT
BRM-01	Carbon-fibre monocoque body p...	2.4 m, hides the fan bay; SI->mm x1000 in cad/broom.scad	1	2,200	2,200
BRM-02	Handle shaft + brass pommel	tapered Ø34->Ø22 mm, leather-wrapped grip	1	180	180
BRM-03	Bristle fairing leaf	~780 carbon-straw strands, aerodynamic shroud	1	640	640
BRM-04	Electric ducted fan (EDF) unit	360 N max each; main-lift in bristle shroud + in-shaft trim fans	8	520	4,160
BRM-05	Brushless motor for EDF	~12 kW peak, 6S-14S, duct-matched	8	340	2,720
BRM-06	ESC (electronic speed control...	200 A, telemetry, 1st-order ~40 ms response	8	150	1,200
BRM-07	Li-ion battery pack	2600 Wh usable, hot-swappable cartridge	1	3,100	3,100
BRM-08	Battery management system (BM...	14S smart BMS, cell balancing + SoC telemetry	1	260	260
BRM-09	Power distribution board	800 A bus, redundant rails	1	180	180
BRM-10	Flight controller MCU	Cortex-M4F (thumbv7em-none-eabihf), 400 Hz loop	1	95	95
BRM-11	IMU (redundant)	triple-redundant 6-DOF, 1 kHz	3	55	165
BRM-12	Magnetometer	3-axis, maneuver-compensated	2	18	36
BRM-13	Barometer	high-res, for altitude hold	2	12	24
BRM-14	RTK-GPS receiver + antenna	cm-grade, dual-band	1	420	420
BRM-15	UWB ranging tag	indoor cm positioning to pitch anchors	2	40	80
BRM-16	Solid-state LiDAR	360deg, edge collision avoidance	2	600	1,200
BRM-17	Low-latency datalink radio	redundant 5G + dedicated mesh	2	140	280
BRM-18	Ballistic recovery parachute ...	low-altitude rated, pyro deploy	1	1,500	1,500
BRM-19	Airbag skirt	underbody impact airbag, impact-triggered	1	450	450
BRM-20	Master kill-switch receiver	referee e-stop -> gentle descent	1	60	60
BRM-21	5-point harness + saddle	straddle seat, energy-absorbing	1	320	320
BRM-22	Rider intent controls	handlebar grips, throttle, lean sensors	1	210	210
BRM-23	Brass compass/attitude gauge	cosmetic + real attitude readout	1	90	90
BRM-24	LED trajectory strip	addressable, night-match light show	1	70	70
BRM-25	Heat pipe (sintered copper)	Ø6 mm, full-shaft length, motor->shaft spreader	4	22	88
BRM-26	Air-over-motor duct shroud	routes lift airflow across windings (air = coolant)	8	16	128
BRM-27	In-duct winding temp sensor	NTC, one per fan, feeds the governor	8	3	24
BRM-28	Thermal interface material	phase-change pad, motor + ESC to spreader	1	18	18
BRM-29	DShot ESC wiring harness	bidirectional DShot600, 8 channels + telem	1	45	45
BRM-30	CAN-FD vehicle bus	5 Mbit, BMS + ESC telem + pose to Dementor	1	30	30
BRM-31	Hardware abstraction layer	firmware skin around the Rust core	1	0	0

UNIT TOTAL (prototype): $19,973

DRAWN	DATE	UNITS	SCALE	PART	REV	CAD
NIMBUS HW	**2026-06-26**	**mm / SI**	**NTS**	**BRM**	**v0.1**	**cad/broom.scad**