

ASTER HOME SYSTEMS

Aster M55 Television

Operating Guide

Model	M55
Product code	AST-M55-2024
Edition	Edition 2.0 - October 2024

Installation, reception, connected-device and service information for the Aster M55.

Read the safety information before installing or operating the product.

Guide map

Use the page references below to find installation, controls and service information.

Topic	Page	Topic	Page
Important precautions	3	Home network	9
Unpacking and identification	4	Troubleshooting	10
Stand and wall installation	5	Temperature management / E06	11
Handset and initial tuning	6	Care and storage	12
Picture and sound	7	Technical data	13
Inputs and connected equipment	8	Service information	14

This guide applies only to Aster M55, product code AST-M55-2024.

Important precautions

Install and operate the unit only under the conditions described in this guide.

Mains isolation

The mains plug is the disconnect device and must remain accessible. Unplug the unit before cleaning, moving or fitting a wall bracket.

Air circulation

Keep the upper exhaust openings clear and allow 12 cm above the cabinet. Enclosed shelving requires an open rear or active ventilation.

Moisture and objects

Do not expose the product to dripping water, steam or rain. Never place containers of liquid on the cabinet or insert objects through the ventilation slots.

- Use two people to lift the unit and do not press on the display surface.
- Secure furniture and the television against tipping.
- Stop use immediately if the enclosure becomes unusually hot or produces an odour.

Unpacking and identification

Open the top of the carton and remove accessories before lifting the display.

Identification label

The rear label lists Model M55 and Product code AST-M55-2024. The serial number is unique to the unit.

Packing material

Retain the moulded corner protectors if the product may be transported. Do not place adhesive labels on the panel.

Supplied item	Quantity
Aster M55 television	1
Centre pedestal and neck	1 set
Mounting screws	6
Aster handset	1
AAA cells	2
Mains cable	1
Setup leaflet	1

Stand and wall installation

Place the panel face down on its protective sleeve over a flat table before attaching the pedestal.

Pedestal

Fit the neck to the base, then attach the assembly to the rear mounting points using the marked screws. Tighten evenly without power tools.

Wall bracket

The mounting pattern is 200 × 200 mm. Select a bracket rated for at least 22 kg and have the wall fixings assessed by a qualified installer.

Ventilation clearance

Allow 12 cm above, 8 cm at both sides and 5 cm behind the set. Do not cover the temperature sensor opening near the upper rear vent.

Restricted airflow can cause automatic brightness reduction, shutdown or a temperature-related error.

Handset and initial tuning

Install the batteries, connect the antenna or cable feed, and press Power.

Initial choices

Select the menu language, broadcast region and home-use mode. Store-display mode is not recommended in a residence.

Automatic tuning

Choose terrestrial or cable reception and allow the scan to finish. Signal conditions determine which channels are stored.

Handset pairing

Infrared functions operate immediately. For voice control, hold Menu and OK for four seconds while facing the set.

Source selection

Press Input to choose broadcast TV, HDMI, component adapter or USB media.

- Do not remove power during channel storage.
- Network setup can be completed later from the Connections menu.

Picture and sound controls

Aster modes store separate values for television, HDMI and application playback.

Panel protection

Static-image detection can lower brightness after extended inactivity. This function is not a substitute for varied content.

Audio output

Select TV Speakers, Optical or HDMI Audio System. If an external receiver is used, avoid enabling delay on both devices.

Setting	Use
Natural	Balanced viewing in a moderately lit room
Film	Warm colour and reduced edge enhancement
Sports	Higher motion processing and brighter image
Low latency	Reduced processing for interactive sources
Speech focus	Raises dialogue frequencies
Late night	Reduces abrupt loudness changes

Inputs and connected equipment

Power down devices before changing cables. The Aster M55 provides three HDMI inputs, one USB-A port, Ethernet, optical audio and an antenna input.

Cable routing

Keep signal cables away from the mains lead and do not force plugs at an angle.

Computer use

Select a supported 16:9 resolution and use Low latency mode if pointer response is important.

Port	Location	Notes
HDMI 1	Rear	General audiovisual source
HDMI 2	Rear	ARC audio return
HDMI 3	Side	Convenient temporary connection
USB-A	Side	Media storage, 5 V current limit
Ethernet	Rear	Wired network
Optical	Rear	Digital audio output
Antenna	Rear	Broadcast RF input

Home network and applications

The network menu supports dual-band Wi-Fi or wired Ethernet.

Wireless setup

Choose the network name and enter its security key. If the connection is weak, test the television closer to the access point or use Ethernet.

Software services

Applications and programme catalogues are provided by independent operators and can change without a television software fault.

Updates

Automatic updates are downloaded in standby when network standby is enabled. A manual check is available under Support > System Update.

Account removal

Use Reset Applications to remove local sessions without deleting tuned broadcast channels.

Aster account services and Velora account services are separate and are not interchangeable.

Troubleshooting

Check external equipment and the installation before arranging service.

Restart

Disconnect mains power for 30 seconds, reconnect and wait for the home screen.

Information to record

Note Model M55, product code AST-M55-2024, software version and any displayed code.

Symptom	Action
No power	Check outlet, cable and local standby key
No broadcast picture	Inspect antenna path and repeat signal test
No HDMI picture	Select the correct input and test another cable
No external audio	Check output setting and receiver input
Network unavailable	Restart router and renew the connection
Unit switches off	Check sleep timer and ventilation clearances
Remote intermittent	Replace batteries and clear the receiver window

Temperature management and code E06

The Aster M55 monitors internal airflow and temperature near the upper rear ventilation path.

E06 meaning

On the Aster M55, error E06 indicates a temperature-sensor fault or an implausible reading from the internal thermal monitoring circuit.

Immediate action

Switch the television off, unplug it and allow it to cool for at least 20 minutes. Confirm that the upper and rear ventilation openings are clear and that the specified clearances are available.

When service is required

If E06 returns soon after a cool start in an adequately ventilated position, disconnect the product and contact Aster service. Do not remove the rear cover or attempt to replace the sensor.

Related shutdown

A protection shutdown without E06 can also occur when room temperature is excessive or vents are obstructed; correct the installation before restarting.

Error meanings are product-specific. This E06 definition applies to Aster M55, product code AST-M55-2024.

Care and storage

Disconnect power before cleaning and allow the cabinet to cool.

Display cleaning

Use a dry optical-grade microfibre cloth. For persistent marks, dampen the cloth slightly with distilled water. Never apply liquid to the screen.

Cabinet and vents

Wipe the cabinet with a soft cloth and use a soft brush on external vent grilles. Do not use compressed air through the openings.

Storage

Store upright in a dry location between -10 and 45 °C. Protect the panel from pressure and keep the pedestal hardware with the product.

Battery handling

Remove depleted handset batteries promptly and take them to an appropriate collection point.

- Avoid solvents, alcohol and abrasive material.
- Do not wrap the unit while it is warm.
- Inspect cables for damage before reuse after storage.

Technical data

Values below describe the Aster M55 configuration.

Item	Value
Model / product code	M55 / AST-M55-2024
Display	55-inch 3840 × 2160 LCD
HDMI inputs	3; HDMI 2 with ARC
Other connections	1 × USB-A, Ethernet, optical audio, antenna
Wireless	2.4/5 GHz Wi-Fi, Bluetooth handset
Speakers	2 × 10 W
Dimensions with stand	1235 × 785 × 278 mm
Net mass	17.6 kg
Wall mount	200 × 200 mm
Rated supply	220-240 V AC, 50/60 Hz
Operating temperature	5-32 °C

Specifications are subject to production tolerances and regional tuner configuration.

Service and regulatory information

Service for the Aster M55 is handled through Aster-authorized support channels.

Before contact

Record the serial number, observed code, operating conditions and results of the guide's checks. Keep any separate purchase evidence available if warranty service is requested.

Safety service

Disconnect the television after liquid exposure, physical damage, repeated overheating or a persistent E06 temperature-sensor fault.

Disposal

Use an approved electronic-equipment collection scheme. Remote-control batteries must be removed and handled separately where required.

Documentation

This operating guide is reference OG-M55-EN-2.0 and applies only to Model M55, Product code AST-M55-2024.

Support route	Details
Web	service.aster.example/m55
Telephone	+36 1 555 0191
Hours	Weekdays 08:30-16:30 CET