

ORION MOBILITY

Orion E4

Owner's guide and technical specification

Model	E4 Long Range
Vehicle code	ORI-E4-77
Model year	2026
Edition	Revision 1.0 - January 2026

Instructions and technical data for identification, safe use, AC/DC charging, scheduling and routine care.

Read the identification, safety and applicability information before relying on this document.

Contents

This guide is organised around vehicle identification, high-voltage safety and charging.

Section	Page	Section	Page
Vehicle identification	3	Charge-time estimation	8
High-voltage safety	4	Scheduled charging	9
Battery specification	5	Temperature conditions	10
AC charging	6	Cables and connectors	11
DC rapid charging	7	Fault messages	12
Routine care	13	Technical summary	14

3. Vehicle identification

Model identity

The owned vehicle described by this guide is the Orion E4 Long Range, vehicle code ORI-E4-77. Specifications for another Orion or another manufacturer model must not be applied to this vehicle.

Identification plate

The vehicle identification plate is located on the left door aperture. Charging information in this edition applies to model year 2026 vehicles with the 64 kWh usable battery.

Software and options

Display wording may change after an update, but the electrical ratings in the technical summary remain controlling unless Orion issues a replacement specification.

Product	Orion E4 Long Range
Vehicle code	ORI-E4-77
AC inlet	Type 2
DC inlet	CCS2

4. High-voltage safety

Qualified work only

The traction battery, orange high-voltage cables and charging electronics contain dangerous voltage. Do not open, modify or bypass them.

Damaged equipment

Stop charging if the inlet, cable or wallbox is damaged, wet internally or unusually hot. Isolate the supply and obtain qualified inspection.

Earthing and protection

AC charging must use a correctly earthed installation with the protective devices required by the wallbox and local electrical rules.

Solar installations

Photovoltaic panels are not a vehicle charger. The vehicle must receive controlled AC through compliant conversion, protection and charging equipment.

5. Traction battery specification

Usable energy

The Orion E4 Long Range has 64 kWh usable battery energy. Gross physical capacity is 68 kWh; charge-time calculations in this guide use the usable value.

State of charge

The displayed state of charge (SoC) is an estimate of usable energy remaining. A charge-time estimate requires at least the current SoC, target SoC and available charging power.

Recommended daily range

For routine use, Orion recommends a target between 70% and 80% unless additional range is needed. A 100% target is appropriate before a longer journey when charging completes close to departure.

Usable capacity	64 kWh
Gross capacity	68 kWh
Nominal system voltage	400 V class
Recommended daily target	70-80%

6. AC charging

Maximum AC input

The vehicle supports up to 11 kW AC using three-phase 400 V, 16 A per phase through a Type 2 connection.

Lower-power equipment

The E4 can charge from a correctly installed lower-rated wallbox, but charging power and speed are limited by the lowest active limit: vehicle, wallbox, cable, site circuit or load-management setting.

Higher-rated equipment

A wallbox advertised at 22 kW does not raise the E4 above 11 kW. The onboard charger accepts no more than the vehicle rating.

Single-phase supply

On a single-phase installation the available power may be materially lower. Confirm the wallbox and site ratings before estimating time.

Connector	Type 2
Maximum AC power	11 kW
Supply at maximum	3-phase 400 V, 16 A/phase
Onboard charger	11 kW three-phase

7. DC rapid charging

CCS2 input

The E4 supports CCS2 direct-current rapid charging at compatible public chargers.

Peak power

Peak DC input is 125 kW under favourable battery temperature and state-of-charge conditions. It is not an AC rating and must not be used to size a home wallbox.

Charge curve

Power reduces as the battery approaches a high state of charge. Displayed completion estimates adapt to battery temperature and station capability.

DC connector	CCS2
Peak DC input	125 kW
Typical 10-80% claim	About 31 minutes under reference conditions

8. Charge-time estimation

Required inputs

A meaningful estimate requires current SoC, target SoC and the sustained charging power. If current SoC is missing, ask for it rather than presenting a precise full-charge time.

Energy calculation

Required battery energy equals usable capacity multiplied by the change in SoC. From 20% to 80%, the change is 60%, so the battery receives $64 \text{ kWh} \times 0.60 = 38.4 \text{ kWh}$.

Efficiency assumption

For a planning estimate on AC, use 90% wall-to-battery efficiency unless measured data is available. Grid energy for the 20%-to-80% example is $38.4 / 0.90 = 42.67 \text{ kWh}$.

Time calculation

At a sustained 11 kW, $42.67 / 11 = 3.88$ hours, approximately 3 hours 53 minutes. Temperature, balancing and load management can extend actual time.

Do not state a full-charge time when the current state of charge or sustained available power is unknown.

9. Scheduled and managed charging

Departure schedule

Set a target and departure time in the vehicle or compatible wallbox. Avoid conflicting schedules in both systems.

Dynamic current

The E4 accepts a wallbox control signal that varies current within the permitted range. Temporary reduction from solar-surplus or household load management is normal.

Grid import

Whether grid energy may supplement solar generation is controlled by the site energy-management configuration, not by the vehicle specification.

Interrupted sessions

If charging pauses, confirm the wallbox status and site power before resetting the vehicle.

10. Temperature and charging conditions

Cold battery

Low battery temperature can reduce both AC acceptance and DC rapid-charging power. The vehicle may use energy to condition the battery.

Hot conditions

Charging power can reduce to protect the battery and connector. Provide ventilation around charging equipment.

Estimate tolerance

Planning estimates exclude conditioning, cell balancing and household load-management interruptions unless stated.

Reference temperature	20 C
Planning tolerance	+/- 15% under normal AC conditions
Outdoor charging	Use equipment rated for the environment

11. Cables and connectors

Type 2 cable

Use a cable rated for at least the configured phase current. Inspect pins, seals and strain relief before use.

Portable equipment

A portable charging lead must be used only on a circuit assessed for continuous load. It is not a substitute for a correctly installed wallbox where one is required.

Adapters

Do not use unapproved adapters or connect photovoltaic DC conductors to the vehicle inlet.

Release

Stop the session before disconnecting. If the connector remains locked, use the vehicle menu and follow the emergency release instructions.

12. Charging messages

AC power unavailable

The vehicle has not detected a valid control signal or supply. Check wallbox status and cable seating.

Charging power limited

The site, wallbox or vehicle has set a lower current. This can be normal during dynamic load management.

Isolation fault

Stop charging and obtain qualified inspection. Do not repeatedly reset an isolation warning.

External equipment fault

Consult the wallbox or inverter document for equipment-specific codes. An unrelated model's message table must not be applied.

Message	First response
AC supply unavailable	Check wallbox power and connector
Charge current limited	Review load-management status
Isolation fault	Stop and obtain qualified inspection

13. Routine care and storage

Inlet care

Keep the inlet clean and dry. Do not apply lubricant or cleaning fluid to contacts.

Extended storage

For storage longer than four weeks, leave the battery near 50% and check it periodically.

Service

High-voltage service must be carried out by trained personnel. Record any charging-system repair with the vehicle identity.

Document retention

Keep purchase, charging-equipment and installation records together so the installed configuration can be verified.

14. Technical summary

Applicability

These values apply only to the Orion E4 Long Range identified by vehicle code ORI-E4-77.

Document control

Source ID s6-ev-specification; revision 1.0, January 2026.

Item	Specification
Vehicle	Orion E4 Long Range
Vehicle code	ORI-E4-77
Usable battery	64 kWh
Maximum AC input	11 kW, 3-phase 400 V, 16 A/phase
AC connector	Type 2
Peak DC input	125 kW CCS2
Planning efficiency	90% wall-to-battery for stated examples
Direct PV-panel connection	Not permitted