

VOLTARC CHARGING

# VoltArc Pro 22

Commercial wallbox technical data

|              |               |
|--------------|---------------|
| Model        | Pro 22        |
| Product code | VA-P22-32     |
| Rated output | 22 kW         |
| Edition      | Datasheet 4.2 |

Technical data for a non-installed 22 kW commercial wallbox. It is included as a wrong-product comparison source.

Read the identification, safety and applicability information before relying on this document.

# Contents

| Section            | Page |
|--------------------|------|
| Product overview   | 2    |
| Electrical ratings | 3    |
| Protection         | 4    |
| Installation       | 5    |
| Communications     | 6    |
| Technical summary  | 7    |

### 3. Electrical ratings

#### Rated output

The VoltArc Pro 22 supplies up to 22 kW at 32 A per phase on a three-phase 400 V circuit.

#### Application

The product is intended for commercial parking installations with a suitably rated feeder and load-management system.

#### Vehicle limit

Actual charging remains limited by the connected vehicle.

|                 |                |
|-----------------|----------------|
| Supply          | 3-phase 400 V  |
| Maximum current | 32 A per phase |
| Maximum output  | 22 kW          |
| Connector       | Type 2 socket  |
| Product code    | VA-P22-32      |

## 4. Protective functions

### DC detection

Integrated 6 mA DC residual-current monitoring is provided.

### Upstream protection

Circuit protection and RCD selection must follow the installation design.

### Thermal control

Output reduces at high internal temperature.

## 5. Installation

### Feeder

Design the feeder for continuous 32 A per phase operation and local diversity rules.

### Commissioning

Record model, serial, circuit and maximum current.

### Not installed at HOME-001

The HOME-001 as-built schedule identifies a GridNest W11, not this VoltArc product.

## 6. Communications

### Ethernet

Ethernet supports management-system connection.

### OCPP

OCPP 1.6J is available for commercial charge-point management.

### No HS-EV-2 profile

This document does not claim HelioSync HS-EV-2 compatibility.

# 7. Technical summary

## Dataset role

This full datasheet is a hard-negative source. Its 22 kW rating must not replace the rating of the installed GridNest W11.

| Model                 | VoltArc Pro 22                   |
|-----------------------|----------------------------------|
| Product code          | VA-P22-32                        |
| Rated output          | 22 kW                            |
| Rated current         | 32 A per phase                   |
| Installed at HOME-001 | No                               |
| Source ID             | s6-alternative-wallbox-datasheet |