

iEP SkySAFE 2.0

Aviation Safety Assessment Report

Application Reference: APP-001

Application reference	APP-001
IFC filename	ZHA-B-BWK-C-HR-R18.ifc
Report generated	2026-05-19 07:59 UTC
Pipeline version	0.1.0

STAGE 1 -- IFC INGESTION & VALIDATION

PASS

- PASSFile located on SFTP landing directory
- PASSIFC schema validated: IFC4 / IFC+SG v1.0
- PASSFilename: ZHA-B-BWK-C-HR-R18.ifc

STAGE 2 -- EXTERIOR SHELL EXTRACTION

PASS

Status	OK
Exterior elements extracted	3,174
Mesh vertices	280,406
Mesh triangles	540,984

STAGE 3 -- HEIGHT ANALYSIS

COMPLETE

Site elevation (IfcSite.RefElevation)	0.0 m (local datum)
Lowest point -- ground slab soffit	-5.0 m
Highest point -- roof apex (local)	214.975 m
Building height	219.975 m
Peak height above mean sea level (AMSL)	214.975 m AMSL -- used for all aviation assessments

STAGE 4 -- GROSS FLOOR AREA (GFA)

Proposed GFA71,005.7 m²

STAGE 4b -- FACADE MATERIAL SURVEY

Unique material types identified: 9

Material	Elements
NLRS_f2_beton prefab	2078
NLRS_f2_beton ihwg	570
NLRS_a_isolatie	104
NLRS_h2_staal	61
Default	44

ISR_Algemeen	35
ISR_Staal_S355	5
NLRS_n7_isolatie EPS	4
NLRS_f2_beton ihwg (ongewapend)	1

STAGE 5 -- COMPOSITE HEIGHT TEMPLATE (CHT) INTERSECTION

**PENETRATION
DETECTED**

Max permitted height (CHT) 88.85 m AMSL

Building peak height 101.55 m AMSL

Penetration depth **12.7 m**

Penetrated zones:

Zone	Permitted (m AMSL)	Building (m AMSL)	Excess (m)
CHT Zone A -- Primary Obstacle Limitation	88.85	101.55	12.7

Action required: CHT penetration triggers mandatory ADP officer review. CAAS must assess whether a height reduction, LOC conditions, or a formal aeronautical study is required before a Letter of Consent can be issued.

STAGE 6 -- OLS (OBSTACLE LIMITATION SURFACES) INTERSECTION

1 surface(s) penetrated

Penetrated surfaces:

Surface	Runway	OLS Height (m AMSL)	Building (m AMSL)	Depth (m)
Transitional Surface	RWY 02L/20R	94.13	101.55	7.42

Surfaces clear:

PASS Approach Surface

PASS Take-off Climb Surface

PASS Inner Horizontal Surface

PASS Conical Surface

PASS Outer Horizontal Surface

Note: OLS penetration must be declared in the LOC application and assessed by CAAS aerodromes engineers.

STAGE 7 -- ILS TECHNICAL TEMPLATE IMPACT

1 template(s) breached

Breached templates:

Template	System	Runway	Ceiling (m AMSL)	Building (m AMSL)	Excess (m)
ILS-WSSS-02L-L OC	Localiser (LOC)	RWY 02L	85.0	101.55	16.55

Templates clear:

PASS ILS-WSSS-02L-GP

PASS ILS-WSSS-20R-LOC

PASS ILS-WSSS-20R-GP

Action required: ILS template breach requires an RF propagation study by the CAAS ILS team before the LOC application can progress.

ASSESSMENT SUMMARY		
Check	Result	Detail
IFC Ingestion & Validation	PASS	ZHA-B-BWK-C-HR-R18.ifc
Exterior Shell Extraction	PASS	3,174 elements, 540,984 triangles
Height Analysis	COMPLETE	219.975 m building height, 214.975 m AMSL peak
Gross Floor Area	PENDING	71,005.7 m²
Composite Height Template (CHT)	FAIL	Penetration: 12.7 m
OLS Intersection	FAIL	1 surface(s) penetrated
ILS Technical Template	FAIL	1 template(s) breached