

Site Features, Roles, Flows, and Certificate Architecture Guide

US-English documentation for the current WebAppExperimental266 site structure, page-to-asset relationships, role activation paths, certificate workflows, YubiKey login handling, and automated test behavior.

Site Features, Roles, Flows, and Certificate Architecture Guide (en-US)

This guide documents the current structure of the site, the roles that are actually wired into the repository, the pages and assets those roles activate, the most common request flows, the certificate-authority processes behind privileged access, and how the automated tests interact with the application.

Current-scope note: The repository currently implements **public**, **authenticated user**, **site admin (admin certificate)**, and **YubiKey MFA policy** flows. A dedicated **group admin** role is **not implemented in the current checkout**, and the `/Experimental/*` YubiKey policy hook exists even though no Razor Pages currently live under that folder.


Feature summary

- Public visitors can browse public card dumps, open ArcGIS maps, switch language, and download public files.
- Authenticated users can sign in through an OIDC provider and manage their own records.
- Site admins must pass the normal login flow **and** present a mapped admin client certificate to access the admin-records surface.
- YubiKey MFA is modeled as a second factor for `/Experimental/*`: a signed-in user must also present a trusted YubiKey PIV certificate and pass OCSP validation.
- The app can integrate with Azure Key Vault, Cosmos DB, Blob Storage, AWS services, and GCP services through feature flags.
- Tests are run with `dotnet test`; they are not executed during plain compilation.

Role inventory

Role	Implemented now	Gate	Main active pages	Main assets/services activated
Public visitor	Yes	None	Home, Privacy, About, public downloads	ArcGIS public URL, CRUD read for public rows, static assets
Authenticated user	Yes	OIDC login (Azure AD, AWS Cognito, or GCP Identity)	My Records, Upload, owner Details/Edit/Delete	Auth cookie, CRUD owner queries, inline filters, user ArcGIS URL
Site admin	Yes	OIDC login + AdminCertificate policy	Admin Records CRUD	Client certificate, audit logging, full CRUD, admin ArcGIS URL
YubiKey MFA user	Policy only	OIDC login + YubiKeyMfa policy	/Experimental/* if pages are added	YubiKey PIV certificate, OCSP, optional attestation checks
Group admin	No	Not implemented	None	None

Diagram 1 — whole-site structure



The site surface is centered on three implemented controller areas:

- `HomeController` for public content and role-based map selection.
- `RecordsController` for owner-scoped CRUD actions after sign-in.
- `AdminRecordsController` for admin-scoped CRUD actions after both primary login and certificate validation.


The repo also wires a YubiKey policy to `/Experimental/*`, but there are no Razor Pages under `Pages/Experimental` in this checkout.

Page and route inventory

Route or surface	Access	Core code path	What it does
<code>/</code>	Public	<code>HomeController.Index</code>	Lists public records and chooses a public/user/admin ArcGIS map URL
<code>/Privacy</code> , <code>/Home/Privacy</code>	Public	<code>HomeController.Privacy</code>	Static privacy page
<code>/AboutUs</code> , <code>/Home/AboutUs</code>	Public	<code>HomeController.AboutUs</code>	Static about page
<code>POST /Home/SetLanguage</code>	Public	<code>HomeController.SetLanguage</code>	Persists culture choice in a cookie
<code>/Records</code>	Authenticated user	<code>RecordsController.Index</code>	Lists the current user's records
<code>/upload</code>	Authenticated user	<code>RecordsController.Create</code>	Uploads a JSON card dump and metadata
<code>/Records/Details/{id}</code>	Owner/public read rules	<code>RecordsController.Details</code>	Shows one record
<code>/Records/Edit/{id}</code>	Owner only	<code>RecordsController.Edit</code>	Updates title/description
<code>/Records/Delete/{id}</code>	Owner only	<code>RecordsController.Delete</code>	Removes a record
<code>/Records/Download/{id}</code>	Public or authorized	<code>RecordsController.Download</code>	Downloads file content

Route or surface	Access	Core code path	What it does
/AdminRecords/*	Site admin	AdminRecordsController.*	Full-record CRUD and admin search/filter
/Account/SignIn , /Account/SignOut	Public/authenticated	Microsoft Identity UI	Starts or ends the primary login session
/Experimental/*	YubiKey MFA policy	Razor Pages convention	Reserved for second-factor protected pages

Diagram 2 — which pages interact with which assets




Key page-to-asset relationships:

Page	Asset or external dependency	Purpose
Home	ArcGIS iframe URL	Chooses public, user, or admin map based on auth and admin-certificate result
Home	CRUD store	Reads up to 50 public records
Records pages	CRUD store	Reads or writes owner-scoped records
Records/Admin views	Inline JavaScript + static assets	Client-side table filtering and layout

Page	Asset or external dependency	Purpose
Admin Records	Client certificate + audit service	Unlocks admin surface and records access attempts
Sign-in UI	OIDC provider	Establishes the primary identity
/Experimental/*	YubiKey certificate + OCSP responder	Enforces a second factor when the folder is used
Every HTTPS request	Azure Key Vault server certificate (optional feature)	Supplies the TLS server identity to Kestrel

Diagram 3 — common event flows




The most common user journeys are:

1. **Browse public content** → open the home page → see public records and the public ArcGIS map.
2. **Sign in and upload** → complete OIDC login → open My Records → upload a JSON file → write metadata and file bytes to the CRUD store.

3. **Enter the admin surface** → sign in → request `/AdminRecords` → pass `AdminCertificateRequirementHandler` → unlock full CRUD.
4. **Enter a YubiKey-protected route** → sign in → request `/Experimental/*` → pass YubiKey issuer, thumbprint, optional attestation, and OCSP checks.


Diagram 4 — role activation state model



This role model reflects what the current code actually activates:

- **Anonymous** users only get public content.
- **Authenticated** users unlock owner-scoped CRUD pages.
- **Site admins** are a stricter state on top of authenticated users and require a mapped certificate.
- **YubiKey MFA users** are another stricter state on top of authenticated users and are intended for `/Experimental/*`.
- **Group admin** is a requested documentation concept, but there is no route, policy, or handler for it in the repository.


Diagram 5 — what programs and functions activate during key interactions



The main request paths activate these application components:

Interaction	Main controller/function path	Supporting services/functions
Open home page	HomeController.Index	LoggingHelper.TrackFunctionCall , CrudDbContext.CrudRecords , IAuthorizationService.AuthorizeAsync , ArcGisSettings
Upload record	RecordsController.Create	UploadPolicy , UserIdentityHelper , CrudDbContext.SaveChangesAsync
Browse own records	RecordsController.Index	UserIdentityHelper.GetStableUserId , CrudDbContext
Open admin pages	AdminCertificateRequirementHandler then AdminRecordsController.*	AdminCertificateAuditService , CrudDbContext
Open YubiKey-protected route	YubiKeyRequirementHandler	OcsPValidationService , YubiKeySettings , TLS client certificate chain
Client-side filtering	Views/Records/Index.cshtml and Views/AdminRecords/Index.cshtml inline scripts	Bootstrap, jQuery, nonce-bearing script tags when CSP is enabled

Diagram 6 — certificate authority and YubiKey workflow



The certificate architecture splits into two major trust paths:

Server certificate path

- The site can pull its **server TLS certificate** from **Azure Key Vault** at startup.
- Kestrel installs that server certificate for HTTPS.
- Every browser session depends on this server-side TLS identity.


Privileged client-certificate path

- **Site admins** present a client certificate that must come from an allowed issuer and map to the signed-in admin's configured thumbprint.
- **YubiKey MFA users** present a client certificate backed by a private key generated on YubiKey PIV hardware.
- The **OpenBSD admin CA** can sign YubiKey CSRs and operate the **OCSP responder** used during YubiKey validation.
- Revocation is especially important for the YubiKey flow because the app checks OCSP status during protected requests.

Role-specific certificate expectations

Role	Client certificate required	Validation path
Public	No	Server TLS only
Authenticated user	No	OIDC login only
Site admin	Yes	<code>AdminCertificateSettings.AllowedIssuers</code> + mapped thumbprint
YubiKey MFA user	Yes	Allowed CA issuer + optional CA thumbprint + optional attestation + OCSP
Group admin	No implementation	No current validation path

Diagram 7 — how tests interact with the site and when they run



The current repository behavior is:

- `dotnet build WebAppExperimental266.sln` compiles the application and test projects, but **does not run tests**.
- `dotnet test WebAppExperimental266.Tests/WebAppExperimental266.Tests.csproj` compiles as needed, discovers xUnit tests, and then runs them.
- Integration tests use `WebApplicationFactory<Program>` and a temporary SQLite database so they can send real HTTP requests through the app pipeline.

Test coverage map

Test area	What it exercises
Models tests	Configuration objects, defaults, validation helpers
Service tests	Auth handlers, OCSP logic, nonce services, cloud wrapper services
Extension tests	mTLS registration and pipeline ordering
Controller authorization tests	Required authorization attributes and policy usage
Integration tests	Home/Privacy routes, service registration, security headers, app startup
Security-focused tests	mTLS, YubiKey, admin certificate, nonce, OCSP behavior

Current timing answer

The automated tests run **during dotnet test** , not during a plain `dotnet build` . In the current validation run for this task, the repository passed **362 tests**.

Operational observations and gaps

- The repository contains a strong certificate-driven admin and YubiKey story, but **group-admin-specific flows are not yet implemented**.
- `/Experimental/*` is already reserved for YubiKey MFA, so future feature work can attach new Razor Pages there without redesigning the auth model.
- The home page is the clearest page-to-asset hub because it combines database reads, authorization-sensitive ArcGIS selection, and public downloads.
- The admin views and user views both ship inline filter scripts, so CSP/nonce behavior matters for these pages when nonce services are enabled.

Files most relevant to these diagrams

- `WebAppExperimental266/Program.cs`
- `WebAppExperimental266/Controllers/HomeController.cs`
- `WebAppExperimental266/Controllers/RecordsController.cs`
- `WebAppExperimental266/Controllers/AdminRecordsController.cs`
- `WebAppExperimental266/Extensions/ServiceCollectionExtensions.cs`
- `WebAppExperimental266/Extensions/CrudAndAdminExtensions.cs`
- `WebAppExperimental266/Services/AdminCertificateRequirementHandler.cs`
- `WebAppExperimental266/Services/YubiKeyRequirementHandler.cs`
- `WebAppExperimental266/Services/CrudRecordAuthorizationHandler.cs`
- `WebAppExperimental266/Views/Shared/_Layout.cshtml`
- `WebAppExperimental266/Views/Home/Index.cshtml`
- `WebAppExperimental266/Views/Records/Index.cshtml`
- `WebAppExperimental266/Views/AdminRecords/Index.cshtml`
- `WebAppExperimental266.Tests/Integration/ApplicationIntegrationTests.cs`
- `WebAppExperimental266.Tests/Integration/MtlsIntegrationTests.cs`
- `docs/YUBIKEY_OPENBSD_ADMIN_GUIDE.md`

Generated from `docs/en-US/SITE_FEATURES_ARCHITECTURE_GUIDE.md` for repository documentation.