

The Idea

Data Collection  
Business Plan

Important Links . locx

Colorado .xlsx

Oregon

Pennsylvania .xls

Texas .xlsx

Washington .xls

Illinois .xml

California .xml

File Type : CSV.

Then, visit various resources online

that can do CSV to JSON conversion. <http://codebeautify.org/csv-to-json.json> → codebeautify.json.

In the beginning, colorado . apprealpetitionformat - consolidate - 9.6.22

[ \* [stack overflow com / questions / 54159398](https://stackoverflow.com/questions/54159398) .

{ Open your browser, go to your Firebase

"Consolidate": "Steve Yusash",

"Party": "Colorado Center Party",

"Offices / District": "US House - District 2", ...

and so on and so forth. - console, Realtime Database,

Three Dots on the right : import JSON.

\* To use the Firestore mobile/web client libraries and other

Firebase features, log into the Firebase console, then

click Add project ... Create database Data Structure:

Start in test mode must update your security rules

within 30 days to enable long-term client read/write

access: anyone can view, edit and delete: there are classes

and one of them is Data Structures. • Navigate to Build

> Realtime Database There you will find that yes, one

can Create Database (Who decides to capitalize what?).

Realtime Database location Singapore (Asia - Southeast).

Invalidate JSON. Keys cannot be empty or contain \$# [ ]. /

Find & Replace forward slash / with the dash, not

to read faster, but to hyphenate.

First, take the Excel spreadsheet and clean it up in such a way that the first row contains the headers and everything else is the actual data.

\* [stack overflow com / questions / 40467777](https://stackoverflow.com/questions/40467777)

Then, save it as a CSV file.

- The `github.com/galishel/chalkboard` repository, `/client`, contains the components, the `/store`, and the utilities. That is, `(chalkboard/client/components/Submit.js)`
- makes a component export that includes `import axios from 'axios'`. Now, the death of the semicolon unless `const photoStuff = await axios.post(url, formData, { config })` are for image uploads, while the `const url = '/api/submissions/{assignment.assignmentName}'`?
- `student = $[user.id] & course = ${Assignment.courseId}` while `chalkboard/server/api/index.js` consolidates our routes. `const router = require('express').Router()` `chalkboard/server/api/index.js`. What is the base URL for axios? Because axios knows what comes after localhost. The reason for this is that `chalkboard/server/index.js`
  - sets up the Express App and starts listening on `const PORT = process.env.PORT || 8080`. In [medium.com/bb-tutorials-and-thoughts/how-to-develop-and-build-a-nextjs-app-with-nodejs-backend](https://medium.com/bb-tutorials-and-thoughts/how-to-develop-and-build-a-nextjs-app-with-nodejs-backend), provided the package.json of nodejs API: `"scripts": { "start": "node server.bundle.js"` ... and `"main": "server.js"`, ... we have created the package.json of the NodeJS API, which comes first. Why would you ever want to [nextjs.org/docs/api-routes/introduction](https://nextjs.org/docs/api-routes/introduction) as opposed to creating a separate backend server? Any file inside the `pages/api` is mapped to `/api/*` and will be treated as an API endpoint instead of a "page". Glorifying versus firebase therefore `create../api/index.js` consolidates todo: error handling). `npm install sequelize --save-dev`, & `pg & express`. The Type Error: Cannot read property 'apply' of undefined is element - charable to node-modules/Next/list/sequelize/

next-server.js, that is within the Da Repo context  
that causes us to .../api-utils/node.js await resolve  
(req, res) going down the call-stack ... router.js  
: 222:36 ... it's the routes ... on pages/api/candidate.js  
comment out router.get(...{}) and the apply is from  
node-modules/express/lib/routes/index.js : 696 ...  
the restage (fn, obj) is called with undefined for

- \* Because pages/api/candidate routes.get("/candidate-X", async (req, ...)) is the base URL hosted  
right after /api . localhost:3000/api/candidate-X  
is uniquely 404 | This page could not be found ..  
This has a lot to do with Nextjs naming nextjs.org/docs/api-routes/introduction conventions . Todo: add  
Sequelize: until we get that integrated with Firebase,  
On pages/api/candidate.js, want to query Firebase:  
gooley-webapp-backup-my-eldits config Todo: access  
control middleware & Project Settings @ Firebase Console  
</> Also set up Firebase Hosting for this app  
the-midway - b98f8 , npm install firebase, & -g firebase-tools , firebase login or init or deploy . Stackathon  
time phoenixnap.com/kb/update-node-js-version...  
succes n stable now logout of Firebase, log in now can  
use existing project thanks to stackoverflow.com/questions/  
57941289 default... rules & indices TypeScript with  
ES Lint & dependencies JavaScript single-page app for  
now with CI Github . npm install firebase-admin  
-- save-dev, & firebase . Instead of the NPM firebase-  
admin package which is, that is deprecated,  
stackoverflow.com/questions/70445014

Like Instagram; Vertical Layout

With buttons ↓

Are you currently an elected official or running for office?  Yes  No

Country dropdown with one option

\* Zipcode should prepopulate the address

Slideshare

First & Last Name input prepopulates the rest of the form.

Search functionality is for rigroup & social network

Email password confirm Last Name Middle Initials  
Last Name Title (Optional) Zip Code State City (Optional)

Create Account

[Search database]

↓

First Name
Full Name + title
position
district

Identity Verification API

(Confirm)

More you invest,  
the more shares in the  
company.

Thank you for submitting your information. We will review your information for review.



guofucius

- You will receive an email shortly to confirm your information.

Continue as guest

\*Only for elected officials.

For the visitors:  
Pitch solution / problem 50/50:  
Show the tree  
investing (Not seed data)

White & Black

rgda

mangrove



Mangrove source

npm install axios

Code: unique emails. Grab stuff from Excel file.

- Combine data into one with missing data
- Sort based on hierarchy: start by zipcode!
- Make sure Confirm & Password are the same
- Post and create events only for elected officials,

★ Login. Form onsubmit = [this.submitForm]

SubmitForm = async e  $\Rightarrow$  { e.preventDefault()

var form = e.target

firebase

- auth()
- signInWithEmailAndPassword()
  - form.elements.email.value.toLowerCase(),
  - form.elements.password.value

)

- then (async response  $\Rightarrow$  {
  - var response = await axios.post(  
process.env.API\_URL + '/auth/setLogin',
    - { user: { email: form.elements.email.value.  
toLowerCase() } },
    - { withCredentials: true }

} Router.push('/userProfile')

} catch (err) {  
alert(err)}

}

• On the /auth/setLogin API route,  
var user = req.body.user

req.session.user = { email: user.email }

res.status(200).json({ success: true })

< Form ... onsubmit = [this.submitForm]

process.env.API\_URL is undefined!

! ★ Next.config.js contains environment variables.

- localhost:3000 says
  - Firebase... Enable the given sign-in provider in the Firebase console, ... Authentication > Sign-in method ... Get started ... Email / Password  $\Rightarrow$  Enable firebaseApp.auth(). signInWithEmailAndPassword (username, password). then... There is no user record ... signup > this.submitForm • POST /auth/setLogin / signup / saveUserToDatabase  $\rightarrow$  POST /sessions / userDatabase XPOST https://localhost:3000/undefined/
- Changes to /api/sessions, then the response sessions exists. ! XPOST ./api/usersDatabase 404 (Not Found).
  - ✓ /api/sessions is reachable, and /api/usersDatabase is reachable.
  - ReferenceError ... • With fromBasicPassword defined ... ReferenceError: SweetAlert2 is not defined
  - Reels import SweetAlert1 from 'SweetAlert2' • npm install sweetalert2 --save-dev
  - ! Hold On! email address already in use by another account. (auth / email -already -in -use).
  - The Midway > Authentication 'User' is where we should sign up.
- Test the Login button on localhost:3000 that is index.js. Login means nothing more than /api/sessions ... and channelling Router.push('profilePage')
  - "Login" has nothing to do with Firebase; it is the receipt of a cookie that is an access token. How are sessions sustained?
  - req.session is undefined.
  - npm install express-session cookies.

- How to get the cookie in React | Reactgo reactgo.com
- Can we access the cookie from any and all components?  
Yes. Can we import this functional component and redesign it such that the component is just a function that returns nothing if not the cookie extracted via the "React-cookies" library? First, import the functional component: one can import ViewCookie from `./ViewCookies` but the cookie value isn't accessible until the `<ViewCookie>` component is accessible, via in-line rendering for instance.
- Something that the `ViewCookie` component could do naturally is make submissions to the API route of parameterized choice, which returns a value to the function passed as props.

```
function datafetchpoliticians() { ... const
  data = axios.get('... ')
  this.setState({ data })
}

that is invoked by <ViewCookie propsfn={data} ...>
event bubbling up in React is a thing and likewise is
lifting state up; let's first hardcode the desired cookie.
On the frontend, create the pages/politician-data
directory that requires access to the cookie value on
mount of the ViewCookie.js component, with this binding
to access new scopes like useless() { return eliv...
with the useEffect(() => { propsfn(cookie) }, []) that
only runs once, moved to pages/useless.js, and checks whether
or not the browser has a non-zero length cookie value.
```

Is da-repo.herokuapp.com / loginCookies accessible?

No; Internal Server Error. Once React Cookies joined right after commit 66139b...5c9, that is on commit 3f5e44...889, after the four-threaded Delta compression of 368 objects (source files) while "building" the source Node.js app,

Heroku's software failed to compile.

Why? Module not found: Can't resolve '`!./ViewCookie.js`' in '`/tmp/build-b7afad84a/pages`' ... because of webpack errors.  
the reason being that ViewCookie is "considered to already be there" by Webpack instead of ViewCookie.js (that is) called proper capitalization...

A more accurate filename (VSCode imports recognize file filename "using"):

80/80 objects enumerated, counted, delta compressed using up to 2 threads: 48/48, objects (49/49) written, 17/17 deltas resolved 100% with 15 local objects. - Git on <https://github.com/thelmlmristuoso/Da-Repo.git>  
"Errors: Cannot find module 'react-cookie'..."

"When server rendering, you must wrap your application in an <SSRProvider> to ensure consistent ids are generated between the client and server." - Heroku on pm run deploy  
"Errors: Cannot find module 'react-cookie'"

Is da-repo.herokuapp.com/loginCookies accessible?

No; Internal Server Error. Once React Cookies joined right after commit 66139b...5c9, that is on commit 3d5e44...889, after the four-threaded Delta compression of 368 objects (source files) while "building" the source Docker.js app,

Heroku's software failed to compile.

Why? Module not found: Can't resolve '!/ViewCookie.js'

\* in '/tmp/build\_b7afdb84a/pages' ... because of webpack errors.

The reason "being" that ViewCookie is "considered to already be there" by Webpack instead of ViewCookie.js (that is) called proper capitalization..

A more accurate rename (VSCode imports recognize file rename "visiting").

80/80 objects enumerated, counted, delta compressed using up to 2 threads: 48/48, objects (49/49) written, 17/17 deltas resolved 100% with 15 local objects. - Git on https://github.com/thellluistuoso/Da-Repo.git

"Error: Cannot find module 'React-cookie'..."

"When server rendering, you must wrap your application in an <SSRProvider> to ensure consistent ids are generated between the client and server" - Heroku or pm run deploy

"Error: Cannot find module 'React-cookie'"

This is how the developers.ballotpedia.org does API calls:

```
var myHeaders = new Headers();
myHeaders.append("Content-Type", "application/json");
myHeaders.append("X-API-Key", "your-api-key");
var requestOptions = {
```

```
method: 'GET'
```

```
headers: myHeaders
};
```

Via Javascript:

```
npmjs.com/package/react-cookie  
fetch('...api4.ballotpedia.org/data...', requestOptions)  
  .then(response => response.text())  
  .then(result => console.log(result))  
  .catch(error => console.log('error', error));
```

We can request Voting Districts · Current Officeholders ·

\*Election Dates · \*Election Ballots & Results · For \* there  
is a distinction between "by point" · "by parameters" · "by  
State"; remember the election date: recursive database sub-  
queries are made based on everything about the election.

It turns out that localhost has so many different kinds of  
cookies which, like Google Analytics (and one other - something  
odd) the IP-based one is the odd one and they both arrive  
on localhost from somewhere mysterious and exciting, therefore  
we should check the value set on that cookie, maybe our secret  
master key. For now, the cookies should signify the email  
address and password and master key via key-value pairs.

The event that triggers login is the same event that has Firebase  
know that "There is no user record..." alert message. But it's  
not just incorrect login, it's `console.firebaseio.google.com/v1/0/  
project/the-midway-698d8/authentication/users`. What is the  
password? We can send a password reset email. Although the  
Authentication tab gives user unique identifiers, we would like  
to see the password that conveniently appears on the Firestore  
Database, in the new-users collection, from which we can  
construct `localhost:3000/profilePage`, which currently displays  
404 | This page could not be found.

On the profilePage, we should display what is now known  
at the /users page and a personalized greeting. We are granted  
react-cookies that integrates universal-cookie, universal-cookie-  
express, and has: `import { withCookies, Cookies } from 'react-cookies'`.

good news: ballotpedia does sell their data and API.

Bad news: it's all like 12K+. Nothing over 20K though.  
If we get sufficient funding that'll be no problem, since once we have the API it'll be permanent; then we can devote research and a team to develop our own API.  
Focus on a state: first want to render the `LoginCookies` component on `index.js`: import `ProfilePage` from '`/profilePage.js`'. Second, after rendering want to pass down what's currently in the `this.state` resurrection of the `username` & `password` fields. Third, the `profilePage.js` constructor(`props`) → `this.state = { ...props, implicit as seen on ProfilePage name="Dean" };`. Fourth along the lines of above within `ProfilePage` render <`LoginCookies cookie={this.state.props}`>. Fifth can we reach the `ProfilePage` component? Yes. We are able to render the `LoginCookies` component through `ProfilePage` on `index.js`. Is Stack Overflow always offline? No.

Would be nice if the login screen wasn't present in the list of users though. \* Removes "React Cookies" from `CookieView.js`. \* Want to streamline the next page; React-snowfall, the criticism (`ProfilePage` is all the time) - keep header/footer; now it is - move snowfall to no cookies. Effective. No cookies goes well with no content. The eventful button. The class name `ui-OrbitButton`, that is styled borders transparent. For the `Signup` box want to fetch cookies. Commenting already in JSX `{...}`, check `Object.keys(this.state.cookieValue)`. `this.length != 0`, is accessible via `CookieView.js`. Passes the `GeoClio` query as props with `alex(...)`. First step is `Object.keys(this.state.flattenedAddress)[0]` \* Want each object to have random color; class or in-line?

Tri Sep. 30.

Goals. (09/22/2021). Change the signup box both voters and politicians to include address. For the Built-in Retina Display 13.3-inch ( $2560 \times 1600$ ). The height is  $1600/350$ , =, on pages/signup-form.js, the updated value of the height and width that is  $(1600/350)vh$ , therefore we can center items in the existing flexbox: \* ~~reverse fraction notation~~  $\times 100$  is multiply by  $2 = 43.75vh$ ; universalizes signup-form box. (Why not 50% of view height? On the first, want not `<h2>` but button styles fontFamily don't get applied, why? to the child divs, we can use our own fonts.) `<div>...` Instead of `margin-left: & div's width;` flexDirection: 'row', justifyContent: 'center'. In styles.css, no quotes unless required. Then does `<Snowfall/>` cover the field of view? (What is `<main>`? Wraps are good for overlays; background-size: cover images whereas `background-color` & `background-color`, do not.

box-shadow overlay: inset 0 0 0 200px rgba(255, 0, 150, 0.3); ([stack overflow .com/questions/36679649](https://stackoverflow.com/questions/36679649)).

Looking for classes that don't exist, styles JSX with phone-sized screens. `flexbox`, like `background-color`, is good for examining computed styles; moves styles to styles.css. View Height = Scroll Height? No; `<Snowfall/>` takes up a lot of space on mobile screens! It will grow to fill the nearest relative positioned parent element, unlike the canvas element.

- "Store this file securely, because your new key can't be recovered if lost"
- the-midway-698f8-firebase-adminsdk-a2023-  
b45366faf0.json

The example known from [levvelup.gitconnected.com/firebase-import-json-to-firebase-eb6a4aefc2657](https://levvelup.gitconnected.com/firebase-import-json-to-firebase-eb6a4aefc2657) will be using 3 files:

1. config.js
  - Contains and exports our firebaseConfig object.
2. serviceAccount.json
  - Contains our (at least, soon to be ours) service account configuration, generated & downloadable via Settings → Users and Permissions → Service Accounts tab → Node.js → Generate New Private Key → Generate Key → Save the file to serviceAccount.json.
3. import.js therefore is a JSON file, technically the fourth.

// Imports

```
const firestoreServices = require('firebase-export-import');
```

This line is simply the import of a foreign library.

```
const firebaseConfig = require('./config.js');
```

Config.js is the generic Firebase Configuration already used.

```
const serviceAccount = require('./serviceAccount.json');
```

After making these configuration imports, access the ADI.

// JSON To Firestore

```
const jsonToFirestore = async () => {
```

try {

```
    console.log('Initializing "firebase"');
```

```
    await firestoreServices.initializeApp(serviceAccount,
```

```
        firebaseConfig.databaseURL);
```

```
    console.log('Firebase initialized');
```

```
    await firestoreServices.restore('./data-clean.firebaseio/
```

users.json);

```
    console.log('Upload Success');
```

} catch (error) {

```
    console.log(error);
```

}

On the same `~/.lla-Repo/pages/api/database (68cf7c2) ×`  
node import.js → Error: Cannot find module 'firebase-export-import' ... `npm install firebase-export-import`.  
`const { initializeFirebaseApp } = require('firebase-export-import')`

`initializeApp` is not a function. ⇒ `initializeApp` is some kind of function. After 57397608 and

72086575 on stackoverflow.com/questions/... What's the default `initializeApp`? No "exports" main defined 68943610 Error: Could not load the default credentials.

`58127896 npmjs.com/package/firebase-export-import`

It's not called `serviceAccountKey.json`, on `npmjs.com/package/firebase-export-import`, Firebase might call rename it.

Stackoverflow we can edit posts!

"Here's an error writing the document: Error: Could not load the default credentials. Browse to <https://cloud.google.com/docs/authentication/getting-started> for more information." ★ `require` knows to look for `'node_modules/firebase-admin'`; `document`.

Overwrites whatever is in the database at those key: value pairs. (What are the data types? `collection`, `doc` want a string while `set` wants an object. ★ When we write to `db` we get a timestamp, called `WriteResult`.

★ It won't overwrite what's in the collection beyond the specified document, like the shard; the smallest unit of data space; the document name is so important.

Thus the JSON is in collection.

Once the file obtained via `services.arcgis.com` is downloaded or even just copied and pasted into JSON format, wrap it in `{ "arcGISdata": ... }` because these we can name

the `arcGisData` collection. This brings us as far as `arcGisData.css : docTitle`. Should it suffice to convert the first-level properties list at "features" from an array into an object? `name: "un...84"` This wouldn't be practicable because `type: "name"` "features" is a list of objects. Error writing document: `Error: 3 INVALID_ARGUMENT: Cannot convert an array value in an array value.`

Since the `arcGisData` object has the "features" key at which point the list is at `nestedContent[docTitle]`. In Firebase, new collections show up upon refresh however not upon no refresh, therefore let's see if Firebase is in something other than React, is it? It's the single-page application.

`if (typeof nestedContent === "list")  
~/Da-Repo/pages/api/database ({68cf7c2}) node import.js`  
Are there different formats for `console.error`? Yes; `console.log`, `console.info`, `console.clear`, `console.error`, `console.warn`, and `assert`, and `console.count`, `.trace`, `.table`, `.time` & `.timeEnd`, `.group` and `.groupEnd`, `.groupCollapsed`, ([medium.com/theleanprogrammer/...](https://medium.com/theleanprogrammer/)) the array is an instance of an array while it is an object. If `nestedContent[docTitle]` instanceof `Array`, then `docTitle` is equal to "features" which corresponds to an array. The values within this array are primarily objects.

Want each feature value to be a document within the collection, call it `FeatureCollection`. Can arrow functions within `map` directly to the object {}? No; confuses with return. Customizes the flattening & objectifying of the array into an object, and splicing into & removal of. Implements `React-items-carousel` in a class component. Alphabetically ordered functions & `this.state`, creating fetch API route for `arcGisData`, first on componentDidMount and on `arcGisData.js`.


To be continued... wards, counties, aldermans, and the show user's thing for which coordinates to work  
translation framework coordinates show up long before  
entering an address, because they are JSON objects...  
I want to display PDF of our history on the back  
story.

How does GitHub prohibit  $151.94\text{MB} > 100.00\text{MB}$   
the GitHub file size limit while Heroku allows  
large files? *downloaded faithfully from*  
**arcGIS** *that is our source of morning glory.* We  
have information on topics like OBJECTID, LABEL,  
District CouncilRep First & Last Rep-Type  
coordinates SHAPE\_LENGTH SHAPE\_Area.

When you enter a Pennsylvania address

- Each politician's "namecard"  
should be in this format for now
- The update is actually a de-stress;  
the data that we are getting get  
county lists as labelled in the  
excel file.

• They call it Pennsylvania for a  
season or so we believe like the Krusty Krab.  
The Pennsylvania address pattern I takes up via the Geoclio  
API; there's Route 2 that is so much better than what  
we have for Route One; For Pennsylvania we are getting  
the county possibly through a built-in dataset in our  
Firebase database • We don't even need Lat/Long  
unless we're looking closer than just the county because  
the county is whatever we say it is. Otherwise the  
latitude & longitude come from the ArcGIS query or  
from the data we have downloaded via GeoJSON format  
or alternatively from the Reverse geocoding API  
under the appellation of Geoclio the reverse  
geocoding API.



\* ... navigator happens once we allow location in Chrome.  
the useEffect function keeps looping once: SettersetCurrentView to the [ currentPosition, setCurrentPosition ] React Hook. The success "variable" that only gets set once.  
The Next.js admonition that global CSS cannot be imported from files other than your Custom <App>... it is possible  
that the existence of the export itself. After initializing  
Next.js PDFtron.com/blog/webviewer/how-to-build-a-next-js-pdf-viewer, yes libraries are crawled by  
Next.js. Install npm i @pdftron/webviewer that is  
the root. Package.json postinstall & download -webviewer  
prompts dialogue on npm install ★ pdftron.com/documentation  
/web/faq/geolocation-errors/ path: /webviewer/lib!  
because you can see the lib folder in /public next to  
files. Therefore adds localhost:3000/mangenie-the-  
backstory. console.log google.com/google/maps-apis/credentials?project=midway-361901 + CREATE  
CREDENTIALS. API key 1 ApibotActivatedMaps  
You must enable Billing on the Google Cloud Project  
Current Location leads to the map getting stuck!  
Instead of Analyze data with Leaf.js and Mapbox GL JS,  
we can build Google Maps and instead of pdf-viewer-  
Reactjs we can implement PDFtron. After the Allyn Akola  
tutorial that enables us to use Google Map API in a  
React App, want to continue styling the app via MapContainer  
.js that allows a customizable GoogleMap API. Further  
more there's the Leaf.js and WebViewer APIs that might  
have more features!

- Added some sort of google maps functionality to the shown users part. That's a decent step, are you gonna be able to extract lat/long from your location that way too?
- chrome://settings/content/location • http://localhost:3000  
wants to Know your location Block Allow Links you to the Pfingsten area (without a mask). The in MapContainer.js  
useEffect(() => { navigator.geolocation.getCurrentPosition(success); })

It looks like adding console logs makes the map think twice before (doesn't) jump to static, the current position. Back to the original question we can extract lat/long ✓ and can we put it on a marker?

? How does GoogleMap address the child divs <Marker...? Yes, we are going to be able to extract lat/long that's beyond question.


Task 2. Need to "somehow" link that to "ArcGIS" using the method I mentioned earlier - that is the most probable method of the ancients. Buried in the lost sands of time, ArcGIS API for JavaScript: [developer.arcgis.com/documentation/mapping-apis-and-services/search/reverse-geocoding/](https://developer.arcgis.com/documentation/mapping-apis-and-services/search/reverse-geocoding/)

npm install @arcgis/core. The keys are being mapped to from {this.state.flattenedAddress[key]} Like likes like. "the response has been received!".  
this.state.latingQuery.flattened is just like  
this.state.flattenedAddress;

- Is there a way to organize the results from the query?  
For this example (and the others), all the `.card` items are inside a `.cardList` container element. Why does `<title..>` disappear in React JSX? At "last" in `pages/index.js`. Why can we do `background-color: url("https: ...` but not `background-color`? Is there an "implicit" flexbox such that line-adjacent divs are in two rows, equivalent effectively to `display: flex; flex-direction: column;`?

★ Formally write out the "motion". Converts the address, lat/long queries to card(s) via [getflywheel.com/Layout/Layout-CSS-Grid-Layout-HOW-TO/](http://getflywheel.com/Layout/Layout-CSS-Grid-Layout-HOW-TO/) to display key:value pairs in rows 1 & 2 to represent. Google Chrome: find computed styles by keyname. ★ divs are scaled all to the widest key, because since space character is the line break enabled? Return of the ProfilePage! Circular background & gradient.

- Create a file `index.js` in the API folder → We'll import these functions into our app in our `index.js`. `pages/api/index.js` → `pages/index.js` • Above, we added import for `axios`, the URL to fetch our data, and exported functions to `read` and `create` data from our forum. In the forum project folder, our app structure will look like this.



`pages/index.js - forum`

- How to build a Login App with `Next.js` and `Strapi CMS`.
- This tutorial will cover building a forum website and providing user authentication and authorization on the site.

★ Prerequisites. To fully grasp this tutorial, you need:

- Node.js installed
- Knowledge of `Next.js`. Then we install `Strapi`.

`npm create strapi-app`  
`forum-backend --quickstart`

The command above sets up `Strapi` for our app with all dependencies required. Here `forum-backend` is the name of our project folder. The `--quickstart` option sets up `Strapi` with a `SQLite` database. Above it proceeds to set up the admin UI. Once the process is complete, it runs `(strapi develop)` and opens up a URL in your browser. (`http://localhost:1337/admin`)

- Collection and Field Setup `Strapi API tester`
- `localhost:1337/api/strapi-forums` : Building our front-end
- To install `Next.js` `npx create-next-app forum`

Setting up our fetch Request

`strapi.io/blog/how-to-build-a-forum-app-with-nextjs-and-strapi-cms`

Getting data from `Strapi` : Setting up our fetch Request.

`npm install axios` Create a file `index.js` in the API folder. Here, we will set up our fetch request.

Import these functions into our app in our `index.js` file:

```
import { readForum, createQuestion } from "./api";
axios.get(url) in our index.js file of all places fetch the data from Strapi and pass it to Displayforum.js component to display it: We will fetch the data from Strapi in our index.js file and pass it to Displayforum.js component to display it: now that we have added authentication to our app, we can add the username received
```

[strapi.io/blog/how-to-build-a-forum-app-with-nextjs-and-strapi-cms](https://strapi.io/blog/how-to-build-a-forum-app-with-nextjs-and-strapi-cms)

### [...nextauth].js

```
import NextAuth from "next-auth"
import GoogleProvider from "next-auth/providers/google"
export default NextAuth({
  secret: process.env.secret,
  providers: [
    GoogleProvider({
      clientId: process.env.clientId,
      clientSecret: process.env.clientSecret,
      authorizationUrl: "https://accounts.google.com/o/oauth2/v2/auth?prompt=consent&access_type=offline&response_type=code",
      })
  ],
})
```

f) Create `secret`, `clientId`, and `clientSecret` that is `SECRET`, `GOOGLE_CLIENT_ID`, `GOOGLE_CLIENT_SECRET`

To use the credentials in the `[...nextauth].js` file, you can create a `.env` file and set up your environmental variables:

\* the `secret` can be any string, while `console.cloud.google.com/apis/credentials` has the `client secret` & `client id`.


Want: filters by selected date values!

### The Address Tree Query

- Decreases height of main page to 0.
- Removes Verbal goofy advertisement
- ProfilePageOld class removed, edited in pink by Akhil, tools: General Assembly Member, to the Search function. Removes "selected" text.
- Edits in grey "slate" background
- Card class - convert the purple background color to something else?
- That "gradient" background for the individual card "elements" - change it to "slate" color, while (no longer index-based gradient), but Object.keys (this state).

CSS to make it look like a tree.

\* bulge for when you fully explored the tree  
Transform the cards



[Stackoverflow.com/questions/38750705/filter-object-properties-by-key-in-es6](https://stackoverflow.com/questions/38750705/filter-object-properties-by-key-in-es6)

Want to resolve Errors cannot find module 'fs'

results. O. fields. congressional\_districts. O. current\_legislators.  
O. references. ballotpedia-il. We were able to "fix" rendering by commenting out the < LoginCookies props={this.props} /> {/\* ... \*/} component...  
! Unhandled Runtime Error TypeError: Cannot read properties of null (reading 'data') · let newData = await this.state.arcGISData.data.response.  
This data is being fetched separately, from axios.get('/api/arcGISData') in getArcGISData but not in setArcGISData why; not merge them together?  
The contents of async setArcGISData() I ... "were accidentally" commented "back" in! Comment it. That's TypeError: destroy is not a function on the two useEffect hooks on the Login component. typeofnan.dev/fix-untangled-typeerror-destroy-is-not-a-function-in-react/  
return () => { console.log('This will be logged on unmount'); };  
I; as you fix "Destroy is not a function" errors and queryGeocodingAddressCatalog "makes it" half halfway through index.js → ProfilePage.js Old.js → LoginCookiesOld.js. Pass props instead of { name, cookieSet }, which will be "directly" upon import from ProfilePageOld, "undefined". The "old" Roger page · Reenacts CookiesNew.js. Now all we need to do is remove those tiny text on the top labeling the fields - big improvement!, like things like these: results. O. fields. congressional\_districts. O. current\_legislators. O. references. ballotpedia-il.

Here on the cards we want to get names like Don Beyer, Mark Warner, don't need to repeat the address "that we just searched for", Timothy Kaine; on dash.geocod.io/usage shows, upon page reload, 2 lookups with 21 fields, for a "subtotal" of 23 out of ~2,500 on the free tier. After "the address data", there is a "small" amount of physical data e.g. besides the address, there's latitude & longitude ("what" is the social.youtube-il?), there is a lot of U.S. census data and statistics, metadata about the meta-data source and right after that, the population value, margin of errors and schooling completion status... these are numeric, education-related values. Population with veteran status & Period of military service for veterans · Metadata on the housing universe, a key-property called... Household type by household... · Marital status · Number of households · Household income · Population by...

... We who are living & looking on the meaning of happiness... we don't know how much census data we have, but it goes from 2010, 2011, ..., 2021. **The source and survey, & the population by minimum level of education.**

... by age range (Population by) · Sex Statistics & metadata · Race and ethnicity percentages statistics · Finally but not last, record type and carrier route, & information about the facility, the building, and the delivery area and location. Group these fields together & look at the keys, because these are universal.

Splits the cards between current - legislators Don Beyer and Mark Warner. Now reading down line by line. Based on dash.

geocod.io/usage we are able to increment Lookups and Tickets by refreshing the page, but is unaffected by saving & updating the frontend via VSCode. Todo: Add General Assembly members

to the search function please, now all we need to do is remove those tiny text on the top labeling the fields. The first thing we "need" to do is remove the address components, style that like address components. Referring to the results object, we have the geo-top accuracy of 1, latitude and longitude, information about the

Congressional Districts numbers and proportion, the current legislators' numeric biography & contact, social, references to places like bioguide, thomas, opensecrets, lis, cspan, govtrack, votemart,

ballotpedia, Washington Post, icpsr, and wikipedia. The legislators data is originally collected and aggregated by <https://github.com/unitedstates/>. "Just as" we have information on

subjects like Don Beyer we "also" have information on legislators > senators like Mark Warner, following this immediately

we have Timothy Kaine in the same fashion. Then there is

**the State House District 2, Arlington County Public Schools with Unified LEA code & low or high-grade.**

Then, there is timezone name, utc\_offset, observes\_dlt, abbreviation and source. Census results, including year, state fips · county fips · tract code · block code · block group · full fips · metro statistical area, place name & fips. A lot of census and statistically-related data. 2010 & 2011...

daylight  
savings time?

bobbyhale.com/blog/react-on-hovers-show-text

What we want to do is have the key show up when you hovering over the proper div.


onMouseOver = [handleMouseOver]  $\Rightarrow$  this. handleMo-

onMouseOut = [handleMouseOut] weave(key)

if the key being generalized is the same as the key being hovered upon, then generalizes it.  
This console.log for geocoding address query & reverse latitude & longitude.

Also, what's the biggest thing holding us back atm to get general assembly members displayed?

- Tammy Duckworth and Dick Durbin.



#1 priority - List all state-level-and-above politicians on the search tab/site

To find state rep. members

1111 Avenue St, Chicago IL 60603

Folders = States → Illinois → State → Illinois House. n/52

~~Statehouse~~. District number =  2nd column is distr. #

Only one state rep. per address

Convert code to state if two letters.

Navigate to that folder.

get Name/Party


Senator first then Representative

position : [state] state

filters if name == "Vacant"  
then filter it out.

representative

Organize file structure



Shell for politician dashboard built out

Remember the `pages/api/users.js`, that initializes the firebase APP. ~~all it does is await db.collection~~

~~randomize~~  
Don't touch just focus on `pages/users.js`. We have moved the `/actions` folder to still, as before, meet the working directory... and finally we have social/client/src/components/Posts/Posts.js.

Whoops! ~~importing Posts in users.js leads to importing Post in Posts~~. Instead of doing the importing of a file structure let's create `Post.js` adjacent with after spinning `Posts.js` both in `pages/components/Posts/` folder; it's a directory!

A post within a Post means pts

In the meanwhile, we can package.json with

ReferenceErrors:

is NOT

Sets the post data function

setPostData object `postData`. Now, when submitting

Wavelength a message, currentId is not to the card rendering. Defined. Inadvertently merging `zoom.js` & `App.js`, the currentId

3 face-to-face social/client/package.json - Da-Repo.  
cover off setPostData  
only son see defined.

`const [postData, setpostData]` is a "native" built-in function! Why not test it by importing the whole function? ★ We already have Creator, we don't have title, we do have message, from which imports Creator and we still have pages/actions/posts.js

selected file Creator  
may be from the Cookie object

Post

build & export functions

Creator

Message

index.js is in social/client/src/api/index.js, originally.

★ Instead of pages/api/index.js, we can access pages/actions/posts API.js. Moves it to there.

We have imported users.js, posts.js, post API.js and (unused) styles.js. We are making some kind of comparison between pages/users.js and social/client/src/components/Form/Form.js. The currentList is actually passed as a property to pages/users.js.

Form.js is "being" imported from social/client/src/app.js

★ Only using getPosts from './actions/posts'; and therefore, since we pushed api.fetchPosts() into export const getPosts, we know how to effectively fetch new posts, deal with the existing posts. Module not found : Can't resolve './components/Posts/Posts'.

★ Moved: social/client/src/components/Form/Form.js in the original tutorial... to pages/users.js.

Moved: social/client/src/actions/posts.js in the original tutorial... to pages/actions/posts.js.

Moved: social/client/src/api/index.js from the tutorial that is memories-project to pages/actions/post API.js


Moved: We did import, to pages/src/styles.js. These are in a category of their own!

\* npm will tell you the correct version for conflicting peer dependencies like "babel-eslint": "^8.2.6",

[stack overflow . com / questions / 44822146 / git-heroku-repository-object-not-found](https://stackoverflow.com/questions/44822146/git-heroku-repository-object-not-found) git push heroku master --no-verify  
The procedure for deploying from Herokuapp.com to Vercel.app: build directly from the repository to Render & Bit.co: chart-demo-1.herokuapp.com

① ~/chart-demo (master) ✓

② The Nangsoone Build Command \$ npm i --force & npm run build



PostgreSQL

Name Region \* Closest region to your location. Heroku dyno name to from chart-demo-1 to herokuapp.com to chart-demo-1. Why are the Regions

Oregon (US West), Frankfurt (EU Central), Ohio (US East), Singapore (Southeast Asia). Is it always Deploy succeeded? Status? What is the maximum number of

Dashboard Overview services?  → Web Service

[dashboard.render.com/select-repo?type=web](https://dashboard.render.com/select-repo?type=web)

instead of <https://git.heroku.com/chart-demo-1.git>, want to have <https://github.com/gladishel/Graphs.git> Instead of node index.js, want npm start. [github.com/PostgresApp/PostgresApp/issues/509](https://github.com/PostgresApp/PostgresApp/issues/509) Privacy & Security > Automation > PostgreSQL Terminal  npm update --force

git pull heroku master. Try to run locally chart-demo!

\* npm run test Uses routes /api/webs/ Uses model instanceMethods seed script failing.

\* Postgres > Preferences: Open Database with Postico

Troubleshoot Sequelize - database connection time-out. Sequelize sync times out

stacktrace in terminal REINDEX DATABASE dbname;

~psql .reindex database "boilemakers-test";

(Why does PostgreSQL 12 move to the top of the page when you close the pgsql Terminal?)

seed.js - Lab > Sequelize - User - Contact

Start with a fresh install of this lab.

[github.com/muhibel/connect-session-sequelize/issues/105](https://github.com/muhibel/connect-session-sequelize/issues/105)

update 6.0.0 to 7.0.0

star [chart-demos.onrender.com/channels/1](https://chart-demos.onrender.com/channels/1) why are the images all empty? What is the AxiosError ERR-BAD-RESPONSE status code 500.../messages.js:34:28 (undefined reading 'dataValues'). Want to POST!

① [chart-demos-1.herokuapp.com](https://chart-demos-1.herokuapp.com/) (gladish.dean@gmail.com)

→ [chart-demos.onrender.com](https://chart-demos.onrender.com) ~/chart-demos

gooley-frontend: Large file storage!

checkers-makers.herokuapp.com (gladish.dean@gmail.com)

<https://git.heroku.com/chart-demos-1.git>

<https://git.heroku.com/checkersmakers.git>

What is getSameByRef for? [node] clean exit - waiting

for changes before restart Currently babel-eslint is

^10.0.1. Found: babel-eslint@10.1.0 While resolving:

checkersmakers@2.0.0. eslint-config-fullstack

babel-eslint@

Could not resolve dependency

peer babel-eslint@"^8.2.6" from eslint-config-fullstack@6.0.0 instead of 10.1.0

The node engine version is also specified in package.json!

node: ~12.11.1 → v16.17.0

try npm test, or npm run seed. - "pg": "^7.9.0",

+ "pg": "^8.5.1", then npm install

Again downgrading "babel-eslint": "10.0.1" to "8.2.6")

! ② checkersmakers → chess-renderer \* Your one free Render database will expire after 90 days ... Option 2: Use bit.io

(Full-Stack (Academy) App Deployment Guide)

login on bit.io via GitHub, → Connect Tab

[dashboard.render.com](https://dashboard.render.com): Environment Variables

DATABASE\_URL <postgres://chart-demos-user:EWYW...>

Using environment database url triggers re-deploy, on [dashboard.render.com](https://dashboard.render.com)!

and setPostData.

One-time email code such as Bloomberg? Sent in JSON files of all the Ohio and Texas county elected officials if you could add that in that'd be great. How? Do the exact same thing you did with Illinois and Pennsylvania. Where do the JSON files OhioCountyEO.json, WashingtonCountyEO.json → and TexasCountyEO.json? They go to like something similar to public → data → States → Illinois → County → IllinoisCountyEO.json... therefore this is where the abstraction starts to break down: adds files to "respective" locations: Elected Officials. git pull origin master. ReferenceError: document is not defined. document.getElementById('root'). social/client/public/index.html. Have you figured out the post function yet? ReferenceError: dispatch is not defined pages/use.js if (currenttel) { dispatch(updatePost(currenttel, postData)); } in client/src/components/Form/Form.js. In Form.js, what we do is import { createPost, updatePost } from '../actions/posts'; import { createPost, updatePost } from '...'; actions/posts'; has already been done by someone → mapDispatchToProps = (dispatch) => { return { ... updatePostThunk: () => (currenttel, postData) => { dispatch(updatePost(currenttel, postData)) } } } → this.props.updatePostThunk(this.state.currenttel, this.state.postData)... What is clear() in memories-project, the MERN? It's a functional component function with everything that comes with it: React this - binding implicit or explicit. Todo: Configure clear() function, with its setcurrenttel

ConnectionErrors [sequelizeConnectionError]: Must use SSR  
(works locally)

③ gentle-hamlet-62265 ~/2006-FSA-CH-WEB-FI-JPFP

④ gooley-frontend-test-2 LFS! Large File Storage.

⑤ gooley-webapp-test-2 No PostgreSQL

⑥ grace-shopper. npm start. Warning: Accessing non-existent property "Car" of module exports inside circular dependency.. [noelemon] clean -xit -waitney for changes before restart. Update "pg" from

^7.9.0 to ^8.5.1, then npm install.

\* "babel-eslint": "^10.0.1", → peer babel-eslint@^8.2.6  
(both in "dependencies" and "DevDependencies")

\* "node": "~12.11.1" → "node": "^14.13.1 || >=16.0.0"

npm install .

from chart-demo

Yes, npm run seed works!

Creates the expected origin remote clean at  
github.com/glaelish/grace-shopper, that's  
present among the git remotes; although  
it's "meant" to be non-existent, dashboard.sondes.com  
"intends" only to deploy from the git remotes tied  
to "glaelish". Adds \$ npm run start-dev to Start  
Command...

⑦ stackathon-1 ~/stackathon/stackathon

"eslint-config-fullstack": "^6.0.0" → ?  
"pg" is only in dependencies!

\* On Github, 2006-FSA-CH-WEB-FI-JPFP

cheesemakes grace-shopper all on Bit.io  
and apparently on glaelish-clean@gmail.com!  
via OAuth

• fast-island-81242; where does this Heroku dyno  
come from? ~/Graphs this in Bit.io is tied to  
dean.glaelish@gmail.com

! Why are ~/chart-demo and ~/Graphs both github.com/glaelish/Graphs.git?

① Change npm run start to npm start. On dashboard  
render.com. Yarn builds to npm install

Yarn: What is the difference & when do each appear?

hidden-reaches-6050 ~ /create-react-app-blog

\* git pull! You never know when you're making multiple  
references to the same repository for instance  
github.com/glaelishl/Desap's git ...

~ /create-react-app-blog (master) git log

already been deployment? npm start

hidden-reaches-6050 → create-react-app-blog  
? takes a few seconds for dashboard.render.com/web/  
raw to find glaelishl/movie-reviews, a new reposito-  
ry. How is URL https://movie-reviews-wizy  
.onrender.com generated?

"Deprecated" what is the difference between npm start,  
and npm run start? Is there a record for git  
push (not just git commit history)?

~ /capstone-chalkboard: Wolfram-school.

What is glaelishl/chalkboardofficial?

\* Thanks for putting the npm test feature; it  
makes testing databases more "transparent".

da-sepo → The Mangrove ✓

~ /space-shopper (master) npm test ... mocha:

command not found.

npm test X i "before each" hook for "renders the  
email in an h3".

movie-topics.herokuapp.com git.heroku.com/pod-  
website-S.git

✓ morning-everglades-36780 is fun-fact-generator  
What is Yarn, what is NPM? How does DATABASE URL  
work on dashboard.render.com Environment tab?

• ~ /audio https://git.heroku.com/internet-youtube-  
streaming.git . Create-react-app-blog is hosted on  
port 3000 via npm start.

dashboard.seneca.com successful deploys have this in common:  
· npm install · npm start · yarn · npm run start-dev, community.seneca.com/t/web-service-deployment-failed/3594. serve command not found bash:

StackOverflow.com/questions/55529917 tools: try yarn serve -s build. \* npm uninstall -g serve or npm i -S serve  
\* yarn global add serve

There's also yarn versus npm & npm start, npm run start-dev, npm install. And DATABASE\_URL?ssl=true.  
gooley-frontend: Currently, github.com/gaelishel/gooley-frontend is on commit 16e12d6 sweetalert2 instead of sweetalert March 23, 2022, 12:38 AM EDT.  
try git push edits master