目录

一 LINUX 平台下的基本命令 **2**

1 文件和目录操作 2

2 文件内容查看与处理命令 3

3 系统信息查看命令 5

4 权限相关命令 7

一 LINUX 平台下的基本命令

作业中要求使用 Linux 平台进行操作，我正好在阿里云租了一台 2 核 2g 的服务器，安装的系统是 Ubuntu 24.04。这个作业我将会使用 ssh 连接到我的服务器，并在服务器上进行操作。我使用 termius 这个工具来连接服务器。

我会分类别来操作一些基础命令。

1 文件和目录操作

1. 查看当前所在目录：`pwd`
2. 查看当前目录下的文件：`ls`
3. 以详细形式查看文件：`ls -l`
4. 查看隐藏文件：`ls -a`

```
root@iZbp11a51jwdv4pjbv2r1oZ:~# pwd
/root
root@iZbp11a51jwdv4pjbv2r1oZ:~# ls
alist  clashctl  clash-for-linux-install  derp  frp  n2n  rustDesk  snap
root@iZbp11a51jwdv4pjbv2r1oZ:~# ls -l
total 32
drwxr-xr-x  2 root root 4096 Feb  9 14:25 alist
drwxr-xr-x  7 root root 4096 Mar  2 17:35 clashctl
drwxr-xr-x  6 root root 4096 Mar  2 17:35 clash-for-linux-install
drwxr-xr-x  2 root root 4096 Mar  9 19:47 derp
drwxr-xr-x  3 root root 4096 Feb 21 12:31 frp
drwxr-xr-x 17 root root 4096 Feb  9 22:49 n2n
drwxr-xr-x  3 root root 4096 Mar  2 21:18 rustDesk
drwx------  3 root root 4096 Mar 14 12:23 snap
root@iZbp11a51jwdv4pjbv2r1oZ:~#  ls -a
.      .bash_history  clashctl                derp      .local  .profile          snap  .viminfo
..     .bashrc        clash-for-linux-install frp       n2n     .pydistutils.cfg  .ssh  .wget-hsts
alist  .cache         .config                 .lesshst  .pip    rustDesk          .vim
```

图 1 命令 1.1-1.4

5. 创建一个目录
6. 进入目录
7. 创建空文件
8. 向文件写入内容
9. 查看文件内容
10. 复制文件

```
root@iZbp11a51jwdv4pjbv2r1oZ:~# mkdir linux_test
root@iZbp11a51jwdv4pjbv2r1oZ:~# cd linux_test
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# touch file1.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# ehco "hello, linux" > file1.txt
Command 'ehco' not found, did you mean:
  command 'ehlo' from snap ehlo (0.0.83)
  command 'echo' from deb coreutils (9.4-3ubuntu6.2)
See 'snap info <snapname>' for additional versions.
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# echo "hello, linux" > file1.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# cat file1.txt
hello, linux
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# cp file1.txt file2.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# cat file2.txt
hello, linux
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test#
```

图 2 命令 1.5-1.10

11. 重命名文件
12. 删除文件
13. 返回上一级目录
14. 删除目录

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# mv file1.txt  newfile.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# ls
file2.txt  newfile.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# rm newfile.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# ls
file2.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_test# cd ..
root@iZbp11a51jwdv4pjbv2r1oZ:~# ls
alist  clashctl  clash-for-linux-install  derp  frp  linux_test  n2n  rustDesk  snap
root@iZbp11a51jwdv4pjbv2r1oZ:~# rm -r linux_test/
root@iZbp11a51jwdv4pjbv2r1oZ:~# ls
alist  clashctl  clash-for-linux-install  derp  frp  n2n  rustDesk  snap
root@iZbp11a51jwdv4pjbv2r1oZ:~#
```

图 3 命令 1.11-1.14

2 文件内容查看与处理命令

我先使用如下命令创建了一个测试文件夹，然后测试命令

```
mkdir linux_homework
cd linux_homework\
echo -e "apple\nbanana\napple\norange\nbanana\nlinux\ncommand\npipe" > words.txt
```

1. 查看完整内容

```
root@iZbp11a51jwdv4pjbv2r1oZ:~# mkdir linux_homework
root@iZbp11a51jwdv4pjbv2r1oZ:~# ls
alist  clashctl  clash-for-linux-install  derp  frp  linux_homework  n2n  rustDesk  snap
root@iZbp11a51jwdv4pjbv2r1oZ:~# cd linux_homework/
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# echo -e "apple\nbanana\napple\norange\nbanana\nlinux\nco
mmand\npipe" > words.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# ls
words.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# cat words.txt
apple
banana
apple
orange
banana
linux
command
pipe
```

图 4 命令 2.1

2. 查看文件前几行
3. 查看文件后几行
4. 统计文件行数、单词数、字符数
5. 统计文件行数

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# head -n 3 words.txt
apple
banana
apple
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# tail -n 3 words.txt
linux
command
pipe
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# wc words.txt
 8  8 52 words.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# wc -l words.txt
8 words.txt
```

图 5 命令 2.2-2.5

6. 对文件内容排序
7. 去除相邻重复行
8. 查找包含 apple 的行
9. 查找包含 banana 的行，并显示行号

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# sort words.txt
apple
apple
banana
banana
command
linux
orange
pipe
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# uniq words.txt
apple
banana
apple
orange
banana
linux
command
pipe
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# grep "apple" words.txt
apple
apple
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# grep -n "banana" words.txt
2:banana
5:banana
```

图 6 命令 2.6-2.9

3 系统信息查看命令

1. 查看系统内核和系统信息
2. 查看当前用户名
3. 查看当前日期时间
4. 显示日历

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# uname -a
Linux iZbp11a51jwdv4pjbv2r1oZ 6.8.0-90-generic #91-Ubuntu SMP PREEMPT_DYNAMIC Tue Nov 18 14:14:30 UTC 2
025 x86_64 x86_64 x86_64 GNU/Linux
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# whoami
root
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# date
Sat Apr 25 03:57:12 PM CST 2026
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# cal
     April 2026
Su Mo Tu We Th Fr Sa
          1  2  3  4
 5  6  7  8  9 10 11
12 13 14 15 16 17 18
19 20 21 22 23 24 25
26 27 28 29 30
```

图 7 命令 3.1-3.4

其中第四个命令需要先安装 ncal，我使用 `sudo apt install ncal` 安装之后就可以正常使用了。

5. 查看磁盘空间
6. 查看内存使用情况

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# df -h
Filesystem      Size  Used Avail Use% Mounted on
tmpfs           162M  1.5M  160M   1% /run
efivarfs        256K  7.4K  244K   3% /sys/firmware/efi/efivars
/dev/vda3        40G  5.8G   32G  16% /
tmpfs           807M     0  807M   0% /dev/shm
tmpfs           5.0M     0  5.0M   0% /run/lock
/dev/vda2       197M  6.2M  191M   4% /boot/efi
overlay          40G  5.8G   32G  16% /var/lib/docker/rootfs/overlayfs/f6fdeb7a0935974bbc5df63262aeeeb1
eab665b7deb467c5473618aaa7edeb16
overlay          40G  5.8G   32G  16% /var/lib/docker/rootfs/overlayfs/237c5d820903ac7889c5633f264a81a5
cfbd5beb6d68c2e52780dcf004e0fbc2
overlay          40G  5.8G   32G  16% /var/lib/docker/rootfs/overlayfs/8b23e10ea750512823dc7b98534178b2
485c5248054f51408fb1b2651dcba3a4
overlay          40G  5.8G   32G  16% /var/lib/docker/rootfs/overlayfs/27db7f8296651a194aea4a077a1dfe1e
2ca5ca9a74782f6885fae7792df73f73
tmpfs           162M   12K  162M   1% /run/user/0
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# free -h
               total        used        free      shared  buff/cache   available
Mem:           1.6Gi       664Mi       226Mi       3.3Mi       889Mi       948Mi
Swap:             0B          0B          0B
```

图 8 命令 3.5-3.6

7. 查看系统进程和资源占用

```
Myserver
top - 16:00:00 up 75 days, 23:44,  2 users,  load average: 0.01, 0.02, 0.00
Tasks: 141 total,   1 running, 140 sleeping,   0 stopped,   0 zombie
%Cpu(s):  0.0 us,  4.8 sy,  0.0 ni, 95.2 id,  0.0 wa,  0.0 hi,  0.0 si,  0.0 st
MiB Mem :   1613.0 total,    207.5 free,    688.7 used,    884.0 buff/cache
MiB Swap:      0.0 total,      0.0 free,      0.0 used.    924.3 avail Mem

    PID USER      PR  NI    VIRT    RES    SHR S  %CPU  %MEM     TIME+ COMMAND
      1 root      20   0   22940  13056   8576 S   0.0   0.8  15:38.32 systemd
      2 root      20   0       0      0      0 S   0.0   0.0   0:01.70 kthreadd
      3 root      20   0       0      0      0 S   0.0   0.0   0:00.00 pool_workqueue_release
      4 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-rcu_g
      5 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-rcu_p
      6 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-slub_
      7 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-netns
      9 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/0:0H-events_highpri
     12 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-mm_pe
     13 root      20   0       0      0      0 I   0.0   0.0   0:00.00 rcu_tasks_kthread
     14 root      20   0       0      0      0 I   0.0   0.0   0:00.00 rcu_tasks_rude_kthread
     15 root      20   0       0      0      0 I   0.0   0.0   0:00.00 rcu_tasks_trace_kthread
     16 root      20   0       0      0      0 S   0.0   0.0   0:27.08 ksoftirqd/0
     17 root      20   0       0      0      0 I   0.0   0.0   3:25.52 rcu_preempt
     18 root      rt   0       0      0      0 S   0.0   0.0   0:18.02 migration/0
     19 root     -51   0       0      0      0 S   0.0   0.0   0:00.00 idle_inject/0
     20 root      20   0       0      0      0 S   0.0   0.0   0:00.00 cpuhp/0
     21 root      20   0       0      0      0 S   0.0   0.0   0:00.00 cpuhp/1
     22 root     -51   0       0      0      0 S   0.0   0.0   0:00.00 idle_inject/1
     23 root      rt   0       0      0      0 S   0.0   0.0   0:16.23 migration/1
     24 root      20   0       0      0      0 S   0.0   0.0   0:21.53 ksoftirqd/1
     26 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/1:0H-events_highpri
```

图 9 命令 3.7

8. 查看当前系统进程

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# ps aux
USER         PID %CPU %MEM    VSZ   RSS TTY      STAT START   TIME COMMAND
root           1  0.0  0.7  22940 13056 ?        Ss   Feb08  15:38 /usr/lib/systemd/systemd --system --
root           2  0.0  0.0      0     0 ?        S    Feb08   0:01 [kthreadd]
root           3  0.0  0.0      0     0 ?        S    Feb08   0:00 [pool_workqueue_release]
root           4  0.0  0.0      0     0 ?        I<   Feb08   0:00 [kworker/R-rcu_g]
root           5  0.0  0.0      0     0 ?        I<   Feb08   0:00 [kworker/R-rcu_p]
root           6  0.0  0.0      0     0 ?        I<   Feb08   0:00 [kworker/R-slub_]
root           7  0.0  0.0      0     0 ?        I<   Feb08   0:00 [kworker/R-netns]
root           9  0.0  0.0      0     0 ?        I<   Feb08   0:00 [kworker/0:0H-events_highpri]
root          12  0.0  0.0      0     0 ?        I<   Feb08   0:00 [kworker/R-mm_pe]
root          13  0.0  0.0      0     0 ?        I    Feb08   0:00 [rcu_tasks_kthread]
root          14  0.0  0.0      0     0 ?        I    Feb08   0:00 [rcu_tasks_rude_kthread]
root          15  0.0  0.0      0     0 ?        I    Feb08   0:00 [rcu_tasks_trace_kthread]
root          16  0.0  0.0      0     0 ?        S    Feb08   0:27 [ksoftirqd/0]
root          17  0.0  0.0      0     0 ?        I    Feb08   3:25 [rcu_preempt]
root          18  0.0  0.0      0     0 ?        S    Feb08   0:18 [migration/0]
root          19  0.0  0.0      0     0 ?        S    Feb08   0:00 [idle_inject/0]
root          20  0.0  0.0      0     0 ?        S    Feb08   0:00 [cpuhp/0]
root          21  0.0  0.0      0     0 ?        S    Feb08   0:00 [cpuhp/1]
root          22  0.0  0.0      0     0 ?        S    Feb08   0:00 [idle_inject/1]
root          23  0.0  0.0      0     0 ?        S    Feb08   0:16 [migration/1]
root          24  0.0  0.0      0     0 ?        S    Feb08   0:21 [ksoftirqd/1]
root          26  0.0  0.0      0     0 ?        I<   Feb08   0:00 [kworker/1:0H-events_highpri]
root          27  0.0  0.0      0     0 ?        S    Feb08   0:00 [kdevtmpfs]
root          28  0.0  0.0      0     0 ?        I<   Feb08   0:00 [kworker/R-inet_]
root          29  0.0  0.0      0     0 ?        S    Feb08   0:02 [kauditd]
root          31  0.0  0.0      0     0 ?        S    Feb08   0:04 [khungtaskd]
root          33  0.0  0.0      0     0 ?        S    Feb08   0:00 [oom_reaper]
```

图 10 命令 3.8

由于使用的是我的服务器，所以系统进程比较多。没有全部截下来。

9. 查看历史命令

```
 801  uname -a
 802  whoami
 803  date
 804  cal
 805  apt install ncal
 806  cal
 807  clear
 808  uname -a
 809  whoami
 810  date
 811  cal
 812  clea
 813  clear
 814  df -h
 815  top
 816  df -h
 817  clear
 818  df -h
 819  clear
 820  top
 821  clear
 822  free -h
 823  df -h
 824  free -h
 825  clear
 826  ps aux
 827  clear
 828  history
```

图 11 命令 3.9

历史记录中包含了我之前使用过的命令，包括一些测试命令和安装命令等。这里只截了本次课程展示的几个历史命令。

4 权限相关命令

1. 创建脚本文件

2. 查看文件权限
3. 给文件添加可执行权限
4. 再次查看权限变化
5. 查看文件详细状态信息

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# touch test.sh
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# ls -l test.sh
-rw-r--r-- 1 root root 0 Apr 25 16:07 test.sh
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# chmod +x test.sh
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# ls -l test.sh
-rwxr-xr-x 1 root root 0 Apr 25 16:07 test.sh
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# stat test.sh
  File: test.sh
  Size: 0               Blocks: 0          IO Block: 4096   regular empty file
Device: 253,3   Inode: 1179125     Links: 1
Access: (0755/-rwxr-xr-x)  Uid: (    0/    root)   Gid: (    0/    root)
Access: 2026-04-25 16:07:12.238643435 +0800
Modify: 2026-04-25 16:07:12.238643435 +0800
Change: 2026-04-25 16:07:26.812080642 +0800
 Birth: 2026-04-25 16:07:12.238643435 +0800
```

图 12 命令 4.1-4.5

5 管道符组合命令

1. 把文件内容传给 sort 排序后去重

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# cat words.txt | sort | uniq
apple
banana
command
linux
orange
pipe
```

图 13 命令 5.1

2. 统计每个单词出现次数

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# cat words.txt | sort | uniq -c
      2 apple
      2 banana
      1 command
      1 linux
      1 orange
      1 pipe
```

图 14 命令 5.2

3. 找出包含字母 a 的行，并排序

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# cat words.txt | grep "a" | sort
apple
apple
banana
banana
command
orange
```

图 15 命令 5.3

4. 在当前目录中筛选.txt 文件
5. 在进程列表中查找 bash 相关进程
6. 查看最近使用的命令

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# ls -l | grep ".txt"
-rw-r--r-- 1 root root 52 Apr 25 15:47 words.txt
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# ps aux | grep bash
root      219565  0.0  0.0   2616   128 ?        Ss   Mar09   0:00 /bin/sh -c bash /app/build_cert.sh $
DERP_HOST $DERP_CERTS /app/san.conf &&     /app/derper --hostname=$DERP_HOST     --certmode=manual
--certdir=$DERP_CERTS     --stun=$DERP_STUN      --a=$DERP_ADDR     --http-port=$DERP_HTTP_PORT     --v
erify-clients=$DERP_VERIFY_CLIENTS
root      243312  0.0  0.2   9052  4480 tty1     S+   Mar14   0:00 -bash
root      568015  0.0  0.3   9300  6016 pts/0    Ss   15:46   0:00 -bash
root      568468  0.0  0.1   6544  2304 pts/0    S+   16:12   0:00 grep --color=auto bash
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# history | tail
  833  ls -l test.sh
  834  stat test.sh
  835  cat words.txt | sort
  836  cat words.txt | sort | uniq
  837  cat words.txt | sort | uniq -c
  838  cat words.txt | uniq -c
  839  cat words.txt | grep "a" | sort
  840  ls -l | grep ".txt"
  841  ps aux | grep bash
  842  history | tail
```

图 16 命令 5.4-5.6

7. 筛选磁盘挂载信息

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# df -h | grep "/"
tmpfs           162M  1.5M  160M   1% /run
efivarfs        256K  7.4K  244K   3% /sys/firmware/efi/efivars
/dev/vda3        40G  5.8G   32G  16% /
tmpfs           807M     0  807M   0% /dev/shm
tmpfs           5.0M     0  5.0M   0% /run/lock
/dev/vda2       197M  6.2M  191M   4% /boot/efi
overlay          40G  5.8G   32G  16% /var/lib/docker/rootfs/overlayfs/f6fdeb7a0935974bbc5df63262aeeeb1
eab665b7deb467c5473618aaa7edeb16
overlay          40G  5.8G   32G  16% /var/lib/docker/rootfs/overlayfs/237c5d820903ac7889c5633f264a81a5
cfbd5beb6d68c2e52780dcf004e0fbc2
overlay          40G  5.8G   32G  16% /var/lib/docker/rootfs/overlayfs/8b23e10ea750512823dc7b98534178b2
485c5248054f51408fb1b2651dcba3a4
overlay          40G  5.8G   32G  16% /var/lib/docker/rootfs/overlayfs/27db7f8296651a194aea4a077a1dfe1e
2ca5ca9a74782f6885fae7792df73f73
tmpfs           162M   12K  162M   1% /run/user/0
```

图 17 命令 5.7

8. 统计文件行数
9. 统计单词出现次数，并按出现次数从高到低排序

```
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# cat words.txt | wc -l
8
root@iZbp11a51jwdv4pjbv2r1oZ:~/linux_homework# cat words.txt | sort | uniq -c | sort -nr
      2 banana
      2 apple
      1 pipe
      1 orange
      1 linux
      1 command
```

图 18 命令 5.8-5.9