Introduction to Yocto

Advanced Embedded Linux Development

with **Dan Walkes**



Learning objectives:

Introduce the BitBake tool
Introduce the Poky distribution
Yocto layer model
Yocto terminology



What is Yocto?

- Way to roll your own Linux Distribution for embedded devices
 - Not just root filesystem
 - Includes redistributable packages for each piece of software
- Launched in 2011
- Includes embedded build tools and an Embedded Distribution Poky (sounds like hockey)



What is Yocto?

- Build system is licensed MIT
- Uses text file configuration and "bitbake" tool based on Python/Bash
- Builds most everything from source, including all build tools
 - Used to support binary reproducibility



Setting up the Yocto Environment

- Basic steps at <u>https://docs.yoctoproject.org/brief-yoctoprojectq</u> s/index.html
 - Clone the "poky" project a submodule in your repository
 - Use branch specified in assignment
 - git add/git commit with the submodule at the correct branch before running build.sh
 - source poky/oe-init-build-env
 - bitbake core-image-minimal
 - Work on something else for a few hours!




Setting up the Yocto Environment

- source poky/oe-init-build-env
 - Uses the source command (synonym for .)
- source <filename>
 - Any variables created or modified by the script
 <filename> will remain available after the script exits
 - Runs in the same subshell (whereas ./filename runs in a new shell)
- What does this mean?
 - poky/oe-init-build-env sets up environment variables for our current terminal session



Poky Build Directory

- A "build" directory at the root folder is created for you with the first "source poky/oe-init-build-env" step
- This is where all build output and log files will be generated





Yocto Terminology

- Builds are performed by the bitbake utility
- How do you bake bits?
 - Recipes are used to bake bits!
- Recipes are a set of instructions processed by the build engine.
- Recipes are defined in .bb and .inc text files



Yocto Terminology

- Recipes are defined in .bb and .inc text files
- .bb typically contains source and version information
- .inc contains build and deploy instructions, may contain python or bash fragments



Yocto Terminology

- Packages contain binary artifacts from the build
- Images are build outputs
 - Binary root filesystem image
 - Linux kernel image
 - u-boot or grub bootloader image



Yocto Layer Model

- Designed to support both collaboration and customization.
- Collection of directories on the filesystem virtually "layered" to make an equivalent build hierarchy

meta-aesd/recipes-aesd-assignments/images/core-image-aesd.bb meta-aesd/recipes-aesd-assignments/aesd-assignments/aesd-assignments_git.bb meta-aesd/recipes-core/busybox/busybox.bbappend

meta-oe/recipes-core/busybox/busybox.inc meta-oe/recipes-core/images/core-image-base.bb



recipes-aesd-assignments/images/core-image-aesd.bb recipes-aesd-assignments/aesd-assignments_get.bb recipes-core/busybox/busybox.inc recipes-core/busybox/busybox.bbappend recipes-core/images/core-image-base.bb

Çi

Yocto Layers

- Organized in a way to override or add to recipes
 - Might make the build work a slightly different way
 - Apply a patch for a specific version of hardware
 - Configure for a GUI vs terminal only
- Might add support for new recipes
 - In our case aesd-assignments
- Might add support for new images
 - In our case core-image-aesd



Adding a Yocto Layer

- source poky/oe-init-build-env
- bitbake-layers create-layer ../../meta-aesd
- bitbake-layers add-layer ../../meta-aesd
 - Already done for your starter repo
 - See meta-aesd/conf/layer.conf and

./build.sh



Adding a Custom Image

- Add core-image-aesd.bb with single line "inherit core-image"
- Pulls a core set of packages (like busybox) into our build.



Ç

Yocto MACHINE

- •How did we specify the target architecture in buildroot?
 - Specified in our defconfig file

```
DEFAULT_DEFCONFIG=configs/qemu_aarch64_virt_defconfig
```

```
echo "Using default defconfig ${DEFAULT_DEFCONFIG}"

make -C ${BUILDROOT} defconfig BR2_DEFCONFIG=${DEFAULT_DEFCONFIG} BR2_EXTERNAL=${EXTERNAL_REL_BUILDROOT}
```

Yocto uses a MACHINE variable in build/conf/local.conf

The list of machines supported by the Yocto Project as shipped include the following:

```
MACHINE ?= "qemuarm"
MACHINE ?= "qemuarm64"
MACHINE ?= "qemumips"
MACHINE ?= "qemumips64"
MACHINE ?= "qemuppc"
MACHINE ?= "qemux86"
MACHINE ?= "qemux86-64"
MACHINE ?= "genericx86-64"
MACHINE ?= "genericx86-64"
MACHINE ?= "beaglebone"
MACHINE ?= "mpc8315e-rdb"
MACHINE ?= "mgc8315e-rdb"
MACHINE ?= "edgerouter"
```