
Design layer

the whole layer, as one document

Contents

1 Durable jobs	4
1.1 Foundation	4
1.2 Pending updates	5
1.3 System at a glance	5
1.4 Whole model	7
1.5 Worker definitions and codecs	10
1.6 Admission and uniqueness	11
1.6.1 Conservative uniqueness profile	11
1.6.2 Caller-owned business transaction	12
1.7 Storage and migrations	12
1.8 Attempts and acknowledgements	13
1.9 Cancellation and operator recovery	15
1.10 Runtime capacity and deadlines	16
1.11 Reads, administration and retention	17
1.12 Observations	18
1.13 Verification and retained extensions	18
1.13.1 Complete capability inventory	19
Glossary	20

ROOT DESIGN

Durable jobs

1 Durable jobs

1.1 Foundation

Grind admits typed work durably and fences each execution attempt. Applications own the meaning and safety of external effects.

GOAL

Admit typed work without executing it

An application defines a **Worker**, starts one runtime, and submits a **Job** with immediate or delayed availability. The durable receipt and typed handle support later recovery.

GOAL

Preserve uncertainty across process and database failures

Lost replies require reconciliation against durable commands. Expired ownership cannot acknowledge work. Safe delivery after an unknown effect requires an explicit application replay policy or an operator decision.

GOAL

Retain the full job-system scope

Ordinary queues, uniqueness, retries, schedules, administration, observations and testing compose independently. Broader queue controls, dependency workflows, batches and other retained capabilities remain specified below with explicit gaps.

NO-GOAL

Guarantee exactly-once external effects

PostgreSQL transitions are atomic. An external payment, message or HTTP call is outside that transaction unless the application supplies its own durable protocol.

NO-GOAL

Own application authentication or compensation

Operator attribution is evidence, not authorization. Saga owns typed workflow progress and compensation; a Grind job invoking a local Saga does not make each Saga step durable.

INVARIANT

Admission and execution are separate

Input and key encoding precede storage. Admission never invokes the handler. Exact deployed worker and codec versions are required to execute stored input.

mechanism

INVARIANT

A retry counter never grants ownership

All execution writes require the complete **Attempt fence**. Refunding an **Attempt ordinal** does not restore an expired epoch.

mechanism

INVARIANT

Runtime failure never invents a business error

Typed errors retain their codec or remain explicitly unrecorded. Operational failure, contract mismatch and uncertainty have separate representations.

mechanism

PRINCIPLE

Use durable rows as authority

An event, a returned handler value, or an elapsed timeout cannot establish a committed job outcome. Recovery reads the matching durable receipt or current job.

PRINCIPLE

Make resource ownership explicit

Grind owns its supervised processes, main pool lifetime and reserved renewal pools. Applications may borrow the main pool and own outer business transactions.

- Scope and oracle boundaries are recorded in [ADR-0001](#). Historical changes and their provenance are recorded in [ADR-0011](#).

1.2 Pending updates

ruling Define a hard bound for queued storage checkout

The absolute deadline is calculated before pgo checkout, but the pinned pool does not arm a receive timeout while queued. Pool overload shedding or connection transfer ends that wait. Decide whether the public deadline must include a hard queue-wait bound.

[ADR-0008](#)

build Complete retained queue and schedule capabilities

Priority, live controls, cluster/rate/partition limits, recurring schedules, notification infrastructure, plugin contracts and richer administration need executable contracts and implementations. Local concurrency and delayed admission implement narrower behavior.

[ADR-0001](#)

build Complete dependency workflows, batches and chunks

Durable dependency edges, named step results, batch callbacks and homogeneous chunk dispatch retain separate contracts. They must preserve admission ambiguity, attempt fencing and per-item outcomes without importing Saga compensation into the queue core.

[ADR-0010](#)

build Extend uniqueness beyond the conservative profile

Cross-worker matching, arbitrary state sets, broader replacement, backfill and bulk uniqueness need concrete equality, locking and reconciliation contracts. Ordinary bulk insertion cannot imply unique admission parity.

[ADR-0003](#)

verify Establish fresh qualification for the chosen release

Retained benchmark and resilience summaries describe historical source and dependencies. A new qualification must record source, dependencies, hardware, budgets, validity verdicts and failed runs; existing scenario coverage does not prove unconditional liveness or full Oban/Pro parity.

[ADR-0009](#)


ruling Decide fallback installation identity strength

When either endpoint lacks a PostgreSQL cluster identifier, binding compares only database OID and schema. Distinct clusters may collide and compatibility is nontransitive. A stricter identity or constrained deployment contract needs an explicit decision.

[ADR-0008](#)

1.3 System at a glance

One Durable jobs context owns admission, persisted outcomes, attempt authority and queue runtime.




LEGEND



Dependency arrows do not confer authorization or shared transaction ownership.

- The runtime targets Erlang/OTP. Direct ecosystem dependency is Sinal. Standard Gleam JSON supplies ordinary codecs; schema-aware conversion is an application choice.
- The main pool is configured by the caller's `pog.Config`. Each used queue adds one consumer, a renewer and a reserved one-connection renewal pool. Pruning is optional; processing can be disabled while admission and reads remain available.



LEGEND



The coordinator keeps capacity occupied until an attempt and its acknowledgement settle. Renewal has an independent actor and pool.

- Local units are Worker definitions, Admission and uniqueness, Storage and migrations, Attempts and acknowledgements, Cancellation and recovery, Runtime capacity, Reads and retention, Observations, and Verification and extensions.

1.4 Whole model

Persistent job identity, command identity and execution authority have different lifetimes.

Job state

<code>queued</code> Ready ordinary work.	<code>scheduled</code> Delayed work awaiting availability.	<code>retryable</code> Observed failure scheduled for another attempt.
<code>executing</code> Owned by a live attempt fence.	<code>succeeded</code> Committed typed output.	
<code>business_failed</code> Terminal business failure or scheduling budget exhaustion.	<code>runtime_failed</code> Terminal operational failure.	
<code>contract_mismatch</code> Stored/deployed contract refused.	<code>uncertain</code> Effect outcome requires investigation; nonterminal.	
<code>discarded</code> Explicitly discarded with reason.	<code>cancelled</code> Committed cancellation; not proof of absent effects.	

Job `entity` `stateful` `Durable jobs` `owned by Durable jobs`

Retained record of a submitted versioned worker contract.

ATTRIBUTES


`derived` **Identity** · Installation × Int
Database-generated job ID is installation-local and never substitutes for a submission key.

- authored** **Worker contract** · Worker ID × worker version × codec versions
Input/output and optional error versions are checked at execution and read attachment.
- authored** **Scheduling** · Queue × availability × limits
Relative availability is resolved by PostgreSQL. Attempts, snoozes and replays have separate counters.
- derived** **State** · Job state [job-state](#) · [job-lifecycle](#)
Only committed storage commands change lifecycle state.
- derived** **Execution evidence** · Optional attempt fence / cancellation / uncertainty
Uncertain retains effect evidence and ownership evidence. Cancellation intent remains independent until attributed terminal resolution settles the job.
- derived** **Outcome and retention** · Optional encoded output/error/reason/cause/finished time
finished_at exists for six terminal states and never for Uncertain.

RELATIONSHIPS

- 1 : 0..n** Admission, acknowledgement and operator-resolution receipts refer to the job and cascade when it is pruned.

STATE MACHINE



- Immediate admission chooses Queued; delayed admission chooses Scheduled. The single diagram initial node represents ordinary admission. Eligibility also requires queue, exact worker version, due database time, remaining budget and current row locks; an arrow alone grants no execution authority.

Admission receipt

entity

immutable

Durable jobs

owned by Admission

Original command decision retained independently of later job state.

ATTRIBUTES

authored

Identity · Installation × submission key
All submissions retain a supplied or generated identity.

derived

Fingerprint · SHA256 prepared command
Plain and unique commands use different domain tags. Exact encoded input, worker/codecs, queue, limit, schedule and uniqueness action participate; correlation and maximum replay count do not.

derived

Decision · Inserted | Existing | Rescheduled
Original job, actual conflict queue/state and decision time survive matching-window and job-state changes.

Attempt fence

value-object

immutable

Durable jobs

owned by Attempt execution

Authority to write one executing attempt.

ATTRIBUTES

derived

Identity · Job ID × attempt ID × epoch × owner
Attempt ID and epoch distinguish claims even when the retry ordinal repeats. Owner includes runtime incarnation.

derived

Validity · Executing state × live database lease × contract match
Exact lease expiry is invalid. Renewing the same owner changes lease expiry without changing the authority identity.

Uniqueness policy

value-object

immutable

Durable jobs

owned by Admission

Typed candidate selection and conservative conflict action.

ATTRIBUTES

authored

Key and scope · Full input | selected key; WithinQueue | AcrossQueues
Selected keys retain a nonempty name/version and typed encoder. Worker identity/version always participate.

authored

Period · Within(positive duration, origin) | WhileRetained
Origin is insertion or schedule; supported millisecond bounds are checked by the constructor.

authored

Eligible states · Incomplete | ScheduledOnly | IncompleteOrSucceeded | AllRetained
These profiles filter current rows without changing key identity.

authored

Action · KeepExisting | RescheduleTo(timestamp)
Only a scheduled candidate may change availability. Input, worker/version and identity remain unchanged.

Refinement	Validation owner	Failure contract
Worker/codecs/queue identity and positive source limits	Source-owned builders	Panic at definition time; no deployment starts
Runtime schema, deadlines, used queue tuning, duplicate workers	Config.check and start	Typed configuration error before resources start
Encoded input/key and payload byte limit	Preparation	InvalidInput before checkout or writes

Refinement	Validation owner	Failure contract
Output/error codec acceptance and byte limit	After handler returns	Terminal runtime failure; no synthetic business error
Nonempty resolution identity/by/details	Operator command construction	Rejected attribution/command before resolution
List limit and quarantine/prune batch	Administration	Positive bounded page/batch; maximum ten thousand

Axis	Owner and identity	What it proves
Submission	Caller/generated key and exact command	One admission decision, while receipt remains
Uniqueness	Worker/key contract and incoming eligibility	An equivalent retained candidate was selected
Execution	Attempt fence and database time	Authority for a current storage write
Acknowledgement	Command ID and exact proposal/fence	The actual committed disposition
Resolution	Resolution ID, decision and attribution	An operator command was applied
Correlation	Application tracing value	No authority or idempotency guarantee

- The typed JobHandle retains installation, queue, worker contract and output/error codecs. A Conflict includes its real route and compatible handle. PendingSubmission retains the prepared fingerprint; it is not a handle proving admission.

1.5 Worker definitions and codecs

Typed application values cross storage through explicit versioned JSON contracts.

Worker definition

responsibility

Retain typed handlers and all policies needed to interpret stored input.

interface

worker.new wraps Result; worker.responding receives Context and returns Response. Builders select queue, version, codecs, attempts, timeout, snoozes, retry and abandonment.

interactions

Configuration erases heterogeneous workers through retained typed closures. Storage and reads check declared versions before decoding.

invariants

Duplicate worker ID/version is rejected across the runtime. Multiple versions may coexist; there is no fallback. Source-owned invalid constructors panic; runtime Config.check returns typed validation errors.

failure

Invalid input/key encoding refuses admission before storage. Stored contract mismatch prevents handler execution. Output/error refusal after effects becomes terminal RuntimeFailed, with no retry.

Response	Scheduling/accounting	Outcome ownership
Succeeded(output)	Terminal; output encoded once	Output codec refusal is operational failure
Failed(error)	Retry only below limit and when policy permits	Optional error codec preserves typed error; otherwise explicitly unrecorded
Snoozed(delay, reason)	Refund attempt; increment separate snooze count	Snooze exhaustion is business failure with cause
Discarded / Cancelled	Terminal reason	Does not prove earlier effects absent
Uncertain(evidence)	Bypasses retry policy	Operator recovery or explicit replay safety required

- Defaults: queue default; worker/codecs version 1; maximum attempts 20; timeout 15 minutes; maximum snoozes 100; HoldUncertain. Retry uses 15-second exponential delay capped at one day with up to ten percent jitter. Delays are clamped to supported nonnegative bounds.

- Context retains job/attempt/queue, correlation, attempts/snoozes, optional main-pool connection and a handler-owned cooperative cancellation selector. A forged local testing context grants no storage authority.

BEHAVIOR

An encoding failure follows an executed effect

Given The handler returned a value after executing application code.

When The output or configured error encoder rejects it or exceeds the payload limit.

Then The acknowledgement proposes `RuntimeFailed` and does not request another attempt. The failure does not undo effects.

level: boundary area: Worker outcomes

- The default payload bound is one MiB. No codec version string proves equivalent implementations; applications change versions and retain compatible deployed code. See [ADR-0002](#), [worker contracts](#) and [external codec consumer](#).

1.6 Admission and uniqueness

One atomic admission command combines receipt lookup, candidate selection and any permitted mutation.

Admission

responsibility

Prepare exact typed input and durably choose `Inserted`, `Existing` or `Rescheduled`.

interface

`job.new` and setters; `grind.submit`; `submit_in`; `reconcile_submission`; `Admission` and `SubmitError`.

interactions

Prepares input/key before checkout; PostgreSQL locks the receipt/domain and candidate rows; typed handles retain the selected actual route.

invariants

All submissions have receipt identities. Matching receipt is checked before a new decision. Same identity/different fingerprint is `IdConflict`. Admission never runs the handler.

failure

`InvalidInput` and known pre-commit refusal differ from `CommitUnknown`. An absent receipt during reconciliation remains unknown; it is not proof that the original transaction cannot still commit.

- `with_id` supplies a submission key, not the durable integer job ID. Retrying ordinary `job.new` without preserving a key creates another command. A `PendingSubmission` is the preferred retained recovery token after `CommitUnknown`.
- after resolves its duration against database time at admission. `at` retains an absolute timestamp, with past values made immediately eligible. Correlation and replay policy are retained on insertion but excluded from receipt equality; changing either under an existing key returns the original decision.

BEHAVIOR

A lost admission reply is reconciled

Given A prepared command returned `CommitUnknown` and its original `PendingSubmission` remains available.

When Reconciliation finds its matching durable receipt.

Then It returns the original admission decision without rerunning uniqueness or executing work. A conflicting receipt returns `IdConflict`; missing receipt remains unknown.

level: boundary area: Admission

1.6.1 Conservative uniqueness profile

- `full_input` uses input JSON and its codec version. `selected` uses a named key, key codec version and typed projection. Jobs without matching retained key material do not participate; arbitrary ordinary rows cannot be reconstructed from a new projection closure.

- Equality hashes PostgreSQL jsonb text: object order is normalized; repeated fields use PostgreSQL last-wins semantics; array order matters; exponent notation normalizes; 1 and 1.0 remain distinct. This differs from exact prepared-request byte equality and from Oban Basic containment.
- Worker ID/version always scope the domain. WithinQueue is default; AcrossQueues stays inside the installation. Defaults are Incomplete states and KeepExisting. Incomplete includes Uncertain; other profiles are ScheduledOnly, IncompleteOrSucceeded and AllRetained.
- within uses a positive bounded duration from insertion or scheduled time with an inclusive cutoff. while_retained has no time cutoff; pruning ends participation. Incoming period and state filter are predicates, not extra namespaces.
- A transaction advisory lock hashes schema, worker ID/version, key contract and PostgreSQL key digest; queue is excluded, so same-key admission serializes even across queue-local policies; FOR KEY SHARE protects candidates against pruning. The default lock wait is two seconds and must clear the storage deadline by at least one second. Lock timeout is UniquenessContended, not Existing.
- Reschedule changes availability only on eligible scheduled work, preserving identity, payload and contract. Other states return Existing. Across-queue conflict handles retain the selected queue, not the submitting queue.

1.6.2 Caller-owned business transaction

- submit_in accepts a checked SingleConnection inside an open READ COMMITTED transaction for the same database. It issues no BEGIN or COMMIT, temporarily scopes search_path and lock_timeout, and restores them. A failed statement may abort the caller transaction.
- Its reply means staged admission, not commit. No lifecycle admitted event is emitted. The borrowed call inherits the outer transaction timeout rather than acquiring another Grind deadline. SERIALIZABLE and REPEATABLE READ are refused without weakening the caller transaction. Applications retaining those isolation levels may commit a business outbox and dispatch it separately under stable submission identity.
- After a lost outer COMMIT reply, reconciling an admission receipt proves that job admission occurred. An older matching receipt cannot prove that this retry's surrounding business writes committed. The application needs its own business-command reconciliation.
- Concrete authority and alternatives are recorded in [ADR-0003](#) and [ADR-0004](#). Executable consumers: [admission](#) and [concurrent uniqueness tests](#).

1.7 Storage and migrations

The adapter owns one exact schema and forward-only transactions. Unknown commit does not authorize blind repetition of effects.

PostgreSQL adapter

responsibility

Scope SQL to one installation, preserve physical schema contracts and distinguish known refusal from uncertain reply.

interface

grind.Config from pog.Config; start/migrate/connection; internal bounded checkout and generated or dynamic queries.

interactions

Main pool is shared with application queries. Borrowed admission uses caller transaction settings; migrations use independent step budgets.

invariants

Grind-owned transactions pin READ COMMITTED and restore application search_path. A failed cleanup retires the connection. The bounded wrapper runs its callback at most once and never retries its SQL body after stale-holder replacement.

failure

Unavailable pools, connection loss and uncertain COMMIT can deny a reliable reply. Deadline and cleanup cannot prove rollback. Installation binding is a misuse guard, not authentication.

- Client installation identity uses database OID, schema and optional pg_control_system cluster ID. Cluster comparison is enforced when both values exist; fallback OID/schema comparison has collision and nontransitivity limits. Schema identifiers are quoted and validated for PostgreSQL length and reserved/unsafe names.

- Existing schema lookup avoids demanding database CREATE permission from an installed role. Concurrent creation is rechecked. The original creation error is retained if that recheck fails.
- Current source migrations are versions 11–13. Version 11 is the baseline; 12 adds finished-time retention and dependent receipt lifecycle; 13 adds correlation and replay accounting, uncertainty indexing and snooze cause. The hand-maintained source list is authoritative. priv migrations mirror exact step SQL for Cigogne consumers.
- Each step takes a schema-keyed transaction advisory lock first, rereads markers, applies DDL, writes the marker and checks physical shape before COMMIT. Earlier committed steps survive a later failure. Unknown step reply can be safely rechecked/ rerun because lock and marker decide application.
- Shape validation rejects unsupported marker versions, wrong relations/columns/indexes/sequences/foreign keys, obsolete storage_owner and stray Grind-prefixed objects. It does not quietly adopt an Oban schema. Experimental version 10 needs an explicit reinstall; no automatic destructive reset is performed.
- Default migration budget is thirty seconds per step and lock wait two seconds. Large table work can exhaust it; default finalization and foreign-key validation acquire real locks. Operators quiesce/drain and budget migration rather than infer a zero-downtime guarantee.
- Static SQL is Squirrel generated; dynamic admission/ACK/resolution predicates remain hand-maintained. Regeneration replaces generated files as a whole. See [ADR-0007](#), [ADR-0008](#), [migration mirrors](#) and [operator procedure](#).

1.8 Attempts and acknowledgements

Each admitted execution obtains a new authority identity. A handler result becomes an outcome only after a fenced command commits.

Claim and attempt execution

responsibility

Claim due work, decode the exact deployed contract, run one handler, and retain its result until settlement.

interface

Internal claim, lease, attempt and acknowledgement commands; testing.drain for explicit manual processing.

interactions

The coordinator claims one slot at a time; a temporary actor owns the linked handler and retained ACK proposal; the renewer maintains live leases.

invariants

Every new write checks executing state, attempt ID, epoch, owner, codec contract and a live database-time lease. Same-owner renewal is not takeover. Handler invocation is not repeated by ACK recovery.

failure

Contract mismatch parks the row before handler execution. Child startup refusal before StartAttempt releases/refunds its exact claim. Handler/attempt death leaves lease-based recovery, not synthetic success or business failure.

Attempt actor phase ready Claim acquired; StartAttempt not yet received. running One linked handler is active.
waiting Handler result retained for ACK/reconciliation. finished Completion reported; actor has no further execution authority.

Attempt actor entity stateful Durable jobs owned by Attempt execution

Temporary local owner of one handler invocation and its acknowledgement proposal.


ATTRIBUTES

derived **Request** · ClaimedJob × runtime owner × coordinator/renewer
 Retains the attempt fence, deployment and local completion callbacks.

derived **Phase** · Attempt actor phase [attempt-phase](#) · [attempt-progress](#)
 Local phase does not replace the persistent job state.

derived Pending completion · Optional Execution × stable ACK command × retry count
Only one handler result is retained. Retry diagnostics count ACK attempts, not business attempts.

STATE MACHINE



- Actor death from linked handler failure is destruction of this local entity, not a committed transition to Finished. The durable job remains fenced until lease recovery. StopWorker destroys the actor from any phase; it does not create a Finished state or resolve storage. A successful first ACK can go directly from Running to Finished.
- Claims increment the attempt ordinal. Snooze refunds one attempt and increments snooze_count. Explicitly replay-safe expiry refunds and increments replay_count, bounded independently. Fresh attempt ID/epoch fence old processes even when the ordinal repeats.
- Due claims select the earliest available_at then job ID among exact deployed worker versions, using FOR NO KEY UPDATE SKIP LOCKED. This is a selection order, not a starvation/fairness guarantee. Each claim poll first quarantines at most one expired row in the queue, including versions absent from the deployed registry. Admin quarantine can cover unpolled queues in bounded batches. HoldUncertain preserves evidence; bounded ReplayAfterLeaseExpiry clears old ownership and queues work only without pending cancellation.
- The handler is linked to the attempt actor. Its finite timeout stops/unlinks it. HoldUncertain proposes uncertainty; explicit replay-safe policy stops renewal and lets lease expiry deliver again. Runtime failure alone is no proof of replay safety.

Acknowledgement recovery

responsibility

Commit one actual disposition and reconcile lost replies without reinvoking the handler.

interface

Stable command ID, exact proposal hash and durable ACK receipt; admin.reconcile_acknowledgement for manual recovery.

interactions

The attempt actor retries both known rollback and ambiguous ACK replies. The consumer keeps its slot occupied; reserved renewal covers running and pending attempts.

invariants

A matching receipt returns the original committed state/cause. Conflicting command/proposal is refused. Receipt lookup is allowed after expiry; a fresh write is not. Cancellation can change a proposed non-uncertain state before commit. An explicit Uncertain proposal preserves its evidence and cancellation intent.

failure

If no receipt is found and ownership has expired, ACK cannot commit. Lease recovery preserves uncertainty. Reconciliation lacks availability detail present only in a fresh UPDATE RETURNING reply.

BEHAVIOR

The first acknowledgement rolls back

Given The handler already returned and the attempt actor retains its proposal.

When The first ACK fails with a known rollback.

Then The actor retries that same command and proposal while its fence permits it. It does not run the handler again and it continues occupying local capacity.

level: boundary area: Attempt recovery

- Completion-pending renewal has a finite lifetime of one lease duration after completion notice. Once that window ends, receipt reconciliation may continue but cannot create a write under an expired fence. A slow ACK row cannot stall healthy siblings because renewal skips locked rows.
- ACK receipts fingerprint the full proposal and fence. Matching receipts are checked before writes and after a zero-row update. Renewing a lease cannot invalidate that command. See [ADR-0005](#) and [ACK fault tests](#).

1.9 Cancellation and operator recovery

A request to stop and evidence of an unknown effect answer different questions.

Cancellation

responsibility

Record inactive cancellation or cooperative executing intent and arbitrate races atomically.

interface

grind.cancel; CancellationResult; worker cancellation selector.

interactions

Committed intent is observed by renewal and delivered to the handler once. ACK checks cancellation under the same fenced row transition.

invariants

Completion first preserves the finished result. Cancellation intent first wins non-uncertain ACK precedence. Explicit Uncertain retains its evidence and cancellation intent in either ordering. Expired ownership cannot overwrite recovery. Repeating an unknown cancellation is safe; Uncertain is not implicitly replayed.

failure

A live handler may ignore intent or already have performed effects. Database/scheduler progress is required for observation; there is no unconditional cancellation latency. Cancellation intent cannot certify that an effect was prevented or completed.

BEHAVIOR

Cancellation precedes an explicit uncertain response

Given Cancellation intent committed while the handler was executing.

When The handler returns Uncertain and its ACK wins with a live fence.

Then Storage commits Uncertain with the exact effect evidence and retained attempt fence. Cancellation intent remains recorded. Operator listing includes the row and ordinary pruning excludes it. AuthorizeReplay is refused. An attributed terminal confirmation can settle the effect.

level: boundary area: Cancellation precedence

BEHAVIOR

Cancellation follows an uncertain acknowledgement

Given An uncertain acknowledgement already committed.

When The caller requests cancellation.

Then The result is AlreadyUncertain. Storage retains the evidence and records cancellation intent. AuthorizeReplay is refused; attributed terminal confirmation remains available.

level: boundary area: Cancellation precedence

- Lease quarantine after pending cancellation also preserves Uncertain and suppresses automatic replay. Matching acknowledgement retries return the original committed Uncertain disposition without reinvoking the handler. [ADR-0012](#) records the rationale and historical evidence limits.

Operator resolution

responsibility

Settle or authorize a new attempt after application investigation of uncertain work.

interface

admin.list; resolution(id, by, details); ConfirmSuccess(output), ConfirmFailure(error), AuthorizeReplay; resolve_uncertain.

interactions

Encodes the selected typed value before storage, locks the uncertain row and commits an attributed durable resolution receipt.

invariants

Nonempty command/attribution fields; exact full command equality; AlreadyApplied returns original state. AuthorizeReplay is refused with pending cancellation; terminal confirmations can settle it. ConfirmFailure requires an error codec.

failure

Value rejection writes nothing. Different reuse is a conflict; lost reply is resolved by repeating the identical command. Authorizing replay cannot certify an external effect did not occur.

- Applications own operator permissions, evidence gathering, external status queries and replay/idempotency decisions. Resolution IDs and by/details fields do not authenticate anyone. Durable retention bounds command recovery.
- See [public recovery consumer](#) and [operator contracts](#).

1.10 Runtime capacity and deadlines

Independent renewal protects lease progress from ordinary main-pool saturation. It does not eliminate infrastructure stalls.

Supervised runtime

responsibility

Own process and pool lifetimes, queue capacity, timers and shutdown.

interface

check/start/supervised/named/stop; queue tuning; without_consumers/without_pruner.

interactions

RestForOne supervision orders pool/deadline ownership, forwarder, runtime, per-queue consumers and pruner. Each consumer owns its reserved renewal pool.

invariants

Current schema is required before consumer start. Named runtime lookup survives restart. Failed startup unwinds all acquired resources, registry and caches. Running and ACK-pending attempts count against local capacity.

failure

Stop invalidates retained connections/lifetime tokens. Shutdown grace bounds cooperative drain; remaining workers leave fenced lease recovery. Node crash, database outage and OS suspension have no liveness guarantee.

- Queue defaults: ten local slots, 250-millisecond polling, thirty-second lease, fifteen-second shutdown grace. Queues are derived from registered workers; duplicate queue tuning and tuning unused queues are refused. Local slots do not cap all nodes or serialize equivalent job effects.
- Claim/refill is serialized one free slot per mailbox message. The coordinator yields between slots and owns at most one poll timer. Polling is the current wakeup mechanism; fairness, LISTEN/NOTIFY and live pause/scale are retained gaps.
- Storage deadline D defaults to four seconds. Lease L must satisfy $L \geq 4D$. Renewal arms its L/3 timer before the query; the reserve isolates it from admission/ACK checkout. The timing argument assumes an established progressing connection, bounded storage work and actor progress; initial reconnect, same-row contention and OS scheduling remain outside it.

Boundary	Owned budget	Practical limit
Ordinary storage	Absolute deadline calculated before checkout; callback executes at most once	Queued pgo checkout has no unconditional receive timeout; late transferred candidates are refused before SQL
Migration step	Separate thirty-second default transaction budget	Large DDL and lock acquisition may fail; earlier steps remain committed

Boundary	Owned budget	Practical limit
Borrowed transaction	Caller transaction timeout	No new Grind BEGIN/COMMIT or checkout budget
Handler	Fifteen-minute default execution timeout	Stopping a process cannot retract an already executed effect
await within	Monotonic wait checks after reads; adaptive polls	Final read may extend beyond within; pool queue wait may exceed D

- The FFI retires stale holders/reconnection candidates within one absolute deadline, probes sockets under a separate watchdog and preserves unrelated Erlang exceptions. A narrow pog conversion exception is mapped; broad catches never forge rollback. See [ADR-0005](#), [ADR-0008](#) and [deadline boundary](#).

1.11 Reads, administration and retention

Typed read attachment checks stored contracts. Retention deliberately limits recovery.

Reads and administration

responsibility

Return committed typed outcomes and bounded payload-free operator views.

interface

bind/arguments/state/outcome/await; admin.list, quarantine_expired, prune_finished and receipt reconciliation.

interactions

Reads check installation, queue, worker and codec versions. List uses ascending job ID, optional queue/state filters and a bounded page size.

invariants

Native values are decoded only by the retained compatible codecs. Uncertain is nonterminal. Administrative attribution is not access control.

failure

Missing job, stale installation, incompatible contract and invalid stored payload remain read errors. Timeout does not cancel work or prove absence of a commit.

- Outcome is Pending(state), Succeeded(output), Failed(failure, optional terminal cause, description), Discarded(reason), Cancelled(reason) or Uncertain(evidence). Business(error), BusinessUnrecorded and RuntimeFailure retain distinct causes. await starts at twenty milliseconds, doubles to a five-hundred-millisecond polling cap and reads committed state.

Retention

responsibility

Delete old terminal jobs and dependent receipt rows in bounded concurrent-safe batches.

interface

Default pruner: seven-day retention, thirty-second interval, batch ten thousand; explicit admin.prune_finished.

interactions

Selects finished rows older than database-time cutoff using FOR UPDATE SKIP LOCKED, ordered by finished_at/ID; cascades receipt foreign keys. Admission candidate locks prevent deleting a selected retained conflict.

invariants

Only six terminal states with finished_at are pruned. Uncertain work remains retained. No leader election is needed for concurrent bounded pruning.

failure

Pruning permanently ends admission/ACK/resolution reconciliation and while_retained uniqueness. Runtime/schema outages can postpone deletion; configured retention is not an exact deletion instant.

- An application requiring permanent deduplication archives its own durable business identity. A Grind submission receipt is neither an eternal tombstone nor an effect ledger. See [ADR-0007](#).

1.12 Observations

Durable rows establish outcomes; events explain transitions and runtime pressure.

Typed Sinal observations

responsibility

Publish payload-free lifecycle evidence and bounded operational diagnostics.

interface

Sixteen grind.telemetry descriptors, typed metadata codecs and measurement builders.

interactions

A supervised forwarder receives bounded producer messages and delivers through Sinal outside database callbacks.

invariants

Lifecycle events require commit reply or matching receipt. `submit_in` and `pure reconcile_submission` emit no admitted event. Diagnostics do not grant commit authority. Metadata excludes inputs/outputs, raw SQL/settings/exception terms.

failure

Default forwarder capacity is 1024; events may drop or duplicate. Ordering is per producer only, monotonic time is local, subscriber failure cannot block queue correctness. Missing event does not imply missing job.

Family	Descriptors
Job lifecycle (8)	admitted, claimed, quarantined, acknowledged, resolved, cancellation_decided, released, contract_mismatch_recorded
Pruning (2)	completed, failed
Diagnostics (6)	renewal, acknowledgement, acknowledgement_retry, checkout, claim_failed, capacity

- Acknowledgement/resolution observations distinguish Replied and Reconciled and report the actual receipt disposition. A retry may publish another observation of the same commit. Consume stable identities when deduplicating operational counts.
- Renewal reports signed database lease headroom at measurement, not delivery. Checkout reports actual unclamped wait; nested storage wrappers do not double-count checkout. Capacity includes pending ACK occupancy. Native diagnostic enum codecs reject unknown stored labels.
- Handler cancellation observation requires progressing renewal and is best effort within its cadence, not a global delivery guarantee. See [ADR-0009](#) and [descriptor schemas](#).

1.13 Verification and retained extensions

Independent consumers, PostgreSQL faults and a frozen oracle answer different questions.

Verification boundary

responsibility

Prove public typing, codec behavior, fenced PostgreSQL transitions and scoped comparison independently.

interface

`testing.perform/perform_with/drain`; consumer package; root tests; oracle manifests; benchmark and resilience harnesses.

interactions

Inline helpers round-trip input/output/configured error codecs without a database. Drain drives real manual attempts; oracle runs Oban separately against classified shared scenarios.

invariants

Inline helpers do not simulate lease, timeout, retry or persistence. External consumers cannot use internal modules. Passing a paired scenario proves only its declared equivalent configuration.

failure

Database-free helpers execute real application code in the calling process. Drain timeout kills its runner but leaves lease recovery for claimed work. Missing/invalid benchmark audit cannot count as a pass.

- `testing.perform_with` supplies synthetic Context overrides, including already-fired cancellation and an optional connection. Without an error codec, direct typed `Failed(error)` remains visible. `drain` handles one real job at a time up to its bound; disable automatic consumers to avoid competing processing.
- The primary behavioral oracle is Oban 2.24.1 open source. Grind default backoff, exact encoded uniqueness, opt-in matching, bounded attempt ownership and durable command receipts have deliberate differences. Pro families require original explicit contracts or a licensed oracle; source availability cannot be assumed.
- Keep root regression tests, separate consumer tests, migration conformance mirrors, fault proxies, scenario manifests, audit invariants and machine-readable catalogs. Historical measured summaries and command provenance belong to evidence/ADRs; they do not qualify arbitrary future dependencies.

1.13.1 Complete capability inventory

Family	Current contract	Retained intended contract / missing surface
Job records and attempts	Typed input/output/error, correlation, eleven states and counters	Priority, tags, metadata, full attempt audit and suspension with explicit state/retention rules
Admission	Immediate/absolute/relative; receipts; borrowed transaction	Bulk commands with per-item atomicity, conflicts and ambiguity; uniqueness bulk needs independent contract
Queue control	Static local concurrency/poll/lease/grace	Pause/resume/scale and registration management; cluster/global/rate/partition limits with durable authority and fairness
Uniqueness	Exact key profile, incoming state/time filter, scheduled reschedule	Cross-worker domains, arbitrary states, broader replacements, key backfill and bulk selection
Schedules	One-off database availability	Cron/interval/timezones, DST, missed runs, clock jumps, durable tick identity and elected schedule ownership
Infrastructure/plugins	Concurrent pruner, polling and expiry quarantine	DynamicCron, Lifeline, Stager, Reindexer, leader/notifier contracts, PostgreSQL LISTEN/NOTIFY with loss/poll fallback
Dependency workflows	Ordinary jobs compose in application code	Named durable DAG steps, dependency values/codecs, waits and ignored cancelled/discarded upstream rules; distinct from Saga compensation
Batches	No batch coordinator	Membership and completed/attempted/discarded/cancelled callbacks; callback admission deduplication without exactly-once effect claim
Chunks	One input per handler	Homogeneous count/time flush, retained item IDs, one result per item, missing/duplicate result refusal and partial-failure accounting
Recorder and relay	Committed typed job output and bounded polling await	Named step result retrieval, reusable composition, notification optimization and recovery semantics beyond single-job outputs
Testing	Explicit inline helpers and manual drain	Typed enqueue inspection and broader modes without silently changing runtime authority
Engine and storage	PostgreSQL implementation only	SQLite/engine adapter only after a real consumer establishes minimum port and isolation/clock/fencing semantics
Management	Payload-free list, resolution, prune/quarantine and sixteen events	Richer read/filter APIs, per-node/queue/plugin metrics and explicit operational permissions

- A local Saga inside a job may restart as a whole job under a declared replay-safe policy; it has no durable intermediate compensation journal. Durable Saga uses its own operation identities, codecs and storage, even when sharing Grind's pool. Fabric and Relay compose typed boundaries without a universal retry/error/runtime abstraction.
- See [ADR-0001](#), [ADR-0009](#), [ADR-0010](#), [source coverage](#), [evidence limits](#) and [oracle provenance](#).

Glossary

Every term the layer declares, with the context that owns it.

Acknowledgement

owned by root

A retained proposal for a claimed attempt and a stable command identity. Its receipt records the actual committed disposition, which can differ from the proposal.

Admission receipt

owned by root

A durable record of a submission command fingerprint and its original Inserted, Existing or Rescheduled decision. Its lifetime ends when the referenced job is pruned.

Attempt fence

owned by root

The job, attempt identity, epoch, owner and live lease checked atomically before execution writes. Same-owner renewal preserves the fence; takeover invalidates it.

Attempt ordinal

owned by root

The retry-budget counter. Snooze and authorized abandonment replay refund it, so it can repeat and cannot fence ownership.

Available time

owned by root

The absolute database availability of a job. Relative admission delays are resolved using the database clock; recurring timezone schedules are a separate capability.

Borrowed transaction

owned by root

A caller-owned open READ COMMITTED PostgreSQL transaction used for admission statements without Grind issuing BEGIN or COMMIT.

Cancellation intent

owned by root

A committed request to stop further work. It asks an executing handler to stop cooperatively and forbids replay of an uncertain job. It cannot undo an effect and does not prove that the handler stopped.

Capacity

owned by root

The per-consumer local slot budget occupied by running attempts and attempts with pending acknowledgements. It is not a cluster-wide execution limit.

Claim

owned by root

Database authority to execute an eligible job while its executing state, attempt identity, epoch, owner and lease remain current.

Codec

owned by root

A versioned typed JSON encoder and decoder. Encoder refusal is a value; semantic compatibility across versions belongs to the application.

Correlation

owned by root

Application-supplied or generated tracing context. It is neither the admission idempotency key nor an authorization credential.

Installation

owned by root

One Grind schema in a PostgreSQL database. Database privileges and schema separation provide isolation; the client identity token only guards accidental handle reuse.

Job

owned by root

A retained PostgreSQL record of one versioned worker input, its scheduling and accounting, and its committed outcome. Its integer identity is distinct from the caller submission key.

Key contract

owned by root

Full encoded input with its input codec version, or a named/versioned typed projection. Only jobs admitted with matching retained material participate.

Lease

owned by root

A database-time expiry for a claim. An expired lease grants no new acknowledgement or renewal write, even when the old process is alive.

Observation

owned by root

A best-effort typed Sinal event. Lifecycle observations follow evidence of a committed transition; diagnostic observations describe runtime behavior.

Operator resolution

owned by root

An attributed, idempotent command confirming success/business failure or authorizing replay of an uncertain job after application investigation.

Retention

owned by root

The period after terminal finished_at during which jobs and their dependent receipts remain recoverable. Uncertain jobs have no finished_at and are excluded.

Submission key

owned by root

A caller-supplied or generated string identifying an admission command. Retrying the same retained request and key converges on its durable receipt.

Uncertain effect

owned by root

Evidence that an attempt may have performed an effect whose outcome is unknown. It is not evidence of failure or permission to retry.

Uniqueness domain

owned by root

A matching namespace including installation, worker identity/version, key contract and optional queue. Incoming state and time filters select candidates inside it.

Worker

owned by root

A deployed typed definition retaining worker identity, version, input/output/optional error codecs, queue, handler and execution policies.