C++ Club Meeting 101

Gleb Dolgich

2020-03-05

- Epochs: can we *just* use namespace?
- We need epochs!
- ABI: The Day The Standard Library Died, *by Corentin Jabot*
  - Reddit
- ABI Breaks: Not just about rebuilding, *by Ben Craig*

- Overview

  A quick syntax-based overview of C++20 Concepts, as they are in the standard (circa January 2020).

- Viktor Zverovich
  - Reddit

Reddit

Range-for loops, fold expressions, streams, template definition in .cpp file, RAII, operator overloading, function/constructor `try` block, placement `new`, structured bindings, taking address of a label, variadic templates, overloading `operator,`, algorithms, and many more.

- Bartek Filipek
  - Reddit

- Sy Brand, Microsoft
  - Reddit

- Shafik Yaghmour
  - GitHub

A header-only, tiny and easy to use library for game programming and much more written in modern C++, mainly known for its innovative entity-component-system (ECS) model.

- GitHub (C++17, MIT)
- Reddit

- Article

- Daniel Martin

- Colby Pike (vector-of-bool)
- Reddit
- GitHub
- Specification

libman is a new level of indirection between package management and build systems.

dds is Drop-Dead Simple build and package manager.

- CppCon 2019: Robert Schumacher "How to Herd 1,000 Libraries"

"Making new friends" idiom by Dan Saks

Wikibooks

> *The goal is to simplify creation of friend functions for a class template.*

```
 1  template<typename T>
 2  class Foo {
 3      T value;
 4  public:
 5      Foo(const T& t) { value = t; }
 6      friend ostream& operator <<(ostream& os, const Foo<T>& b)
 7      {
 8          return os << b.value;
 9      }
10  };
```

- Article

A hidden gem: `inner_product` (2/2)

Conor Hoekstra @code_report
🔁 @cjdb_ns & @TartanLlama

This makes me so incredibly happy! I literally just yesterday googled, C++17 / C++20 zip to see if they had anything, because I wrote some code in both C++ and #Python and Python was so much more beautiful.

```cpp
int solve(int h, vector<int> w, vector<int> l) {
    int p = 0;
    for (int i = 0; i < w.size(); ++i)
        p = max(p, w[i] - l[i] / 4);
    return max(0, p - h);
}
```

```python
def solve(h, w, l):
    p = max(a - b//4 for a, b in zip(w, l))
    return max(0, p - h)
```

29w • 03/12/2018 • 17:47

Conor Hoekstra @code_report
🔁 @cjdb_ns & @TartanLlama

Also, I just discovered std::inner_product – a beautiful temporary solution to a lack of zip. #cpp #inner_product

```cpp
int solve(int h, vector<int> w, vector<int> l) {
    return max(0, inner_product(begin(w), end(w), begin(l), 0,
        [](auto a, auto b) { return max(a, b); },
        [](auto a, auto b) { return a - b / 4; }) - h);
}
```

27w • 16/12/2018 • 09:30

- Raymond Chen: How can I handle both structured exceptions and C++ exceptions potentially coming from the same source?
  - Reddit
- Raymond Chen: Can I throw a C++ exception from a structured exception?

Quote

Oscar Godson:

> *One of the best programming skills you can have is knowing when to walk away for a while.*