

C++ Club Meeting Notes

Gleb Dolgich

2018-03-08

PDF

Visual Studio 2017 version 15.6 released

- ▶ [Release notes](#)
- ▶ [C++ improvements](#)

Chrome switches to Clang on Windows, ditches MSVC

- ▶ [Ars Technica](#)
- ▶ [LLVM Blog](#)

Building Chrome locally with Clang is about 15% slower than with MSVC.

► [Post](#)

See also:

- [Guy Davidson: Batteries not included: what should go in the C++ standard library?](#)
- [Corentin: A cake for your cherry: what should go in the C++ standard library?](#)
- [Titus Winters: What Should Go Into the C++ Standard Library](#)

► [Jon Kalb](#)

► [Reddit](#)

const modifies what is on its left. Unless there is nothing on its left, in which case it modifies what's on its right.

► [CppCoreGuidelines NL.26: Use conventional const notation](#). Reason: Conventional notation is more familiar to more programmers. Consistency in large code bases.

C++: Thoughts on Dealing with Signed/Unsigned Mismatch

- ▶ [IT Hare](#)
- ▶ [Reddit](#)
- ▶ [Previously on Reddit](#)

Matters discussed here are related to mitigation of certain decisions which were made 50+ years ago and which are pretty much carved in stone now.

Developers, while trying to get rid exactly of signed/unsigned warning, turned a perfectly-working-program-with-warnings, into a program-without-warnings-but-which-fails-once-a-day-or-so.

Stealth features responsible for half of F-35 defects

- ▶ Defence News (2018)
- ▶ JSF C++ Coding Standard (2005)
- ▶ HackerNews (1), HackerNews (2)
- ▶ F-35 Joint Strike Fighter benefits from modern software testing, quality assurance (2013)
- ▶ F-35 Software Reliability, Reddit

<...> so-called quality escapes – errors made by Lockheed's workforce that could include drilling holes that are too big or installing a dinged part

- ▶ [Reddit question](#)
- ▶ Book: [C++ Templates: The Complete Guide](#), 2nd ed, by Vandervoorde, Josuttis, Gregor
- ▶ Video: [Introduction to C++ Template Metaprogramming - Sasha Goldshtein](#)
- ▶ Video: CppCon 2014: Walter E. Brown "Modern Template Metaprogramming: A Compendium [Part 1](#), [Part 2](#)
- ▶ Video: CppCon 2016: Arthur O'Dwyer "Template Normal Programming [Part 1](#), [Part 2](#)

The main "rule" when doing template metaprogramming is, "if the value yield by such an expression is non-sensical, this function / class / etc... is skipped"

C++ Metaprogramming (cont.)

C++:

```
1  template <
2      typename T
3      , std::enable_if_t<
4          std::negation_v<
5              std::conjunction<
6                  std::is_arithmetic<T>::type
7                  , std::is_same<T, QStringList>::type
8              >
9          >
10     >* = nullptr>
11  QDataStream& operator>>(QDataStream& stream, T& obj);
```

Lisp:

```
1 (enable_if
2   (not
3     (and
4       (is_arithmetic T)
5       (is_same T QStringList)
6     )
7   )
8 )
```

Non-virtual destructors

► Post

```
1 struct B {  
2     B() { std::cout << 'b'; }  
3     ~B() { std::cout << 'B'; }  
4 };  
5 struct D : B {  
6     D() { std::cout << 'd'; }  
7     ~D() { std::cout << 'D'; }  
8 };  
9 int main() {  
10     B* p = new D;  
11     delete p;  
12 }
```

► Herb Sutter's GotW #5 – “base’s destructor should be virtual or protected.”

StackOverflow

```
1 shared_ptr<int> sptr2(nullptr);
2 cout << "sptr2 use_count: " << sptr2.use_count() << endl;
3
4 shared_ptr<int> sptr6(nullptr, default_delete<int>());
5 cout << "sptr6 use_count: " << sptr6.use_count() << endl;
```

Output:

```
1 sptr2 use_count: 0
2 sptr6 use_count: 1
```

Stephan T. Lavavej:

Unintentional Zen-like saying in the C++17 Standard: "If the path is empty, stop."