

# Polymorphism

## Concepts of Programming Languages Lecture 4

# Practice Problem

```
let k = fun x -> fun y -> x in  
let x = 3 + k k 2 3 4 in  
k x (k x)
```

*Would UTop throw a type error on the above expressions? If not, what does it evaluate to?*

# Answer

```
let k = fun x -> fun y -> x in  
let x = 3 + k k 2 3 4 in  
k x (k x)
```

# Practice Problem

Implement the function

```
val bitonic : int -> int -> int -> int list
```

so that **bitonic i j k** is a list of consecutive integers from **i** to **j** to **k**, e.g.,

```
bitonic 1 5 3 = [1;2;3;4;5;4;3]
```

# Outline

- » Discuss **polymorphism** in general
- » Demo **examples** of polymorphic functions

# Polymorphism

# Recall: Polymorphism and Lists

```
let rec length l =  
  match l with  
  | [] -> 0  
  | x :: xs -> 1 + length xs
```

*What is the type of the length function?*

Does this function depend on the values in the list?

# Recall: The List Type

`[1;2;3]`

`int list`

`["1";"2";"3"]`

`string list`

`[[1;1];[2;2];[3;3]]`

`int list list`



# Recall: The List Type

`[1;2;3]`

`int list`

`["1";"2";"3"]`

`string list`

`[[1;1];[2;2];[3;3]]`

`int list list`

The `list` type is an example of a **parametrized** type

# Recall: The List Type

`[1;2;3]`

`int list`

`["1";"2";"3"]`

`string list`

`[[1;1];[2;2];[3;3]]`

`int list list`

The `list` type is an example of a **parametrized** type

A function on lists is *polymorphic* (with respect to the list parameter) if it can be apply to a list parametrized by *any* type

# Recall: The List Type

[1;2;3]

**int list**

["1";"2";"3"]

**string list**

[[1;1];[2;2];[3;3]]

**int list list**

The list type is an example of a **parametrized** type

A function on lists is *polymorphic* (with respect to the list parameter) if it can be apply to a list parametrized by *any* type

For this, we need *type parameters* to stand for *any* type:

# Recall: The List Type

[1;2;3]

**int list**

["1";"2";"3"]

**string list**

[[1;1];[2;2];[3;3]]

**int list list**

The list type is an example of a **parametrized** type

A function on lists is *polymorphic* (with respect to the list parameter) if it can be apply to a list parametrized by *any* type

For this, we need *type parameters* to stand for *any* type:

**'a, 'b, 'c, ...**

# Not all functions are polymorphic

```
let rec sum l =  
  match l with  
  | [] -> 0  
  | x :: xs -> x + sum xs
```

# Not all functions are polymorphic

```
let rec sum l =  
  match l with  
  | [] -> 0  
  | x :: xs -> x + sum xs
```

*Can this function be applied to a list parametrized by any type?*

# Not all functions are polymorphic

```
let rec sum l =  
  match l with  
  | [] -> 0  
  | x :: xs -> x + sum xs
```

*Can this function be applied to a list parametrized by any type?*

**Answer:** No, it can only be applied to **int lists**

# Not all functions are polymorphic

```
let rec sum l =  
  match l with  
  | [] -> 0  
  | x :: xs -> x + sum xs
```

*Can this function be applied to a list parametrized by any type?*

**Answer:** No, it can only be applied to **int lists**

OCaml's type inference is good at "guessing" when functions are polymorphic



# Example

*Implement the function*

***reverse : 'a list -> 'a list***

*such that **reverse l** is the same as **l** but in reverse order*

# High Level

```
let rec rev_int (l : int list) : int list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let rec rev_string (l : string list) : string list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let _ = assert (rev_int [1;2;3] = [3;2;1])  
let _ = assert (rev_string ["1";"2";"3"] = ["3";"2";"1"])
```

# High Level

```
let rec rev_int (l : int list) : int list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let rec rev_string (l : string list) : string list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let _ = assert (rev_int [1;2;3] = [3;2;1])  
let _ = assert (rev_string ["1";"2";"3"] = ["3";"2";"1"])
```

Copy/pasting code is *time consuming* and *error prone*

# High Level

```
let rec rev_int (l : int list) : int list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let rec rev_string (l : string list) : string list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let _ = assert (rev_int [1;2;3] = [3;2;1])  
let _ = assert (rev_string ["1";"2";"3"] = ["3";"2";"1"])
```

Copy/pasting code is *time consuming* and *error prone*

**Polymorphism** allows for better code reuse. The *same* function can be applied in multiple contexts

# Basic Example

```
let id = fun x -> x
let a = id 0
let b = id (0 = 0)
let c = id id
```

# Basic Example

```
let id = fun x -> x
let a = id 0
let b = id (0 = 0)
let c = id id
```

We want to be able to define functions that can be used in multiple contexts *and* that we can type check

# Basic Example

```
let id = fun x -> x
let a = id 0
let b = id (0 = 0)
let c = id id
```

We want to be able to define functions that can be used in multiple contexts *and* that we can type check

Important: We can evaluate this if we *don't* type check

# Basic Example

```
let id = fun x -> x
let a = id 0
let b = id (0 = 0)
let c = id id
```

We want to be able to define functions that can be used in multiple contexts *and* that we can type check

Important: We can evaluate this if we *don't* type check

*But if we type-check, what should be the type of **id**?*



# Polymorphism

# Polymorphism

There are two common kinds of polymorphism

# Polymorphism

There are two common kinds of polymorphism

1. **Ad Hoc Polymorphism:** The ability to overload function names so that different types can share interfaces

# Polymorphism

There are two common kinds of polymorphism

1. **Ad Hoc Polymorphism:** The ability to overload function names so that different types can share interfaces
2. **Parametric polymorphism:** The ability to define functions that are *agnostic* to (parts of) the types, giving it more reusability

# Polymorphism

There are two common kinds of polymorphism

1. **Ad Hoc Polymorphism:** The ability to overload function names so that different types can share interfaces

2. **Parametric polymorphism:** The ability to define functions that are *agnostic* to (parts of) the types, giving it more reusability

our focus

# Ad Hoc Polymorphism

```
let add (x : float) (y : float) = x +. y  
let add (x : string) (y : string) = x ^ y  
(* This doesn't work in OCaml... *)
```

# Ad Hoc Polymorphism

```
let add (x : float) (y : float) = x +. y  
let add (x : string) (y : string) = x ^ y  
(* This doesn't work in OCaml... *)
```

Ad hoc polymorphism is essentially **function overloading**

# Ad Hoc Polymorphism

```
let add (x : float) (y : float) = x +. y  
let add (x : string) (y : string) = x ^ y  
(* This doesn't work in OCaml... *)
```

Ad hoc polymorphism is essentially **function overloading**

Functions can be defined and used for different types of inputs



# Ad Hoc Polymorphism

```
let add (x : float) (y : float) = x +. y
let add (x : string) (y : string) = x ^ y
(* This doesn't work in OCaml... *)
```

Ad hoc polymorphism is essentially **function overloading**

Functions can be defined and used for different types of inputs

Then we can define code against *interfaces* (this is common in object oriented programming)

# Parametric Polymorphism

```
let id = fun x -> x
let a = id 0
let b = id (0 = 0)
let c = id id
```

# Parametric Polymorphism

```
let id = fun x -> x
let a = id 0
let b = id (0 = 0)
let c = id id
```

Parametric polymorphism allows for functions which are agnostic to the types of its inputs (this is what OCaml does)

# Parametric Polymorphism

```
let id = fun x -> x
let a = id 0
let b = id (0 = 0)
let c = id id
```

Parametric polymorphism allows for functions which are agnostic to the types of its inputs (this is what OCaml does)

*For example, we can write a single identity function and use it in multiple contexts*

# Type Parameters

```
let id : 'a -> 'a = fun x -> x
```

# Type Parameters

```
let id : 'a -> 'a = fun x -> x
```

The "parametric" part is the fact that types have *parameters*

# Type Parameters

```
let id : 'a -> 'a = fun x -> x
```

The "parametric" part is the fact that types have *parameters*

**Type parameters** are instantiated at particular types according to the context

# Looking Ahead: Quantification

```
let id : 'a . 'a -> 'a = fun x -> x
```



# Looking Ahead: Quantification

```
let id : 'a . 'a -> 'a = fun x -> x
```

In reality, types variables in OCaml are **quantified**

# Looking Ahead: Quantification

```
let id : 'a . 'a -> 'a = fun x -> x
```

In reality, types variables in OCaml are **quantified**

Just like with expression variables, we don't like *unbound* type variables

# Looking Ahead: Quantification

```
let id : 'a . 'a -> 'a = fun x -> x
```

In reality, types variables in OCaml are **quantified**

Just like with expression variables, we don't like *unbound* type variables

We read this "**id** has type **t -> t** for any type **t**"

# Polymorphism and Type Inference

```
fun f -> fun x -> f (x + 1)
```

In OCaml, the type of an expression depends on how its subexpressions are *used*

OCaml can figure out what is the "most" polymorphic type we can give to an expression

This is called **type inference**

demo  
(remove)

There are many subtleties  
to this...

# Subtlety 1: Type Annotations

```
let rec rev ('a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let id : 'a -> 'a = fun x -> x
```

# Subtlety 1: Type Annotations

```
let rec rev ('a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let id : 'a -> 'a = fun x -> x
```

Parametric polymorphism is *not* just removing type annotations



# Subtlety 1: Type Annotations

```
let rec rev ('a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let id : 'a -> 'a = fun x -> x
```

Parametric polymorphism is *not* just removing type annotations

There are PLs *without* polymorphism *or* type annotations

# Subtlety 1: Type Annotations

```
let rec rev ('a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let id : 'a -> 'a = fun x -> x
```

Parametric polymorphism is *not* just removing type annotations

There are PLs *without* polymorphism *or* type annotations

There are PLs *with* polymorphism that *require* type annotations

# Subtlety 2: Type Inference

```
let rec rev ('a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let id : 'a -> 'a = fun x -> x
```

# Subtlety 2: Type Inference

```
let rec rev ('a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let id : 'a -> 'a = fun x -> x
```

Polymorphism is *not* the same as having type inference

# Subtlety 2: Type Inference

```
let rec rev ('a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let id : 'a -> 'a = fun x -> x
```

Polymorphism is *not* the same as having type inference

In OCaml, polymorphism is deeply connected with its type inference system, but they are distinct (we can choose to annotate all our OCaml code)

# Subtlety 2: Type Inference

```
let rec rev ('a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: l -> rev l @ [x]
```

```
let id : 'a -> 'a = fun x -> x
```

Polymorphism is *not* the same as having type inference

In OCaml, polymorphism is deeply connected with its type inference system, but they are distinct (we can choose to annotate all our OCaml code)

*We will take up this topic at the end of the course*

# Subtlety 3: Dynamic Dispatch

```
let to_string (x : 'a) : string = ...  
(* This is not possible in OCaml *)
```

# Subtlety 3: Dynamic Dispatch

```
let to_string (x : 'a) : string = ...  
(* This is not possible in OCaml *)
```

Parametric polymorphism cannot be used for *dispatch*



# Subtlety 3: Dynamic Dispatch

```
let to_string (x : 'a) : string = ...  
(* This is not possible in OCaml *)
```

Parametric polymorphism cannot be used for *dispatch*

We can't write a polymorphic function that "checks the type" to see what to do

# Practice Problem

```
let rec f x = f (f (x + 1)) in f
```

*What is the type of the above OCaml expressions?*

# Answer

```
let rec f x = f (f (x + 1)) in f
```

# Aside: Parametricity

# Aside: Parametricity

*Can you write function of type **'a -> 'a**?*

# Aside: Parametricity

*Can you write function of type `'a -> 'a`?*

*Can you write a another?*

# Aside: Parametricity

*Can you write function of type '**a** -> 'a?*

*Can you write a another?*

**Parametricity** refers the (very cool) observation that polymorphic types often restrict the kinds of functions you can write in a *mathematically rigorous sense*

# Summary

Polymorphism allows functions to be agnostic to (parts of) the types of its parameters

Parametric polymorphism does not allow for dynamic dispatch, it must given the *same* implementation at any particular type