

# Exploiting LED Rolling-Shutter Effect in Indoor Positioning System Modern Mobile Communications

YANG GUANG

1140339072

May 29, 2015

## Abstract

It has been very mature to locate one's position in the outdoors using GPS like satellite positioning systems in a relatively acceptable deviation. However, Indoor Positioning System (IPS), still cannot be available in modern indoor environment such as airport or grand shopping plazas due to several constraints. But IPS has been proved to be very useful in the perspective future by the industry. Although this topic has been researched in recent 10 years in many related methods, there are two key issues of hardware cost against accuracy that cannot make a good balance between one another. In this article, we first give some research on related works of indoor positioning system, mainly on five systems of RADAR[00], Centaur[12], Cricket[04], Ubicarse[14], and Luxapose[14], then we fulfill the detail implementation of Luxapose, one method exploits visible light communication to realize IPS and evaluate its performance on some key factors of accuracy and available limit distance.

*Keywords:* IPS , AoA , Rolling Shutter, VLC

## 1. Introduction

Smart devices with cameras and LEDs are abundant in today's environment. This abundance creates an untapped opportunity for using these devices for wireless communication. Meanwhile, even if localization technology based on GPS developed maturely, we find the inconvenience with indoor localizations in malls or airports, which in fact in great need of the technology support of indoor localization since the environment is complex.

Indoor localization serves these situations, and it can detect a wireless user's gesture, movement, or can do location-based authentication. In this article we draw a novel way by exploiting the LED lights to realize this indoor localization problem.

This report does some survey on existing indoor localization methods and introduces some representative works in section 2. In section 3 we explicit the major task of Luxapose, involving the working scenario and techniques we planned to utilize, then we give a detailed definition of the indoor localization with LED AoA algorithm. In section 4 we introduced how the system been built on different modules. In section 5 we make an evaluation on several key metrics of location distance and accuracy and look forward to some future work that are needed to be worked on.

## **2. Related Works**

Indoor localization has been worked on for years since its demand in industry is badly. We review four major representative work based on RF, acoustic, and MIMO techniques, the four main methods today in research of indoor localization. We analysis their defects to show the advancement in our work of Indoor Localization with LEDs.

### **2.1 RF-based Localization [Radar (2000)] [Centaur (2012)]**

WiFi-based indoor localization approaches have been the center of attention in the field of indoor localization, due to their low deployment cost, potential for reasonable accuracy and readiness to be applied to mobile devices. Existing WiFi-based solutions usually fall into one of two categories: fingerprint-based and model-based approaches. We introduce fingerprint-based method by the Radar system, and model-based by the Centaur system.

While these methods have been shown to achieve promising localization accuracy (below 10 meters at 90% tile) under lab conditions, large-scale accurate indoor localization systems have yet to be developed. For example, given realworld fingerprint sampling conditions, the localization accuracy of existing approaches in large venues like shopping malls and airports can still be up to 25m at 90% tile; similar results are reported by Google[1]

#### **2.1.1 RF-based Localization [Radar (2000)]**

The fingerprint-based solution fingerprints locations in the area pf interest and then searches for the best matching location.



2.2  
Acoustic-  
based  
Lo-  
cal-  
iza-  
tion  
[Cricket (2004)]

2.3  
MIMO-  
based  
Lo-  
cal-  
iza-  
tion  
[Ubicarse (2014)]

Cras  
gravi-  
da,  
es-  
t  
v-  
el  
in-  
ter-  
dum  
eu-  
is-  
mod,  
tor-  
tor  
mi  
lobor-  
tis  
mi,

quis adipiscing elit lacus ut orci. Phasellus nec fringilla nisi, ut vestibulum  
neque. Aenean non risus eu nunc accumsan condimentum at sed ipsum.

Aliquam  
fringilla  
non

di-  
am  
sed  
var-  
ius.  
Sus-  
pendisse  
tel-  
lus  
fe-  
lis,  
hen-  
drerit  
non  
biben-  
dum

ut, adipiscing vitae diam. Lorem ipsum dolor sit amet, consectetur adip-  
iscing elit. Nulla lobortis purus eget nisl scelerisque, commodo rhoncus  
lacus porta. Vestibulum vitae turpis tincidunt, varius dolor in, dictum lectus.  
Aenean ac ornare augue, ac facilisis purus. Sed leo lorem, molestie sit amet  
fermentum id, suscipit ut sem. Vestibulum orci arcu, vehicula sed tortor id,  
ornare dapibus lorem. Praesent aliquet iaculis lacus nec fermentum. Morbi  
eleifend blandit dolor, pharetra hendrerit neque ornare vel. Nulla ornare,  
nisl eget imperdiet ornare, libero enim interdum mi, ut lobortis quam velit  
bibendum nibh.



Figure 2: Fish

Morbi tempor congue porta. Proin sem-  
per, leo vitae faucibus dictum, metus mau-  
ris lacinia lorem, ac congue leo felis eu  
turpis. Sed nec nunc pellentesque, gravi-  
da eros at, porttitor ipsum. Praesent con-  
sequat urna a lacus lobortis ultrices eget ac  
metus. In tempus hendrerit rhoncus. Mau-  
ris dignissim turpis id sollicitudin lacinia.  
Praesent libero tellus, fringilla nec ullamcor-  
per at, ultrices id nulla. Phasellus placerat  
a tellus a malesuada.

### 3. Problem Definition and Algorithm of Luxapose

Fusce in nibh augue. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. In dictum accumsan sapien, ut hendrerit nisi. Phasellus ut nulla mauris. Phasellus sagittis nec odio sed posuere. Vestibulum porttitor dolor quis suscipit bibendum. Mauris risus lectus, cursus vitae hendrerit posuere, congue ac est. Suspendisse commodo eu eros non cursus. Mauris ultrices venenatis dolor, sed aliquet odio tempor pellentesque. Duis ultricies, mauris id lobortis vulputate, tellus turpis eleifend elit, in gravida leo tortor ultricies est. Maecenas vitae ipsum at dui sodales condimentum a quis dui. Nam mi sapien, lobortis ac blandit eget, dignissim quis nunc.

1. First numbered list item
2. Second numbered list item

Donec luctus tincidunt mauris, non ultrices ligula aliquam id. Sed varius, magna a faucibus congue, arcu tellus pellentesque nisl, vel laoreet magna eros et magna. Vivamus lobortis elit eu dignissim ultrices. Fusce erat nulla, ornare at dolor quis, rhoncus venenatis velit. Donec sed elit mi. Sed semper tellus a convallis viverra. Maecenas mi lorem, placerat sit amet sem quis, adipiscing tincidunt turpis. Cras a urna et tellus dictum eleifend. Fusce dignissim lectus risus, in bibendum tortor lacinia interdum.

### 4. System Modules Implementation

### 5. Evaluation and Conclusion

### References

- Radar (2000).** P.Bahl, V.N. Padmanabhan, "Radar: An in-building RF-Based User Location and Tracking System." *Proc. of IEEE INFOCOM*, volumn 2, pp. 775-784, 2000.
- Cricket (2004).** Nissanka Bodhi Priyantha, "The Cricket Indoor Location System." *ACM SIGCOMM*,2004.
- Centaur (2012).** R.Nandakumar, K.K.Chintalapudi, and V.N.Padmanabhan, "Centaur: Locating Devices in an Office Environment." *ACM Mobi-com*,2012.

**Luxapose (2014).** Ye-Sheng Kuo, Pat Pannnuto, "Luxapose: Indoor Positioning with Mobile Phones and Visible Light." *ACM Mobicom*,2014.

**Ubicarse (2014).** Swarun Kumar, Stephanie Gil, Dina Katabi, Daniela Rus, "Accurate Indoor Localization with Zero Start-up Cost." *ACM Mobicom*,2014.

1. Googlers Talk Indoor Maps For 40 Minutes,  
"http://www.webpronews.com/googlers-talk-indoor-maps-for-40-minutes-video-2013-05." .