
Nuclear Reactor Thermal-Hydraulics

NUGN520 - Homework

By

GUILLAUME L'HER



Department of Nuclear Engineering
COLORADO SCHOOL OF MINES

Homework submitted for the Nuclear Reactor Thermal-Hydraulics class at the Colorado School of Mines.

SPRING 2017

TABLE OF CONTENTS

	Page
1 Heat transfer and fluid flow, nonmetallic coolants	1
1.1 [9-3] - Nitrogen-cooled reactor	1
1.1.1 Problem	1
1.1.2 Solution	1
1.2 [9-6] - W'/q	2
1.2.1 Problem	2
1.2.2 Solution	3
1.3 [J1] - Temperature distribution	3
1.3.1 Problem	3
1.3.2 Solution	3
1.4 [J2] -	5
1.4.1 Problem	5
1.4.2 Solution	5
1.5 [J3] -	6
1.5.1 Problem	6
1.5.2 Solution	6
Bibliography	7

HEAT TRANSFER AND FLUID FLOW, NONMETALLIC COOLANTS

Several exercises from the book written by M. M. El Wakil [1] are tackled in this homework. The problems in this section relate to the ninth chapter of the book, covering the subject of heat transfer and fluid flow, for nonmetallic coolants.

1.1 [9-3] - Nitrogen-cooled reactor

1.1.1 Problem

A nitrogen-cooled reactor uses UO_2 fuel. The fuel elements are 0.5 in in diameter and are encased in a graphite can 0.1 in thick. At a particular cross section the coolant pressure and bulk temperature are 6 atm and $1000^\circ F$. The stream velocity is 375 fps. At the same section the volumetric thermal source strength is $2 \times 10^6 \text{ Btu} \cdot \text{h}^{-1} \cdot \text{ft}^{-3}$ and the maximum fuel temperature is $5000^\circ F$. Determine (a) the heat-transfer coefficient and (b) the necessary equivalent diameter of the coolant channel. Neglect contact resistance between the fuel and the graphite. Use $k_g = 35 \text{ Btu} \cdot \text{h}^{-1} \cdot \text{ft}^{-1} \cdot ^\circ F^{-1}$ (aged).

1.1.2 Solution

We can use Equation 5.38a from the book [1], which states, for a cylindrical fuel element with cladding and coolant:

$$(1.1) \quad T_{f,m} - T_b = \frac{q''' r_f^2}{2k_f} + q''' r_f \left(\frac{r_w - r_f}{k_g} + \frac{1}{h} \right)$$

Where:

$T_{f,m}$ = Maximum temperature in the fuel
 T_b = Coolant bulk temperature
 r_f = Fuel radius position
 r_w = Wall radius position
 k_g = Aged thermal conductivity of graphite

We can reorganize the terms to express h . Doing so gives us:

$$(1.2) \quad h = \frac{1}{((5000 - 1000 - \frac{1}{2e6*(0.25/12)} \left(\frac{2e6*(0.25/12)^2}{2*1.1} \right) - \frac{(0.1/12)}{35})}$$

And so, $h = 11.6 \text{ Btu} \cdot \text{h}^{-1} \cdot \text{ft}^{-2} \cdot ^\circ\text{F}^{-1}$.

We can now use the Dittus-Boelter equation, $Nu = 0.023Re^{0.8}Pr^{0.4}$, to compute the equivalent diameter needed. The bulk properties are used in this correlation.

This equation translates to:

$$(1.3) \quad \frac{hD_e}{k} = 0.023 \left(\frac{D_e v \rho}{\mu} \right)^{0.8} \left(\frac{c_p \mu}{k} \right)^{0.4}$$

This gives:

$$(1.4) \quad D_e = \left(0.023 \left(\frac{k}{h} \frac{v \rho}{\mu} \right)^{0.8} \left(\frac{c_p \mu}{k} \right)^{0.4} \right)^5$$

Using data from tables of Nitrogen at 6 atn and 1000°F , we get:

$k = ?$
 $v = 375 \text{ fps} = x \text{ fph}$
 $\rho = 0.16 \text{ lb} \cdot \text{ft}^{-3}$
 $\mu = 8.76 \text{ lb} \cdot \text{ft}^{-1} \cdot \text{h}^{-1}$
 $c_p = 0.27 \text{ Btu} \cdot \text{lb}^{-1} \cdot ^\circ\text{F}^{-1}$
 $h = 11.6 \text{ Btu} \cdot \text{h}^{-1} \cdot \text{ft}^{-2} \cdot ^\circ\text{F}^{-1}$

1.2 [9-6] - W'/q

1.2.1 Problem

Ligh liquid water is used as a reactor coolant. In a particular channel, the average bulk temperature is 300°F . Determine the percent change in W'/q if it were to be used in the same channel, with the same mass-flow rate, the same mean temperature between cladding and coolant, but at average bulk temperature of 200°F and 400°F . Assume saturated conditions in all cases.

1.2.2 Solution

Equation 9.9 from the book [1] can be used. It states:

$$(1.5) \quad \frac{W'}{q} = 7.07 * 10^{-14} \left(\frac{1}{D_e^{0.2}} \right) \left(\frac{v^{2.8}}{h \Delta T_m} \right) \rho^{0.8} \mu^{0.2} = \alpha \rho^{0.8} \mu^{0.2}$$

α can be taken as a constant given the data. The only variable is the change in bulk temperature, implying a change in density and viscosity. The table from the appendix gives the following data:

$$\rho(200^\circ F) = 60.1 \text{ lb.ft}^{-3}$$

$$\rho(300^\circ F) = 57.3 \text{ lb.ft}^{-3}$$

$$\rho(400^\circ F) = 53.6 \text{ lb.ft}^{-3}$$

$$\mu(200^\circ F) = 0.74 \text{ lb.ft}^{-1}.\text{h}^{-1}$$

$$\mu(300^\circ F) = 0.45 \text{ lb.ft}^{-1}.\text{h}^{-1}$$

$$\mu(400^\circ F) = 0.33 \text{ lb.ft}^{-1}.\text{h}^{-1}$$

So, we get :

$$(1.6) \quad \left. \frac{W'}{q} \right|_{T_b=300^\circ F} = 21.7\alpha$$

$$(1.7) \quad \left. \frac{W'}{q} \right|_{T_b=200^\circ F} = 24.9\alpha = 11.1\% \left. \frac{W'}{q} \right|_{T_b=300^\circ F}$$

$$(1.8) \quad \left. \frac{W'}{q} \right|_{T_b=400^\circ F} = 19.4\alpha = -10.6\% \left. \frac{W'}{q} \right|_{T_b=300^\circ F}$$

1.3 [J1] - Temperature distribution

1.3.1 Problem

For pressure driven laminar flow between parallel plates of separation h , the velocity components are $u = U(1 - y^2/h^2)$, $v = w = 0$, where U is the centerline velocity. Similarly to the example done in class, use an energy equation to find the temperature distribution $T(y)$ for a constant wall temperature T_w .

1.3.2 Solution

We can write the energy equation:

$$(1.9) \quad \rho c_p \left(\frac{\partial T}{\partial t} + \vec{v} \cdot \nabla T \right) = k \nabla^2 T + \mu \Phi + \dot{q}$$

In a steady state, with constant heat generation and no dissipation terms, we can write:

$$(1.10) \quad \rho c_p (\vec{v} \cdot \nabla T) = k \nabla^2 T$$

In 2-D cartesian coordinates:

$$(1.11) \quad \rho c_p \left(u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} \right) = k \left(\frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} \right)$$

Noting that $\alpha = \frac{k}{\rho c_p}$, and that $v = 0$, we can write:

$$(1.12) \quad \frac{u}{\alpha} \frac{\partial T}{\partial x} = \frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2}$$

We can assume that the rate of change of temperature in the x-direction will be negligible compared to the rate of change in temperature in the y-direction, thus, $\frac{\partial^2 T}{\partial x^2} \ll \frac{\partial^2 T}{\partial y^2}$. We can now substitute the velocity distribution $u(y)$:

$$(1.13) \quad \frac{U}{\alpha} \left(1 - \frac{y^2}{h^2} \right) \frac{\partial T}{\partial x} = \frac{\partial^2 T}{\partial y^2}$$

Integration with respect to y, we obtain:

$$(1.14) \quad \frac{\partial T}{\partial y} = \frac{U}{\alpha} \frac{\partial T}{\partial x} \left(y - \frac{y^3}{3h^2} \right) + C_1$$

Knowing the symmetry boundary condition $\frac{\partial T}{\partial y} \Big|_{y=0} = 0$, we can set $C_1 = 0$. Integrating a second time:

$$(1.15) \quad T(y) = \frac{U}{2\alpha} \frac{\partial T}{\partial x} \left(y^2 - \frac{y^4}{6h^2} \right) + C_2$$

Knowing the boundary condition $T(y=0) = T_m$, we can set $C_2 = T_m$. However, this implies knowing T_m . Another boundary condition states that $T(y=h/2) = T_w$, T_w being the temperature at the plate surface. In that case, $C_2 = T_m = T_w - \frac{23}{192} \frac{U}{\alpha} \frac{\partial T}{\partial x} h^2$.

And so,

$$(1.16) \quad T(y) = \frac{U}{2\alpha} \frac{\partial T}{\partial x} \left(y^2 - \frac{y^4}{6h^2} \right) + T_w - \frac{23}{192} \frac{U}{\alpha} \frac{\partial T}{\partial x} h^2$$

1.4 [J2] -

1.4.1 Problem

Consider steady laminar fluid flow in a fixed duct of equilateral triangular cross section. Take the side length as s and the center of the triangle at the origin, with one side parallel to the x axis. (a) Write the equations of the line segments defining the sides of the triangle. (b) Using from (a) a product form for the velocity of the fluid, develop a solution of the Navier-Stokes equation. Gravity may be ignored.

1.4.2 Solution

The equation defining the segments of the triangle are:

$$(1.17) \quad y = -\frac{s}{2\sqrt{3}}$$

$$(1.18) \quad y = x\sqrt{3} + \frac{s}{\sqrt{3}}$$

$$(1.19) \quad y = -x\sqrt{3} + \frac{s}{\sqrt{3}}$$

We can then define the section of the triangle to be:

$$(1.20) \quad S(x, y) = \left(y + \frac{s}{2\sqrt{3}}\right) \left(y + x\sqrt{3} - \frac{s}{\sqrt{3}}\right) \left(y - x\sqrt{3} - \frac{s}{\sqrt{3}}\right)$$

The Navier-Stokes equation can be written:

$$(1.21) \quad \mu \left(\frac{\partial^2 v_z}{\partial x^2} + \frac{\partial^2 v_z}{\partial y^2} \right) = \frac{\partial p}{\partial z}$$

We can assume that the velocity in the z -direction depends on the section, so that:

$$(1.22) \quad v_z = C_1 S(x, y)$$

And so:

$$(1.23) \quad \frac{\partial^2 v_z}{\partial x^2} = C_1 (-6y - s\sqrt{3})$$

$$(1.24) \quad \frac{\partial^2 v_z}{\partial y^2} = C_1(6y - s\sqrt{3})$$

$$(1.25) \quad \frac{\partial^2 v_z}{\partial x^2} + \frac{\partial^2 v_z}{\partial y^2} = -2C_1 s\sqrt{3}$$

Substituting this equation into the Navier-Stokes equation:

$$(1.26) \quad -2C_1 s\sqrt{3} = \frac{1}{\mu} \frac{\partial p}{\partial z} \implies C_1 = \frac{1}{2\mu s\sqrt{3}} \frac{\partial p}{\partial z}$$

And consequently,

$$(1.27) \quad v_z = \frac{1}{2\mu s\sqrt{3}} \frac{\partial p}{\partial z} \left(y + \frac{s}{2\sqrt{3}} \right) \left(y + x\sqrt{3} - \frac{s}{\sqrt{3}} \right) \left(y - x\sqrt{3} - \frac{s}{\sqrt{3}} \right)$$

1.5 [J3] -

1.5.1 Problem

Scaling for the Navier-Stokes (NS) equation. Consider the NS equation with gravity neglected, $\rho \frac{d\vec{V}}{dt} = -\nabla p + \mu \nabla^2 \vec{V}$. Suppose that $p(\vec{x}, t)$ and $\vec{V}(\vec{x}, t)$ solve these equations. There are scaling relationships, $\vec{V}_\tau = \tau^\alpha \vec{V}(\tau^\beta \vec{x}, \tau^\gamma t)$ and $p_\tau = \tau^\delta p(\tau^\beta \vec{x}, \tau^\gamma t)$ for any positive τ , such that p_τ and \vec{V}_τ also solve the NS equation. (a) What are the relations between the exponents α, β, γ , and δ for this scaling to hold? (b) The equation of continuity also holds, $\nabla \cdot \vec{V}_\tau = 0$. Does this impose any further condition on the four exponents? Why or why not?

1.5.2 Solution

BIBLIOGRAPHY

- [1] M. M. EL-WAKIL, *Nuclear Heat Transport*, American Nuclear Society, 1993.