Nuclear Reactor Thermal-Hydraulics

NUGN520 - Homework

By

GUILLAUME L'HER



Department of Nuclear Engineering COLORADO SCHOOL OF MINES

Homework submitted for the Nuclear Reactor Thermal-Hydraulics class at the Colorado School of Mines.

SPRING 2017

TABLE OF CONTENTS

																		P	ag	e
1	Rea	ctor H	eat Genei	ratio	n															1
	1.1	[7-6] -				 														1
		1.1.1	Problem			 														1
		1.1.2	Solution		•	 									•	. .				1
Bi	ibliog	raphy																		7

CHAPTER

REACTOR HEAT GENERATION

everal exercises from the book written by M. M. El Wakil [1] are tackled in this homework. The problems in this section relate to the seventh and eight chapter of the book, covering the subject of heat conduction in reactor elements.

1.1 [7-6] -

1.1.1 Problem

A very long fin is rectangular in cross-section 0.48*0.24 in. It generates 2×10^6 Btu.h⁻¹.ft⁻³. The fin base is at $1000^\circ F$. It is cooled by a gas at $600^\circ F$ with a uniform heat transfer coefficient 100 Btu.h⁻¹.ft⁻². $^\circ F$ ⁻¹. Using a network with $\Delta x = 0.12$ in., write the necessary set of finite difference equations for the nodal points and solve by any one of the techniques at your command. k for the fin material = 10 Btu.h⁻¹.ft⁻¹. $^\circ F$ ⁻¹

1.1.2 Solution

First, one can note that the problem is missing a graph. The considered geometry is given in Figure 1.1.




Figure 1.1: Representation of the problem geometry

We can identify four types of nodes: inner, y-bound (next to the upper boundary), x-bound (next to the right boundary) and corner.

The inner node temperature T_n is given by Equation 1.1.

(1.1)
$$T_n = \frac{T_{n-\Delta x} + T_{n+\Delta x} + T_{n-\Delta y} + T_{n+\Delta y}}{4} + \frac{\Delta T_g}{2}$$

In our case, we can see that $T_{n-\Delta y} = T_{n+\Delta y}$ by symmetry for the inner nodes. Consequently, we obtain Equation 1.2.

(1.2)
$$T_n = \frac{T_{n-\Delta x} + T_{n+\Delta x} + 2T_{n+\Delta y}}{4} + \frac{\Delta T_g}{2}$$

For the x-bound nodes, we can write Equation 1.3.

(1.3)
$$T_n = \frac{T_{n-\Delta x} + T_{n+\Delta y} + Bi_{\Delta x}T_f}{2 + 2Bi_{\Delta x}} + \frac{\Delta T_g}{2 + Bi_{\Delta x}}$$

For the y-bound nodes, we can write Equation 1.4

(1.4)
$$T_n = \frac{T_{n-\Delta x} + T_{n+\Delta x} + 2T_{n+\Delta y} + 2Bi_{\Delta x}T_f}{4 + 2Bi_{\Delta x}} + \frac{\Delta T_g}{2 + Bi_{\Delta x}}$$

And finally, for the corner node, we can write (as seen in problem 7.1 previously) Equation 1.5.

$$T_{n} = \frac{T_{n-\Delta x} + T_{n+\Delta y} + 2Bi_{\Delta x}T_{f}}{2 + 2Bi_{\Delta x}} + \frac{\Delta T_{g}}{2 + 2Bi_{\Delta x}}$$

A few exceptions can be noted. Indeed, the two leftmost points, on the base of the fin, are given to be at $1000^{\circ}F$.

We can consequently write the matrix A.

 $\frac{\Delta T_g}{2}$ can be calculated using $\Delta T_g = \frac{(\Delta x)^2 q'''}{2k}$. T_f , the temperature of the gas, is known. We can thus obtain b.

$$b = \begin{bmatrix} 1000 \\ 1000 \\ 7.2 \\ 229.5 \\ 7.2 \\ 229.5 \\ 7.2 \\ 229.5 \\ 229.5 \\ 330.5 \end{bmatrix}$$

The equation A.x = b can thus be solved, using Python. The python script is given in 1.1.2.1. We obtain the following results (Equation 1.6):

$$T(0,0) = 1000.0$$

$$T(0,1) = 1000.0$$

$$T(1,0) = 804.0$$

$$T(1,1) = 740.9$$

$$T(2,0) = 705.3$$

$$T(2,1) = 665.0$$

$$T(3,0) = 658.5$$

$$T(3,1) = 635.7$$

$$T(4,0) = 628.3$$

$$T(4,1) = 617.8$$

1.1.2.1 Python script

```
import numpy as np
m = 10
        # size of system is m x m
dx = 0.12
deltax, k, qtriple, h = (dx/10)**2, 10., 2.e6, 100. # BG units
tb = 1000.
ts = 600.
dtg = (0.5*deltax)*qtriple/k
bi = h * dx / k
amat = np.zeros((m,m))
b = np.zeros(m)
amat[0,0] = 1.
amat[1,1] = 1.
b[0] = tb
b[1] = tb
for i in range(2, m, 2):
        amat[i,i-2] = -0.25
        amat[i,i] = 1.
        amat[i,i+1] = -0.5
        amat[i,i+2] = -0.25
        b[i] = dtg/2.
    except IndexError:
        break
for i in range(3, m, 2):
    try:
        amat[i,i-2] = -1/(2*bi+4)
        amat[i,i-1] = -1/(bi+2)
        amat[i,i] = 1.
        amat[i,i+2] = -1/(2*bi+4)
        b[i] = (bi*ts + dtg)/(bi+2)
    except IndexError:
        break
amat[m-1,m-1] = 1.
amat[m-1,m-2] = -1/(2*bi+2)
amat[m-1,m-3] = -1/(2*bi+2)
b[m-1] = (2*bi*ts + dtg)/(2*bi+2)
amat[m-2,m-2] = 1.
amat[m-2,m-1] = -1/(bi+2)
amat[m-2,m-4] = -1/(bi+2)
b[m-2] = (bi*ts + dtg)/(bi+2)
print(b)
ysol = np.linalg.solve(amat,b)
```

```
print('Temperature solution:')

temp = []
for i in range(5):
    for j in range(2):
        temp.append("T(%s,%s)" % (i, j))

for i,t in enumerate(temp):
    print("%s = %.1f" % (t, ysol[i]))

# check of solution:
if not np.allclose(np.dot(amat, ysol), b):
    print("Solution does not match!")
```

BIBLIOGRAPHY

[1] M. M. El-Wakil, $Nuclear\ Heat\ Transport$, American Nuclear Society, 1993.