
Laboratory Pipelines

Cody Glickman

`cody.glickman@ucdenver.edu`

2018

Contents

BLAST Usage	1
Microbiome Analysis	2
1 QIIME2 Microbiome	2
Gene Prediction Methodolgy	3
1 Genome Gene Prediction	3
2 Metagenomic Gene Prediction	3
BASHING	4

BLAST Usage

Make BLAST Database

-dbtype [prot/nucl] protein or nucleotide, use

-parse_seqids

to enable retrieval of sequences by sequence identifiers.

```
makeblastdb -in [input_seq] -dbtype prot -out Combined_VF -title "Combined_VF"
```

```
blastp -db [Path_to_Database] -out results.txt -outfmt 6 -query [input_seqs]  
-max_target_seqs 2
```

Output format Useful [outfmt link](#) on biostars. Formats of interest include 5 XML

Blast output, 6 tabular output, 10 comma-separated values

Standard columns in outfmt 6:

1. qseqid query (e.g., gene) sequence id
2. sseqid subject (e.g., reference genome) sequence id
3. pident percentage of identical matches
4. length alignment length
5. mismatch number of mismatches
6. gapopen number of gap openings
7. qstart start of alignment in query
8. qend end of alignment in query
9. sstart start of alignment in subject
10. send end of alignment in subject
11. evalue expect value
12. bitscore bit score

Additional columns can be specific by -outfmt "6 std qlen"

Columns in Tab-separated format

qseqid sseqid pident length mismatch gapopen qstart qend sstart send evalue bitscore

Microbiome Analysis

1 QIIME2 Microbiome

Cite vHMM [Earth Virome Project](#).

```
## Load required libraries
module load qiime2
source activate qiime2-2017.12

## Create demux sequences
qiime tools import --type 'SampleData[PairedEndSequencesWithQuality]'
--input-path manifest_file.csv --output-path [paired-end-demux]
--source-format PairedEndFastqManifestPhred33

## Perform Dada2 Processing
bsub qiime dada2 denoise-paired --i-demultiplexed-seqs [paired-end-demux]
--p-trunc-len-f 280 --p-trunc-len-r 279 --p-max-ee Inf --p-chimera-method
pooled --p-n-threads 0 --o-representative-sequences [rep-seqs]
--o-table [table]

## Summarize Table
bsub qiime feature-table summarize --i-table table.qza --o-visualization table.qzv

## Assign Taxonomy
bsub qiime feature-classifier classify-sklearn --i-classifier [Database File]
--i-reads [rep-seqs] --o-classification [taxonomy]

## Visualize Taxonomy
qiime metadata tabulate --m-input-file ./Qiime_demo/taxonomy.qza --o-visualization [taxon
```

Gene Prediction Methodolgy

Utilize **Prodigal** to predict genes in prokaryotes.

1 Genome Gene Prediction

```
prodigal -i [input_seqs] -o my_genes -a my_proteins.faa
```

2 Metagenomic Gene Prediction

```
prodigal -i [input_seqs] -o my_genes -a my_proteins.faa -p meta
```

```
## Hello World  
print(x)
```

BASHING

PHASTER Summary to Table Parser Input File is summary.txt from Phaster and the output table is output.txt

The following workflow is wrapped into table_parsing_workflow.sh the folder with the summary file should be in the same directory as the workflow and python script.

```
sed -i '' -n '/REGION/, $p' $table
```

```
sed -i '' -e 's/-//g' $table
```

```
sed -i '' -e 's/REGION_POSITION/ASSEMBLY_CONTIG_NUMBER  
CONTIG_LENGTH          CONTIG_DEPTH/g' $table
```

```
awk -v OFS="\t" '$1=$1' $table > output.txt
```

```
./Table_Parsing.py output.txt $table
```