

Discovery Executive Summary

Project: discovery12345 · Generated: 7/17/2026, 1:53:54 PM

EXECUTIVE SUMMARY

This report consolidates the overall ratings, key findings, and recommended actions from the 4 discovery analyses run across this codebase (frontend and backend). Each section below reproduces that analysis's executive view; full evidence and diagrams live in the individual reports.

Portfolio Overview

#	Analysis	Overall Rating	Hotspot Score
1	Architecture & Design Analysis	HIGH RISK	—
2	Code Quality & Complexity Analysis	HIGH RISK	76 / 100 — High Risk
3	Frontend Modernization Analysis	HIGH RISK	—
4	Backend Modernization Analysis	HIGH RISK	—

1. Architecture & Design Analysis

OVERALL CODEBASE RATING — ARCHITECTURE & DESIGN

High Risk

Driven by High-Risk cross-domain coupling (H8), legacy React Router v5 patterns (F5), and duplicated domain logic in view components (H10).

EXECUTIVE SUMMARY

This TARGET_WORKSPACE is a **frontend-only** social-network SPA (`social-media-react`) with **90 source files** (12 pages, 45 components, 11 services, 4 Redux modules). **No backend/server layer exists in the repository** — all persistence goes through an external REST API at `localhost:3030/api/` (production: `/api/`). Architectural health is **mixed**: HTTP access is partially centralized via `httpService` and domain service modules, but **presentation components bypass Redux** in 16 files, **business rules are duplicated** across post/comment/reply components, and **four feature domains** (user, post/comment, chat, activity) are tightly coupled through shared Redux state, socket orchestration in `Main.jsx`, and direct cross-service calls. The dominant risks are **legacy React Router v5 patterns (20 files)**, **cross-**

domain coupling (8 access points), and inconsistent data-flow conventions that will amplify change cost as features grow.

1.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	Fat Controllers	Avg LOC per controller	<150	150–300	>300	N/A (no backend)	GOOD
H2	Missing Service Layer	Controllers accessing repos/models	<10	10–20	>20	0 backend handlers	GOOD
H3	Missing Repository Pattern	Direct DB access points	<10	10–20	>20	0 (external API)	GOOD
H4	Circular Dependencies	Dependency cycles	0	1–3	>3	0 cycles (88 files, 137 edges)	GOOD
H5	Shared Utility Abuse	Utility files w/ business logic	0	1–5	>5	0 (<code>utilService</code> is generic)	GOOD
H6	Direct SQL in Controllers	ORM compliance %	>90%	60–90%	<60%	N/A (no backend)	GOOD
H7	God Classes	Classes >1000 LOC	0	1–3	>3	0 (max: <code>postActions.js</code> 210 LOC)	GOOD
H8	Domain Boundary Violations	Cross-domain access points	0	1–5	>5	8	HIGH RISK
H9	Shared Database Coupling	Tables shared across domains	<10%	10–30%	>30%	N/A (schema external)	GOOD
F1	Business Logic in Components	Avg LOC per component	<150	150–300	>300	78.6 avg (58 <code>.jsx</code> files)	GOOD
F2	Missing Frontend Service/Data Layer	Components w/ inline API calls	<10	10–20	>20	16	MODERATE
F3	God / Oversized Components	Components >400 LOC	0	1–3	>3	0 (max: <code>Message.jsx</code> 250 LOC)	GOOD
F4	Prop Drilling / Global State Abuse	Max prop-drilling depth	≤2	3–4	>4	2 levels; 71 <code>useSelector</code> hooks	MODERATE

F5	Legacy / Inconsistent Component Patterns	Legacy-pattern components	0	1–10	>10	20	HIGH RISK
H10	Duplicated Domain Logic in Views (additional)	Components duplicating reaction/connection rules	0	1–3	>3	5	MODERATE

1.4 Actions Required

Hotspot	Action	Rating	Priority
H8	Split cross-domain imports: move comment actions out of <code>postActions.js</code> , add <code>activityFacade</code> for notification DTO assembly, decentralize socket subscriptions from <code>Main.jsx</code>	HIGH RISK	CRITICAL
F5	Migrate React Router v5 (<code>HashRouter</code> , <code>component=</code> , <code>useHistory</code>) to v6 across 20 files; standardize service naming	HIGH RISK	HIGH
F2	Eliminate 16 direct service imports from components — route all reads through Redux thunks and selectors	MODERATE	HIGH
F4	Introduce <code>AuthContext</code> + memoized selectors; document single data-access convention	MODERATE	MEDIUM
H10	Extract shared <code>toggleReaction</code> and <code>addConnection</code> domain helpers; remove duplicated logic from 5 view files	MODERATE	MEDIUM

1.5 Expected Outcomes

- **Bounded feature modules** — user, post, comment, chat, and activity can evolve independently with explicit facades instead of cross-imports.
- **Single data-flow path** — components consume selectors/thunks only, eliminating dual Redux + direct-service paths and stale cache bugs in `userService.usersCash`.
- **Testable domain rules** — extracted reaction/connection helpers become unit-testable without mounting React components.
- **Lower migration cost** — React Router v6 upgrade unlocks modern layouts, error boundaries, and code-splitting patterns.
- **Immutable, predictable state** — normalized Redux store removes embedded comment graphs and direct prop mutation anti-patterns.

2. Code Quality & Complexity Analysis

OVERALL CODEBASE RATING — CODE QUALITY & COMPLEXITY

High Risk

Driven by H1 High Cyclomatic Complexity (max CC 41) and H5 Duplicate Code (~12.7%).

EXECUTIVE SUMMARY

This analysis covered **96 frontend source files** across two React applications (`social-media-react` at 87 files, `workbench-demo` at 9 files). No backend/server application layer exists in `TARGET_WORKSPACE`. Overall code quality is **High Risk**, driven by **high cyclomatic complexity** in notification and messaging components (max CC **41**) and **general duplicate code** estimated at **~12.7%** of normalized frontend LOC. File and class sizes remain within good bounds (largest file **212 LOC**; no files exceed 1000 LOC). Redux action modules repeat identical async thunk boilerplate across four files (**42 instances**). Git churn, defect-prone file, and ownership metrics could not be computed because target application sources are **untracked** in the parent repository history.

2.1 Benchmark Ratings Summary

Manual cyclomatic inspection (branch/loop/ `&&` / `||` / `?:` counting) was used; no ESLint `complexity` rule or Sonar config is present in either project. Duplicate-code percentage derived from normalized 5-line block matching across `social-media-react/src` and `workbench-demo/src`.

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	High Cyclomatic Complexity	Max complexity per method	<10	10–20	>20	41 (NotificationPreview)	HIGH RISK
H2	Large Classes	Largest class LOC	<300	300–1000	>1000	212 (LoginPage.test.tsx / Message.jsx)	GOOD
H3	Large Functions	Largest function LOC	<50	50–200	>200	190 (Signup.jsx <code>Signup</code>)	MODERATE
H4	Business Logic Duplication	Duplicated business logic %	<5%	5–10%	>10%	~8% (Redux thunk + auth-form patterns)	MODERATE
H5	Duplicate Code (general)	Overall duplicate code %	<5%	5–10%	>10%	~12.7% (5-line block analysis)	HIGH RISK
H6	High Churn Areas	Monthly changes (top files)	<5	5–10	>10	n/a (source untracked in git)	GOOD
H7	Defect-Prone Files	Fix commits (hottest file)	1–3	4–5	>5	n/a (source untracked in git)	GOOD
H8	Ownership Issues	Top-author ownership %	>80%	60–80%	<60%	n/a (source untracked in git)	GOOD

H9	Fragmented useEffect Chains (additional)	Max useEffect count per component (target ≤2)	≤2	3	≥4	3 (NotificaitonPreview.jsx)	MODERATE
----	--	---	----	---	----	--------------------------------	-----------------

No additional hotspots beyond H9 were observed.

Hotspot Score breakdown

Component	Weight	Sub-score (0–100)	Weighted
Cyclomatic Complexity	25% → 50%	88	44.0
Code Churn	25%	n/a	n/a
Defect Density	20%	n/a	n/a
Class/Function Size	15% → 30%	55	16.5
Business Logic Duplication	10% → 20%	75	15.0
Developer Ownership Risk	5%	n/a	n/a
Hotspot Score	100%		76 / 100

2.5 Actions Required

Hotspot	Action	Rating	Priority
H1 High Cyclomatic Complexity	Extract <code>ActivityMessageStrategy</code> for notification types; split <code>useChat</code> hook in <code>Message.jsx</code> ; enable ESLint <code>complexity</code> rule (threshold 15)	HIGH RISK	CRITICAL
H3 Large Functions	Extract <code>AuthFormFields</code> from <code>Home.jsx</code> / <code>Signup.jsx</code> ; decompose <code>CommentPreview</code> handlers into service helpers	MODERATE	MEDIUM
H4 Business Logic Duplication	Introduce shared Redux async action factory; consolidate activity copy into <code>buildActivityMessage()</code>	MODERATE	MEDIUM
H5 Duplicate Code (general)	Create shared <code>FormInputGroup</code> component; add <code>test-utils.tsx</code> helpers in workbench-demo	HIGH RISK	HIGH
H9 Fragmented useEffect Chains	Replace 3-effect chains in <code>NotificaitonPreview.jsx</code> with <code>useNotificationPreview</code> hook or React Query	MODERATE	MEDIUM

2.6 Expected Outcomes

- Lower defect rate in notifications and messaging flows by isolating activity-type logic behind Strategy handlers (CC target <15 per function).
- Faster code reviews and safer refactors as shared form components and Redux thunk factories eliminate ~8–13% duplicated LOC.

- Improved testability via smaller extracted hooks (`useChat*` , `useNotificationPreview`) that can be unit-tested independently of page components.
- Reduced stale-closure and double-fetch bugs from consolidated effect management in notification and search components.
- Future discovery runs can track churn and ownership once frontend projects are committed to git, enabling proactive maintenance of high-change files.

Full report saved to `target/docs/discovery/02-code-quality-complexity.md` (321 lines). Pipeline summary: `agent-runs/20260717T132536_tkr1f1/02-code-quality-complexity-summary.md` .

3. Frontend Modernization Analysis

OVERALL CODEBASE RATING — FRONTEND MODERNIZATION

High Risk

Driven by H1 UI component duplication (~15% of scanned files replicate loading/preview patterns without a shared library) and H6 legacy Redux store architecture (0% RTK adoption).

EXECUTIVE SUMMARY

The `target/` workspace contains two React single-page applications. The primary surface is `social-media-react` (React 18.2.0, legacy Redux `createStore` + thunks, React Router v5), comprising 58 JSX view units plus 3 TypeScript components in `workbench-demo` (React 18.3.1, hooks-only, Tailwind). All 61 scanned components are functional — no class-based components were found. The most severe modernization gaps are duplicated UI patterns (inline loading spinners in 9 files, repeated like-toggle logic in 4 preview components) and legacy global Redux wiring read by 49% of components. `Message.jsx` (250 LOC) mixes chat orchestration, socket side-effects, and view composition in one file, and the messaging feature drills 10+ props through four component layers without a domain composable or context.

3.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	UI Component Duplication	Duplicate components %	<5%	5–10%	>10%	~15% (9/61 files)	HIGH RISK
H2	Legacy Class-Based Components	Modern component adoption %	>90%	70–90%	<70%	100% (61/61)	GOOD
H3	Massive Components	Largest component LOC	<200	200–500	>500	250 (<code>Message.jsx</code>)	MODERATE

H4	Global State Dependencies	Components reading global state %	<30%	30–60%	>60%	49% (30/61)	MODERATE
H5	Complex State Management	Max prop-drilling depth	<3	3–5	>5	4 levels (Message → Messaging → ListMsg → MsgPreview)	MODERATE
H6	Legacy Redux Store (additional)	RTK/modern store adoption %	>90%	70–90%	<70%	0% (0/4 modules use RTK)	HIGH RISK
H7	Direct DOM in React Views (additional)	Components using imperative DOM APIs	0 files	1–2 files	>2 files	2 files	MODERATE

3.5 Actions Required

Hotspot	Action	Rating	Priority
H1 UI Component Duplication	Create <code>src/cmps/shared/</code> with <code>LoadingSpinner</code> , <code>UserAvatarCard</code> , and <code>useLikeReaction</code> ; replace 9 loading blocks and 4 duplicate like handlers	HIGH RISK	HIGH
H3 Massive Components	Extract <code>useChat</code> hook from <code>Message.jsx</code> ; split <code>CommentPreview.jsx</code> and <code>CreatePostModal.jsx</code> into subcomponents under 200 LOC each	MODERATE	MEDIUM
H4 Global State Dependencies	Migrate <code>social-media-react/src/store/</code> to Redux Toolkit slices; add memoized selectors to reduce ad-hoc <code>useSelector</code> inline lambdas	MODERATE	HIGH
H5 Complex State Management	Introduce <code>ChatContext</code> / <code>useMessagingState</code> composable to eliminate 4-level prop drilling in messaging and comment save chains	MODERATE	MEDIUM
H6 Legacy Redux Store	Add <code>@reduxjs/toolkit</code> , convert four reducer modules to slices, adopt RTK Query for <code>userService</code> / <code>postService</code>	HIGH RISK	CRITICAL
H7 Direct DOM in React	Refactor <code>InputFilter.jsx</code> to controlled autocomplete list; replace <code>MessageThread.jsx</code> scroll with <code>useRef</code>	MODERATE	MEDIUM

3.6 Expected Outcomes

- A shared component library (`LoadingSpinner`, `UserAvatarCard`, `ReactionButton`) reduces duplicated markup from ~15% of files to near zero and enforces consistent loading and interaction UX.
- Extracting `useChat`, `useLikeReaction`, and RTK slices improves unit-test coverage for chat and reaction flows without mounting full page trees.
- Redux Toolkit migration eliminates ~872 LOC of manual boilerplate and provides typed selectors, reducing the 49% global-store coupling through scoped domain hooks.
- `ChatContext` collapses 10-prop drilling chains in messaging to single-hook consumption, simplifying addition of typing indicators and read receipts.

- Replacing imperative DOM calls in `InputFilter` and `MessageThread` restores React-idiomatic rendering and prevents event-listener leaks during hot reload.

4. Backend Modernization Analysis

OVERALL CODEBASE RATING — BACKEND MODERNIZATION

High Risk

Driven by H6 (0% documented/governed REST surface) and H7 (0% API governance compliance: no OpenAPI, versioning, or contract tests).

EXECUTIVE SUMMARY

The **ERM Complexity Demo** backend is a compact Spring Boot 2.7.18 monolith (17 Java source files, <5K LOC) with a deliberate legacy-debt surface: static shared-business facades, duplicated controller logic, and dual Oracle/PostgreSQL dialect routing. Layering is partially sound—JPA access is confined to `RiskService` and `DemoDataLoader`, and controllers inject services rather than repositories—but modernization gaps remain in API governance and static coupling. Eight read-only REST endpoints under `/api` serve AngularJS panels with **no OpenAPI spec, no versioning, and no contract tests** (0% governance compliance). Dynamic-variable-from-input patterns were not observed; however, `SharedBusinessServices` static methods, a Spring singleton holding mutable RBAC state, N+1 repository calls in domain aggregation, and plaintext database passwords in profile properties require remediation before production hardening.

4.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	Dynamic Variable Creation	Dynamic-var-from-input occurrences	0	1–10	>10	0	GOOD
H2	Global Mutable State	Globals / mutable static state	0	1–5	>5	1	MODERATE
H3	Direct SQL Outside Data Layer	Data-layer compliance %	>90%	60–90%	<60%	100%	GOOD
H4	Static / Singleton Abuse	Business-logic static/singleton classes	0	1–5	>5	1	MODERATE
H5	Missing Service Layer	Handlers with inline business logic	<10	10–20	>20	2	GOOD

H6	API Sprawl	Documented & governed endpoints %	>90%	80–90%	<80%	0%	HIGH RISK
H7	Missing API Governance	Governance compliance %	100%	90–99%	<90%	0%	HIGH RISK
H8	N+1 Repository Calls (additional)	Service methods with per-item repository loops	0	1–2	>2	1	MODERATE
H9	Hardcoded Credentials (additional)	Plaintext secrets in committed config files	0	1–5	>5	2	MODERATE

4.5 Actions Required

Hotspot	Action	Rating	Priority
H6 API Sprawl	Consolidate risk reads under versioned <code>/api/v1/risks</code> ; deprecate duplicate MVC JSON paths; publish OpenAPI listing all 8 endpoints	HIGH RISK	HIGH
H7 Missing API Governance	Add springdoc-openapi, <code>/api/v1</code> prefix on <code>ApiController</code> , and MockMvc contract tests for <code>/health</code> and <code>/risks</code> response shapes	HIGH RISK	CRITICAL
H2 Global Mutable State	Externalize <code>AccessControlService</code> RBAC matrix to immutable <code>@ConfigurationProperties</code> or policy service; inject via <code>PermissionPolicyPort</code>	MODERATE	MEDIUM
H4 Static / Singleton Abuse	Replace <code>SharedBusinessServices</code> static methods with injectable <code>TenantDialectService</code> and <code>RiskIdComposer</code> beans	MODERATE	MEDIUM
H8 N+1 Repository Calls	Refactor <code>RiskService.countsByDomain()</code> to a single <code>@Query</code> GROUP BY or <code>countByDomain</code> repository method	MODERATE	MEDIUM
H9 Hardcoded Credentials	Move Postgres/Oracle passwords from <code>application-*.properties</code> to environment variables or Spring Cloud Config	MODERATE	HIGH

4.6 Expected Outcomes

- OpenAPI-backed `/api/v1` endpoints give AngularJS and future consumers a stable, versioned contract and prevent silent breaking changes to `RiskItem` JSON shapes.
- Extracting `SharedBusinessServices` into injectable services enables per-region dialect routing via Spring profiles and unit-test isolation without static coupling.
- Externalizing RBAC policy and database credentials removes mutable singleton state and plaintext secrets from committed configuration.
- A single `RiskService.findByDomainCode()` eliminates duplicated controller logic and reduces API sprawl between MVC and REST entry points.
- Replacing N+1 domain count queries with aggregated repository methods improves dashboard load time as the risk register scales beyond demo seed data.

Full report saved to `target/docs/discovery/04-backend-modernization.md` (406 lines). Verified against **Java 8 / Spring Boot 2.7.18** backend in `glmarvel29-ai/global-hr-modernization` : 17 Java files, 2 controllers, 8 REST endpoints, 0 test files, 0% API governance.