GBMI Longitudinal Working Group Cohort Summaries

- 1 Set Up
- 2 Overview of scripts
- 3 Overall Cohort Summary
- 4 Onset Summary
- 5 Progression Summary
- 6 Running the pipeline on all phenotypes
- 7 Prepare files for sharing

1 Set Up

These scripts will compute descriptive summary statistics of the overall biobank cohort, as well as each onset and progression phenotype.

The code is designed to use similar inputs as those provided for separate scripts for PRS validation. Please ensure the following R packages are available and installed.

```
install.packages(c("optparse", "data.table", "dplyr", "tidyr", "purrr", "survival", "broom"))
```

2 Overview of scripts

Every function call, regardless of `--mode`, needs three main flags:

- `--mode`: one of `cohort`, `onset`, or `progression`
- `--pheno-files`: one file, or a comma-separated list of files (see “Ancestry-specific vs. combined datasets” examples below). In multi-ancestry cohorts, summary statistics across all ancestry groups will also be generated. The script operates the same for biobanks and phenotypes with a single ancestry group.
- `--prefix`: where to write output, e.g. `results/mytrait/mytrait`. Any missing directories in the path are created automatically.

Everything else has a GBMI-convention default (`--id-col=IID`, `--sex-col=sex`, `--event-col=event`, `--birthyear-col=birthyear`, etc.), but should be overridden with `--*-col` flags to match your actual column names. The script does **not** guess column names — a mismatch raises a “column not found” error naming exactly which column it looked for and couldn’t find.

2.1 Age vs. date columns

This applies to enrollment and follow-up in `cohort` mode. For each of those two fields, the underlying age can be supplied two ways, and you should pick **one** depending on what is most readily available:

- **Exact age** (e.g. `age_at_recruitment`): point the plain `-col` flag (`--enrollment-col` or `--followup-col` / `--followup-col-in-file`) directly at it. Used as-is, no conversion.
- **Date or year** (e.g. `year_at_recruitment`, or a `YYYY-MM-DD` string): point the matching `-date-col` flag (`--enrollment-date-col` or `--followup-date-col` / `--followup-date-col-in-file`) at it instead. This is converted to age using `--birthyear-col`. Bare 4-digit years are used directly; anything else is parsed as `YYYY-MM-DD`.

Don’t supply both flags for the same field. If enrollment or follow-up live in a *separate* file from `--pheno-files` (via `--enrollment-file` / `--followup-file`), the `-col` / `-date-col` flags describe the column **in that separate file**, not in `--pheno-files` — see the “Ancestry-specific datasets to be joined” example below.

`onset` and `progression` mode only use age since `--eventage-col` and `--onsetage-col` are read straight from `--pheno-files` (used for time-to-event GWAS), which should already have this information. For progression specifically, if `--eventage-col` is not found in the phenotype file, the script automatically derives it from `--onsetage-col` + `--time-to-progression-col` (elapsed time since first diagnosis) — see the progression examples below.

2.2 Ancestry-specific vs. combined datasets

`--pheno-files` accepts either:

- **One file** that already has every ancestry stacked together, with an ancestry column matching `--ancestry-col` — nothing further needed.
- **A comma-separated list** of per-ancestry files (no ancestry column required in each), paired with `--ancestry-labels` — a comma-separated list of labels, same order and same length as `--pheno-files` — which gets stamped onto each file before they’re combined.

If you’re looping over many phenotypes and not every one has a file for every ancestry, add `--skip-missing-ancestries`: any file in the list that doesn’t exist (and its paired label) is dropped with a warning, rather than failing the whole run.

2.3 Histogram and KM masking for data privacy

Two independent flags control what gets suppressed before results leave the biobank:

- **`--min-cell-count`** (default `0`, i.e. off): any histogram bin (age, birthyear, enrollment, follow-up, …) with a count below this threshold is set to `NA`, and a `minimum_cell_count_pass` column is added to that file so recipients can see exactly which bins were masked.
- **`--km-min`** (onset/progression only, default `0`, i.e. off): re-groups the Kaplan-Meier time axis so that every *published* time point has at least this many people at risk, experiencing the event, and censored — merging adjacent time bins together as needed. This protects the survival curve itself, which `--min-cell-count` does not touch (that flag only applies to the histogram tables).

Both are optional and independent — use one, both, or neither depending on your biobank’s disclosure policy. The examples below marked “minimum sample size” show both in action, including what the masked output looks like compared to the unmasked version.

3 Overall Cohort Summary

This step only needs to be run one time. The key input information is

- sex
- ancestry
- birthyear
- age or date of enrollment
- age or date of last follow up

The input dataset can either be (1) combined file with all individuals used for GWAS analysis or (2) list of ancestry-specific files. If enrollment and/or last-followup information are contained in separate files (each assumed to include all individuals), that can be combined in this step.

3.1 Outputs

Every run in `cohort` mode writes the following files (all gzip-compressed, tab-separated), stratified by ancestry x sex, with `"ALL"` rollup rows across ancestry and/or sex:

- **`*_sample_sizes.txt.gz`** — `n` per ancestry and sex
- **`*_summaries.txt.gz`** — mean/median/sd of `birthyear`, `enrollment_age`, `enrollment_year`, `followup_age`, and `followup_time` (follow-up age minus enrollment age), per ancestry and sex
- **`*_birthyear_histogram.txt.gz`** — counts by ancestry, sex, birth year
- **`*_enrollmentAge_histogram.txt.gz`** — counts by ancestry, sex, enrollment age
- **`*_enrollmentYear_histogram.txt.gz`** — counts by ancestry, sex, enrollment year (`birthyear + enrollment_age`)
- **`*_followup_histogram.txt.gz`** — counts by ancestry, sex, total follow-up time (in years)

When `--min-cell-count` is set, each of the five histogram files above gains a `minimum_cell_count_pass` column, and `n` is set to `NA` wherever a bin fell below the threshold (see the “minimum sample size” example and the masked-vs-unmasked comparison below).

Below are example scripts for different file availability scenarios (example with UK Biobank)

3.2 Full dataset ready (age at enrollment / recruitment)

```
Rscript gbmi_cohort_summaries.R \
--mode=cohort \
--pheno-files=UKBB_cohort.txt \
--id-col=s \
--sex-col=sex \
--ancestry-col=pop \
--birthyear-col=birthyear \
--enrollment-col=age_at_recruitment \
--followup-col-in-file=age_death_or_lastvisit \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_cohort_summaries/UKBB_cohort
```

```
## Warning messages:
## 1: package ‘optparse’ was built under R version 4.5.2
## 2: package ‘data.table’ was built under R version 4.5.2
## 3: package ‘dplyr’ was built under R version 4.5.2
## 4: package ‘tidyr’ was built under R version 4.5.2
## 5: package ‘purrr’ was built under R version 4.5.2
## 6: package ‘survival’ was built under R version 4.5.2
## 7: package ‘broom’ was built under R version 4.5.2
## creating output directory  TTE_Summary/UKBB_cohort_summaries
## RUN COMPLETE: yes
```

3.3 Full dataset ready (year of enrollment / recruitment)

```
Rscript gbmi_cohort_summaries.R \
--mode=cohort \
--pheno-files=UKBB_cohort.txt \
--id-col=s \
--sex-col=sex \
--ancestry-col=pop \
--birthyear-col=birthyear \
--enrollment-date-col=year_at_recruitment \
--followup-date-col-in-file=year_death_or_lastvisit \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_cohort_summaries2/UKBB_cohort
```

3.4 Full dataset ready (example with minimum sample size)

When `--min-cell-count` is specified for data privacy reasons (default is 0), histogram bins below that minimum number are masked as NA. This creates an additional column `minimum_cell_count_pass` in the histogram files.

```
Rscript gbmi_cohort_summaries.R \
--mode=cohort \
--pheno-files=UKBB_cohort.txt \
--id-col=s \
--sex-col=sex \
--ancestry-col=pop \
--birthyear-col=birthyear \
--enrollment-col=age_at_recruitment \
--followup-col-in-file=age_death_or_lastvisit \
--male-value=1 --female-value=0 \
--min-cell-count=10 \
--prefix=TTE_Summary/UKBB_cohort_summaries_MIN/UKBB_cohort
```

```
## Warning messages:
## 1: package ‘optparse’ was built under R version 4.5.2
## 2: package ‘data.table’ was built under R version 4.5.2
## 3: package ‘dplyr’ was built under R version 4.5.2
## 4: package ‘tidyr’ was built under R version 4.5.2
## 5: package ‘purrr’ was built under R version 4.5.2
## 6: package ‘survival’ was built under R version 4.5.2
## 7: package ‘broom’ was built under R version 4.5.2
## creating output directory  TTE_Summary/UKBB_cohort_summaries_MIN
## RUN COMPLETE: yes
```

3.5 Ancestry-specific datasets to be joined

```
Rscript gbmi_cohort_summaries.R \
--mode=cohort \
--pheno-files=UKBB_cohort_AFR.txt,UKBB_cohort_CSA.txt,UKBB_cohort_EUR.txt \
--ancestry-labels=AFR,CSA,EUR \
--id-col=s \
--sex-col=sex \
--ancestry-col=pop \
--birthyear-col=birthyear \
--enrollment-file=UKBB_enrollment_YEAR.txt --enrollment-date-col=year_at_recruitment --enrollment-id-col=s \
--followup-file=UKBB_followup.txt --followup-col-in-file=age_death_or_lastvisit --followup-id-col=s \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_cohort_summaries_ANC/UKBB_cohort
```

3.6 Example Results



4 Onset Summary

This step can be conducted with the phenotype files used to conduct TTE GWAS. The key input information is

- sex
- ancestry
- birthyear
- `event`: onset case/control status
- `eventage`: age or date of diagnosis (cases) or last follow up (controls)

The key outputs are

- Summary statistics and histograms of age of diagnosis
- KM curves of disease onset

4.1 Outputs

Every run in `onset` mode writes (gzip-compressed, tab-separated, overall and stratified by ancestry + sex, with `event` as an additional case/control stratum):

- **`*_sample_sizes.txt.gz`** — `n` per ancestry, sex, `event` group
- **`*_summaries.txt.gz`** — mean/median/sd of age at event/censoring (`age`) and calendar year of event/censoring (`eventyear`), by ancestry, sex, `event`
- **`*_age_histogram.txt.gz`** — counts by ancestry, sex, age, `event`
- **`*_year_histogram.txt.gz`** — counts by ancestry, sex, calendar year, `event`
- **`*_km.txt.gz`** — Kaplan-Meier estimates of age-at-onset, one curve per ancestry and sex stratum: `time`, `n.risk`, `n.event`, `n.censor`, `estimate` (event-free probability), `std.error`, `conf.low` / `conf.high`, and `n_total` / `n_events_total` for that stratum

Note that `--min-cell-count` masks small counts (and adds `minimum_cell_count_pass`) in the two histogram files above, and `--km-min` re-bins `*_km.txt.gz` so every published time point meets the minimum at-risk/event/censor counts — see the comparison plot at the end of this section.

4.2 Combined-ancestry phenotype file

```
Rscript gbmi_cohort_summaries.R \
--mode=onset \
--pheno-files=UKBB_HYPTENSESS_pheno.txt \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=event \
--eventage-col=age \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_HYPTENSESS/UKBB_HYPTENSESS
```

```
## Warning messages:
## 1: package ‘optparse’ was built under R version 4.5.2
## 2: package ‘data.table’ was built under R version 4.5.2
## 3: package ‘dplyr’ was built under R version 4.5.2
## 4: package ‘tidyr’ was built under R version 4.5.2
## 5: package ‘purrr’ was built under R version 4.5.2
## 6: package ‘survival’ was built under R version 4.5.2
## 7: package ‘broom’ was built under R version 4.5.2
## creating output directory  TTE_Summary/UKBB_HYPTENSESS
## RUN COMPLETE: yes
```

4.3 Combined-ancestry phenotype file (time unit conversion)

If event age is measured in days, please add the `--units` flag. Allowable units are years (default), months, and days.

```
Rscript gbmi_cohort_summaries.R \
--mode=onset \
--pheno-files=UKBB_HYPTENSESS_pheno_days.txt \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=event \
--eventage-col=age \
--units='days' \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_HYPTENSESS_DAY/UKBB_HYPTENSESS
```

```
## Warning messages:
## 1: package ‘optparse’ was built under R version 4.5.2
## 2: package ‘data.table’ was built under R version 4.5.2
## 3: package ‘dplyr’ was built under R version 4.5.2
## 4: package ‘tidyr’ was built under R version 4.5.2
## 5: package ‘purrr’ was built under R version 4.5.2
## 6: package ‘survival’ was built under R version 4.5.2
## 7: package ‘broom’ was built under R version 4.5.2
## RUN COMPLETE: yes
```

4.4 Combined-ancestry phenotype file (with minimum sample sizes)

When `--km-min` is specified for data privacy reasons (default is 0), the data table used to create KM curves is re-grouped so that time bins include a sufficient number of samples.

```
Rscript gbmi_cohort_summaries.R \
--mode=onset \
--pheno-files=UKBB_HYPTENSESS_pheno.txt \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=event \
--eventage-col=age \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_HYPTENSESS_MIN/UKBB_HYPTENSESS \
--km-min=10 \
--min-cell-count=10
```

```
## Warning messages:
## 1: package ‘optparse’ was built under R version 4.5.2
## 2: package ‘data.table’ was built under R version 4.5.2
## 3: package ‘dplyr’ was built under R version 4.5.2
## 4: package ‘tidyr’ was built under R version 4.5.2
## 5: package ‘purrr’ was built under R version 4.5.2
## 6: package ‘survival’ was built under R version 4.5.2
## 7: package ‘broom’ was built under R version 4.5.2
## creating output directory  TTE_Summary/UKBB_HYPTENSESS_MIN
## RUN COMPLETE: yes
```

4.5 Ancestry-specific phenotype files

```
Rscript gbmi_cohort_summaries.R \
--mode=onset \
--pheno-files=UKBB_HYPTENSESS_pheno_AFR.txt,UKBB_HYPTENSESS_pheno_CSA.txt,UKBB_HYPTENSESS_pheno_EUR.txt \
--ancestry-labels=AFR,CSA,EUR \
--id-col=s \
--sex-col=sex \
--ancestry-col=pop \
--event-col=event \
--eventage-col=age \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_HYPTENSESS_ANC/UKBB_HYPTENSESS
```

4.6 Ancestry-specific phenotype files (more general)

Feel free to keep a fixed list of ancestries if looping through multiple phenotype files, as the script will skip over any missing files with the flag `--skip-missing-ancestries`

```
Rscript gbmi_cohort_summaries.R \
--mode=onset \
--pheno-files=UKBB_HYPTENSESS_pheno_AFR.txt,UKBB_HYPTENSESS_pheno_CSA.txt,\
UKBB_HYPTENSESS_pheno_EUR.txt,UKBB_HYPTENSESS_pheno_OTHER.txt \
--ancestry-labels=AFR,CSA,EUR,OTHER \
--skip-missing-ancestries \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=event \
--eventage-col=age \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_HYPTENSESS_ANC2/UKBB_HYPTENSESS
```

```
## Warning messages:
## 1: package ‘optparse’ was built under R version 4.5.2
## 2: package ‘data.table’ was built under R version 4.5.2
## 3: package ‘dplyr’ was built under R version 4.5.2
## 4: package ‘tidyr’ was built under R version 4.5.2
## 5: package ‘purrr’ was built under R version 4.5.2
## 6: package ‘survival’ was built under R version 4.5.2
## 7: package ‘broom’ was built under R version 4.5.2
## RUN COMPLETE: yes
## Warning message:
## In combine_ancestry_files(pheno_files, ancestry_col = ancestry_col,  :
##   1 of 4 ancestry file(s) not found and skipped: UKBB_HYPTENSESS_pheno_OTHER.txt (OTHER)
```

4.7 Example Results







5 Progression Summary

Similar to onset summaries, this step can be conducted with the phenotype files used to conduct TTE GWAS. The key input information is

- sex
- ancestry
- birthyear
- `event`: progression case/control status (may have a different name than onset)
- `eventage`: age or date of second diagnosis (progression cases) or last follow up (controls)
- `time-to-progression`: time from first diagnosis to second diagnosis or last follow up **optional, only to be used if event age not available**
- `onsetage`: age or date of first diagnosis

The key outputs are

- Summary statistics and histograms of baseline and progression age
- KM curves of disease progression by time from first diagnosis or absolute age

5.1 Outputs

Every run in `progression` mode writes (gzip-compressed, tab-separated, stratified by ancestry, sex, `event`):

- **`*_sample_sizes.txt.gz`** — `n` per ancestry, sex, `event`
- **`*_summaries.txt.gz`** — mean/median/sd of onset age, event age, and event year, by ancestry, sex, `event`
- **`*_baselineAge_histogram.txt.gz`** — counts by ancestry, sex, age-at-first-diagnosis, `event`
- **`*_eventAge_histogram.txt.gz`** — counts by ancestry, sex, age-at-second-event/censoring, `event`
- **`*_[year/month]_histogram.txt.gz`** — counts by ancestry, sex, time-since-first-diagnosis, `event`
- **`*_age_km.txt.gz`** — Kaplan-Meier curve of progression on an absolute-age time scale
- **`*_[year/month]_km.txt.gz`** — Kaplan-Meier curve of progression on a time-since-first-diagnosis time axis

As above, `--min-cell-count` masks small counts and adds `minimum_cell_count_pass` to the histogram files; `--km-min` re-bins the `*_km.txt.gz` files.

5.2 Combined-ancestry phenotype file (age of progression column)

```
Rscript gbmi_cohort_summaries.R \
--mode=progression \
--pheno-files=UKBB_HYPTENSESStoCKD_pheno.txt \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=secondEvent \
--eventage-col=pheno2Age \
--onsetage-col=diagAge \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_HYPTENSESStoCKD/UKBB_HYPTENSESStoCKD
```

```
## Warning messages:
## 1: package ‘optparse’ was built under R version 4.5.2
## 2: package ‘data.table’ was built under R version 4.5.2
## 3: package ‘dplyr’ was built under R version 4.5.2
## 4: package ‘tidyr’ was built under R version 4.5.2
## 5: package ‘purrr’ was built under R version 4.5.2
## 6: package ‘survival’ was built under R version 4.5.2
## 7: package ‘broom’ was built under R version 4.5.2
## creating output directory  TTE_Summary/UKBB_HYPTENSESStoCKD
## RUN COMPLETE: yes
```

5.3 Combined-ancestry phenotype file (time to progression column)

```
Rscript gbmi_cohort_summaries.R \
--mode=progression \
--pheno-files=UKBB_HYPTENSESStoCKD_pheno.txt \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=secondEvent \
--time-to-progression-col=secondTime \
--onsetage-col=diagAge \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_HYPTENSESStoCKD2/UKBB_HYPTENSESStoCKD
```

5.4 Combined-ancestry phenotype file (time unit conversion)

Time units are assumed to be in years for both endpoints, and thus two units must be provided for `--units`. The default is `"years,years"`, but below is an example with `onsetAge` measured in years and `secondTime` (time from initial onset) measured in days.

```
Rscript gbmi_cohort_summaries.R \
--mode=progression \
--pheno-files=UKBB_HYPTENSESStoCKD_pheno_days.txt \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=secondEvent \
--time-to-progression-col=secondTime \
--onsetage-col=diagAge \
--units='years,days' \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_HYPTENSESStoCKD_DAY/UKBB_HYPTENSESStoCKD
```

```
## Warning messages:
## 1: package ‘optparse’ was built under R version 4.5.2
## 2: package ‘data.table’ was built under R version 4.5.2
## 3: package ‘dplyr’ was built under R version 4.5.2
## 4: package ‘tidyr’ was built under R version 4.5.2
## 5: package ‘purrr’ was built under R version 4.5.2
## 6: package ‘survival’ was built under R version 4.5.2
## 7: package ‘broom’ was built under R version 4.5.2
## `age` not found in the phenotype file(s); deriving age at second event as `diagAge` + `secondTime` instead.
## RUN COMPLETE: yes
```

5.5 Ancestry-specific phenotype files

```
Rscript gbmi_cohort_summaries.R \
--mode=progression \
--pheno-files=UKBB_HYPTENSESStoCKD_pheno_AFR.txt,UKBB_HYPTENSESStoCKD_pheno_CSA.txt,\
UKBB_HYPTENSESStoCKD_pheno_EUR.txt,UKBB_HYPTENSESStoCKD_pheno_OTHER.txt \
--ancestry-labels=AFR,CSA,EUR,OTHER \
--skip-missing-ancestries \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=secondEvent \
--eventage-col=pheno2Age \
--onsetage-col=diagAge \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_HYPTENSESStoCKD_ANC/UKBB_HYPTENSESStoCKD
```

5.6 Example Results





6 Running the pipeline on all phenotypes

Summaries for all phenotypes can be computed and organized using the following code (examples in bash and R below):

NOTE: Some summary statistics were not included in the final meta-analysis following our QC procedures, e.g., due to small sample size or observed inflation. Please ensure that those phenotype files are not included in the summary analysis.

6.1 Bash (explicit list of phenotypes)

```
onset_phenos=(HYPTENSESS T1D T2D CAD)

for onset_pheno in "${onset_phenos[@]}";; do

Rscript gbmi_cohort_summaries.R \
--mode=onset \
--pheno-files=UKBB_${onset_pheno}_pheno_AFR.txt,UKBB_${onset_pheno}_pheno_CSA.txt,UKBB_${onset_pheno}_pheno_EUR.t
xt,UKBB_${onset_pheno}_pheno_OTHER.txt \
--ancestry-labels=AFR,CSA,EUR,OTHER \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=event \
--eventage-col=age \
--skip-missing-ancestries \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_${onset_pheno}/UKBB_${onset_pheno}

done
```

```
prog_phenos=(HYPTENSESStoCKD HYPTENSESStoMI HYPTENSESStoHEARTFAIL)

for prog_pheno in "${prog_phenos[@]}";; do

Rscript gbmi_cohort_summaries.R \
--mode=progression \
--pheno-files=UKBB_${prog_pheno}_pheno_AFR.txt,UKBB_${prog_pheno}_pheno_CSA.txt,UKBB_${prog_pheno}_pheno_EUR.txt,
UKBB_${prog_pheno}_pheno_OTHER.txt \
--ancestry-labels=AFR,CSA,EUR,OTHER \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=secondEvent \
--eventage-col=pheno2Age \
--onsetage-col=diagAge \
--skip-missing-ancestries \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_${prog_pheno}/UKBB_${prog_pheno}

done
```

6.2 Bash (text file of phenotypes)

```
while read onset_pheno; do

Rscript gbmi_cohort_summaries.R \
--mode=onset \
--pheno-files=UKBB_${onset_pheno}_pheno_AFR.txt,UKBB_${onset_pheno}_pheno_CSA.txt,UKBB_${onset_pheno}_pheno_EUR.t
xt,UKBB_${onset_pheno}_pheno_OTHER.txt \
--ancestry-labels=AFR,CSA,EUR,OTHER \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=event \
--eventage-col=age \
--skip-missing-ancestries \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_${onset_pheno}/UKBB_${onset_pheno}

done < onset_phenos.txt
```

```
while read prog_pheno; do

Rscript gbmi_cohort_summaries.R \
--mode=progression \
--pheno-files=UKBB_${prog_pheno}_pheno_AFR.txt,UKBB_${prog_pheno}_pheno_CSA.txt,UKBB_${prog_pheno}_pheno_EUR.txt,
UKBB_${prog_pheno}_pheno_OTHER.txt \
--ancestry-labels=AFR,CSA,EUR,OTHER \
--id-col=s \
--sex-col=sex \
--birthyear-col=birthyear \
--ancestry-col=pop \
--event-col=secondEvent \
--eventage-col=pheno2Age \
--onsetage-col=diagAge \
--skip-missing-ancestries \
--male-value=1 --female-value=0 \
--prefix=TTE_Summary/UKBB_${prog_pheno}/UKBB_${prog_pheno}

done < prog_phenos.txt
```

6.3 R

```
onset_phenos = c('HYPTENSESS', 'T1D', 'T2D', 'CAD')

for (onset_pheno in onset_phenos) {
  system2(command='Rscript',
          args=c(
            'gbmi_cohort_summaries.R',
            '--mode=onset',
            paste0('--pheno-files=UKBB_', onset_pheno, '_pheno_AFR.txt,UKBB_', onset_pheno, '_pheno_CSA.txt,UKBB
_', onset_pheno, '_pheno_EUR.txt,UKBB_', onset_pheno, '_pheno_OTHER.txt'),
            '--ancestry-labels=AFR,CSA,EUR,OTHER',
            '--id-col=s',
            '--sex-col=sex',
            '--birthyear-col=birthyear',
            '--ancestry-col=pop',
            '--event-col=event',
            '--eventage-col=age',
            '--skip-missing-ancestries',
            '--male-value=1', '--female-value=0',
            paste0('--prefix=TTE_Summary/UKBB_', onset_pheno, '/UKBB_', onset_pheno)))
}
```

```
prog_phenos=c('HYPTENSESStoCKD', 'HYPTENSESStoMI', 'HYPTENSESStoHEARTFAIL')

for (prog_pheno in prog_phenos) {
  system2(command='Rscript',
          args=c(
            'gbmi_cohort_summaries.R',
            '--mode=progression',
            paste0('--pheno-files=UKBB_', prog_pheno, '_pheno_AFR.txt,UKBB_', prog_pheno, '_pheno_CSA.txt,UKBB_',
prog_pheno, '_pheno_EUR.txt,UKBB_', prog_pheno, '_pheno_OTHER.txt'),
            '--ancestry-labels=AFR,CSA,EUR,OTHER',
            '--id-col=s',
            '--sex-col=sex',
            '--birthyear-col=birthyear',
            '--ancestry-col=pop',
            '--event-col=secondEvent',
            '--eventage-col=pheno2Age',
            '--onsetage-col=diagAge',
            '--skip-missing-ancestries',
            '--male-value=1', '--female-value=0',
            paste0('--prefix=TTE_Summary/UKBB_', prog_pheno, '/UKBB_', prog_pheno)))
}
```

7 Prepare files for sharing

All individual summary files are gzip compressed, and should be organized within a TTE_Summary directory (as in the example script). For final sharing, please upload the entire TTE_Summary directory to the GBMI Google Cloud Bucket (e.g., `gsutil cp TTE_Summary/* gs://gbmi-[biobank]/TTE_Summary/` or `gcloud storage rsync TTE_Summary gs://gbmi-[biobank]/TTE_Summary/`).

Thank you very much for your contributions to this project, and please do not hesitate to contact us with any questions!

- Tony Chen chentony@broadinstitute.org
- Wei Zhou wzhou@broadinstitute.org
- Ida Surakka isurakka@umich.edu