

Name

Client

Project Name

Type | Quantity




Disclaimer:-

Brighton Lighting reserves the right to revise, modify, or discontinue any product in this catalogue without prior notice as LED technology evolves; Information herein is for general purposes only and based on data available at publication, Tolerances are ±10% luminous flux, ±12% efficacy, and ±1.5 CRI); all sales are subject to Brighton Lighting's general terms and conditions.

Spin E


BR-SPE10.830W44W-F, 10W



Product Description : Designed for clean, uniform illumination, this reflectorless downlight delivers soft, glare-controlled lighting with a minimalist appearance. Its recessed light source and precision optical design ensure excellent visual comfort while maintaining high lighting efficiency. Ideal for indoor applications requiring seamless architectural integration and consistent illumination.

Finish	: White
Reflector	: White
Dimension	: Dia 85mm H 76mm
Cutout	: Dia 75mm
Wattage	: 10W
Lumen	: 1000lm
CCT	: 3000K
CRI	: >90
Protection Rating	: IP44
Macadam	: 3 step
Material	: Die Cast Aluminium
Lifetime	: L70>50,000 hrs
Voltage	: 220-240V AC
Class	: II
IK Protection	: IK 02
Diffuser	: Polycarbonate
Ambient Temp [C°]	: -20°~45°
Power Factor	: λ > .95 ^[5] EN55015
THD	: < 10%
Weight	: 0.3 KG
DC (mA)	: 350mA
Beam Angle	: 60°

Photometric



For Detailed Installation instruction, please consult the QR Code.

Values are based on nominal current at a case temperature of 45°C under normal operating conditions.
These values are provided for informational purposes only and do not constitute a warranty or guarantee of performance.