

PRODUCT SPECIFICATION SHEET

Revision New
Code:
Issue Date: 05/12/2016

ITEM REF / CODE

40002052-0**A. PRODUCT DETAILS**

Customer Name:	Sega Pac Pty Ltd
Customer Description:	Vacuum seal packing laminate for cooked food products
Customer Code:	SEG-809
Material Structure Description:	14µm PVdC PET / Adhesive / 70µm PE
AchievePack Internal Description:	SEG SL PVDC PET / 70UM PE 740mm
APN Barcode Number:	NA

B. PRINTING INFORMATION & SPECIFICATIONS

Printing Process:	Rotogravure / Cylinder Printing
Print Quality Standard:	High-Definition Glossy Cylinders
Rewind Direction to Customer:	PE Side Inside (Sealant layer internal)
Print Number Colours:	6 Colors
Total Retain Solvent Limit:	< 5.0 mg/m ²
Solid Colour Variation (tolerance):	$\Delta E < 2.0$
APN Bar Code Scan Quality:	Grade A



C. PHYSICAL PROPERTY SPECIFICATIONS & TOLERANCES

The following testing metrics reflect minimal threshold tolerances, ranges, or industrial packaging parameters:

Opacity (White Films):	N/A
Optical Density (Metallised):	N/A
Lamination Bond Strength (1st Pass):	Min 200 gf/25mm
Heat Seal Strength (Sealing limit):	Min 1,000 gf/25mm (B/B seals)
WVTR (Water Vapor Barrier):	< 5 cc/m²/day (38°C, 90% RH)
OTR (Oxygen Gas Barrier):	< 10 cc/m²/day (25°C, 0% RH)
COF External (Coefficient of Friction):	0.20 – 0.40 (outside to outside)
COF Internal (Friction sealant):	0.15 – 0.20 (inside to inside)
Total Thickness (microns):	86um ± 10%
Laminate Yield (gsm):	86 gsm ± 10%
Repeat Length (± 1mm):	Plain
Slit Width (± 1mm tolerance):	740mm

D. OTHER TECHNICAL INFORMATION

Odour & Migration:	The material supplied shall be free from excessive odour and shall not cause any deterioration in the organoleptic character of the food nor bring about any unacceptable change in the quality of the food.
General Workmanship:	The material supplied shall be of an acceptable commercial standard free from bubbles, streaks, creasing, or foreign matter, any of which may preclude its satisfactory
Issue date: 23/06/15	conversion or end use Application. page 2 / 4

Product Stewardship & Recyclability:



This film covered by the specification can be classified under Plastics Identification Code 7 (OTHER). Flexible packaging cannot be disposed of currently in curbside collection although clean film can be recycled using industrial recyclers. Cardboard cores can be recycled by industrial recyclers if the film and tape is removed.

E. SLITTING, PACKING, TRANSPORT & STORAGE INFORMATION

	Cardboard layer pads used as packaging on the pallet can be recycled by industrial recyclers. Where AchievePack has suggested that our product and/or packaging can be recycled AchievePack can assist with identifying suitable recyclers.
Roll Core ID (Diameter):	Paper core ID 76
Joins Tape Specification:	Red
Maximum Joins Allowed:	1 max
Position of Joins (flagging):	Butt/In register, Red tape flags on Left hand side of roll
Roll Label Requirements:	To contain Customer name, jdfadfsfsdob details, roll ID, roll weight etc...
Roll Size / Length / Weight:	asdfdsf
Stack roll on pallet layout:	adfadsfasdfadf
Pallet Setup Type:	Plain wood
General Transport Packaging:	Pallet contents to be secured on pallet to withstand the rigours of transport, handling, and storage. Pallet contents at delivery must be in good condition and fit for intended use.

